

**RF EXPOSURE PART 2 TEST REPORT****Applicant Name:**

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

10/24/2024 – 10/31/2024

Test Site/Location:

Element, Columbia, MD, USA

Document Serial No.:

1M2408260069-02.A3L (Rev1)

FCC ID:

A3LSMS938B

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model(s):


SM-S938B/DS

Device Serial Numbers:

Pre-Production Samples [0829M]

Note: This revised test report supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.



RJ Ortanez

Executive Vice President



| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 1 of 65 |

T A B L E O F C O N T E N T S

| | | |
|----|---|----|
| 1 | DEVICE UNDER TEST | 3 |
| 2 | RF EXPOSURE LIMITS | 5 |
| 3 | TIME VARYING TRANSMISSION TEST CASES | 7 |
| 4 | FCC MEASUREMENT PROCEDURES (FREQ < 6 GHZ) | 11 |
| 5 | MEASUREMENT TEST SETUP (FREQ < 6 GHZ) | 27 |
| 6 | TEST CONFIGURATIONS (FREQ < 6 GHZ) | 32 |
| 7 | CONDUCTED TX CASES (FREQ < 6 GHZ) | 37 |
| 8 | EQUIPMENT LIST | 61 |
| 9 | MEASUREMENT UNCERTAINTIES | 62 |
| 10 | CONCLUSION | 63 |
| 11 | REFERENCES | 64 |

APPENDIX A: TEST SETUP PHOTOGRAPHS

APPENDIX B: TEST SEQUENCES

APPENDIX C: TEST PROCEDURES FOR SUB6 NR + NR RADIO

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 2 of 65 |

1 DEVICE UNDER TEST

1.1 Device Overview

| Band & Mode | Operating Modes | Tx Frequency |
|--------------------|-----------------|--|
| GSM/GPRS/EDGE 850 | Voice/Data | 824.20 - 848.80 MHz |
| GSM/GPRS/EDGE 1900 | Voice/Data | 1850.20 - 1909.80 MHz |
| UMTS 850 | Voice/Data | 826.40 - 846.60 MHz |
| UMTS 1750 | Voice/Data | 1712.4 - 1752.6 MHz |
| UMTS 1900 | Voice/Data | 1852.4 - 1907.6 MHz |
| LTE Band 12 | Voice/Data | 699.7 - 715.3 MHz |
| LTE Band 17 | Voice/Data | 706.5 - 713.5 MHz |
| LTE Band 13 | Voice/Data | 779.5 - 784.5 MHz |
| LTE Band 26 | Voice/Data | 814.7 - 848.3 MHz |
| LTE Band 5 | Voice/Data | 824.7 - 848.3 MHz |
| LTE Band 66 | Voice/Data | 1710.7 - 1779.3 MHz |
| LTE Band 4 | Voice/Data | 1710.7 - 1754.3 MHz |
| LTE Band 25 | Voice/Data | 1850.7 - 1914.3 MHz |
| LTE Band 2 | Voice/Data | 1850.7 - 1909.3 MHz |
| LTE Band 41 | Voice/Data | 2498.5 - 2687.5 MHz |
| NR Band n5 | Voice/Data | 826.5 - 846.5 MHz |
| NR Band n66 | Voice/Data | 1712.5 - 1777.5 MHz |
| NR Band n25 | Voice/Data | 1852.5 - 1912.5 MHz |
| NR Band n2 | Voice/Data | 1852.5 - 1907.5 MHz |
| NR Band n41 | Voice/Data | 2501.01 - 2685 MHz |
| NR Band n77 | Voice/Data | 3455.01 - 3544.98 MHz; 3705 - 3975 MHz |
| 2.4 GHz WIFI | Voice/Data | 2412 - 2462 MHz |
| 5 GHz WIFI | Voice/Data | U-NII-1: 5180 - 5240 MHz U-NII-2A: 5260 - 5320 MHz U-NII-2C: 5500 - 5720 MHz U-NII-3: 5745 - 5825 MHz U-NII-4: 5845 - 5885 MHz |
| 6 GHz WIFI | Voice/Data | U-NII-5: 5945 - 6415 MHz U-NII-6: 6435 - 6515 MHz U-NII-7: 6535 - 6875 MHz U-NII-8: 6895 - 7115 MHz |
| 2.4 GHz Bluetooth | Data | 2402 - 2480 MHz |
| NFC | Data | 13.56 MHz |
| UWB | Data | 6489.6 - 7987.2 MHz |

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 3 of 65 |

1.2 Time-Averaging Algorithm for RF Exposure Compliance

This device is enabled with Qualcomm® Smart Transmit feature. This feature performs time averaging algorithm in real time to control and manage transmitting power and ensure the time-averaged RF exposure is in compliance with FCC requirements all the time. DUT contains embedded file system (EFS) version 23 configured for the second generation (GEN2) for Sub6.

The Smart Transmit algorithm maintains the time-averaged transmit power, in turn, time-averaged RF exposure of SAR_{design_target} , below the predefined time-averaged power limit (i.e., P_{limit} for sub-6 radio), for each characterized technology and band.

Smart Transmit allows the device to transmit at higher power instantaneously, as high as P_{max} , when needed, but enforces power limiting to maintain time-averaged transmit power to P_{limit} for frequencies < 6 GHz.

Note that the device uncertainty is 1.0 dB for this DUT.

The following input parameters are key parameters that are required for functionality of the Smart Transmit feature. These parameters cannot be accessed by the end user, because at the factory they are entered through the embedded file system (EFS) entries by the OEM.

- $Tx_power_at_SAR_design_target$ (P_{limit} in dBm) for Tx transmitting frequency < 6 GHz

The maximum time-average transmit power, in dBm, at which this radio configuration (i.e., band and technology) reaches the SAR_{design_target} . This SAR_{design_target} is pre-determined for the specific device, and it shall be less than the regulatory SAR limit after accounting for all design related tolerances. The time-averaged SAR is assessed against this SAR_{design_target} in real time to determine the compliance. The P_{limit} could vary with technology, band, antenna and DSI (device state index), therefore it has unique value for each technology, band, antenna and DSI.

This purpose of the Part 2 report is to demonstrate the DUT complies with FCC RF exposure requirement under Tx varying transmission scenarios, thereby validity of Qualcomm® Smart Transmit feature implementation in this device. It serves to compliment the Part 0 and Part 1 Test Reports to justify compliance per FCC.

1.3 Part 2 Test Case Reduction for Multiple Filings

Per FCC guidance, the number of test cases for Part 2 evaluation can be reduced in the case of multiple filings using the same chipset after full part 2 testing on the first filing. While the same chipset and Smart Transmit algorithm are used in this model, DUT with the final SW was tested for power measurements to verify the integration. The SAR, as described in Section 3, measurements are excluded per FCC guidance.

1.4 Bibliography

| Report Type | Report Serial Number |
|--------------------------------|----------------------|
| RF Exposure Part 0 Test Report | 1M2408260069-27.A3L |
| RF Exposure Part 1 Test Report | 1M2408260069-01.A3L |
| RF Exposure Compliance Summary | 1M2408260069-03.A3L |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 4 of 65 |

2 RF EXPOSURE LIMITS

2.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

2.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

2.3 RF Exposure Limits for Frequencies Below 6 GHz

Table 2-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

| HUMAN EXPOSURE LIMITS | | |
|---|---|---|
| | UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g) | CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g) |
| Peak Spatial Average SAR Head | 1.6 | 8.0 |
| Whole Body SAR | 0.08 | 0.4 |
| Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc. | 4.0 | 20 |

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 5 of 65 |

2.4 RF Exposure Limits for Frequencies Above 6 GHz

Per §1.1310 (d)(3), the MPE limits are applied for frequencies above 6 GHz. Power Density is expressed in units of W/m² or mW/cm².

Peak Spatially Averaged Power Density was evaluated over a circular area of 4 cm² per interim FCC Guidance for near-field power density evaluations per October 2018 TCB Workshop notes.

Table 2-2
Human Exposure Limits Specified in FCC 47 CFR §1.1310

| Human Exposure to Radiofrequency (RF) Radiation Limits | | |
|---|--|-----------------------------|
| Frequency Range [MHz] | Power Density [mW/cm ²] | Averaging Time [Minutes] |
| (A) Limits for Occupational / Controlled Environments | | |
| 1,500 – 100,000 | 5.0 | 6 |
| (B) Limits for General Population / Uncontrolled Environments | | |
| 1,500 – 100,000 | 1.0 | 30 |

Note: 1.0 mW/cm² is 10 W/m²

2.5 Time Averaging Windows for FCC Compliance

Per October 2018 TCB Workshop Notes, the below time-averaging windows can be used for assessing time-averaged exposures for devices that are capable of actively monitoring and adjusting power output over time to comply with exposure limits.

| Interim Guidance | Frequency (GHz) | Maximum Averaging Time (sec) |
|------------------|--------------------|------------------------------------|
| SAR | < 3 | 100 |
| | 3 – 6 | 60 |
| MPE | 6 - 10 | 30 |
| | 10 - 16 | 14 |
| | 16 – 24 | 8 |
| | 24 – 42 | 4 |
| | 42 – 95 | 2 |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 6 of 65 |

3 TIME VARYING TRANSMISSION TEST CASES

To validate the time averaging feature and demonstrate the compliance in Tx varying transmission conditions, the following transmission scenarios are covered in the Part 2 test:

1. During a time-varying Tx power transmission: To prove that the Smart Transmit feature accounts for Tx power variations in time accurately.
2. During a call disconnect and re-establish scenario: To prove that the Smart Transmit feature accounts for history of past Tx power transmissions accurately.
3. During a technology/band handover: To prove that the Smart Transmit feature functions correctly during transitions in technology/band.
4. During a DSI (Device State Index) change: To prove that the Smart Transmit feature functions correctly during transition from one device state (DSI) to another.
5. During an antenna (or beam) switch: To prove that the Smart Transmit feature functions correctly during transitions in antenna (such as AsDiv scenario) or beams (different antenna array configurations) or beams (different antenna array configurations).
6. SAR vs. PD exposure switching during sub-6+mmW transmission: To prove that the Smart Transmit feature functions correctly and ensures total RF exposure compliance during transitions in SAR dominant exposure, SAR+PD exposure, and PD dominant exposure scenarios.
7. During time window switch: To prove that the Smart Transmit feature correctly handles the transition from one time window to another specified by FCC, and maintains the normalized time-averaged RF exposure to be less than normalized FCC limit of 1.0 at all times.
8. SAR exposure switching between two active radios (radio1 and radio2): To prove that the Smart Transmit feature functions correctly and ensures total RF exposure compliance when exposure varies among SAR_radio1 only, SAR_radio1 + SAR_radio2, and SAR_radio2 only scenarios.
9. System level compliance continuity: Within terrestrial networks (WWAN, WLAN, BT, etc.): To demonstrate the time averaged RF exposure compliance continuity during technology transition in both single-radio and multi-radio transmission scenarios and under both modes (i.e., ON and airplane) of WWAN modem.

NOTE: Technology in this test refers to WWAN, WLAN and/or Bluetooth

NOTE: For WWAN, theoretically, either sub6 radio or mmW radio can be selected for this system level compliance continuity test as Smart Transmit internal operation is identical. Thus, the test with either WWAN sub6 or mmW radio is sufficient. However, since FCC time average window for WWAN mmW NR is 4 seconds, to be more practical and feasible in actual measurement, sub6 WWAN radio is recommended to be selected for this test.

NOTE: BT allowed maximum power will be at one of the 3 levels populated in EFS depending on transmission scenarios, and BT's Pmax allocated by Smart Transmit is always \leq Plimit. Therefore, for 10.b), either WWAN or WLAN can be selected as a terrestrial network for demonstrating the compliance continuity during bi-directional transitions between non-terrestrial networks and terrestrial network. Test with one pair of terrestrial and non-terrestrial radios is sufficient as the continuity among all terrestrial technologies is covered and validated.

As described in Part 0 report, the RF exposure is proportional to the Tx power for a SAR- and PD-characterized wireless device. Thus, feature validation in Part 2 can be effectively performed through conducted (for $f < 6\text{GHz}$)

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 7 of 65 |

and radiated (for $f \geq 6\text{GHz}$) power measurement. Therefore, the compliance demonstration under dynamic transmission conditions and feature validation are done in conducted/radiated power measurement setup for transmission scenario 1 through 10.

To add confidence in the feature validation, the time-averaged SAR and PD measurements are also performed but only performed for transmission scenario 1 to avoid the complexity in SAR and PD measurement (such as, for scenario 3 requiring change in SAR probe calibration file to accommodate different bands and/or tissue simulating liquid).

The strategy for testing in Tx varying transmission condition is outlined as follows:

- Demonstrate the total RF exposure averaged over FCC defined time windows does not exceed FCC's SAR and PD limits, through time-averaged power measurements
 - Measure conducted Tx power (for $f < 6\text{GHz}$) versus time, and radiated Tx power (EIRP for $f > 10\text{GHz}$) versus time.
 - Convert it into RF exposure and divide by respective FCC limits to get normalized exposure versus time.
 - Perform running time-averaging over FCC defined time windows.
 - Demonstrate that the total normalized time-averaged RF exposure is less than 1 for all transmission scenarios (i.e., transmission scenarios 1, 2, 3, 4, 5, 6, 7, and 8) at all times.

Mathematical expression:

For $< 6\text{ GHz}$ transmission only:

$$1g_or_10gSAR(t) = \frac{\text{conducted_Tx_power}(t)}{\text{conducted_Tx_power_P}_{limit}} * 1g_or_10gSAR_P_{limit} \quad (1a)$$

$$\frac{\frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t 1g_or_10gSAR(t) dt}{FCC\ SAR\ limit} \leq 1 \quad (1b)$$

For sub-6+mmW transmission:

$$1g_or_10gSAR(t) = \frac{\text{conducted_Tx_power}(t)}{\text{conducted_Tx_power_P}_{limit}} * 1g_or_10gSAR_P_{limit} \quad (2a)$$

$$4cm^2PD(t) = \frac{\text{radiated_Tx_power}(t)}{\text{radiated_Tx_power_input.power.limit}} * 4cm^2PD_input.power.limit \quad (2b)$$

$$\frac{\frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t 1g_or_10gSAR(t) dt}{FCC\ SAR\ limit} + \frac{\frac{1}{T_{PD}} \int_{t-T_{PD}}^t 4cm^2PD(t) dt}{FCC\ 4cm^2\ PD\ limit} \leq 1 \quad (2c)$$

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 8 of 65 |

where, $conducted_Tx_power(t)$, $conducted_Tx_power_P_{limit}$, and $1g_or_10gSAR_P_{limit}$ correspond to the measured instantaneous conducted Tx power, measured conducted Tx power at P_{limit} , and measured $1gSAR$ or $10gSAR$ values at P_{limit} corresponding to sub-6 transmission. Similarly, $radiated_Tx_power(t)$, $radiated_Tx_power_input_power_limit$, and $4cm^2PD_input_power_limit$ correspond to the measured instantaneous radiated Tx power, radiated Tx power at $input_power_limit$ (i.e., radiated power limit), and $4cm^2PD$ value at $input_power_limit$ corresponding to mmW transmission. Both P_{limit} and $input_power_limit$ are the parameters pre-defined in Part 0 and loaded via Embedded File System (EFS) onto the EUT. T_{SAR} is the FCC defined time window for sub-6 radio; T_{PD} is the FCC defined time window for mmW radio.

- Demonstrate the total RF exposure averaged over FCC defined time windows does not exceed FCC's SAR and PD limits, through time-averaged SAR and PD measurements. Note as mentioned earlier, this measurement is performed for transmission scenario 1 only.
 - For sub-6 transmission only, measure instantaneous SAR versus time; for LTE+sub6 NR transmission, request low power (or all-down bits) on LTE so that measured SAR predominantly corresponds to sub6 NR.
 - For LTE + mmW transmission, measure instantaneous E-field versus time for mmW radio and instantaneous conducted power versus time for LTE radio.
 - Convert it into RF exposure and divide by respective FCC limits to obtain normalized exposure versus time.
 - Perform time averaging over FCC defined time window.
 - Demonstrate that the total normalized time-averaged RF exposure is less than 1 for transmission scenario 1 at all times.

Mathematical expression:

- For sub-6 transmission only:

$$1g_or_10gSAR(t) = \frac{pointSAR(t)}{pointSAR_P_{limit}} * 1g_or_10gSAR(t)_P_{limit} \quad (3a)$$

$$\frac{\frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t 1g_or_10gSAR(t) dt}{FCC\ SAR\ limit} \leq 1 \quad (3b)$$

- For sub-6 + $f \geq 6GHz$ transmission:

$$1g_or_10gSAR(t) = \frac{conducted_Tx_power(t)}{conducted_Tx_power_P_{limit}} * 1g_or_10gSAR_P_{limit} \quad (4a)$$

$$4cm^2PD(t) = \frac{[pointE(t)]^2}{[pointE_input_power_limit]^2} * 4cm^2PD_input_power_limit \quad (4b)$$

$$\frac{\frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t 1g_or_10gSAR(t) dt}{FCC\ SAR\ limit} + \frac{\frac{1}{T_{PD}} \int_{t-T_{PD}}^t 4cm^2PD(t) dt}{FCC\ 4cm^2PD\ limit} \leq 1 \quad (4c)$$

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 9 of 65 |

where, $pointSAR(t)$, $pointSAR_{P_{limit}}$, and $1g_or_10gSAR_{P_{limit}}$ correspond to the measured instantaneous point SAR, measured point SAR at P_{limit} , and measured 1gSAR or 10gSAR values at P_{limit} corresponding to sub-6 transmission. Similarly, $pointE(t)$, $pointE_{input.power.limit}$, and $4cm^2PD_{input.power.limit}$ correspond to the measured instantaneous E-field, E-field at $input.power.limit$, and $4cm^2PD$ value at $input.power.limit$ corresponding to mmW transmission.

Note: cDASY6 measurement system by Schmid & Partner Engineering AG (SPEAG) of Zurich, Switzerland measures relative E-field, and provides ratio of $\frac{[pointE(t)]^2}{[pointE_{input.power.limit}]^2}$ versus time.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 10 of 65 |

4 FCC MEASUREMENT PROCEDURES (FREQ < 6 GHz)

This chapter provides the test plan and test procedure for validating Qualcomm Smart Transmit feature for sub-6 transmission. The 100 seconds time window for operating $f < 3\text{GHz}$ is used as an example to detail the test procedures in this chapter. The same test plan and test procedures described in this chapter apply to 60 seconds time window for operating $f \geq 3\text{GHz}$.

4.1 Test Sequence Determination for Validation

Following the FCC recommendation, two test sequences having time-variation in Tx power are predefined for sub-6 ($f < 6\text{GHz}$) validation:

- Test sequence 1: request DUT's Tx power to be at maximum power, measured P_{max}^{\dagger} , for 80s, then requesting for half of the maximum power, i.e., measured $P_{max}/2$, for the rest of the time.
- Test sequence 2: request DUT's Tx power to vary with time. This sequence is generated relative to measured P_{max} , measured P_{limit} and calculated $P_{reserve}$ (= measured P_{limit} in dBm - $total_min_reserve$ in dB) of DUT based on measured P_{limit} .

The details for generating these two test sequences is described and listed in Appendix E.

NOTE: For test sequence generation, "measured P_{limit} " and "measured P_{max} " are used instead of the " P_{limit} " specified in EFS entry and " P_{max} " specified for the device, because the Smart Transmit feature operates against the actual power level of the " P_{limit} " that was calibrated for the DUT. The "measured P_{limit} " accurately reflects what the feature is referencing to, therefore, it should be used during feature validation testing. The RF tune up and device-to-device variation are already considered in Part 0 report prior to determining P_{limit} .

4.2 Test Configuration Selection Criteria for Validating Smart Transmit Feature

For validating the Smart Transmit feature, this section provides the general guidance to select test cases.

4.2.1 Time-Varying Tx Power Transmission

The Smart Transmit time averaging feature operation is independent of bands, modes, and channels for a given technology. Hence, validation of Smart Transmit in one band/mode/channel per technology is sufficient. Two bands per technology are proposed and selected for this testing to provide high confidence in this validation.

Note this test is designed for single radio transmission scenario. If UE supports sub6 NR in both non-standalone (NSA) and standalone (SA) modes, then validation in time-varying Tx power transmission scenario described in this section needs to be performed in SA mode. Otherwise, it needs to be performed in NSA mode with LTE anchor set to low power. The choice between SA and NSA mode needs to also take into account the selection criteria described below. In general, one mode out of the two modes (NSA or SA) is sufficient for this test.

The criteria for the selection are based on the P_{limit} values determined in Part 0 report. Select two bands* in each supported technology that correspond to least** and highest*** P_{limit} values that are less than P_{max} for validating Smart Transmit. Note:

1. P_{max} refers to maximum Tx power configured for this device in this technology/band (not rated P_{max}). This P_{max} definition applies throughout this Part 2 report.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 11 of 65 |

2. If $P_{limit} > P_{max}$, the validation test with time-varying test sequences is not needed as no power enforcement will be required in this condition.

* If one P_{limit} level applies to all the bands within a technology, then only one band needs to be tested. In this case, within the bands having the same P_{limit} , the radio configuration (e.g., # of RBs, channel#) and device position that correspond to the highest *measured* 1gSAR at P_{limit} shown in Part 1 report is selected.

** In case of multiple bands having the same least P_{limit} within the technology, then select the band having the highest *measured* 1gSAR at P_{limit} .

*** The band having a higher P_{limit} needs to be properly selected so that the power limiting enforced by Smart Transmit can be validated using the pre-defined test sequences. If the highest P_{limit} in a technology is too high where the power limiting enforcement is not needed when testing with the pre-defined test sequences, then the next highest level is checked. This process is continued within the technology until the second band for validation testing is determined.

4.2.2 Change In Call

The criteria to select a test configuration for call-drop measurement is:

- Select technology/band with least P_{limit} among all supported technologies/bands, and select the radio configuration (e.g., # of RBs, channel#) in this technology/band that corresponds to the highest *measured* 1gSAR at P_{limit} listed in Part 1 report.
- In case of multiple bands having same least P_{limit} , then select one band/radio configuration for this test.

This test is performed with the DUT's Tx power requested to be at maximum power, the above band selection will result in Tx power enforcement (i.e., DUT forced to have Tx power at $P_{reserve}$) for longest duration in one FCC defined time window. The call change (call drop/reestablish) is performed during the Tx power enforcement duration (i.e., during the time when DUT is forced to have Tx power at $P_{reserve}$). One test is sufficient as the feature operation is independent of technology and band.

4.2.3 Change In Technology/Band

The selection criteria for this measurement is, for a given antenna, to have DUT switch from a technology/band with lowest P_{limit} within the technology group (in case of multiple bands having the same P_{limit} , then select the band with highest *measured* 1gSAR at P_{limit}) to a technology/band with highest P_{limit} within the technology group, in case of multiple bands having the same P_{limit} , then select the band with lowest *measured* 1gSAR at P_{limit} in Part 1 report, or vice versa.

This test is performed with the DUT's Tx power requested to be at maximum power, the technology/band switch is performed during Tx power enforcement duration (i.e., during the time when DUT is forced to have Tx power at $P_{reserve}$).

4.2.4 Change In Antenna

The criteria to select a test configuration for antenna switch measurement is:

- Whenever possible and supported by the DUT, first select antenna switch configuration within the same technology/band (i.e., same technology and band combination).

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 12 of 65 |

- Then, select any technology/band that supports multiple Tx antennas, and has the highest difference in P_{limit} among all supported antennas.
- In case of multiple bands having same difference in P_{limit} among supported antennas, then select the band having the highest *measured* 1gSAR at P_{limit} in Part 1 report.

This test is performed with the DUT's Tx power requested to be at maximum power in selected technology/band, and antenna change is conducted during Tx power enforcement duration (i.e., during the time when DUT is forced to have Tx power at $P_{reserve}$).

4.2.5 Change In DSI

The criteria to select a test configuration for DSI change test is

- Select a technology/band having the $P_{limit} < P_{max}$ within any technology and DSI group, and for the same technology/band having a different P_{limit} in any other DSI group. Note that the selected DSI transition need to be supported by the device.

This test is performed with the DUT's Tx power requested to be at maximum power in selected technology/band, and DSI change is conducted during Tx power enforcement duration (i.e., during the time when DUT is forced to have Tx power at $P_{reserve}$).

4.2.6 Change In Time Window

FCC specifies different time window for time averaging based on operation frequency. The criteria to select a test configuration for validating Smart Transmit feature and demonstrating the compliance during the change in time window is

- Select any technology/band that has operation frequency classified in one time window defined by FCC (such as 100-seconds time window), and its corresponding P_{limit} is less than P_{max} if possible.
- Select the 2nd technology/band that has operation frequency classified in a different time window defined by FCC (such as 60-seconds time window), and its corresponding P_{limit} is less than P_{max} if possible.
- Note it is preferred both P_{limit} values of two selected technology/band less than corresponding P_{max} , but if not possible, at least one of technologies/bands has its P_{limit} less than P_{max} .

This test is performed with the EUT's Tx power requested to be at maximum power in selected technology/band. Test for one pair of time windows selected is sufficient as the feature operation is the same.

4.2.7 SAR Exposure Switching

If supported, the test configuration for SAR exposure switching should cover

1. SAR exposure switch when two active radios are in the same time window
2. SAR exposure switch when two active radios are in different time windows. One test with two active radios in any two different time windows is sufficient as Smart Transmit operation is the same for RF exposure switch in any combination of two different time windows. For device supporting LTE + mmW NR, this test is covered in SAR vs PD exposure switch validation.

The Smart Transmit time averaging operation is independent of the source of SAR exposure (for example, LTE vs. Sub6 NR) and ensures total time-averaged RF exposure compliance. Hence, validation of Smart Transmit in any one simultaneous SAR transmission scenario (i.e., one combination for LTE + Sub6 NR transmission) is sufficient, where the SAR exposure varies among SAR_{radio1} only, $SAR_{radio1} + SAR_{radio2}$, and SAR_{radio2} only scenarios.

| | | | |
|---|--------------------------------|--|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | | Page 13 of 65 |

The criteria to select a test configuration for validating Smart Transmit feature during SAR exposure switching scenarios is

- Select any two < 6GHz technologies/bands that the EUT supports simultaneous transmission (for example, LTE+Sub6 NR).
- Among all supported simultaneous transmission configurations, the selection order is
 1. select one configuration where both P_{limit} of radio1 and radio2 is less than their corresponding P_{max} , preferably, with different P_{limits} . If this configuration is not available, then,
 2. select one configuration that has P_{limit} less than its P_{max} for at least one radio. If this can not be found, then,
 3. select one configuration that has P_{limit} of radio1 and radio2 greater than P_{max} but with least $(P_{limit} - P_{max})$ delta.

Test for one simultaneous transmission scenario is sufficient as the feature operation is the same.

4.2.8 Exposure Category Switch

The criteria to select a test configuration for exposure category switch measurement is:

1. If the device's intended exposure mode is configured for time averaged exposure mode operation, then:
 - If $P_{limit} < P_{max}$ for at least one radio out of all supported technology/band/antenna/DSI, then:
 - (a) Out of all head exposure DSIs, select a technology/band/antenna/DSI having the least P_{limit} ($< P_{max}$), furthermore, having the largest difference between P_{max} and P_{limit} ($P_{limit} < P_{max}$) should be considered in the selection. Then, select a second DSI in the non- head exposure category DSI that has the least P_{limit} among all the non-head DSIs for the same technology/band/antenna. This technology/band/antenna and selected DSIs are used for head to non-head to head exposure switch test. If the $P_{limit} > P_{max}$ for all supported technology/band/antenna/DSI in head exposure category, then this test is not required.
 - (b) Similarly, out of all non-head exposure DSIs, select a technology/band/antenna/DSI having the least P_{limit} ($< P_{max}$), furthermore, having the largest difference between P_{max} and P_{limit} ($P_{limit} < P_{max}$) should be considered in the selection. Then, select a second DSI in the head exposure category DSI that has the least P_{limit} among all the head DSIs for the same technology/band/antenna. This technology/band/antenna and selected DSIs are used for non-head to head to non-head exposure switch test. If the $P_{limit} > P_{max}$ for all supported technology/band/antenna/DSI in non-head exposure category, then this test is not required.
 - If $P_{limit} > P_{max}$ for all supported technology/band/antenna/DSIs for both head and non-head DSI categories, then:
 - c) select a supported sub6 simultaneous transmission scenario (like LTE + FR1 NSA, or LTE interband ULCA, or FR1 interband NR-DC, etc.) in head DSI that has $P_{limit} < P_{max} + 10 \cdot \log(N)$ for all radios of selected technology(s)/band(s)/antenna(s), where N is the number of active radios in selected sub6 simultaneous transmission scenario.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 14 of 65 |

Note that the antennas determined for the selected radios of simultaneous transmission scenario should be in the same antenna group if EUT is configured with GEN2_SUB6 or GEN2_SUB6_MMW. Then, select a second DSI in the non-head exposure category that has the lowest Plimit among all the non-head DSIs for all the radios of the selected technology(s)/band(s)/antenna(s) simultaneous transmission scenario. This selected technology(s)/band(s)/antenna(s) and selected DSIs are used for head to non-head to head exposure switch test. If the head DSI has $P_{limit} > P_{max} + 10 \cdot \log(N)$ for all radios supported in sub6 simultaneous transmission scenarios, then this test is not required.

- d) select a supported sub6 simultaneous transmission scenario (like LTE + FR1 NSA, or LTE interband ULCA, or FR1 interband NR-DC, etc.) in non-head DSI that has $P_{limit} < P_{max} + 10 \cdot \log(N)$ for all radios of the selected technology(s)/band(s)/antenna(s), where N is the number of active radios in selected sub6 simultaneous transmission scenario. Note that the antennas determined for the selected radios of simultaneous transmission scenario should be in the same antenna group if EUT is configured with GEN2_SUB6 or GEN2_SUB6_MMW. Then, select a second DSI in the head exposure category that has the lowest Plimit among all the head DSIs for all the radios of the selected technology(s)/band(s)/antenna(s) simultaneous transmission scenario. This selected technology(s)/band(s)/antenna(s) and selected DSIs are used for non-head to head to non-head exposure switch test. If the non-head DSI has $P_{limit} > P_{max} + 10 \cdot \log(N)$ for all radios supported in sub6 simultaneous transmission scenarios, then this test is not required.
- Use the highest measured 1g_or_10g SAR at Plimit ($P_{limit} < P_{max}$) shown in Part 1 report for the selected tech/band/antenna/DSI out of all radio configurations and device positions in Equation (3a), (4a), (5a) and (6a) to calculate time-varying SAR. However, in the case of $P_{limit} > P_{max}$, the SAR measured in Part 1 report for the corresponding radio configuration selected and tested in Part 2 should be applied in Equation (3a), (4a), (5a) and (6a).
2. If the device's intended exposure mode is configured for peak exposure mode operation, then:
 - a) Select a supported sub6 simultaneous transmission scenario (like LTE + FR1 NSA, or LTE interband ULCA, or FR1 interband NR-DC, etc.) in head DSI that has $P_{limit} < P_{max} + 10 \cdot \log(N)$ for all radios of selected technology(s)/band(s)/antenna(s), where N is the number of active radios in selected sub6 simultaneous transmission scenario. Note that the antennas determined for the selected radios of simultaneous transmission scenario should be in the same antenna group if EUT is configured with GEN2_SUB6 or GEN2_SUB6_MMW. Then, select a second DSI in the non-head exposure category that has the lowest Plimit among all the non-head DSIs for all the radios of the selected technology(s)/band(s)/antenna(s) simultaneous transmission scenario. This selected technology(s)/band(s)/antenna(s) and selected DSIs are used for head to non-head to head exposure switch test. If the head DSI has $P_{limit} > P_{max} + 10 \cdot \log(N)$ for all radios supported in sub6 simultaneous transmission scenarios, then this test is not required.
 - b) Select a supported sub6 simultaneous transmission scenario (like LTE + FR1 NSA, or LTE interband ULCA, or FR1 interband NR-DC, etc.) in non-head DSI that has $P_{limit} < P_{max} + 10 \cdot \log(N)$ for all radios of the selected technology(s)/band(s)/antenna(s), where N is the number of active radios in selected sub6 simultaneous transmission scenario. Note that the antennas determined for the selected radios of simultaneous transmission scenario should be in the same antenna group if EUT is configured with GEN2_SUB6 or GEN2_SUB6_MMW. Then, select a second DSI in the head exposure category that has the lowest Plimit among all the head DSIs for all the radios of the selected technology(s)/band(s)/antenna(s) simultaneous transmission scenario. This selected technology(s)/band(s)/antenna(s) and selected DSIs are used for non-head to head to non-head exposure switch test. If the non-head DSI has $P_{limit} >$

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 15 of 65 |

$P_{max} + 10 \cdot \log(N)$ for all radios supported in sub6 simultaneous transmission scenarios, then this test is not required.

- Use the highest measured 1g_or_10g SAR at P_{limit} ($P_{limit} < P_{max}$) shown in Part 1 report for the selected tech/band/antenna/DSI out of all radio configurations and device positions in Equation (3a), (4a), (5a) and (6a) to calculate time-varying SAR. However, in the case of $P_{limit} > P_{max}$, the SAR measured in Part 1 report for the corresponding radio configuration selected and tested in Part 2 should be applied in Equation (3a), (4a), (5a) and (6a).

4.2.9 System Level Compliance Continuity

The purpose of system level compliance test is to demonstrate the compliance continuity in the following scenarios:

1. Across technology switch
2. During transition from single technology to multi-technology
3. In transition when WWAN went from ON to airplane mode
4. Active WLAN radio and/or Bluetooth (BT) radio with WWAN in airplane mode
5. Time window transition when WWAN in airplane mode

Note: Technology in this section refers to WWAN, WLAN or BT

The selection criteria for radios to be tested is to select a radio which has the largest P_{max}/P_{limit} ratio among all configurations supported (including SISO, MIMO, DBS, SISO+MIMO or DBS+MIMO whichever appropriate) within each technology and within the same antenna group.

If the device supports simultaneous transmission of WWAN, WLAN and BT, then the selection criteria for system level compliance continuity test is:

- For a given DSI and antenna group, select band/antenna configurations for WWAN, WLAN and BT technologies that have the largest ($P_{max} - P_{limit}$) delta. In case of multiple bands/antennas having the same difference between P_{max} and P_{limit} within a given technology, then select any one band/antenna out of them.

NOTE: The antennas corresponding to the selected technologies/bands for the system level compliance continuity test case should be in the same antenna group if EUT is configured with GEN2_SUB6 or GEN2_SUB6_MMW.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 16 of 65 |

4.3 Test Procedures for Conducted Power Measurements

This section provides general conducted power measurement procedures to perform compliance test under dynamic transmission scenarios described in Section 3. In practice, an adjustment can be made in these procedures. The justification/clarification may be provided.

4.3.1 Time-Varying Tx Power Transmission

This test is performed with the two pre-defined test sequences described in Section 4.1 for all the technologies and bands selected in Section 4.2.1. The purpose of the test is to demonstrate the effectiveness of power limiting enforcement and that the time-averaged SAR (corresponding time-averaged Tx power) does not exceed the FCC limit at all times (see Eq. (1a) and (1b)).

Test procedure

1. Measure P_{max} , measure P_{limit} and calculate $P_{reserve}$ (measured P_{limit} in dBm – $total_min_reserve$ in dB) and follow Section 4.1 to generate the test sequences for all the technologies and bands selected in Section 4.2.1. Both test sequence 1 and test sequence 2 are created based on measured P_{max} and measured P_{limit} of the DUT. Test condition to measure P_{max} and P_{limit} is:
 - a. Measure P_{max} with Smart Transmit disabled and callbox set to request maximum power.
 - b. Measure P_{limit} with Smart Transmit peak exposure mode enabled, and callbox set to request maximum power.
2. Set DUT to the intended Smart Transmit exposure mode, establish radio link in desired radio configuration, with callbox requesting the DUT's Tx power to be at pre-defined test sequence 1, measure and record Tx power versus time, and then convert the conducted Tx power into 1gSAR or 10gSAR value (see Eq. (1a)) using measured P_{limit} from above Step 1. Perform running time average to determine time-averaged power and 1gSAR or 10gSAR versus time as illustrated in Figure 4-1 where using 100-seconds time window as an example.

Note: In Eq.(1a), instantaneous Tx power is converted into instantaneous 1gSAR or 10gSAR value by applying the measured worst-case 1gSAR or 10gSAR value at P_{limit} for the corresponding technology/band/antenna/DSI reported in Part 1 report.

Note: For an easier computation of the running time average, 0 dBm can be added at the beginning of the test sequences the length of the responding time window, for example, add 0dBm for 100-seconds so the running time average can be directly performed starting with the first 100-seconds data using excel spreadsheet. This technique applies to all tests performed in this Part 2 report for easier time-averaged computation using excel spreadsheet.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 17 of 65 |




Figure 4-1
Running Average Illustration

3. Make one plot containing:
 - a. Instantaneous Tx power versus time measured in Step 2,
 - b. Requested Tx power used in Step 2 (test sequence 1),
 - c. Computed time-averaged power versus time determined in Step 2,
 - d. Time-averaged power limit (corresponding to FCC SAR limit of 1.6 W/kg for 1gSAR or 4.0W/kg for 10gSAR) given by

$$Time\ averaged\ power\ limit = meas.P_{limit} + 10 \times \log\left(\frac{FCC\ SAR\ limit}{meas.SAR_Plimit}\right) \quad (5a)$$

where $meas.P_{limit}$ and $meas.SAR_Plimit$ correspond to measured power at P_{limit} and measured SAR at P_{limit} .

4. Make another plot containing:
 - a. Computed time-averaged 1gSAR or 10gSAR versus time determined in Step 2
 - b. FCC $1gSAR_{limit}$ of 1.6W/kg or FCC $10gSAR_{limit}$ of 4.0W/kg.
5. Repeat Steps 2 ~ 4 for pre-defined test sequence 2 and replace the requested Tx power (test sequence 1) in Step 2 with test sequence 2.
6. Repeat Steps 2 ~ 5 for all the selected technologies and bands.
7. The validation criteria are, at all times, the time-averaged power versus time shown in Step 3 plot shall not exceed the time-averaged power limit (defined in Eq. (5a)), in turn, the time-averaged 1gSAR or 10gSAR versus time shown in Step 4 plot shall not exceed the FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR (i.e., Eq. (1b)).

4.3.2 Change In Call Scenario

This test is to demonstrate that Smart Transmit feature accurately accounts for the past Tx powers during time-averaging when a new call is established.

The call disconnect and re-establishment needs to be performed during power limit enforcement, i.e., when the DUT's Tx power is at $P_{reserve}$ level, to demonstrate the continuity of RF exposure management and limiting in call change scenario. In other words, the RF exposure averaged over any FCC defined

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 18 of 65 |

time window (including the time windows containing the call change) doesn't exceed FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

Test procedure

1. Measure P_{limit} for the technology/band selected in Section 4.2.2. Measure P_{limit} with Smart Transmit peak exposure mode enabled, and callbox set to request maximum power.
2. Set DUT to the intended Smart Transmit exposure mode.
3. Establish radio link with callbox in the selected technology/band.
4. Request DUT's Tx power at 0 dBm for at least one time window specified for the selected technology/band, followed by requesting DUT's Tx power to be at maximum power for about ~60 seconds, and then drop the call for ~10 seconds. Afterwards, re-establish another call in the same radio configuration (i.e., same technology/band/channel) and continue callbox requesting DUT's Tx power to be at maximum power for the remaining time of at least another full duration of the specified time window. Measure and record Tx power versus time. Once the measurement is done, extract instantaneous Tx power versus time, convert the measured conducted Tx power into 1gSAR or 10gSAR value using Eq. (1a), and then perform the running time average to determine time-averaged power and 1gSAR or 10gSAR versus time.

NOTE: In Eq.(1a), instantaneous Tx power is converted into instantaneous 1gSAR or 10gSAR value by applying the measured worst-case 1gSAR or 10gSAR value at P_{limit} for the corresponding technology/band/antenna/DSI reported in Part 1 report.

5. Make one plot containing: (a) instantaneous Tx power versus time, (b) requested power, (c) computed time-averaged power, (d) time-averaged power limit calculated using Eq.(5a).
6. Make another plot containing: (a) computed time-averaged 1gSAR or 10gSAR versus time, and (b) FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

The validation criteria are, at all times, the time-averaged power versus time shall not exceed the time-averaged power limit (defined in Eq.(5a)), in turn, the time-averaged 1gSAR or 10gSAR versus time shall not exceed the FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR (i.e., Eq. (1b)).

4.3.3 Change In Technology/Band

This test is to demonstrate the correct power control by Smart Transmit during technology switches and/or band handovers.

Similar to the change in call test in Section 4.3.2, to validate the continuity of RF exposure limiting during the transition, the technology and band handover needs to be performed when DUT's Tx power is at $P_{reserve}$ level (i.e., during Tx power enforcement) to make sure that the DUT's Tx power from previous $P_{reserve}$ level to the new $P_{reserve}$ level (corresponding to new technology/band). Since the P_{limit} could vary with technology and band, Eq. (1a) can be written as follows to convert the instantaneous Tx power in 1gSAR or 10gSAR exposure for the two given radios, respectively:

$$1g_or_10gSAR_1(t) = \frac{conducted_Tx_power_1(t)}{conducted_Tx_power_P_{limit_1}} * 1g_or_10gSAR_P_{limit_1} \quad (6a)$$

$$1g_or_10gSAR_2(t) = \frac{conducted_Tx_power_2(t)}{conducted_Tx_power_P_{limit_2}} * 1g_or_10gSAR_P_{limit_2} \quad (6b)$$

| | | | |
|---|--------------------------------|--|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | | Page 19 of 65 |

$$\frac{1}{T_{SAR}} \left[\int_{t-T_{SAR}}^{t_1} \frac{1g_or_10gSAR_1(t)}{FCC\ SAR\ limit} dt + \int_{t-T_{SAR}}^t \frac{1g_or_10gSAR_2(t)}{FCC\ SAR\ limit} dt \right] \leq 1 \quad (6c)$$

where, *conducted_Tx_power_1(t)*, *conducted_Tx_power_P_{limit_1}*, and *1g_or_10gSAR_P_{limit_1}* correspond to the measured instantaneous conducted Tx power, measured conducted Tx power at *P_{limit}*, and measured 1gSAR or 10gSAR value at *P_{limit}* of technology1/band1; *conducted_Tx_power_2(t)*, *conducted_Tx_power_P_{limit_2}*(t), and *1g_or_10gSAR_P_{limit_2}* correspond to the measured instantaneous conducted Tx power, measured conducted Tx power at *P_{limit}*, and measured 1gSAR or 10gSAR value at *P_{limit}* of technology2/band2. Transition from technology1/band1 to the technology2/band2 happens at time-instant '*t₁*'.

Test procedure

1. Measure *P_{limit}* for both the technologies and bands selected in Section 4.2.3. Measure *P_{limit}* with Smart Transmit peak exposure mode enabled, and callbox set to request maximum power.
2. Set DUT to the intended Smart Transmit exposure mode. Establish radio link with callbox in first technology/band selected. Establish radio link with callbox in first technology/band selected.
3. Request DUT's Tx power at 0 dBm for at least one time window specified for the selected technology/band, followed by requesting DUT's Tx power to be at maximum power for about ~60 seconds, and then switch to second technology/band selected. Continue with callbox requesting DUT's Tx power to be at maximum power for the remaining time of at least another full duration of the specified time window. Measure and record Tx power versus time for the full duration of the test.
4. Once the measurement is done, extract instantaneous Tx power versus time, and convert the conducted Tx power into 1gSAR or 10gSAR value using Eq. (6a) and (6b) and corresponding measured *P_{limit}* values from Step 1 of this section. Perform the running time average to determine time-averaged power and 1gSAR or 10gSAR versus time.

NOTE: In Eq.(6a) & (6b), instantaneous Tx power is converted into instantaneous 1gSAR or 10gSAR value by applying the measured worst-case 1gSAR or 10gSAR value at *P_{limit}* for the corresponding technology/band/antenna/DSI reported in Part 1 report.

5. Make one plot containing: (a) instantaneous Tx power versus time, (b) requested power, (c) computed time-averaged power, (d) time-averaged power limit calculated using Eq.(5a).
6. Make another plot containing: (a) computed time-averaged 1gSAR or 10gSAR versus time, and (b) FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

The validation criteria are, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed the FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR (i.e., Eq. (6c)).

4.3.4 Change In Antenna

This test is to demonstrate the correct power control by Smart Transmit during antenna switches from one antenna to another. The test procedure is identical to Section 4.3.3, by replacing technology/band switch operation with antenna switch. The validation criteria are, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 20 of 65 |

NOTE: If the DUT does not support antenna switch within the same technology/band, but has multiple antennas to support different frequency bands, then the antenna switch test is included as part of change in technology and band (Section 4.3.3) test.

4.3.5 Change In DSI

This test is to demonstrate the correct power control by Smart Transmit during DSI switches from one DSI to another. The test procedure is identical to Section 4.3.3, by replacing technology/band switch operation with DSI switch. The validation criteria are, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

4.3.6 Change In Time Window

This test is to demonstrate the correct power control by Smart Transmit during the change in averaging time window when a specific band handover occurs. FCC specifies time-averaging windows of 100s for Tx frequency < 3GHz, and 60s for Tx frequency between 3GHz and 6GHz.

To validate the continuity of RF exposure limiting during the transition, the band handover test needs to be performed when EUT handovers from operation band less than 3GHz to greater than 3GHz and vice versa. The equations (3a) and (3b) in Section 2 can be written as follows for transmission scenario having change in time window,

$$1gSAR_1(t) = \frac{\text{conducted_Tx_power_1}(t)}{\text{conducted_Tx_power_P}_{limit_1}} * 1g_or\ 10g_SAR_P_{limit_1} \quad (7a)$$

$$1gSAR_2(t) = \frac{\text{conducted_Tx_power_2}(t)}{\text{conducted_Tx_power_P}_{limit_2}} * 1g_or\ 10g_SAR_P_{limit_2} \quad (7b)$$

$$\frac{1}{T1_{SAR}} \left[\int_{t-T1_{SAR}}^{t_1} \frac{1g_or\ 10g_SAR_1(t)}{FCC\ SAR\ limit} dt \right] + \frac{1}{T2_{SAR}} \left[\int_{t-T2_{SAR}}^t \frac{1g_or\ 10g_SAR_2(t)}{FCC\ SAR\ limit} dt \right] \leq 1 \quad (7c)$$

where, *conducted_Tx_power_1(t)*, *conducted_Tx_power_P_{limit_1}(t)*, and *1g_or 10g_SAR_P_{limit_1}* correspond to the instantaneous Tx power, conducted Tx power at *P_{limit}*, and compliance *1g_or 10g_SAR* values at *P_{limit_1}* of band1 with time-averaging window '*T1_{SAR}*'; *conducted_Tx_power_2(t)*, *conducted_Tx_power_P_{limit_2}(t)*, and *1g_or 10g_SAR_P_{limit_2}* correspond to the instantaneous Tx power, conducted Tx power at *P_{limit}*, and compliance *1g_or 10g_SAR* values at *P_{limit_2}* of band2 with time-averaging window '*T2_{SAR}*'. One of the two bands is less than 3GHz, another is greater than 3GHz. Transition from first band with time-averaging window '*T1_{SAR}*' to the second band with time-averaging window '*T2_{SAR}*' happens at time-instant '*t_f*'.

Test procedure

1. Measure *P_{limit}* for both the technologies and bands selected in Section 4.2.6. Measure *P_{limit}* with Smart Transmit peak exposure mode enabled, and callbox set to request maximum power.
2. Set DUT to the intended Smart Transmit exposure mode.

Transition from 100s time window to 60s time window, and vice versa

3. Establish radio link with callbox in the technology/band having 100s time window selected in Section 4.2.6.
4. Request EUT's Tx power to be at 0 dBm for at least 100 seconds, followed by requesting EUT's Tx power to be at maximum power for about ~140 seconds, and then switch to second technology/band (having 60s time window) selected in Section 4.2.6. Continue with callbox requesting EUT's Tx power to be at

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 21 of 65 |

maximum power for about ~60s in this second technology/band, and then switch back to the first technology/band. Continue with callbox requesting EUT's Tx power to be at maximum power for at least another 100s. Measure and record Tx power versus time for the entire duration of the test.

5. Once the measurement is done, extract instantaneous Tx power versus time, and convert the conducted Tx power into 1gSAR or 10gSAR value (see Eq. (7a) and (7b)) using corresponding technology/band Step 1 result, and then perform 100s running average to determine time-averaged 1gSAR or 10gSAR versus time. Note that in Eq.(7a) & (7b), instantaneous Tx power is converted into instantaneous 1gSAR or 10gSAR value by applying the worst-case 1gSAR or 10gSAR value tested in Part 1 for the selected technologies/bands at P_{limit} .
6. Make one plot containing: (a) instantaneous Tx power versus time measured in Step 4.
7. Make another plot containing: (a) instantaneous 1gSAR versus time determined in Step 5, (b) computed time-averaged 1gSAR versus time determined in Step 5, and (c) corresponding regulatory $1gSAR_{limit}$ of 1.6W/kg or $10gSAR_{limit}$ of 4.0W/kg.

Transition from 60s time window to 100s time window, and vice versa

8. Establish radio link with callbox in the technology/band having 60s time window selected in Section 4.2.6.
9. Request EUT's Tx power to be at 0 dBm for at least 60 seconds, followed by requesting EUT's Tx power to be at maximum power for about ~80 seconds, and then switch to second technology/band (having 100s time window) selected in Section 4.2.6. Continue with callbox requesting EUT's Tx power to be at maximum power for about ~100s in this second technology/band, and then switch back to the first technology/band. Continue with callbox requesting EUT's Tx power to be at maximum power for the remaining time for a total test time of 500 seconds. Measure and record Tx power versus time for the entire duration of the test.
10. Repeat above Step 5~7 to generate the plots

The validation criteria is, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed the regulatory $1gSAR_{limit}$ of 1.6W/kg or $10gSAR_{limit}$ of 4.0W/kg.

4.3.7 SAR Exposure Switching

This test is to demonstrate that Smart Transmit feature is accurately accounts for switching in exposures among SAR from radio1 only, SAR from both radio1 and radio2, and SAR from radio2 only scenarios, and ensures total time-averaged RF exposure complies with the FCC limit. Here, radio1 represents primary radio (for example, LTE anchor in a NR non-standalone mode call) and radio2 represents secondary radio (for example, sub6 NR or mmW NR). The detailed test procedure for SAR exposure switching in the case of LTE+Sub6 NR non-standalone mode transmission scenario is provided in APPENDIX F.

Test procedure:

1. Measure conducted Tx power corresponding to P_{limit} for radio1 and radio2 in selected band. Test condition to measure conducted P_{limit} is:
 - Establish device in call with the callbox for radio1 technology/band. Measure conducted Tx power corresponding to radio1 P_{limit} with Smart Transmit peak exposure mode enabled, and callbox set to request maximum power.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 22 of 65 |

- Repeat above step to measure conducted Tx power corresponding to radio2 P_{limit} . If radio2 is dependent on radio1 (for example, non-standalone mode of Sub6 NR requiring radio1 LTE as anchor), then establish radio1 + radio2 call with callbox, and request all down bits for radio1 LTE. In this scenario, with callbox requesting maximum power from radio2 Sub6 NR, measured conducted Tx power corresponds to radio2 P_{limit} (as radio1 LTE is at all-down bits)
- 2. Set DUT to the intended Smart Transmit exposure mode, with EUT setup for radio1 + radio2 call. In this description, it is assumed that radio2 has lower priority than radio1. Establish device in radio1+radio2 call, and request all-down bits or low power on radio1, with callbox requesting EUT's Tx power to be at maximum power in radio2 for at least one time window. After one time window, set callbox to request EUT's Tx power to be at maximum power on radio1, i.e., all-up bits. Continue radio1+radio2 call with both radios at maximum power for at least one time window, and drop (or request all-down bits on) radio2. Continue radio1 at maximum power for at least one time window. Record the conducted Tx power for both radio1 and radio2 for the entire duration of this test.
- 3. Once the measurement is done, extract instantaneous Tx power versus time for both radio1 and radio2 links. Convert the conducted Tx power for both these radios into 1gSAR or 10gSAR value (see Eq. (6a) and (6b)) using corresponding technology/band P_{limit} measured in Step 1, and then perform the running time average to determine time-averaged 1gSAR or 10gSAR versus time.
- 4. Make one plot containing: (a) instantaneous Tx power versus time measured in Step 2.
- 5. Make another plot containing: (a) instantaneous 1gSAR versus time determined in Step 3, (b) computed time-averaged 1gSAR versus time determined in Step 3, and (c) corresponding regulatory $1gSAR_{limit}$ of 1.6W/kg or $10gSAR_{limit}$ of 4.0W/kg.

The validation criteria is, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed the regulatory $1gSAR_{limit}$ of 1.6W/kg or $10gSAR_{limit}$ of 4.0W/kg.

NOTE: If $multi_Tx_factor$ is set to > 1.0 with EFS version 19 (or higher), then in single Tx transmission scenarios, Smart Transmit ensures time-averaged RF exposure is $\leq (SAR_design_target * 10^{(+sub6\ device\ uncertainty/10)}) < regulatory\ RF\ exposure\ limit\ for\ sub6\ radio\ managed\ by\ Smart\ Transmit$. In simultaneous Tx transmission scenarios, Smart Transmit ensures time-averaged RF exposure is $\leq (SAR_design_target * multi_Tx_factor * 10^{(+sub6\ device\ uncertainty/10)}) < regulatory\ RF\ exposure\ limit\ for\ sub6\ radios\ managed\ by\ Smart\ Transmit$. These simultaneous transmission scenarios are listed below:

- 2-or-more radio scenarios within WWAN like EN-DC, LTE ULCA, etc.
- 2-or-more-radio across technologies such as WWAN+WLAN, WWAN+BT, WLAN+BT and WWAN+WLAN+BT transmission scenarios (if WLAN/BT radios are also managed by Smart Transmit).

4.3.8 Exposure Category Switch

This test is performed with the EUT being requested to transmit at maximum power in selected technology/band/antenna/DSI. The change in exposure category is preferably performed during Tx power enforcement (i.e., EUT forced to transmit at a sustainable level). One test is sufficient as this feature operation is independent of technology, band and antenna. Test procedure are:

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 23 of 65 |

In case of head to non-head to head exposure switch test, 'first DSI' in below test procedure refers to head DSI and 'second DSI' refers to non-head DSI. Similarly, in case of non-head to head to non-head exposure switch test, 'first DSI' in below test procedure refers to non-head DSI and 'second DSI' refers to head DSI.

1. Measure *P_{limit}* for all the technology(s)/band(s)/antenna(s)/DSI(s) selected following the above selection criteria. Measure *P_{limit}* with Smart Transmit Peak exposure mode enabled and callbox set to request maximum power.
2. Set EUT to intended Smart Transmit exposure mode.
3. Establish radio link with first DSI and with callbox in the selected technology(s)/band(s)/antenna(s).
4. Request EUT to transmit at 0 dBm for at least 100 seconds, followed by requesting EUT to transmit at maximum Tx power for the active radio(s) for half of the regulatory time window, and then switch to the second DSI for ~10s, and switch back to the first DSI for at least one time window. Throughout this test, when switching between DSIs (i.e., switching between exposure categories), continue with callbox requesting EUT to transmit at maximum Tx power for the active radio(s). Measure and record Tx power versus time for the entire duration of the test.
5. Once the measurement is done, extract instantaneous Tx power versus time, and convert the conducted Tx power into 1g_or_10gSAR value (see Eq. (7a) and (7b)) using the corresponding *P_{limit}* measured in Step 1 and 1g_or_10gSAR value measured in 80-W2112-4 Part 1 report, and then perform 100s running average to determine time-averaged 1g_or_10gSAR versus time as illustrated in Figure 5-1. Note that in Eq.(7a) & (7b), instantaneous Tx power is converted into instantaneous 1g_or_10gSAR value by applying the worst-case 1gSAR value for the selected technologies/bands at *P_{limit}* as reported in 80- W2112-4 Part 1 report.
6. Make one plot containing: (a) computed time-averaged normalized 1g_or_10gSAR of the selected technology(s)/band(s)/antenna(s) versus time determined in Step 5 for exposure under first DSI , (b) total time-averaged normalized exposure for exposure under first DSI if simultaneous transmission scenario was tested, and (c) normalized regulatory limit of 1.0.
7. Make another plot containing: (a) computed time-averaged 1g_or_10gSAR of the selected technology(s)/band(s)/antenna(s) versus time determined in Step 5 for exposure under second DSI, (b) total time-averaged normalized exposure for exposure under second DSI if simultaneous transmission scenario was tested, and (c) normalized regulatory limit of 1.0.

The validation criteria is, at all times, the time-averaged normalized exposure versus time shall not exceed the normalized limit of 1.0 for both first & second DSIs (i.e., both head exposure category and non-head exposure category).

4.3.9 System Level Compliance Continuity

Below is the test flow outline of the system level compliance test. The test contains 6 sections and 5 transitions: Start with WWAN radio transmission (Section A), transition to WLAN transmission (Section B), transition to simultaneous transmission of WWAN + WLAN + BT (Section C), then drop off WWAN radio and set WWAN to airplane mode, at the same time transition to WLAN+BT transmission simultaneously (Section D), transition to BT only transmission (Section E), transition to WLAN only transmission (Section F), and finally transition to simultaneous transmission of WWAN + WLAN + BT (Section G).

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 24 of 65 |




Figure 4-2

Schematic of technology transitions for system level compliance continuity test

1. Measure conducted Tx power corresponding to P_{limit} for all three (WWAN, WLAN & BT) technologies in the selected radio configurations. Test condition to measure conducted P_{limit} for each technology is:
 - Establish device in call with the callbox for the first technology in desired band. Measure conducted Tx power corresponding to the first technology P_{limit} with Smart Transmit Peak exposure mode enabled and callbox set to request maximum power (or maximum duty cycle in case of WLAN/BT).
 - Repeat above step to measure conducted Tx power corresponding to the remaining two technologies' P_{limit} . In the case of BT, measured conducted Tx power is compensated by tested duty cycle and $BT_STANDALONE$ EFS parameter, i.e., measured P_{limit} = conducted power measured in BT standalone condition / $BT_STANDALONE$ / BT_duty_cycle .
2. Set EUT to the intended Smart Transmit exposure mode.
3. As depicted in Figure 4-2, first
 - i. Section A: Establish WWAN connection with the callbox in selected WWAN radio configuration. Request EUT to transmit at 0 dBm for at least one WWAN time window (100s or 60s), followed by requesting EUT to transmit at maximum Tx power for {one WWAN time window (T_{WWAN} = 100s if $f < 3\text{GHz}$ or 60s if $3\text{GHz} < f < 6\text{GHz}$ for FCC, 360s for ICNIRP) + the maximum high power duration allowed in one T_{WWAN} }, denoted as TA_WWAN .
 - ii. Section B: After TA_WWAN , drop WWAN connection and establish WLAN connection with the callbox in selected WLAN radio configuration and request EUT to transmit at maximum duty cycle (and maximum power) for {one WLAN time-window duration (T_{WLAN} = 30s for all WLAN frequency bands for FCC, 360s for ICNIRP) + the maximum high power duration allowed in one T_{WLAN} }, denoted TB_WLAN .
 - iii. Section C: After TB_WLAN , add the selected WWAN and BT radios to have the simultaneous transmission of WWAN + WLAN + BT. Request WWAN radio to transmit at maximum power and request WLAN & BT radios to transmit at maximum duty cycle (and maximum power) for at least one $\max\{TA_WWAN, TB_WLAN, T_{BT}\}$, where, T_{BT} = 100s for FCC, 360s for ICNIRP.
 - iv. Section D: Drop WWAN connection and set WWAN modem into airplane mode. Continue requesting WLAN & BT radios to transmit at maximum duty cycle (and maximum power) for at least two times the $\max\{T_{WLAN}, T_{BT}\}$.
 - v. Section E: Drop WLAN connection. Continue requesting BT radio to transmit at maximum duty cycle (and maximum power). Continue the test for at least one T_{BT} .
 - vi. Section F: In the case of FCC time windows, after at least one T_{BT} , drop BT connection and establish back WLAN connection in selected radio configuration. Continue requesting WLAN radio to transmit

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 25 of 65 |

at maximum duty cycle (and maximum power). Continue the test for at least one max { TWLAN, TBT}. In the case of ICNIRP time windows, Section F is not required.

- vii. Section G: Disable airplane mode and add WWAN and BT connections after Section F in the case of FCC time windows (Disable airplane mode and add WWAN and WLAN connections after Section E in the case of ICNIRP time windows) to have the simultaneous transmission of WWAN + WLAN + BT. Request WWAN radio to transmit at maximum power and request WLAN & BT radios to transmit at maximum duty cycle (and maximum power) for at least one max{TA_WWAN, TB_WLAN, TBT}, where, TBT = 100s for FCC, 360s for ICNIRP.
4. Once the measurement is done, extract instantaneous Tx power versus time for all WWAN, WLAN and BT radios in selected configurations. Similar to technology/band switch test in Section 4.3.3, convert the conducted Tx power for both these radios into 1g_or_10gSAR value (see Eq. (7a) and (7b)) using corresponding technology/band Plimit measured in Step 1, and then perform running average over corresponding time-windows (i.e., 100s/60s for WWAN radio, 30s for WLAN radio and 100s for BT radio in case of FCC time-windows, and 360s for all of them in case of ICNIRP time-windows) to determine time-averaged 1g_or_10gSAR versus time as illustrated in Figure 4-1.
5. Make one plot containing: (a) computed normalized time-averaged 1g_or_10gSAR for WWAN radio configuration versus time determined in Step 4, (b) computed normalized time- averaged 1g_or_10gSAR for WLAN radio configuration versus time determined in Step 4, (c) computed normalized time-averaged 1g_or_10gSAR for WLAN radio configuration versus time determined in Step 4, (d) computed total normalized time-averaged 1g_or_10gSAR versus time (sum of Steps (5.a), (5.b) and (5.c)) determined in Step 4, and (e) corresponding normalized regulatory 1g_or_10gSARlimit limit of 1.0.

The validation criteria is, at all times, the time-averaged 1g_or_10gSAR versus time shall not exceed the regulatory 1g_or_10gSARlimit limit.

NOTE: If *multi_Tx_factor* is set to > 1.0 with EFS version 19 (or higher), then in single Tx transmission scenarios, Smart Transmit ensures time-averaged RF exposure is $\leq (SAR_design_target * 10^{(+ sub6 device uncertainty/10)}) < regulatory RF exposure limit$ for sub6 radio managed by Smart Transmit. In simultaneous Tx transmission scenarios, Smart Transmit ensures time-averaged RF exposure is $\leq (SAR_design_target * multi_Tx_factor * 10^{(+ sub6 device uncertainty/10)}) < regulatory RF exposure limit$ for sub6 radios managed by Smart Transmit. These simultaneous transmission scenarios are listed below:

- 2-or-more radio scenarios within WWAN like EN-DC, LTE ULCA, etc.
- 2-or-more-radio across technologies such as WWAN+WLAN, WWAN+BT, WLAN+BT and WWAN+WLAN+BT transmission scenarios (if WLAN/BT radios are also managed by Smart Transmit).

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 26 of 65 |

5 MEASUREMENT TEST SETUP (FREQ < 6 GHZ)

5.1 Conducted Measurement Test setup

Legacy test setup

The Rohde & Schwarz CMW500 callbox was used in this test. The test setup schematic is shown in Figure 5-1a (Appendix A – Test Setup Photo 1, 2, and 3) for measurements with a single antenna of DUT, and in Figure 5-1b (Appendix A – Test Setup Photo 5) for measurements involving antenna switch. For single antenna measurement, one port (RF1 COM) of the callbox is connected to the RF port of the DUT using a directional coupler. For technology/band switch measurement, one port (RF1 COM) of the callbox used for signaling two different technologies is connected to a combiner, which is in turn connected to a directional coupler. The other end of the directional coupler is connected to a splitter to connect to two RF ports of the DUT corresponding to the two antennas of interest. In the setups, a power meter is used to tap the directional coupler for measuring the conducted output power of the DUT. For all legacy conducted tests, only RF1 COM port of the callbox is used to communicate with the DUT.

All the path losses from RF port of DUT to the callbox RF COM port and to the power meter are calibrated and automatically entered as offsets in the callbox and the power meter via test scripts on the PC used to control callbox and power meter

Sub6 NR test setup:

The Anritsu MT8000A callbox was used in this test. The test setup schematic is the same as the Legacy Test Setup shown in Figure 5-1a (Appendix A – Test Setup Photo 4). One port of the callbox is connected to the RF port of the DUT using a directional coupler. In the setup, the power meter is used to tap the directional coupler for measuring the conducted output power of the DUT.

All the path losses from RF port of DUT to the callbox RF COM port and to the power meter are calibrated and automatically entered as offsets in the callbox and the power meter via test scripts on the PC used to control callbox and power meter.

LTE+Sub6 NR test setup:

LTE conducted port and Sub6 NR conducted port are different on this DUT, therefore, the LTE and Sub6 NR signals for power meter measurement are performed on separate paths as shown below in Figure 5-1c (Also UXM was used in this setup). (Appendix A – Test Setup Photo 6).

All the path losses from RF port of DUT to the callbox RF COM port and to the power meter are calibrated and automatically entered as offsets in the callbox and the power meter via test scripts on the PC used to control callbox and power meter.

LTE+LTE Interband ULCA test setup:

LTE conducted PCC port and LTE conducted SCC conducted port are different on this EUT, therefore, the LTE PCC and LTE SCC signals for power meter measurement are performed on separate paths as shown below in Figure 5-1c (Appendix A – Test Setup Photo 7).

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 27 of 65 |

All the path losses from RF port of DUT to the callbox RF COM port and to the power meter are calibrated and automatically entered as offsets in the callbox and the power meter via test scripts on the PC used to control callbox and power meter.

WLAN SISO test setup:

The Rohde & Schwarz CMW500 callbox was used in this test. The test setup schematic is shown in Figure 5-1d (Appendix A– Test Setup Photo 8) for measurements with a single antenna of DUT and in Figure 5-1g (Appendix A – Test Setup Photo 11) for time-window switch measurements.

All the path losses from RF port of DUT to the callbox RF COM port and to the power meter are calibrated and automatically entered as offsets in the callbox and the power meter via test scripts on the PC used to control callbox and power meter.

WLAN DBS test setup:


The Rohde & Schwarz CMW500 callbox was used in this test. WLAN 2.4GHz port and WLAN 5GHz conducted port are the same on this DUT, therefore, the WLAN signals for power meter measurement are performed on separate paths as shown below in Figure 5-1e (Appendix A – Test Setup Photo 9).

All the path losses from RF port of DUT to the callbox RF COM port and to the power meter are calibrated and automatically entered as offsets in the callbox and the power meter via test scripts on the PC used to control callbox and power meter.

System continuity test setup:


The Rohde & Schwarz CMW500 callbox was used in this test. WWAN conducted port and BT conducted port are the same on this DUT, while the WLAN conducted port is separate. Therefore, the WWAN, WLAN, and BT signals for power meter measurement are performed on paths shown below in Figure 5-1f (Appendix A – Test Setup Photo 10).

All the path losses from RF port of DUT to the callbox RF COM port and to the power meter are calibrated and automatically entered as offsets in the callbox and the power meter via test scripts on the PC used to control callbox and power meter.




(a) Appendix B – Test Setup Photo 1, 2, 3, 4


| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 28 of 65 |



(b) Appendix B – Test Setup Photo 5




(c) Appendix B – Test Setup Photo 6 and 7




(d) Appendix B – Test Setup Photo 8

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 29 of 65 |




(e) Appendix A – Test Setup Photo 9



(f) Appendix A – Test Setup Photo 10

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 30 of 65 |



(g) Appendix A - Test Setup 11
Figure 5-1
Conducted power measurement setup

Both the callbox and power meter are connected to the PC using GPIB cables. Two test scripts are custom made for automation, and the test duration set in the test scripts is 500 seconds.

For time-varying Tx power measurement, the PC runs the 1st test script to send GPIB commands to control the callbox's requested power versus time, while at the same time to record the conducted power measured at DUT RF port using the power meter. The commands sent to the callbox to request power are:

- 0dBm for 100 seconds
- test sequence 1 or test sequence 2 (defined in Section 4.1 and generated in Section 4.2.1), for 360 seconds.
- stay at the last power level of test sequence 1 or test sequence 2 for the remaining time.

Power meter readings are periodically recorded every 100ms. A running average of this measured Tx power over 100 seconds is performed in the post-data processing to determine the 100s-time averaged power.

For call drop, technology/band/antenna switch, and DSI switch tests, after the call is established, the callbox is set to request the DUT's Tx power at 0dBm for 100 seconds while simultaneously starting the 2nd test script runs at the same time to start recording the Tx power measured at DUT RF port using the power meter. After the initial 100 seconds since starting the Tx power recording, the callbox is set to request maximum power from the DUT for the rest of the test. Note that the call drop/re-establish, or technology/band/antenna switch or DSI switch is manually performed when the Tx power of DUT is at $P_{reserve}$ level. See Section 4.3 for detailed test procedure of call drop test, technology/band/antenna switch test and DSI switch test.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 31 of 65 |

6 TEST CONFIGURATIONS (FREQ < 6 GHZ)

6.1 Sub6 transmission

The P_{limit} values, corresponding to 1.0 W/kg (1gSAR) and 2.5 W/kg (10gSAR) of SAR_{design_target} , for technologies and bands supported by DUT are derived in Part 0 report and summarized in Table 6-1. Note all P_{limit} power levels entered in Table 6-1 correspond to average power levels after accounting for duty cycle in the case of TDD modulation schemes.

Table 6-1
 P_{limit} for supported technologies and bands (P_{limit} in EFS file)

| Exposure Scenario | | | Maximum Tune-Up Output Power* | Body-Worn, Hotspot, or Phablet | Head |
|--------------------------|---------|------------------|--|-----------------------------------|--------------------|
| Averaging Volume | | | | 1g/10g | 1g |
| Spacing | | | | 10mm, 0mm | 0mm |
| DSI | | | | 0 | 1 |
| Technology/Band | Antenna | Antenna Group | P _{max} | P _{limit} | P _{limit} |
| GSM 850 | A | AG0 | 25.1 | 29.8 | 29.8 |
| GSM 850 | E | AG1 | 25.1 | 26.5 | 21.0 |
| GSM 1900 | A | AG0 | 22.1 | 18.8 | 32.7 |
| UMTS 850 | A | AG0 | 24.0 | 28.5 | 30.3 |
| UMTS 850 | E | AG1 | 24.0 | 27.0 | 20.5 |
| UMTS 1750 | A | AG0 | 23.0 | 19.0 | 30.6 |
| UMTS 1900 | A | AG0 | 23.0 | 18.0 | 30.2 |
| LTE Band 12/17 | A | AG0 | 24.3 | 27.5 | 28.5 |
| LTE Band 12/17 | E | AG1 | 24.3 | 26.0 | 21.5 |
| LTE Band 13 | A | AG0 | 24.0 | 27.2 | 28.1 |
| LTE Band 13 | E | AG1 | 24.0 | 26.4 | 21.5 |
| LTE Band 26/5 | A | AG0 | 24.0 | 28.2 | 29.5 |
| LTE Band 26/5 | E | AG1 | 24.0 | 26.5 | 21.0 |
| LTE Band 66/4 | A | AG0 | 23.5 | 19.0 | 31.2 |
| LTE Band 66/4 | F | AG1 | 23.5 | 21.0 | 18.5 |
| LTE Band 25/2 | A | AG0 | 23.0 | 18.0 | 30.3 |
| LTE Band 25/2 | F | AG1 | 23.0 | 20.0 | 19.0 |
| LTE Band 41 PC3 | B | AG0 | 22.0 | 19.0 | 34.0 |
| LTE Band 41 PC3 | F | AG1 | 22.0 | 19.0 | 15.5 |
| LTE Band 41 PC2 | B | AG0 | 21.4 | 19.0 | 34.0 |
| LTE Band 41 PC2 | F | AG1 | 21.4 | 19.0 | 15.5 |
| NR Band n5 | A | AG0 | 24.0 | 25.9 | 30.1 |
| NR Band n5 | E | AG1 | 24.0 | 26.5 | 21.0 |
| NR Band n66 | A | AG0 | 23.0 | 19.0 | 31.5 |
| NR Band n66 | F | AG1 | 22.5 | 21.0 | 18.5 |
| NR Band n25/n2 | A | AG0 | 22.5 | 18.0 | 28.9 |
| NR Band n25/n2 | F | AG1 | 22.5 | 20.0 | 19.0 |
| NR Band n41 PC3 (Path 1) | F | AG1 | 24.0 | 18.5 | 16.5 |
| NR Band n41 PC3 (Path 1) | B | AG0 | 21.0 | 19.0 | 16.5 |
| NR Band n41 PC3 (Path 1) | E | AG1 | 20.0 | 16.0 | 13.5 |
| NR Band n41 PC3 (Path 1) | D | AG0 | 19.0 | 16.0 | 13.5 |
| NR Band n41 PC3 (Path 2) | B | AG0 | 24.0 | 20.0 | 21.0 |
| NR Band n41 PC3 (Path 2) | F | AG1 | 21.0 | 18.5 | 16.5 |
| NR Band n41 PC3 (Path 2) | D | AG0 | 22.0 | 18.0 | 19.0 |
| NR Band n41 PC3 (Path 2) | E | AG1 | 18.0 | 16.0 | 16.0 |
| NR Band n77 PC2 | F | AG1 | 25.0 | 18.5 | 14.5 |
| NR Band n77 PC2 | C | AG0 | 19.0 | 14.0 | 10.0 |
| NR Band n77 PC2 | I | AG1 | 24.0 | 18.5 | 14.5 |
| NR Band n77 PC2 | D | AG0 | 19.0 | 14.0 | 10.0 |
| 2.4 GHz WiFi | H | AG1 | 19.0 | 19.5 | 16.0 |
| 2.4 GHz WiFi | J | AG1 | 19.0 | 25.4 | 16.0 |
| 2.4 GHz WiFi | MIMO | AG1 | 17.0 | 19.4 | 16.0 |
| 5 GHz WiFi | H | AG1 | 17.0 | 15.0 | 15.0 |
| 5 GHz WiFi | E | AG1 | 17.0 | 15.0 | 15.0 |
| 5 GHz WiFi | MIMO | AG1 | 17.0 | 15.0 | 15.0 |
| 6 GHz WiFi | H | AG1 | 16.0 | 8.0 | 16.8 |
| 6 GHz WiFi | E | AG1 | 16.0 | 8.0 | 22.9 |
| 6 GHz WiFi | MIMO | AG1 | 16.0 | 8.0 | 17.0 |
| 2.4 GHz Bluetooth | H | AG1 | 17.4 | 21.3 | 18.5 |
| 2.4 GHz Bluetooth | J | AG1 | 17.4 | 25.9 | 20.4 |
| 2.4 GHz Bluetooth | MIMO | AG1 | 12.9 | 17.9 | 17.2 |
| 2.4 GHz Bluetooth LE | H | AG1 | 18.9 | 21.3 | 18.9 |
| 2.4 GHz Bluetooth LE | J | AG1 | 18.4 | 25.9 | 20.4 |
| 2.4 GHz Bluetooth LE | MIMO | AG1 | 12.9 | 17.9 | 17.2 |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 32 of 65 |

* Maximum tune up target power, P_{max} , is configured in NV settings in DUT to limit maximum transmitting power. This power is converted into peak power in NV settings for TDD schemes. The DUT maximum allowed output power is equal to $P_{max} + 1$ dB device uncertainty.

Based on selection criteria described in Section 4.2.1, the selected technologies/bands for testing time-varying test sequences are highlighted in yellow in Table 6-1. Per the manufacturer, the *Total_min_res_ratio* is set to 0.5 in EFS and is used in Part 2 test.

The radio configurations used in Part 2 test for selected technologies, bands, DSIs and antennas are listed in Table 6-2. The corresponding worst-case radio configuration 1gSAR values for selected technology/band/DSI are extracted from Part 1 report and are listed in the last column of Table 6-2.

Based on equations (1a), (2a), (3a) and (4a), it is clear that Part 2 testing outcome is normalized quantity, which implies that it can be applied to any radio configuration within a selected technology/band/DSI. Thus, as long as applying the worst-case SAR obtained from the worst radio configuration in Part 1 testing to calculate time-varying SAR exposure in equations (1a), (2a), (3a) and (4a), the accuracy in compliance demonstration remains the same. Therefore, there may be some differences between the radio configuration selected for Part 2 testing and the radio configuration associated with worst-case SAR obtained in the Part 1 evaluation.

The measured P_{limit} for all the selected radio configurations are listed in below Table 6-2. P_{max} was also measured for radio configurations selected for testing time-varying Tx power transmission scenarios in order to generate test sequences following the test procedures in Section 4.1.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 33 of 65 |

Table 6-2
Radio configurations selected for Part 2 test

| Test Case # | Test Scenario | Tech | Band | Antenna | DSI | Channel | Frequency [MHz] | Test Configurations | SAR Exposure Scenario | Part 1 Worst Case Measured SAR at Plimit (W/kg) | EFS Plimit [dBm] | Tune-up Pmax [dBm] | Measured Plimit [dBm] | Measured Pmax [dBm] |
|-------------|---|------------|------------|---------|-----|---------|-----------------|---------------------------------|-----------------------|---|------------------|--------------------|-----------------------|---------------------|
| 1 | Time Varying Test Sequences | GSM | 1900 | A | 0 | 661 | 1880 | GPRS 4 Tx Slots - | Bottom Edge, 10mm | 0.675 | 18.8 | 21.3 | 18.47 | 21.23 |
| 2 | | WCDMA | 5 | E | 1 | 4183 | 836.5 | RMC - | Left Cheek | 0.872 | 20.5 | 24.0 | 20.88 | 24.62 |
| 3 | | LTE | 41 PC3 | B | 0 | 40620 | 2593.0 | QPSK 1/50/20 MHz BW | Right Edge, 10mm | 0.400 | 19.0 | 22.0 | 18.77 | 21.61 |
| 4 | | NR | n66/SA | F | 1 | 349000 | 3750 | DFT-S-OFDM, QPSK 1/1/45 MHz BW | Right Tilt | 0.709 | 18.5 | 22.5 | 18.40 | 22.55 |
| 5 | | WLAN | 2.4GHz | J | 1 | 1 | 2412 | 802.11b 20MHz BW DSSS | Left Cheek | 0.403 | 16.0 | 19.0 | 16.37 | 18.92 |
| 6 | Change in Call | NR | n77 PC2/SA | F | 1 | 650000 | 3750 | DFT-S-OFDM, QPSK 1/1/100 MHz BW | Right Tilt | 0.732 | 14.5 | 25.0 | 15.37 | 22.52* |
| 7 | Change in Technology/Band/Antenna | LTE | 41 PC3 | F | 1 | 40620 | 2593 | QPSK 1/50/20 MHz BW | Right Tilt | 0.916 | 15.5 | 22.0 | 15.88 | 22.32 |
| | | WCDMA | 5 | E | 1 | 4183 | 836.5 | RMC - | Left Cheek | 0.872 | 20.5 | 24.0 | 20.88 | 24.62 |
| 8 | Change in Time Window | LTE | 5 | E | 1 | 20525 | 836.5 | QPSK 1/25/10 MHz BW | Left Cheek | 0.925 | 21.0 | 24.0 | 21.07 | 24.32 |
| | | WLAN | 5GHz | E | 1 | 36 | 5180 | 802.11ac 20MHz BW DSSS | Right Tilt | 0.449 | 15.0 | 17.0 | 15.61 | 17.23 |
| 9 | WWAN SAR Exposure Switching (EN-DC) Same Time-Window | LTE | 5 | E | 1 | 20525 | 836.5 | QPSK 1/25/10 MHz BW | Left Cheek | 0.925 | 21.0 | 24.0 | 21.07 | 24.32 |
| | | Sub6 NR | n66/SA | F | 1 | 349000 | 3750 | DFT-S-OFDM, QPSK 1/1/45 MHz BW | Right Tilt | 0.709 | 18.5 | 22.5 | 18.40 | 22.55 |
| 10 | WWAN SAR Exposure Switching (EN-DC) Different Time-Window | LTE | 5 | E | 1 | 20525 | 836.5 | QPSK 1/25/10 MHz BW | Left Cheek | 0.925 | 21.0 | 24.0 | 21.07 | 24.32 |
| | | Sub6 NR | n77 PC2/SA | F | 1 | 650000 | 3750 | DFT-S-OFDM, QPSK 1/1/100 MHz BW | Right Tilt | 0.732 | 14.5 | 25.0 | 15.37 | 22.52* |
| 11 | WLAN Dual Band Simultaneous | WLAN | 5GHz | E | 1 | 36 | 5180 | 802.11ac 20MHz BW DSSS | Right Tilt | 0.449 | 15.0 | 17.0 | 15.61 | 17.23 |
| | | | 2.4GHz | J | 1 | 6 | 2437 | 802.11n 20MHz BW DSSS | Left Cheek | 0.403 | 16.0 | 17.0 | 16.37 | 17.02 |
| 12 | System Level Compliance Continuity | WWAN (LTE) | 25 | F | 1 | 26365 | 1882.5 | QPSK 1/50/20 MHz BW | Right Tilt | 0.900 | 19.0 | 23.0 | 19.02 | 23.14 |
| | | Bluetooth | 2.4 | H | 1 | 0 | 2402 | DSSS | Right Cheek | 0.757 | 18.9 | 18.9 | 18.76 | 18.76 |
| | | WLAN | 5GHz | E | 1 | 36 | 5180 | 802.11ac 20MHz BW DSSS | Right Tilt | 0.449 | 15.0 | 17.0 | 15.61 | 17.23 |
| 13 | Exposure Category Switch | NR | n77 PC2/SA | F | 0 | 650000 | 3750 | DFT-S-OFDM, QPSK 1/1/100 MHz BW | Top Edge, 10mm | 0.402 | 18.5 | 25.0 | 19.35 | 22.52* |
| | | | | | 1 | 650000 | 3750 | DFT-S-OFDM, QPSK 1/1/100 MHz BW | Right Tilt | 0.732 | 14.5 | 25.0 | 15.37 | 22.52* |
| 14 | Interband ULCA | LTE | 66 (PCC) | F | 1 | 132322 | 1745 | QPSK 1/50/20 MHz BW | Right Cheek | 0.772 | 18.5 | 23.5 | 18.89 | 23.76 |
| | | | 5 (SCC) | E | 1 | 20525 | 836.5 | QPSK 1/25/10 MHz BW | Left Cheek | 0.925 | 21.0 | 24.0 | 21.07 | 24.32 |

*NR TDD is 70% DC due to the limitations & capabilities of callbox.

Note: The device uncertainty of P_{max} is +/- 1 dB as provided by manufacturer.

Note: The above P_{max} value for GPRS850 and GPRS1900 are for 4 Tx Slots.

| | | |
|---|---------------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 34 of 65 |

Table 6-3
DSI and Corresponding Exposure Scenarios

| Scenario | Description | SAR Test Cases |
|---------------------------|---|--|
| Head (DSI = 1) | <ul style="list-style-type: none"> Device positioned next to head Receiver Active | <i>Head SAR per KDB Publication 648474 D04</i> |
| Hotspot mode (DSI = 0) | <ul style="list-style-type: none"> Device transmits in hotspot mode near body Hotspot Mode Active | <i>Hotspot SAR per KDB Publication 941225 D06</i> |
| Phablet (DSI = 0) | <ul style="list-style-type: none"> Device is held with hand | <i>Phablet SAR per KDB Publication 648474 D04 & KDB Publication 616217 D04</i> |
| Body-worn (DSI = 0) | <ul style="list-style-type: none"> Device being used with a body-worn accessory | <i>Body-worn SAR per KDB Publication 648474 D04</i> |

Based on the selection criteria described in Section 4.2, the radio configurations for the Tx varying transmission test cases listed in Section 3 are:

1. Technologies and bands for time-varying Tx power transmission: Based on selection criteria in Section 4.2.1, The test case 1~5 listed in Table 6-2 are selected to test with the test sequences defined in Section 4.2.1 in both time-varying conducted power measurement and time-varying SAR measurement.
2. Technology and band for change in call test: Based on selection criteria in Section 4.2.2, LTE Band 41, having the lowest P_{limit} among all technologies and bands (test case 6 in Table 6-2), is selected for performing the call drop test in conducted power setup.
3. Technologies and bands for change in technology/band/antenna test: Based on selection criteria in Section 4.2.3 and 4.2.4, test case 7 in Table 6-2 is selected for handover test from a technology/band within one technology group (LTE Band B41 PC3 , DSI=1, antenna F), to a technology/band in the same DSI within another technology group (WCDMA Band 5, DSI=1, antenna E) in conducted power setup.
4. Technologies and bands for change in time-window: Based on selection criteria in Section 4.2.6, for a given DSI=1, test case 8 in Table 6-2 is selected for time window switch between 100s window (LTE Band 5, Antenna E) and 30s window (WLAN 5GHz, Antenna E) in conducted power setup.
5. Technologies and bands for switch in SAR exposure: Based on selection criteria in Section 4.2.7 Scenario 1, test case 9 in Table 6-2 is selected for SAR exposure switching test in one of the supported simultaneous WWAN transmission scenario, i.e., LTE + Sub6 NR active in the same 100s time window, in conducted power setup. Based on selection criteria in Section 4.2.7 Scenario 2, test case 10 in Table 6-2 is selected for SAR exposure switching test in one of the supported simultaneous WWAN transmission scenario, i.e., LTE + Sub6 NR active in different time window (100s to 60s time window), in conducted power setup. Test case 11 in Table 6-2 is selected for SAR exposure switching test in one of the supported simultaneous DBS WLAN transmission scenario, i.e., WLAN + WLAN active in the same 30s time window, in conducted power setup.
6. Technologies and bands for switch in exposure category: Based on selection criteria in Section 4.2.8 Scenario 1, test case 13 in Table 6-2 is selected for switch in exposure category test by establishing a call in NR n77 PC2/SA in DSI=1 (head exposure) and then handing over to DSI=0 (non-head exposure) scenario in conducted power setup, and vice versa.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 35 of 65 |

7. Technologies and bands for system level compliance continuity: Based on selection criteria in Section 4.2.9, test case 12 in Table 6-2 is selected for system level compliance continuity test by establishing a call in LTE Band 25 in DSI=1 and then handing over to WLAN and BT in scenario described in section 4.3.9.
8. Technologies and bands for switch in SAR exposure (Interband ULCA): Based on selection criteria in Section 4.2.7, test case 14 in Table 6-2 is selected for SAR exposure switching test in one of the supported simultaneous LTE transmission scenario, i.e., LTE interband ULCA, in conducted power setup.

Note: All switching and EN-DC test cases (#7 - #14) were done with modes/bands within the same antenna group.

Note: System level compliance continuity was performed with USB disconnected from DUT per Qualcomm 80-W2112-51 RevAE guidance.

6.2 EFS v23 Verification

Per Qualcomm's 80-w2112-5 document, embedded file system (EFS) version 23 products are required to be verified for Smart Tx generation for relevant MCC settings. It was confirmed that this DUT contains embedded file system (EFS) version 23 configured for Smart Tx second generation (GEN2) for Sub6 with MCC settings for the US market.

| EFS v23 Generation | MCC |
|--------------------|-----|
| GEN2_Sub6 | 310 |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 36 of 65 |

7 CONDUCTED TX CASES (FREQ < 6 GHZ)

7.1 Time-varying Tx Power

The measurement setup is shown in Figure 5-1. The purpose of the time-varying Tx power measurement is to demonstrate the effectiveness of power limiting enforcement and that the time-averaged Tx power when represented in time-averaged 1gSAR or 10gSAR values does not exceed FCC limit as shown in Eq. (1a) and (1b), rewritten below:

$$1g_or_10gSAR(t) = \frac{conducted_Tx_power(t)}{conducted_Tx_power_P_{limit}} * 1g_or_10gSAR_P_{limit} \quad (1a)$$

$$\frac{\frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t 1g_or_10gSAR(t) dt}{FCC\ SAR\ limit} \leq 1 \quad (1b)$$

where, $conducted_Tx_power(t)$, $conducted_Tx_power_P_{limit}$, and $1g_or_10gSAR_P_{limit}$ correspond to the measured instantaneous conducted Tx power, measured conducted Tx power at P_{limit} , and measured 1gSAR and 10gSAR values at P_{limit} reported in Part 1 test (listed in Table 6-2 of this report as well).

Following the test procedure in Section 4.3.1, the conducted Tx power measurement for all selected configurations are reported in this section. In all the conducted Tx power plots, the green curve represents time-averaged power and red line represents the conducted power limit that corresponds to FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

Similarly, in all the 1g or 10gSAR plots (when converted using Eq. (1a)), the green curve represents the 100s/60s-time averaged 1gSAR or 10gSAR value calculated based on instantaneous 1gSAR or 10gSAR; and the red line limit represents the FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.


Time-varying Tx power measurements were conducted on test cases #1 ~ #5 in Table 6-2, by generating test sequence 1 and test sequence 2 given in APPENDIX C: using measured P_{limit} and measured P_{max} (last two columns of Table 6-2) for each of these test cases. Measurement results for test cases #1 ~ #5 are given in Sections 9.1.1-9.1.5.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 37 of 65 |

7.1.1 GSM/GPRS/EDGE 1900, Antenna A

Test result for test sequence 1:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




| | |
|---|--------|
| | (W/kg) |
| FCC 1gSAR limit | 1.6 |
| Max 100s-time averaged 1gSAR (green curve) | 0.836 |
| Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 6-2). | |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 38 of 65 |

Test result for test sequence 2:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




| | (W/kg) |
|--|--------|
| FCC 1gSAR limit | 1.6 |
| Max 100s-time averaged 1gSAR (green curve) | 0.808 |
| Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 6-2). | |

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 39 of 65 |

7.1.2 WCDMA Band 5, Antenna E

Test result for test sequence 1:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




| | (W/kg) |
|---|--------|
| FCC 1gSAR limit | 1.6 |
| Max 100s-time averaged 1gSAR (green curve) | 0.914 |
| Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 6-2). | |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 40 of 65 |

Test result for test sequence 2:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




| | (W/kg) |
|--|--------|
| FCC 1gSAR limit | 1.6 |
| Max 100s-time averaged 1gSAR (green curve) | 0.890 |
| Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 6-2). | |

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 41 of 65 |

7.1.3 LTE Band 41, Antenna B

Test result for test sequence 1:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




| | |
|---|--------|
| | (W/kg) |
| FCC 1gSAR limit | 1.6 |
| Max 100s-time averaged 1gSAR (green curve) | 0.396 |
| Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 6-2). | |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 42 of 65 |

Test result for test sequence 2:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




| | |
|---|--------|
| | (W/kg) |
| FCC 1gSAR limit | 1.6 |
| Max 100s-time averaged 1gSAR (green curve) | 0.396 |
| Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 6-2). | |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 43 of 65 |

7.1.4 NR n26 SA, Antenna F

Test result for test sequence 1:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




| | (W/kg) |
|---|--------|
| FCC 1gSAR limit | 1.6 |
| Max 100s-time averaged 1gSAR (green curve) | 0.694 |
| Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 6-2). | |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 44 of 65 |

Test result for test sequence 2:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




| | (W/kg) |
|--|--------|
| FCC 1gSAR limit | 1.6 |
| Max 100s-time averaged 1gSAR (green curve) | 0.698 |
| Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 6-2). | |

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 45 of 65 |

7.1.5 WLAN 2.4GHz, Antenna J

Test result for test sequence:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




| | |
|---|--------|
| | (W/kg) |
| FCC 1gSAR limit | 1.6 |
| Max 30s-time averaged 1gSAR (green curve) | 0.456 |
| Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 6-2). | |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 46 of 65 |

7.2 Change in Call

This test was measured LTE Band NR n77 PC2/SA, Antenna F, DSI = 1, and with callbox requesting maximum power. The call drop was manually performed when the DUT is transmitting at $P_{reserve}$ level as shown in the plot below. The measurement setup is shown in Figure 5-1a. The detailed test procedure is described in Section 4.3.2.

Call drop test result:
Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:



| | |
|---|--------|
| | (W/kg) |
| FCC 1gSAR limit | 1.6 |
| Max 60s-time averaged 1gSAR (green curve) | 0.733 |
| Validated | |

The test result validated the continuity of power limiting in call change scenario.


| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 47 of 65 |

7.3 Change in Technology/Band/Antenna

This test was conducted with callbox requesting maximum power, and with a technology switch from LTE Band 41 PC3, Antenna F, DSI = 1 to WCDMA Band 5, Antenna E, DSI = 1. Following procedure detailed in Section 4.3.3, and using the measurement setup shown in Figure 5-1b, the technology/band switch was performed when the DUT is transmitting at $P_{reserve}$ level as shown in the plot below.

Test result for change in technology/band/Antenna:

Time-averaged conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (6a), (6b) and (6c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the normalized FCC limit of 1.0:



| | (W/kg) |
|---|--------|
| FCC normalized SAR limit | 1.0 |
| Max 100s-time averaged normalized SAR (green curve) | 0.576 |
| Validated | |

The test result validated the continuity of power limiting in technology/band/Antenna switch scenario.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 48 of 65 |


7.4 Change in Time Window

This test was conducted with callbox requesting maximum power, and with time-window switch between LTE Band 5, Antenna E, DSI = 1 (100s window) and WLAN 5GHz, Antenna E, DSI = 1 (30s window). Following procedure detailed in Section 4.3.6, and using the measurement setup shown in Figure 5-1g, the time-window switch via tech/band/antenna switch was performed when the EUT is transmitting at $P_{reserve}$ level.

7.4.1 Test case 1: transition from LTE Band 5 to WLAN 5GHz (i.e., 100s to 300s), then back to LTE Band 5

Test result for change in time-window (from 100s to 30s to 100s):

All the conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (7a), (7b) and (7c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit. Equation (7a) is used to convert the Tx power of device to obtain 100s-averaged normalized SAR in LTE Band 5 as shown in black curve. Similarly, equation (7b) is used to obtain 30s-averaged normalized SAR in WLAN 5GHz as shown in orange curve. Equation (7c) is used to obtain total time-averaged normalized SAR as shown in green curve (i.e., sum of black and orange curves).



| | |
|--|--------|
| | (W/kg) |
| FCC normalized total exposure limit | 1.0 |
| Max time averaged normalized SAR (green curve) | 0.581 |
| Validated | |


| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 49 of 65 |

Plot Notes: Maximum power is requested by callbox for the entire duration of the test, with tech/band switches from 100s-to-30s window at ~247s time stamp, and from 30s-to-100s window at ~292s time stamp. Smart Transmit controls the Tx power during these time-window switches to ensure total time-averaged RF exposure, i.e., sum of black and orange curves given by equation (7c), is always compliant. In time-window switch test, at all times the total time-averaged normalized RF exposure (green curve) should not exceed normalized *SAR_design_target* + 1dB device uncertainty. In this test, with a maximum normalized SAR of 0.581 being ≤ 0.79 ($= 1.0/1.6 + 1\text{dB device uncertainty}$), the above test result validated the continuity of power limiting in time-window switch scenario.

7.4.2 Test case 2: transition from WLAN 5GHz to LTE Band 5 (i.e., 30s to 100s), then back to WLAN 5GH

Test result for change in time-window (from 30s to 100s to 30s):

All the conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (7a), (7b) and (7c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit. Equation (7a) is used to convert the Tx power of device to obtain 30s-averaged normalized SAR in WLAN 5Ghz as shown in black curve. Similarly, equation (7b) is used to obtain 100s-averaged normalized SAR in LTE Band 5 as shown in orange curve. Equation (7c) is used to obtain total time-averaged normalized SAR as shown in green curve (i.e., sum of black and orange curves).



| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 50 of 65 |

| | |
|--|--------|
| | (W/kg) |
| FCC normalized total exposure limit | 1.0 |
| Max time averaged normalized SAR (green curve) | 0.585 |
| Validated | |

Plot Notes: Maximum power is requested by callbox for the entire duration of the test, with tech/band switches from 30s-to-100s window at ~160s time stamp, and from 100s-to-30s window at ~274s time stamp. Smart Transmit controls the Tx power during these time-window switches to ensure total time-averaged RF exposure, i.e., sum of black and orange curves given by equation (7c), is always compliant. In time-window switch test, at all times the total time-averaged normalized RF exposure (green curve) should not exceed normalized $SAR_{design_target} + 1\text{dB}$ device uncertainty. In this test, with a maximum normalized SAR of 0.585 being ≤ 0.79 ($= 1.0/1.6 + 1\text{dB}$ device uncertainty), the above test result validated the continuity of power limiting in time-window switch scenario.


7.5 SAR Exposure Switching (EN-DC) – Same Time-Window

This test was conducted with callbox requesting maximum power, and with the EUT in LTE Band 5 + Sub6 NR Band n66 call. Following procedure detailed in Section 4.3.7 and Appendix D.2, and using the measurement setup shown in Figure 5-1c since LTE and Sub6 NR are on different antenna ports, the SAR exposure switch measurement is performed with the EUT in various SAR exposure scenarios, i.e., in SAR_{sub6NR} only scenario ($t = 0\text{s} \sim 120\text{s}$), $SAR_{sub6NR} + SAR_{LTE}$ scenario ($t = 120\text{s} \sim 240\text{s}$) and SAR_{LTE} only scenario ($t > 240\text{s}$).

Plot Notes: All the conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (7a), (7b) and (7c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit. Equation (7a) is used to convert the LTE Tx power of device to obtain 100s-averaged normalized SAR in LTE Band 5 as shown in black curve. Similarly, equation (7b) is used to obtain 100s-averaged normalized SAR in Sub6 NR n66 as shown in orange curve. Equation (7c) is used to obtain total time-averaged normalized SAR as shown in green curve (i.e., sum of black and orange curves).

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 51 of 65 |

Total Normalized Time-averaged RF Exposure
Tech: LTE, Band 5 / Tech: NR5G SUB6, Band n66



| | |
|--|--------|
| | (W/kg) |
| FCC normalized total exposure limit | 1.0 |
| Max time averaged normalized SAR (green curve) | 0.577 |
| Validated | |


Plot Notes: Device starts predominantly in Sub6 NR SAR exposure scenario between 0s and 120s, and in LTE SAR + Sub6 NR SAR exposure scenario between 120s and 240s, and in predominantly in LTE SAR exposure scenario after t=240s. Here, Smart Transmit allocates a maximum of 100% of exposure margin for Sub6 NR. This corresponds to a normalized 1gSAR exposure value = $100\% \times 0.709 \text{ W/kg measured SAR at Sub6 NR } P_{\text{limit}} / 1.6 \text{ W/kg limit} = 0.443 \pm 1 \text{ dB device related uncertainty}$ (see orange curve between 120s). For predominantly LTE SAR exposure scenario, maximum normalized 1gSAR exposure should correspond to 100% exposure margin = $0.925 \text{ W/kg measured SAR at LTE } P_{\text{limit}} / 1.6 \text{ W/kg limit} = 0.578 \pm 1 \text{ dB device related uncertainty}$ (see black curve after t = 240s). Additionally, in SAR exposure switch test, at all times the total time-averaged normalized RF exposure (green curve) should not exceed normalized SAR_design_target + 1dB device uncertainty. In this test, with a maximum normalized SAR of 0.577 being $\leq 0.79 (= 1.0/1.6 + 1 \text{ dB device uncertainty})$, the above test result validated the continuity of power limiting in SAR exposure switch scenario.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 52 of 65 |

7.6 SAR Exposure Switching (EN-DC) – Different Time-Window

This test was conducted with callbox requesting maximum power, and with the EUT in LTE Band 5 + Sub6 NR Band n77 PC2/SA call. Following procedure detailed in Section 4.3.7 and Appendix D.2, and using the measurement setup shown in Figure 5-1c since LTE and Sub6 NR are on different antenna ports, the SAR exposure switch measurement is performed with the EUT in various SAR exposure scenarios, i.e., in SAR_{sub6NR} only scenario (t =0s ~120s), SAR_{sub6NR} + SAR_{LTE} scenario (t =120s ~ 240s) and SAR_{LTE} only scenario (t > 240s).

Plot Notes: All the conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (7a), (7b) and (7c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit. Equation (7a) is used to convert the LTE Tx power of device to obtain 100s-averaged normalized SAR in LTE Band 5 as shown in black curve. Similarly, equation (7b) is used to obtain 60s-averaged normalized SAR in Sub6 NR n77 PC2/SA as shown in orange curve. Equation (7c) is used to obtain total time-averaged normalized SAR as shown in green curve (i.e., sum of black and orange curves).



| | |
|--|--------|
| | (W/kg) |
| FCC normalized total exposure limit | 1.0 |
| Max time averaged normalized SAR (green curve) | 0.571 |
| Validated | |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 53 of 65 |


Plot Notes: Device starts predominantly in Sub6 NR SAR exposure scenario between 0s and 120s, and in LTE SAR + Sub6 NR SAR exposure scenario between 120s and 240s, and in predominantly in LTE SAR exposure scenario after t=240s. Here, Smart Transmit allocates a maximum of 100% of exposure margin for Sub6 NR. This corresponds to a normalized 1gSAR exposure value = $100\% \times 0.732 \text{ W/kg}$ measured SAR at Sub6 NR $P_{limit} / 1.6 \text{ W/kg}$ limit = $0.458 \pm 1 \text{ dB}$ device related uncertainty (see orange curve between 120s). For predominantly LTE SAR exposure scenario, maximum normalized 1gSAR exposure should correspond to 100% exposure margin = 0.925 W/kg measured SAR at LTE $P_{limit} / 1.6 \text{ W/kg}$ limit = $0.578 \pm 1 \text{ dB}$ device related uncertainty (see black curve after t = 240s). Additionally, in SAR exposure switch test, at all times the total time-averaged normalized RF exposure (green curve) should not exceed normalized $SAR_{design_target} + 1 \text{ dB}$ device uncertainty. In this test, with a maximum normalized SAR of 0.571 being ≤ 0.79 ($= 1.0/1.6 + 1 \text{ dB}$ device uncertainty), the above test result validated the continuity of power limiting in SAR exposure switch scenario.

7.7 SAR Exposure Switching WLAN DBS

This test was conducted with callbox requesting maximum power, and with the EUT in WLAN 2.4GHz + WLAN 5GHz call. Following procedure detailed in Section 4.3.7, and using the measurement setup shown in Figure 5-1d since WLAN channels have different antenna ports, the SAR exposure switch measurement is performed with the EUT in various SAR exposure scenarios, i.e., in $SAR_{WLAN\ 2.4GHz}$ only scenario (t = 0s ~ 120s), $SAR_{WLAN\ 2.4GHz} + SAR_{WLAN\ 5GHz}$ scenario (t = 120s ~ 240s) and $SAR_{WLAN\ 5GHz}$ only scenario (t > 240s).

Plot Notes: All the conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (7a), (7b) and (7c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit. Equation (7a) is used to convert the WLAN Tx power of device to obtain 30s-averaged normalized SAR in WLAN 5GHz as shown in black curve. Similarly, equation (7b) is used to obtain 30s-averaged normalized SAR in WLAN 2.4GHz as shown in orange curve. Equation (7c) is used to obtain total time-averaged normalized SAR as shown in green curve (i.e., sum of black and orange curves).

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 54 of 65 |




| | |
|--|--------|
| | (W/kg) |
| FCC normalized total exposure limit | 1.0 |
| Max time averaged normalized SAR (green curve) | 0.321 |
| Validated | |

Plot Notes: In this test, the total time-averaged normalized RF exposure (green curve) did not exceed normalized limit of 1.0 at all times, the above test result validated the continuity of power limiting in SAR exposure switch scenario.

7.8 System Level Compliance Continuity

This test was conducted with callbox requesting maximum power, and with the EUT in LTE Band 25 + WLAN 5GHz + Bluetooth call. Following procedure detailed in Section 4.3.9, and using the measurement setup shown in Figure 5-1f since WWAN, WLAN, Bluetooth are in different antenna ports, the SAR exposure switch measurement is performed with the EUT in various SAR exposure scenarios, WWAN radio transmission, WLAN transmission, simultaneous transmission of WWAN + WLAN + BT, simultaneous transmission of WLAN + BT in airplane mode, BT in airplane mode, WLAN in airplane mode, and finally simultaneous transmission of WWAN + WLAN + BT.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 55 of 65 |



| | |
|--|--------|
| | (W/kg) |
| FCC normalized total exposure limit | 1.0 |
| Max time averaged normalized SAR (green curve) | 0.810 |
| Validated | |

In this test, the total time-averaged normalized RF exposure (green curve) did not exceed normalized limit of 1.0 at all times, the above test result validated the total RF exposure compliance in system level compliance continuity test scenario.


Note: This test was performed with USB disconnected from DUT per Qualcomm 80-W2112-51 RevYE guidance.

7.9 Exposure Category Switch

This test was conducted with callbox requesting maximum power, and with exposure category switch between NR n77 PC2/SA, Antenna F, DSI = 1 (Head) and LTE Band 48, Antenna F, DSI = 0 (non-Head). Following procedure detailed in Section 4.3.8 and using the measurement setup shown in Figure 5-1a, the exposure category switch was performed when the EUT is transmitting at Preserve level.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 56 of 65 |

7.9.1 Test case 1: Transition from NR n77 PC2/SA DSI=1 (Head) to NR n77 PC2/SA DSI=0 (non-Head), then back to DSI=1 (Head)




| | (W/kg) |
|--|--------|
| FCC normalized total exposure limit | 1.0 |
| Max 60s-time averaged normalized SAR (first DSI, orange curve) | 0.453 |
| Validated | |

Plot Notes: Maximum power is requested by callbox for the entire duration of the test, time-averaged exposure in head DSI gradually increases until t~184s where the device is switched from head exposure DSI (first DSI, orange curve) to non-head exposure DSI (second DSI, black curve) as evident from increase in exposure of black curve and no change in orange curve between t~184s and t~196s. At t~196s, device is switched back from non-head exposure to head exposure as evident from increase in exposure of orange curve and no change in black curve. In this test, the time-averaged normalized RF exposure in head exposure DSI (orange curve) did not exceed normalized limit of 1.0 at all times, and is less than normalized SAR of 0.453 being ≤ 0.79 ($= 1.0/1.6 + 1\text{dB}$ device uncertainty), validating the exposure continuity when switching between head exposure and non-head exposure categories.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 57 of 65 |

7.9.2 Test case 2: Transition from NR n77 PC2/SA DSI=0 (non-Head) to NR n77 PC2/SA DSI=1 (Head), then back to DSI=0 (non-Head)



| | (W/kg) |
|---|--------|
| FCC normalized total exposure limit | 1.0 |
| Max 100s-time averaged normalized SAR (first DSI, orange curve) | 0.252 |
| Validated | |


Plot Notes: Maximum power is requested by callbox for the entire duration of the test, time-averaged exposure in head DSI gradually increases until t~193s where the device is switched from non-head exposure DSI (first DSI, orange curve) to head exposure DSI (second DSI, black curve) as evident from increase in exposure of black curve and no change in orange curve between t~193s and t~208s. At t~193s, device is switched back from head exposure to non-head exposure as evident from increase in exposure of orange curve and no change in black curve. In this test, the time-averaged normalized RF exposure in head exposure DSI (orange curve) did not exceed normalized limit of 1.0 at all times, and is less than normalized SAR of 0.252 being ≤ 0.79 ($= 1.0/1.6 + 1\text{dB}$ device uncertainty), validating the exposure continuity when switching between head exposure and non-head exposure categories.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 58 of 65 |

7.10 SAR exposure Switching (Inter-band ULCA)

This test was conducted with callbox requesting maximum power, and with the EUT switch between LTE Band 5 (PCC), Antenna E, DSI = 1 and LTE Band 66 (SCC), Antenna F, DSI =1. The measurement setup shown in Figure 5-1(c) was used because each LTE do not share the same antenna port. The SAR exposure switch measurement is performed with the EUT in various SAR exposure scenarios, i.e., in SAR_{SCC} max scenario (t =0s ~120s), SAR_{PCC} + SAR_{SCC} max scenario (t =120s ~ 240s) and SAR_{PCC} max scenario (t > 240s).

All the conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (3a), (3b) and (3c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit. Equation (3a) is used to convert the LTE Tx power of device to obtain 100s-averaged normalized SAR in LTE B66 (PCC) as shown in black curve. Similarly, equation (3b) is used to obtain 100s-averaged normalized SAR in LTE B5 (SCC) as shown in orange curve. Equation (3c) is used to obtain total time-averaged normalized SAR as shown in green curve (i.e., sum of black and orange curves).



| | |
|--|--------|
| | (W/kg) |
| FCC normalized total exposure limit | 1.0 |
| Max time averaged normalized SAR (green curve) | 0.567 |
| Validated | |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 59 of 65 |

Plot Notes: Device starts predominantly in LTE B66 (SCC) SAR exposure scenario between 0s and 120s, and in LTE B5 (PCC) SAR + LTE B66 (SCC) SAR exposure scenario between 120s and 240s, and in predominantly in LTE B5 (PCC) SAR exposure scenario after t=240s. In SAR exposure switch test, at all times the total time-averaged normalized RF exposure (green curve) should not exceed normalized *SAR_design_target* + 1 dB device uncertainty. In this test, with a maximum normalized SAR of 0.567 being ≤ 0.79 ($= 1.0/1.6 + 1$ dB device uncertainty), the above test result validated the continuity of power limiting in SAR exposure switch scenario.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 60 of 65 |

8 EQUIPMENT LIST

| Manufacturer | Model | Description | Cal Date | Cal Interval | Cal Due | Serial Number |
|-----------------------|-------------------|---|------------|--------------|------------|-----------------------|
| Agilent | E4404B | Spectrum Analyzer | N/A | N/A | N/A | MY45113242 |
| Agilent | E4438C | ESG Vector Signal Generator | 11/14/2023 | Annual | 11/14/2024 | MY45093852 |
| Agilent | E4438C | ESG Vector Signal Generator | 11/15/2023 | Annual | 11/15/2024 | MY45092078 |
| Agilent | N5182A | MXG Vector Signal Generator | 3/15/2024 | Annual | 3/15/2025 | MY47420651 |
| Agilent | 8753ES | S-Parameter Vector Network Analyzer | 1/10/2024 | Annual | 1/10/2025 | MY40001472 |
| Amplifier Research | 15S1G6 | Amplifier | CBT | N/A | CBT | 433972 |
| Amplifier Research | 15S1G6 | Amplifier | CBT | N/A | CBT | 433974 |
| Anritsu | MT8000A | Radio Communication Test Station | 4/10/2024 | Annual | 4/10/2025 | 6261987983 |
| Anritsu | MT8821C | Radio Communication Analyzer MT8821C | 5/15/2024 | Annual | 5/15/2025 | 6262150047 |
| Anritsu | MA24106A | USB Power Sensor | 12/4/2023 | Annual | 12/4/2024 | 1520501 |
| Anritsu | MA24106A | USB Power Sensor | 4/15/2024 | Annual | 4/15/2025 | 1827528 |
| Anritsu | MA2411B | Pulse Power Sensor | 7/1/2024 | Annual | 7/1/2025 | 1911105 |
| Anritsu | MA2411B | Pulse Power Sensor | 7/10/2024 | Annual | 7/10/2025 | 1126066 |
| COMTECH | AR85729-5/5759B | Solid State Amplifier | CBT | N/A | CBT | M3W1A00-1002 |
| COMTECH | AR85729-5 | Solid State Amplifier | CBT | N/A | CBT | M1S5A00-009 |
| Control Company | 4052 | Long Stem Thermometer | 2/27/2024 | Biennial | 2/27/2026 | 240174346 |
| Control Company | 4040 | Therm./ Clock/ Humidity Monitor | 4/15/2024 | Biennial | 4/15/2026 | 240310280 |
| Control Company | 4052 | Long Stem Thermometer | 2/27/2024 | Biennial | 2/27/2026 | 240171096 |
| K & L | 11SH10-1300/U4000 | High Pass Filter | CBT | N/A | CBT | 11SH10-1300/U4000 - 2 |
| Keysight Technologies | 772D | Dual Directional Coupler | CBT | N/A | CBT | MY52180215 |
| Keysight Technologies | E7515B | UXM 5G Wireless Test Platform | CBT | N/A | CBT | MY59150289 |
| Keysight Technologies | E7770A | Common Interface Unit | CBT | N/A | CBT | MY58290483 |
| Krytar | 110067006 | Directional Coupler, 10 - 67 GHz | CBT | N/A | CBT | 200391 |
| MCL | BW-N6W5+ | 6dB Attenuator | CBT | N/A | CBT | 1139 |
| Mini Circuits | ZA2PD2-63-S+ | Power Splitter | CBT | N/A | CBT | SUU64901930 |
| Mini Circuits | ZAPD-2-272-S+ | Power Splitter | CBT | N/A | CBT | SF702001405 |
| MiniCircuits | NLP-1200+ | Low Pass Filter | CBT | N/A | CBT | VUU78201318 |
| MiniCircuits | SLP-2400+ | Low Pass Filter | CBT | N/A | CBT | R8979500903 |
| MiniCircuits | VLF-6000+ | Low Pass Filter | CBT | N/A | CBT | N/A |
| Mini-Circuits | BW-N20W5+ | DC to 18 GHz Precision Fixed 20 dB Attenuator | CBT | N/A | CBT | N/A |
| Mini-Circuits | NLP-2950+ | Low Pass Filter DC to 2700 MHz | CBT | N/A | CBT | N/A |
| Mini-Circuits | NLP-1200+ | Low Pass Filter DC to 1000 MHz | CBT | N/A | CBT | N/A |
| Mini-Circuits | BW-N20W5 | Power Attenuator | CBT | N/A | CBT | 1226 |
| Mini-Circuits | ZUDC10-83-S+ | Directional Coupler, 0.3 to 8.0 GHz | CBT | N/A | CBT | 2050 |
| Narda | 4216-10 | Directional Coupler, 0.5 to 8.0 GHz, 10 dB | CBT | N/A | CBT | 1492 |
| Narda | 4216-10 | Directional Coupler, 0.5 to 8.0 GHz, 10 dB | CBT | N/A | CBT | 1493 |
| Narda | 4772-3 | Attenuator | CBT | N/A | CBT | 9406 |
| Narda | BW-S3W2 | Attenuator | CBT | N/A | CBT | 120 |
| Narda | BW-S10W2+ | Attenuator | CBT | N/A | CBT | 831 |
| Narda | 4014C-6 | 4 - 8 GHz SMA 6 dB Directional Coupler | CBT | N/A | CBT | N/A |
| Newmark System | NSC-G2 | Motion Controller | CBT | N/A | CBT | 1007-D |
| Pasternack | PE2208-6 | Bidirectional Coupler | CBT | N/A | CBT | N/A |
| Pasternack | PE2209-10 | Bidirectional Coupler | CBT | N/A | CBT | N/A |
| Rohde & Schwarz | CMW500 | Wideband Radio Communication Tester | 1/11/2024 | Annual | 1/11/2025 | 150117 |
| Rohde & Schwarz | CMW500 | Wideband Radio Communication Tester | 1/10/2024 | Annual | 1/10/2025 | 131454 |
| Rohde & Schwarz | NRP8S | 3 Path Dipole Power Sensor | 1/16/2024 | Annual | 1/16/2025 | 109956 |
| Rohde & Schwarz | NRP8S | 3 Path Dipole Power Sensor | 12/14/2023 | Annual | 12/14/2024 | 109052 |
| Rohde & Schwarz | NRP8S | 3-Path Dipole Power Sensor | 12/14/2023 | Annual | 12/14/2024 | 108168 |
| Rohde & Schwarz | NRP50S | 3-Path Dipole Power Sensor | 12/14/2023 | Annual | 12/14/2024 | 101339 |

Notes:

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler, or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. Each equipment item is used solely within its respective calibration period.

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 61 of 65 |

9 MEASUREMENT UNCERTAINTIES

For SAR Measurements

| a | c | d | e= f(d,k) | f | g | h = c x f/e | i = c x g/e | k |
|---|---------------|----------------|--------------|-----------------------|--------------------------|--------------------------------|----------------------------------|----------------|
| Uncertainty Component | Tol. (± %) | Prob. Dist. | Div. | c _i 1gm | c _i 10 gms | 1gm u _i (± %) | 10gms u _i (± %) | v _i |
| Measurement System | | | | | | | | |
| Probe Calibration | 6.55 | N | 1 | 1.0 | 1.0 | 6.6 | 6.6 | ∞ |
| Axial Isotropy | 0.25 | N | 1 | 0.7 | 0.7 | 0.2 | 0.2 | ∞ |
| Hemishperical Isotropy | 1.3 | N | 1 | 0.7 | 0.7 | 0.9 | 0.9 | ∞ |
| Boundary Effect | 2.0 | R | 1.73 | 1.0 | 1.0 | 1.2 | 1.2 | ∞ |
| Linearity | 0.3 | N | 1 | 1.0 | 1.0 | 0.3 | 0.3 | ∞ |
| System Detection Limits | 0.25 | R | 1.73 | 1.0 | 1.0 | 0.1 | 0.1 | ∞ |
| Readout Electronics | 0.3 | N | 1 | 1.0 | 1.0 | 0.3 | 0.3 | ∞ |
| Response Time | 0.8 | R | 1.73 | 1.0 | 1.0 | 0.5 | 0.5 | ∞ |
| Integration Time | 2.6 | R | 1.73 | 1.0 | 1.0 | 1.5 | 1.5 | ∞ |
| RF Ambient Conditions - Noise | 3.0 | R | 1.73 | 1.0 | 1.0 | 1.7 | 1.7 | ∞ |
| RF Ambient Conditions - Reflections | 3.0 | R | 1.73 | 1.0 | 1.0 | 1.7 | 1.7 | ∞ |
| Probe Positioner Mechanical Tolerance | 0.4 | R | 1.73 | 1.0 | 1.0 | 0.2 | 0.2 | ∞ |
| Probe Positioning w/ respect to Phantom | 6.7 | R | 1.73 | 1.0 | 1.0 | 3.9 | 3.9 | ∞ |
| Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation | 4.0 | R | 1.73 | 1.0 | 1.0 | 2.3 | 2.3 | ∞ |
| Test Sample Related | | | | | | | | |
| Test Sample Positioning | 2.7 | N | 1 | 1.0 | 1.0 | 2.7 | 2.7 | 35 |
| Device Holder Uncertainty | 1.67 | N | 1 | 1.0 | 1.0 | 1.7 | 1.7 | 5 |
| Output Power Variation - SAR drift measurement | 5.0 | R | 1.73 | 1.0 | 1.0 | 2.9 | 2.9 | ∞ |
| SAR Scaling | 0.0 | R | 1.73 | 1.0 | 1.0 | 0.0 | 0.0 | ∞ |
| Phantom & Tissue Parameters | | | | | | | | |
| Phantom Uncertainty (Shape & Thickness tolerances) | 7.6 | R | 1.73 | 1.0 | 1.0 | 4.4 | 4.4 | ∞ |
| Liquid Conductivity - measurement uncertainty | 4.2 | N | 1 | 0.78 | 0.71 | 3.3 | 3.0 | 10 |
| Liquid Permittivity - measurement uncertainty | 4.1 | N | 1 | 0.23 | 0.26 | 1.0 | 1.1 | 10 |
| Liquid Conductivity - Temperature Uncertainty | 3.4 | R | 1.73 | 0.78 | 0.71 | 1.5 | 1.4 | ∞ |
| Liquid Permittivity - Temperature Uncertainty | 0.6 | R | 1.73 | 0.23 | 0.26 | 0.1 | 0.1 | ∞ |
| Liquid Conductivity - deviation from target values | 5.0 | R | 1.73 | 0.64 | 0.43 | 1.8 | 1.2 | ∞ |
| Liquid Permittivity - deviation from target values | 5.0 | R | 1.73 | 0.60 | 0.49 | 1.7 | 1.4 | ∞ |
| Combined Standard Uncertainty (k=1) | RSS | | | | | 11.5 | 11.3 | 60 |
| Expanded Uncertainty (95% CONFIDENCE LEVEL) | k=2 | | | | | 23.0 | 22.6 | |

| | | |
|---|--------------------------------|-----------------------------------|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 62 of 65 |

10 CONCLUSION

10.1 Measurement Conclusion

The SAR evaluation indicates that the DUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 63 of 65 |

11 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 64 of 65 |

- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

| | | |
|--|---------------------------------------|--|
| FCC ID: A3LSMS938B | RF EXPOSURE PART 2 TEST REPORT | Approved by: Technical Manager |
| Document S/N: 1M2408260069-02.A3L (Rev1) | DUT Type: Portable Handset | Page 65 of 65 |