



EMI TEST REPORT

Test Report No. : 10658081H-B

Applicant : Sharp Corporation, Communication Systems Division.
Type of Equipment : Smart Phone
Model No. : SH-03G
FCC ID : APYHRO00217
Test standard : FCC Part 15 Subpart B 2015 Class B
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This test report covers EMC technical requirements. It does not cover administrative issues such as Manual or non-EMC test related Requirements. (if applicable)

Date of test: March 17, 2015

**Representative
test engineer:**

T. Shimada

Takumi Shimada
Engineer
Consumer Technology Division

Approved by :

T. Hatakeda

Takahiro Hatakeda
Leader
Consumer Technology Division



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.
*As for the range of Accreditation in NVLAP, you may refer to the WEB address,
<http://www.ul.com/japan/jpn/pages/services/emc/about/mark1/index.jsp#nvlap>

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

13-EM-F0429

REVISION HISTORY

Original Test Report No.: 10658081H-B

[illegible]

CONTENTS	PAGE
SECTION 1: Customer information	4
SECTION 2: Equipment under test (E.U.T.)	4
SECTION 3: Test specification, procedures & results	5
SECTION 4: Operation of E.U.T. during testing	8
SECTION 5: Conducted Emission	10
SECTION 6: Radiated Emission	11
APPENDIX 1: Data of EMI test	12
Conducted Emission	12
Radiated Emission	14
APPENDIX 2: Test instruments	18
APPENDIX 3: Photographs of test setup.....	19
Conducted Emission	19
Radiated Emission	20
Worst Case Position (Horizontal: Y-axis/ Vertical:Y-axis)	22

SECTION 1: Customer information

Company Name : Sharp Corporation, Communication Systems Division.
Address : 2-13-1 Iida Hachihonmatsu HigashiHiroshima-City, Hiroshima, 739-0192,
Japan.
Telephone Number : +81-82-420-1552
Facsimile Number : +81-82-420-1555
Contact Person : Hachiro Hidaka

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Smart Phone
Model No. : SH-03G
Serial No. : Refer to Section 4, Clause 4.2
Receipt Date of Sample : March 13, 2015
Country of Mass-production : China
Condition of EUT : Production prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT : No Modification by the test lab

2.2 Product description

Feature of EUT : SH-03G is Hex-band LTE(B1/B3/B17/B19/B21/B28) and Quad-band W-CDMA (FDD1/5/6/19) and Quad-band GSM(850/900/1800/1900) Smart Phone.
The EUT has the function that Bluetooth wireless technology interface and wireless LAN technical interface for establishing contact and transmitting data with certain device.
Clock frequencies in the system : CPU: 1,958.4MHz (max)
Source oscillation: 19.2MHz(CPU), 27.0MHz(I2C), 27.12MHz(NFC), 48.0MHz(WLAN/BT)

SECTION 3: Test specification, procedures & results

3.1 Test specification

Test specification : FCC Part 15 Subpart B: 2015, final revised on January 21, 2015

Title : FCC 47CFR Part15 Radio Frequency Device
Subpart B Unintentional Radiators

3.2 Procedures and results

Item	Test Procedure	Limits	Deviation	Worst margin	Result
Conducted emission	ANSI C63.4: 2009 7. AC powerline conducted emission measurements	Class B	N/A	[QP] 2.0dB 0.16812MHz, L [AV] 9.5dB 0.16822MHz, N (USB Data Com Mode) 0.16837MHz, N (Standby Mode)	Complied
Radiated emission	ANSI C63.4: 2009 8. Radiated emission measurements	Class B	N/A	2.4dB 123.200MHz, Vertical, QP	Complied

*Note: UL Japan, Inc's EMI Work Procedure 13-EM-W0420.

3.3 Addition to standard

No addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Test room (semi-anechoic chamber)	Conducted emission (+dB)
	150kHz-30MHz
No.1	3.5dB
No.2	3.5dB
No.3	3.4dB
No.4	3.5dB

Test room (semi-anechoic chamber)	Radiated emission						
	(3m*)(+dB)				(1m*)(+dB)		(0.5m*)(+dB)
	9kHz -30MHz	30MHz -300MHz	300MHz -1GHz	1GHz -10GHz	10GHz -18GHz	18GHz -26.5GHz	26.5GHz -40GHz
No.1	4.3dB	5.5dB	6.3dB	5.5dB	5.8dB	5.8dB	4.3dB
No.2	4.2dB	5.4dB	6.3dB	5.4dB	5.7dB	5.9dB	5.6dB
No.3	4.4dB	5.4dB	6.4dB	5.2dB	5.5dB	5.8dB	5.5dB
No.4	4.7dB	5.6dB	6.4dB	5.3dB	5.7dB	5.9dB	5.5dB

*3m/1m/0.5m = Measurement distance

Conducted Emission test

[QP] The data listed in this report meets the limits unless the uncertainty is taken into consideration.

[AV] The data listed in this test report has enough margin, more than the site margin.

Radiated emission test(3m)

The data listed in this report meets the limits unless the uncertainty is taken into consideration.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

3.5 Test Location

UL Japan, Inc. Ise EMC Lab. *NVLAP Lab. code: 200572-0
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	4.0 x 4.5 x 2.7m	4.0 x 4.5 m	-
No.6 measurement room	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	8.8 x 4.6 x 2.8m	2.4 x 2.4m	-
No.11 measurement room	-	6.2 x 4.7 x 3.0m	4.8 x 4.6m	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Data of EMI, Test instruments, and Test set up

Refer to APPENDIX.

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Smart Phone	SH-03G	004401/11/539512/7	Sharp Corporation	EUT
B	microSD Memory Card	SD-C02G	None	TOSHIBA	-
C	Personal Computer	PP11L	CN-0D4571-48643-58P-1053	Dell	-
D	Mouse	M-UAG120	LZ733B70EVV	TOSHIBA	-
E	AC Adapter(PC)	LA65NS1-00	CN-0YD637-71615-64Q-2243	Dell	-
F	Printer	895Cxi	SG8BA1W18J	Hewlett Packard	-
G	AC Adapter(Printer)	C4557-60004	C8L01B	Hewlett Packard	-

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	USB Data Cable	1.20	Shielded	Shielded	-
2	Mouse Cable	0.72	Unshielded	Unshielded	-
3	AC Adaptor Cable (PC)	1.76	Unshielded	Unshielded	-
4	AC Power Cable (PC)	1.20	Unshielded	Unshielded	-
5	Parallel Cable	1.65	Shielded	Shielded	-
6	AC Adapter Cable (printer)	2.00	Unshielded	Unshielded	-
7	AC Power Cable (printer)	1.75	Unshielded	Unshielded	-

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 5: Conducted Emission

5.1 Operating environment

Test place	: No. 1 semi anechoic chamber
Temperature	: See data
Humidity	: See data

5.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT and its peripherals was aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from the LISN/AMN. I/O cables that were connected to the other peripherals were bundled in center. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane. Each EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN/AMN to the input power source. All unused 50 ohm connectors of the LISN/AMN were resistivity terminated in 50 ohm when not connected to the measuring equipment. Photographs of the set up are shown in Appendix 3.

Frequency range	: 0.15 MHz-30MHz
EUT position	: Table top
EUT operation mode	: See Clause 4.1

5.3 Test procedure

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT within a semi anechoic chamber. The EUT was connected to a Line Impedance Stabilization Network (LISN)/ Artificial Mains network (AMN). An overview sweep with peak detection has been performed. The measurements have been performed with a quasi-peak detector and if required, with an average detector.

The conducted emission measurements were made with the following detector function of the test receiver.

Detector Type	: Quasi-Peak and CISPR AV
IF Bandwidth	: 9 kHz

5.4 Test result

Summary of the test results: Pass

Date: March 17, 2015

Test engineer: Takumi Shimada

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 6: Radiated Emission

6.1 Operating environment

Test place : No. 1 semi anechoic chamber
Temperature : See data
Humidity : See data

6.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane. The EUT was set on the edge of the tabletop.
Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength. Photographs of the set up are shown in Appendix 3.

6.3 Test conditions

Frequency range : 30MHz-300MHz (Biconical antenna) / 300MHz-1000MHz (Logperiodic antenna)
1000MHz -13000MHz (Horn antenna)
Test distance : 3m
EUT position : Table top
EUT operation mode : See Clause 4.1

6.4 Test procedure

The height of the measuring antenna varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.
The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver.
The radiated emission measurements were made with the following detector function of the Test Receiver.

Frequency	Below 1GHz	Above 1GHz
Instrument used	Test Receiver	Test Receiver
IF Bandwidth	QP: BW 120kHz	PK: BW 1MHz, CISPR AV: BW 1MHz

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

6.5 Test result

Summary of the test results: Pass

Date: March 17, 2015 Test engineer: Takumi Shimada, Ken Fujita

APPENDIX 1: Data of EMI test

Conducted Emission

DATA OF CONDUCTED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2015/03/17

Report No. : 10658081H

Temp./Humi. : 20deg. C / 40% RH
Engineer : Takumi Shimada

Mode / Remarks : USB Data Com Mode

LIMIT : FCC15.107(a) QP ClassB
FCC15.107(a) AV ClassB



Frequency [MHz]	Reading Level		Corr. Factor [dB]	Results		Limit		Margin		Phase	Comment
	QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dB]	AV [dB]		
0.15000	49.2	12.5	13.2	62.4	25.7	66.0	56.0	3.6	30.3	N	
0.16822	49.7	32.3	13.2	62.9	45.5	65.0	55.0	2.1	9.5	N	
0.19969	41.5	7.7	13.2	54.7	20.9	63.6	53.6	8.9	32.7	N	
0.22301	41.5	24.9	13.3	54.8	38.2	62.7	52.7	7.9	14.5	N	
2.02105	24.5	17.9	13.5	38.0	31.4	56.0	46.0	18.0	14.6	N	
3.81504	28.5	11.5	13.8	42.3	25.3	56.0	46.0	13.7	20.7	N	
0.15000	49.0	12.3	13.2	62.2	25.5	66.0	56.0	3.8	30.5	L	
0.16812	49.9	32.1	13.2	63.1	45.3	65.1	55.1	2.0	9.8	L	
0.19917	41.7	7.8	13.2	54.9	21.0	63.6	53.6	8.7	32.6	L	
0.22435	41.7	25.4	13.3	55.0	38.7	62.7	52.7	7.7	14.0	L	
1.96423	25.3	19.5	13.5	38.8	33.0	56.0	46.0	17.2	13.0	L	
3.81804	31.5	16.2	13.8	45.3	30.0	56.0	46.0	10.7	16.0	L	

CHART : WITH FACTOR. Peak hold data. CALCULATION : RESULT = READING + C.F (LISN + ATTN + CABLE)
Except for the above table : adequate margin data below the limits.

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission (Below 1GHz)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2015/03/17

Report No. : 10658081H

Temp./Humi. : 20deg.C / 40% RH
Engineer : Ken Fujita

Mode / Remarks : USB Data Com Mode Worst axis (Hori Y, Vert Y)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
Except for the data below : adequate margin data below the limits.



Frequency [MHz]	Reading [dBuV]	DET	Antenna	Loss&	Level [dBuV/m]	Angle [Deg]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]	Comment
			Factor [dB/m]	Gain [dB]							
72.030	54.9	QP	6.3	-30.8	30.4	115	256	Hori.	40.0	9.6	
123.200	58.3	QP	12.9	-30.1	41.1	189	100	Vert.	43.5	2.4	
124.200	48.7	QP	13.0	-30.0	31.7	201	153	Hori.	43.5	11.8	
365.596	46.4	QP	16.5	-27.8	35.1	186	120	Vert.	46.0	10.9	
607.134	44.0	QP	19.5	-25.6	37.9	156	118	Hori.	46.0	8.1	
607.134	42.6	QP	19.5	-25.6	36.5	343	100	Vert.	46.0	9.5	
639.088	42.4	QP	19.9	-25.4	36.9	349	100	Vert.	46.0	9.1	
702.995	39.4	QP	20.5	-25.1	34.8	145	107	Hori.	46.0	11.2	
798.460	43.1	QP	21.7	-24.5	40.3	152	100	Hori.	46.0	5.7	
797.690	40.7	QP	21.7	-24.5	37.9	67	100	Vert.	46.0	8.1	
815.980	36.8	QP	21.8	-24.4	34.2	324	229	Hori.	46.0	11.8	
815.975	37.0	QP	21.8	-24.4	34.4	237	100	Vert.	46.0	11.6	

CHART:WITH FACTOR ANT TYPE: -30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE + ATTEN - GAIN(AMP))

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission (Below 1GHz)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2015/03/17

Report No. : 10658081H

Temp./Humi. : 20deg.C / 40% RH
Engineer : Ken Fujita

Mode / Remarks : Standby Mode Worst axis (Hori Y, Vert Y)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
Except for the data below : adequate margin data below the limits.



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
72.020	54.8	QP	6.3	-30.8	30.3	112	261	Hori.	40.0	9.7	
124.100	55.3	QP	13.0	-30.0	38.3	191	100	Vert.	43.5	5.2	
123.700	46.4	QP	12.9	-30.0	29.3	200	152	Hori.	43.5	14.2	
365.652	45.0	QP	16.5	-27.8	33.7	184	122	Vert.	46.0	12.3	
607.131	43.9	QP	19.5	-25.6	37.8	159	122	Hori.	46.0	8.2	
607.136	42.6	QP	19.5	-25.6	36.5	346	100	Vert.	46.0	9.5	
639.088	42.4	QP	19.9	-25.4	36.9	351	100	Vert.	46.0	9.1	
702.995	39.9	QP	20.5	-25.1	35.3	148	100	Hori.	46.0	10.7	
797.530	43.6	QP	21.7	-24.5	40.8	152	100	Hori.	46.0	5.2	
797.660	40.6	QP	21.7	-24.5	37.8	69	100	Vert.	46.0	8.2	
815.984	36.7	QP	21.8	-24.4	34.1	324	223	Hori.	46.0	11.9	
815.975	36.0	QP	21.8	-24.4	33.4	244	100	Vert.	46.0	12.6	

CHART:WITH FACTOR ANT TYPE: -30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE + ATTEN - GAIN(AMP))

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission (Above 1GHz)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2015/03/17

Report No. : 10658081H

Temp./Humi. : 20deg.C / 40% RH
Engineer : Takumi Shimada

Mode / Remarks : USB Data Com Mode Worst Axis (Hori Y, Vert Y)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:AV



Frequency	Reading	DET	Antenna	Loss&	Level	Angle	Height	Polar.	Limit	Margin	Comment
			Factor	Gain							
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
1596.197	51.7	PK	25.2	-34.1	42.8	320	100	Hori.	73.9	31.1	
1596.197	35.9	PK	25.2	-34.1	27.0	320	100	Hori.	73.9	46.9	
1596.197	55.9	PK	25.2	-34.1	47.0	357	146	Vert.	73.9	26.9	
1596.197	40.3	AV	25.2	-34.1	31.4	357	146	Vert.	53.9	22.5	

CHART:WITH FACTOR ANT TYPE: -30MHz:LOOP, 30-300MHz:BICONICAL, 300MHz-1000MHz:LOGPERIODIC, 1000MHz-:HORN
CALCULATION : RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE - GAIN(AMP))

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission (Above 1GHz)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2015/03/17

Report No. : 10658081H

Temp./Humi. : 20deg.C / 40% RH
Engineer : Takumi Shimada

Mode / Remarks : Standby Mode Worst Axis (Hori Y, Vert Y)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:AV



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
1596.197	51.3	PK	25.2	-34.1	42.4	316	100	Hori.	73.9	31.5	
1596.197	36.2	PK	25.2	-34.1	27.3	316	100	Hori.	73.9	46.6	
1596.197	55.8	PK	25.2	-34.1	46.9	359	144	Vert.	73.9	27.0	
1596.197	40.5	AV	25.2	-34.1	31.6	359	144	Vert.	53.9	22.3	

CHART:WITH FACTOR ANT TYPE: -30MHz:1.00P 30-300MHz:BICONICAL 300MHz-1000MHz:1.06PERIODIC 1000MHz-:HORN
CALCULATION : RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE - GAIN(AMP))

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

APPENDIX 2: Test instruments

EMI Test Instruments

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MAEC-01	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 10m	DA-06881	RE/CE	2014/09/01 * 12
MOS-27	Thermo-Hygrometer	CUSTOM	CTH-201	A08Q26	RE/CE	2015/01/13 * 12
MJM-21	Measure	KOMELON	KMC-36	-	RE/CE	-
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE/CE	-
MTR-09	EMI Test Receiver	Rohde & Schwarz	ESU26	100412	RE/CE	2014/06/06 * 12
KBA-05	Biconical Antenna	Schwarzbeck	BBA9106	2513	RE	2014/11/22 * 12
KLA-04	Logperiodic Antenna	Schwarzbeck	USLP9143	361	RE	2014/11/22 * 12
MAT-08	Attenuator(6dB)	Weinschel Corp	2	BK7971	RE	2014/11/20 * 12
MCC-02	Coaxial Cable	Suhner/storm/Agilent /TSJ	-	-	RE	2014/09/12 * 12
MPA-19	Pre Amplifier	MITEQ	MLA-10K01-B01-35	1237616	RE	2015/02/03 * 12
MHA-05	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	253	RE	2014/05/16 * 12
MPA-01	Pre Amplifier	Agilent	8449B	3008A01671	RE	2015/02/04 * 12
MCC-165	Microwave Cable	Junkosha	MWX221	1203S213(1m) / 1311S166(5m)	RE	2014/11/11 * 12
MLS-24	LISN(AMN)	Schwarzbeck	NSLK8127	8127-730	CE(EUT)	2014/07/10 * 12
MLS-26	LISN(AMN)	Schwarzbeck	NSLK8127	8127-732	CE(AE)	2014/07/09 * 12
MTA-28	Terminator	TME	CT-01	-	CE	2014/11/26 * 12
MCC-03	Coaxial Cable	Fujikura/Suhner/TSJ	5D-2W(20m) /3D-2W(7.5m)/ RG400u(1.5m)/ RFM-E421(Switcher)	-/01068 (Switcher)	CE	2014/09/12 * 12
MAT-64	Attenuator(13dB)	JFW Industries, Inc.	50FP-013H2 N	-	CE	2015/01/29 * 12

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item:

CE: Conducted Emissions

RE: Radiated Emissions

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124