

TEST REPORT

Report No.:	BCTC2411184229-2E				
Applicant:	Shenzhen Wellturn Technology Co., Ltd				
Product Name:	Wireless Electronic Pet Fence				
Test Model:	F900 Plus	CHENZH			
Tested Date:	2024-11-26 to 2024-12-25				
Issued Date:	2024-12-25				
She	enzhen BCTC Testing Co., Ltd.				
No.: BCTC/RF-EMC-00	05 Page: 1 of 41 Edition: B.2				



FCC ID: 2ATOX-F900RX

Product Name:	Wireless Electronic Pet Fence
Trademark:	N/A
Model/Type reference:	F900 Plus F900, F910, F910 Plus, F910 Pro
Prepared For:	Shenzhen Wellturn Technology Co., Ltd
Address:	Room 606, Building F, Lvkai Zhihui Park, Liuxian 2nd Road, 71 District, Xin'an Street, Bao'an District, Shenzhen City, China
Manufacturer:	Shenzhen Wellturn Technology Co., Ltd
Address:	Room 606, Building F, Lvkai Zhihui Park, Liuxian 2nd Road, 71 District, Xin'an Street, Bao'an District, Shenzhen City, China
Prepared By:	Shenzhen BCTC Testing Co., Ltd.
Address:	1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date:	2024-11-26
Sample tested Date:	2024-11-26 to 2024-12-25
Issue Date:	2024-12-25
Report No.:	BCTC2411809356-2E
Test Standards:	FCC Part15.519 ANSI C63.10-2013
Test Results:	PASS
Remark:	This is UWB radio test report.

Tested by: Shanshan . Zhang

Approved by:

Shanshan. Zhang / Project Handler

Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

No.: BCTC/RF-EMC-005

Page: 2 of 41



Table of Content

Test	Report Declaration	Page
1.	Version	5
2.	Test Summary	6
3.	Measurement Uncertainty	7
4.	Product Information and Test Setup	8
4.1	Product Information	8
4.2	Test Setup Configuration	9
4.3	Support Equipment	9
4.4	Channel List	9
4.5	Test Mode	
5.	Test Facility And Test Instrument Used	
5.1	Test Facility	11
5.2	Test Instrument Used	
6.	Conducted Emissions	
6.1	Block Diagram Of Test Setup	
6.2	Limit	
6.3	Test procedure	
6.4	EUT operating Conditions	
6.5	Test Result	14
7.	Radiated Emissions	
7.1	Block Diagram Of Test Setup	
7.2	Limit	
7.3	- Test procedure	
7.4	EUT Operating Conditions	
7.5	Test Result	
8.	Shutoff Timing Requirement	
8.1	Block Diagram Of Test Setup	
8.2	Limit	
8.3	- Test procedure	
8.4	EUT Operating Conditions	
8.5	Test Result	
9.	UWB Operation Bandwidth	
9.1	Block Diagram Of Test Setup	32
9.2	Limit	
9.3	Test procedure	32
9.4	FUT Operating Conditions	33
9.5	Test Result	
10.	Peak Emission In A 50 Mhz Bandwidth	
10.1	Block Diagram Of Test Setup	34
10.2	Limit	34
10.3	Test Procedure	34
10.4	EUT Operating Conditions	34
10.5	Test Result	
11	Antenna Requirement	37
11 1	Limit	37
11 1	Test Result	37
12	FUT Photographs	38
· ·		

JC JC JC

еро



		Report No.:	BCTC2411809356-2E	
13.	EUT Test Setup Photographs			39





Page: 4 of 41



1. Version

Report No.	Issue Date	Description	Approved
BCTC2411809356-2E	2024-12-25	Original	Valid



Page: 5 of 41



2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	Conducted Emission	15.207	PASS
2	Shutoff Timing Requirement	15.519(a)(1)	PASS
3	UWB Operation bandwidth	15.503 (a)(d), 15.519(b)	PASS
4	Radiated Emissions	15.209, 15.519(c)(d)	PASS
5	Peak Emission in a 50 MHz bandwidth	15.519(e)	PASS
6	Antenna Requirement	15.203/15.519(a)(2)	PASS

No.: BCTC/RF-EMC-005

Page: 6 of 41



3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
2	3m chamber Radiated spurious emission(9KHz-30MHz)	U=3.7dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission (150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	humidity uncertainty	U=5.3%
10	Temperature uncertainty	U=0.59°C





4. Product Information and Test Setup

4.1 Product Information

Model/Type Reference:	F900 Plus F900, F910, F910 Plus, F910 Pro
Model Differences:	All the model are the same circuit and RF module, except model names and appearance of the color.
Hardware Version:	N/A
Software Version:	N/A
Type of Modulation:	BPSK
Operation Frequency:	3993.6 MHz
Antenna installation:	Chip antenna
Antenna Gain:	 2.3 dBi Remark: ☑ The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. ☐ The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.
Ratings:	DC 5V from adapter or DC 3.7V from battery



No.: BCTC/RF-EMC-005

Page: 8 of 41



4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

Conducted Emission:



Radiated Spurious Emission



4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Wireless Electronic Pet Fence	N/A	F900 Plus	N/A	N/A
E-2	N/A	N/A	N/A	N/A	N/A

ltem	Shielded Type	Ferrite Core	Length	8 9 8 9 8 8	Note
N/A	N/A	N/A	0.6M		N/A

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List





4.5 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For All Mode	Description	Modulation Type
Mode 1	Link mode (Conducted emission and Radiated emission)	

Notes:

- 1. The measurements are performed at the highest, middle, lowest available channels.
- 2. The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

TE, OV t Sea

No.: BCTC/RF-EMC-005

Page: 10 of 41



5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing C o., Ltd. Address:1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuha i Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in con formance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

A2LA certificate registration number is: CN1212

ISED Registered No.: 23583

ISED CAB identifier: CN0017

5.2 Test Instrument Used

Conducted Emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESR3	102075	May 16, 2024	May 15, 2025
LISN	R&S	ENV216	101375	May 16, 2024	May 15, 2025
Software	Frad	EZ-EMC	EMC-CON 3A1	/	/
Pulse limiter	Schwarzbeck	VTSD9561-F	01323	May 16, 2024	May 15, 2025

RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power meter	Keysight	E4419	, j	May 16, 2024	May 15, 2025
Power Sensor (AV)	Keysight	E9300A		May 16, 2024	May 15, 2025
Signal Analyzer20kH z-26.5GHz	Keysight	N9020A	MY49100060	May 16, 2024	May 15, 2025
Spectrum Analyzer9kHz- 40GHz	R&S	FSP40	100363	May 16, 2024	May 15, 2025



Radiated Emissions Test (966 Chamber01)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	May 15, 2023	May 14, 2026
Receiver	R&S	ESR3	102075	May 16, 2024	May 15, 2025
Receiver	R&S	ESRP	101154	May 16, 2024	May 15, 2025
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 16, 2024	May 15, 2025
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	May 21, 2024	May 20, 2025
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	May 21, 2024	May 20, 2025
Amplifier	SKET	LAPA_01G1 8G-45dB	SK202104090 1	May 16, 2024	May 15, 2025
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 21, 2024	May 20, 2025
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35- HG	2034381	May 16, 2024	May 15, 2025
Horn Antenn(18GH z-40GHz)	Schwarzbeck	BBHA9170	00822	May 21, 2024	May 20, 2025
Spectrum Analyzer9kHz- 40GHz	R&S	FSP40	100363	May 16, 2024	May 15, 2025
Software	Frad	EZ-EMC	FA-03A2 RE	١	\

No.: BCTC/RF-EMC-005

Page: 12 of 41



6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

Frequency (MHz)	Limit (dBuV)		
Frequency (MHZ)	Quas-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	
0.50 -5.0	56.00	46.00	
5.0 -30.0	60.00	50.00	

Notes:

1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

6.3 Test procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

a. The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).

b. The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.

c. For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



6.5 Test Result

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101kPa	Phase :	Line
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



No.: BCTC/RF-EMC-005

Page: 14 of 41

Edition: B.2

E



Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101kPa	Phase :	Neutral
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 1



Remark:

All readings are Quasi-Peak and Average values.
 Factor = Insertion Loss + Cable Loss.
 Measurement=Reading Level+ Correct Factor

4. Over= Measurement-Li	mit
-------------------------	-----

No M	k Erog	Reading	Correct	Measure-	Limit	Over	
INO. IVI	K. Fley.	Level	Factor	ment	Luun		
	MHz		dB	dBuV	dBuV	dB	Detector
1	0.2445	25.88	20.07	45.95	61.94	-15.99	QP
2	0.2445	12.47	20.07	32.54	51.94	-19.40	AVG
3	0.3660	22.75	20.08	42.83	58.59	-15.76	QP
4	0.3660	8.75	20.08	28.83	48.59	-19.76	AVG
5 *	0.9105	24.70	20.09	44.79	56.00	-11.21	QP
6	0.9105	7.18	20.09	27.27	46.00	-18.73	AVG
7	1.8285	15.74	20.10	35.84	56.00	-20.16	QP
8	1.8285	-0.97	20.10	19.13	46.00	-26.87	AVG
9	5.1225	14.90	20.15	35.05	60.00	-24.95	QP
10	5.1225	-1.19	20.15	18.96	50.00	-31.04	AVG
11	13.5960	23.87	20.27	44.14	60.00	-15.86	QP
12	13.5960	6.71	20.27	26.98	50.00	-23.02	AVG

JC JC JC

Por



7. Radiated Emissions

7.1 Block Diagram Of Test Setup

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



t sea



(C) Radiated Emission Test-Up Frequency Above 1GHz



7.2 Limit

The radiated emissions at or below 960 MHz from a device operating under the provisions of this section shall not exceed the emission levels in § 15.209. The radiated emissions above 960 MHz from a device operating under the provisions of this section shall not exceed the following average limits when measured using a resolution bandwidth of 1 MHz:

Frequency in MHz	EIRP in dBm
960-1610	-75.3
1610-1990	-63.3
1990-3100	-61.3
3100-10600	-41.3
Above 10600	-61.3

In addition to the radiated emission limits specified in the table in paragraph (c) of this section, UWB transmitters operating under the provisions of this section shall not exceed the following average limits when measured using a resolution bandwidth of no less than 1 kHz:

Frequency in MHz	EIRP in dBm
1164-1240	-85.3
1559-1610	-85.3

Frequency Range of Radiated Measurement



(a) For an intentional radiator the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph:

(1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

(2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.

(3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.

(4) If the intentional radiator operates at or above 95 GHz: To the third harmonic of the highest fundamental frequency or to 750 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
(5) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a) (1)through (4) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this section, whichever is the higher frequency range of investigation.

7.3 Test procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP

Spectrum Parameter	Setting
Above 960MHz in non GPS band	RBW 1 MHz /VBW 3 MHz for Average
Above 960MHz in GPS band	RBW 1 kHz /VBW 3 kHz for Average

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.



c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel, the middlest channel, the Highest channel. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

7.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

7.5 Test Result

Below 30MHz

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Test Voltage:	AC 120V 60Hz, DC 3.7V
Test Mode:	Mode 1	Polarization:	/

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
		and the second sec		PASS
				PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB); Limit line = specific limits(dBuv) + distance extrapolation factor.



Between 30MHz – 1GHz

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 1	Remark:	N/A



Remark:

1.Factor = Antenna Factor + Cable Loss – Pre-amplifier.

2. Measurement=Reading Level+ Correct Factor

3. Over= Measurement-Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		39.8542	26.17	-14.75	11.42	40.00	-28.58	QP
2		66.2662	28.62	-16.97	11.65	40.00	-28.35	QP
3		150.5378	36.16	-19.39	16.77	43.50	-26.73	QP
4		210.7860	36.92	-15.41	21.51	43.50	-21.99	QP
5		356.6758	36.72	-11.39	25.33	46.00	-20.67	QP
6	*	815.9678	29.96	-4.27	25.69	46.00	-20.31	QP

E



Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 1	Remark:	N/A



Remark:

1.Factor = Antenna Factor + Cable Loss – Pre-amplifier.

2. Measurement=Reading Level+ Correct Factor

3. Ov	er= Measurement-L	imit					1
No.	Mk. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	÷
	MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	55.2207	32.99	-14.60	18.39	40.00	-21.61	QP
2	64.6594	35.98	-16.53	19.45	40.00	-20.55	QP
3	88.3421	37.72	-17.79	19.93	43.50	-23.57	QP
4	152.1297	32.62	-19.27	13.35	43.50	-30.15	QP
5	370.7023	33.59	-11.21	22.38	46.00	-23.62	QP
6	* 661.1505	32.16	-6.06	26.10	46.00	-19.90	QP





Spurious radiated emission above 960MHz in non GPS band:

960MHz-1GHz:

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 1	Remark:	N/A





Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 1	Remark:	N/A

-40.0	dBm								
50									
-30									
-60									
-00									
-70									
						FCC 15.	519 UWB non	GPS	
-80									
					0.404.0	and the second	www.	1	6
-90	ستحقي	and and the second states an	### ``ૡ ૡૡ૽ૻૻ૽ૻઌ૽ૻઌૻ૽૽ૻઌૻૻ૽ૻઌૻૻૡ૿ૻૺૡ૾ૻ	_{1.1} 99999999999999999999999999999999999	- Andrew Contraction of the	a mi - Anthon			
-100									
110									
-110									
-120									
96 Dom	50.000			(MHz)				1000.0	0(
1.Fa	nark: actor =	= Antenna Factor +	- Cable Loss -	- Pre-amplifier					
2. N	leasu	rement=Reading L	evel+ Correct	Factor					
3. O)ver=	Measurement-Limi	t				:	1	
		Frequency	Reading	Factor	Level	Limit	Margin		1
	10.	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	Detector	
	A JL	<u>,</u> ,		0.70					┦
´	1 *	999.9200	-88.93	3.70	-85.23	-75.30	-9.93	AVG	

) ED



1GHz-18GHz:

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 1	Remark:	N/A



-2.64

-57.28

-41.30

-15.98

AVG

1 *

8310.000

-54.64



Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 1	Remark:	N/A



Note: The 18GHz-40GHz amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

CHENZHA



Spurious radiated emission in GPS band: 1164MHz-1240MHz:

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 1	Remark:	N/A







Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 1	Remark:	N/A

-60.0 dBn	n						
-70							
-80					FCC	15.519 UWB (GPS 1
-90							
-100	un la	1 Wellow Mar War Am	when white	munumumumu	Marthard Jonan	at many many	White which which are and
-110			• ·				
-120							
-130							
-140							
1164.000			(MHz)				1240.000
Remark: 1.Factor 2. Measu 3. Over=	= Antenna Factor + rement=Reading L Measurement-Lim	- Cable Loss - .evel+ Correct it	- Pre-amplifier Factor	:			/
No.	Frequency (MHz)	Reading (dBm)	Factor (dB)	Level (dBm)	Limit (dBm)	Margin (dB)	Detector
1 *	1187 636	-79.05	-19 92	-98 97	-85.30	-13 67	AVG

JC JC PPR

ероі



1559MHz-1610MHz:

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 1	Remark:	N/A





Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 1	Remark:	N/A

-60.0 dBn	1						
.70							
-70							
-80					FCC 1	5 519 UWB GI	95.2
					1001	0.010 0110 01	<u> </u>
-90							
		ţ					
-100	month white the man that the second sec	www.www.htm	www.	www.www.www.www.www.	WWW.WWWWWW	M M Y WY CHAM	NIN THINK MANUE
			and the set of			an sa fi	
-110							
-120							
-130							
-140							
1559.000			(MHz)				1610.000
Remark:	· · · ·	<u></u>	D 110				
1.Factor	= Antenna Factor +	Cable Loss –	Pre-amplifier.				
2. Measu	2. Measurement=Reading Level+ Correct Factor						
3. Over=				<u></u>		:	1
Na	Frequency	Reading	Factor	Level	Limit	Margin	Detector
INO.	(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	Delector
	· · ·	、	· · ·	· ,	、 <i>/</i>	· · /	
1 *	1577 411	-79.06	-19 26	-98 32	-85.30	-13 02	



8. Shutoff Timing Requirement

8.1 Block Diagram Of Test Setup



8.2 Limit

A UWB device operating under the provisions of this section shall transmit only when it is sending information to an associated receiver. The UWB intentional radiator shall cease transmission within 10 seconds unless it receives an acknowledgement from the associated receiver that its transmission is being received. An acknowledgement of reception must continue to be received by the UWB intentional radiator at least every 10 seconds or the UWB device must cease transmitting.

8.3 Test procedure

- 1. Set the EUT in normal operating mode.
- 2. RBW/VBW=1MHz/1MHz.
- 3. SWT=20S

8.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4.4 Unless otherwise a special operating condition is specified in the follows during the testing.

Page: 30 of 41



8.5 Test Result

Transmitting time	Limit	
6.540 S	10 S	





No.: BCTC/RF-EMC-005

Page: 31 of 41



9. UWB Operation Bandwidth

9.1 Block Diagram Of Test Setup



9.2 Limit

UWB bandwidth. For the purpose of this subpart, the UWB bandwidth is the frequency band bounded by the points that are 10 dB below the highest radiated emission, as based on the complete transmission system including the antenna. The upper boundary is designated fH and the lower boundary is designated fL. The frequency at which the highest radiated emission occurs is designated fM.

Ultra-wideband (UWB) transmitter. An intentional radiator that, at any point in time, has a fractional bandwidth equal to or greater than 0.20 or has a UWB bandwidth equal to or greater than 500 MHz, regardless of the fractional bandwidth.

The UWB bandwidth of a UWB system operating under the provisions of this section must be contained between 3100 MHz and 10,600 MHz.

9.3 Test procedure

A UWB transmitter is defined as "an intentional radiator that, at any point in time, has a fractional bandwidth equal to or greater than 0.20 or has a UWB bandwidth equal to or great than 500 MHz, regardless of the fractional bandwidth.

The frequency at which the maximum power level is measured with the peak detector is designated fM. The peak power measurements shall be made using a spectrum analyzer or EMI receiver with a 1 MHz resolution bandwidth and a video bandwidth of 1 MHz or greater. The instrument shall be set to peak detection using the maximum-hold trace mode. The outermost 1 MHz segments above and below fM, where the peak power falls by 10 dB relative to the level at fM, are designated as fH and fL, respectively: a) For the lowest frequency bound fL, the emission is searched from a frequency lower than fM that has, by inspection, a peak power much lower than 10 dB less than the power at fM and increased

toward fM until the peak power indicates 10 dB less than the power at fM. The frequency of that segment is recorded.

b) This process is repeated for the highest frequency bound fH, beginning at a frequency higher than fM that has, by inspection, a peak power much lower than 10 dB below the power at fM. The frequency of that segment is recorded.

c) The two recorded frequencies represent the highest fH and lowest fL bounds of the UWB transmission, and the -10 dB bandwidth (B - 10) is defined as (fH - fL).82 The center frequency

(fc) is mathematically determined from (fH - fL) / 2.

- d) The fractional bandwidth is defined as 2(fH fL)/(fH + fL).
- e) Determine whether the −10 dB bandwidth (fH − fL) is ≥500 MHz, or whether the fractional

bandwidth 2(fH - fL) / (fH + fL) is ≥ 0.2 .



9.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.5 Test Result

Temperature:	26 ℃	Relative Humidity:	54%RH
Pressure:	101KPa	Test Voltage:	AC120V/60Hz

	Result	Limit (MHz)	
FM(MHz)	The highest emission frequency	4044	/
FL(MHz)	10dB below the highest emission	3498	>3100
FH(MHz)	H(MHz) 10dB above the highest emission		<10600
FC(MHz)	(FH + FL)/2	3947	/
10dB bandwidth(MHz)	FH - FL	898	≥500
Fractional bandwidth 2(FH - FL)/ (FH + FL)		0.228	/





Page: 33 of 41

,TC 3C

PR

ероі



10. Peak Emission In A 50 Mhz Bandwidth

10.1 Block Diagram Of Test Setup



10.2 Limit

There is a limit on the peak level of the emissions contained within a 50 MHz bandwidth centered on the frequency at which the highest radiated emission occurs, fM. That limit is 0 dBm EIRP. It is acceptable to employ a different resolution bandwidth, and a correspondingly different peak emission limit, following the procedures described in § 15.521.

10.3 Test Procedure

The spectral characterization of a UWB device shall begin with a peak-detected radiated measurement because the results obtained from this measurement could preclude the need for subsequent average measurements. For example, if the data collected from the peak-power measurement show that the radiated emissions levels are equal to, or less than, the applicable emissions limit, then these data are adequate to determine compliance. This is predicated on the fact that the average levels are always less than, or equal to, the peak signal level.

The peak detector of the instrument is selected and the maximum hold feature activated. The RBW is set to 1 MHz and the VBW is set to at least 1 MHz (3 MHz is recommended).

10.4 EUT Operating Conditions

The EUT tested system was configured as the statements of 4.4 Unless otherwise a special operating condition is specified in the follows during the testing.

Page: 34 of 41



10.5 Test Result

	Temperature:	26 ℃	Relative Humidity	Relative Humidity:		
Pressure: 10		101KPa	Test Voltage:	Test Voltage:		
	Direction	Frequency(MHz)	Reading level E (dBm) RBW=8MHz	R	E (dBm) RBW=50MHz	Limit (dBm/50MHz)
	Horizontal	3993.6	-24.60		-8.6	0
	Vertical	3993.6	-33.55		-17.55	0

Note: the correct factor of RBW 8MHz to 50MHz is 20 log (50MHz/8 MHz) =16 The test distance is 3m.



-11.84

-24.60

16.00

-8.60

Horizontal:

1 *

) ED

4310.800

-12.76

peak



Vertical:

1 *

4189.000

-21.47



-12.08

-33.55

0.00

-33.55

peak

Page: 36 of 41



11. Antenna Requirement

11.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

11.1 Test Result

The EUT antenna is Chip antenna, non-removable; fulfill the requirement of this section.



No.: BCTC/RF-EMC-005



12. EUT Photographs

EUT Photo



NOTE: Appendix-Photographs Of EUT Constructional Details

Β

API



13. EUT Test Setup Photographs

Conducted emissions Photo



ort S

No.: BCTC/RF-EMC-005

Page: 39 of 41



Radiated Measurement Photos







Page: 40 of 41



STATEMENT

1. The equipment lists are traceable to the national reference standards.

2. The test report can not be partially copied unless prior written approval is issued from our lab.

3. The test report is invalid without the "special seal for inspection and testing".

4. The test report is invalid without the signature of the approver.

5. The test process and test result is only related to the Unit Under Test.

6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.

7. The quality system of our laboratory is in accordance with ISO/IEC17025.

8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: http://www.chnbctc.com

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

***** END *****

No.: BCTC/RF-EMC-005

Page: 41 of 41