

FCC Test Report

(PART 27)

Report No.: RF150720C24-5

FCC ID: HFS-QTAIR7

Test Model: QTAIR7

Received Date: Jul. 20, 2015

Test Date: Aug. 04, 2015 ~ Aug. 07, 2015

Issued Date: Sep. 01, 2015

Applicant: Quanta Computer Inc.

Address: No. 188, Wen Hwa 2nd RD., Kuei Shan Hsiang, Tao Yuan Shien, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan
Hsien 333, Taiwan, R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agency.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results.....	5
2.1 Measurement Uncertainty.....	6
2.2 Test Site And Instruments	7
3 General Information	8
3.1 General Description of EUT	8
3.2 Configuration of System Under Test	9
3.2.1 Description of Support Units	9
3.3 Test Mode Applicability and Tested Channel Detail	10
3.4 EUT Operating Conditions	13
3.5 General Description of Applied Standards.....	13
4 Test Types and Results	14
4.1 Output Power Measurement.....	14
4.1.1 Limits of Output Power Measurement	14
4.1.2 Test Procedures.....	14
4.1.3 Test Setup.....	15
4.1.4 Test Results	16
4.2 Frequency Stability Measurement	23
4.2.1 Limits of Frequency Stability Measurement.....	23
4.2.2 Test Procedure	23
4.2.3 Test Setup.....	23
4.2.4 Test Results	24
4.3 Occupied Bandwidth Measurement.....	25
4.3.1 Limits Of Occupied Bandwidth Measurement	25
4.3.2 Test Procedure	25
4.3.3 Test Setup.....	25
4.3.4 Test Result	26
4.4 Band Edge Measurement	30
4.4.1 Limits of Band Edge Measurement	30
4.4.2 Test Setup.....	30
4.4.3 Test Procedures.....	30
4.4.4 Test Results	31
4.5 Peak To Average Ratio	39
4.5.1 Limits of Peak To Average Ratio Measurement	39
4.5.2 Test Setup.....	39
4.5.3 Test Procedures.....	39
4.5.4 Test Results	40
4.6 Conducted Spurious Emissions	44
4.6.1 Limits of Conducted Spurious Emissions Measurement.....	44
4.6.2 Test Setup.....	44
4.6.3 Test Procedure	44
4.6.4 Test Results	44
4.7 Radiated Emission Measurement.....	46
4.7.1 Limits of Radiated Emission Measurement	46
4.7.2 Test Procedure	46
4.7.3 Deviation from Test Standard	46
4.7.4 Test Setup.....	46
4.7.5 Test Results	47
5 Pictures of Test Arrangements.....	53
Appendix – Information on the Testing Laboratories	54



A D T

Release Control Record

Issue No.	Description	Date Issued
RF150720C24-5	Original Release	Sep. 01, 2015

1 Certificate of Conformity

Product: Tablet PC

Brand: Verizon

Test Model: QTAIR7

Sample Status: Identical Prototype

Applicant: Quanta Computer Inc.

Test Date: Aug. 04, 2015 ~ Aug. 07, 2015

Standards: FCC Part 27, Subpart C, L

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Date:

Sep. 01, 2015

Ivonne Wu / Supervisor

Approved by :



Date:

Sep. 01, 2015

Kay Wu / Supervisor

2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2 (LTE 4)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(d)(4)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 27.53(h)	Occupied Bandwidth	PASS	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	PASS	Meet the requirement of limit.
27.53(h)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(h)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(h)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -26.04dB at 41.61MHz.

Applied Standard: FCC Part 27 & Part 2 (LTE 13)			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(C)(10)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 27.53(g)	Occupied Bandwidth	PASS	Meet the requirement of limit.
27.50(d)(5)	Peak to Average Ratio	PASS	Meet the requirement of limit.
27.53(g)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(g)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(g)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -7.11dB at 2346.00MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

2.2 Test Site And Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Jan. 21, 2015	Jan. 21, 2016
Spectrum Analyzer Agilent	N9010A	MY52220314	Sep. 03, 2014	Sep. 02, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 10, 2014	Dec. 09, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 09, 2015	Feb. 09, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Feb. 04, 2015	Feb. 04, 2016
Loop Antenna	EM-6879	269	Aug. 13, 2014	Aug. 12, 2015
Preamplifier EMCI	EMC 012645	980115	Dec. 12, 2014	Dec. 11, 2015
Preamplifier EMCI	EMC 184045	980116	Jan. 09, 2015	Jan. 08, 2016
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2014	Dec. 26, 2015
Power Meter Anritsu	ML2495A	1232002	Sep. 17, 2014	Sep. 16, 2015
Power Sensor Anritsu	MA2411B	1207325	Sep. 17, 2014	Sep. 16, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2014	Oct. 17, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2014	Oct. 17, 2015
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Nov. 07, 2014	Nov. 06, 2015
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Radio Communication Analyzer	MT8820C	6201240432	Jul. 06, 2015	Jul. 05, 2017

- Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 690701.
5. The IC Site Registration No. is IC7450F-10.

3 General Information

3.1 General Description of EUT

Product	Tablet PC	
Brand	Verizon	
Test Model	QTAIR7	
Status of EUT	Identical Prototype	
Power Supply Rating	5.0Vdc (adapter or host equipment) 3.85Vdc (Li-ion battery)	
Modulation Type	LTE	QPSK, 16QAM
Frequency Range	LTE Band 4 (Channel Bandwidth: 1.4MHz)	1710.7 ~1754.3MHz
	LTE Band 4 (Channel Bandwidth: 3MHz)	1711.5 ~1753.5MHz
	LTE Band 4 (Channel Bandwidth: 5MHz)	1712.5 ~1752.5MHz
	LTE Band 4 (Channel Bandwidth: 10MHz)	1715.0 ~1750.0MHz
	LTE Band 4 (Channel Bandwidth: 15MHz)	1717.5 ~1747.5MHz
	LTE Band 4 (Channel Bandwidth: 20MHz)	1720.0 ~1745.0MHz
	LTE Band 13 (Channel Bandwidth: 5MHz)	779.5 ~ 784.5MHz
	LTE Band 13 (Channel Bandwidth: 10MHz)	782.0MHz
Emission Designator	LTE Band 4 (Channel Bandwidth: 1.4MHz)	1M10G7D
	LTE Band 4 (Channel Bandwidth: 3MHz)	2M70W7D
	LTE Band 4 (Channel Bandwidth: 5MHz)	4M50G7D
	LTE Band 4 (Channel Bandwidth: 10MHz)	8M98G7D
	LTE Band 4 (Channel Bandwidth: 15MHz)	13M5G7D
	LTE Band 4 (Channel Bandwidth: 20MHz)	18M0G7D
	LTE Band 13 (Channel Bandwidth: 5MHz)	4M49G7D
	LTE Band 13 (Channel Bandwidth: 10MHz)	8M96G7D
Max. ERP Power	LTE Band 13 (Channel Bandwidth: 5MHz)	120.78mW
	LTE Band 13 (Channel Bandwidth: 10MHz)	119.12mW
Max. EIRP Power	LTE Band 4 (Channel Bandwidth: 1.4MHz)	206.40mW
	LTE Band 4 (Channel Bandwidth: 3MHz)	197.24mW
	LTE Band 4 (Channel Bandwidth: 5MHz)	197.24mW
	LTE Band 4 (Channel Bandwidth: 10MHz)	198.38mW
	LTE Band 4 (Channel Bandwidth: 15MHz)	205.83mW
	LTE Band 4 (Channel Bandwidth: 20MHz)	205.92mW
Antenna Type	Fixed Internal Antenna	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:


- The EUT contains following accessory devices.

Product	Brand	Model	Description
Battery	McNair	MLP3276120-2P	3.85Vdc, 9100mAh
LTE Module	Marvell	88RF858	--
WLAN Chip	Marvell	88W8887	--


- The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Configuration of System Under Test

<Radiated Emission Test>



<E.R.P. / E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
A.	Earphone	Cotron	Max-301	N/A	N/A
B.	Adapter	N/A	N/A	N/A	N/A

Note:

1. All power cords of the above support units are non-shielded (1.8m).

No.	Signal Cable Description Of The Above Support Units
1.	N/A
2.	N/A

Note:

1. All power cords of the above support units are non-shielded (1.8m).

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	ERP / EIRP	Radiated Emission
LTE Band 4	Y-plane	Z-axis
LTE Band 13	X-plane	X-axis

LTE Band 4

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 2 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 7 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	1 RB / 12 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	1 RB / 37 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	1 RB / 50 RB Offset
-	Frequency Stability	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 2 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 7 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 12 RB Offset
		20000 to 20350	20175	10MHz	QPSK	1 RB / 24 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 37 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 50 RB Offset
-	Occupied Bandwidth	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM	1 RB / 2 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM	1 RB / 7 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM	12 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM	36 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM	50 RB / 0 RB Offset

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	Band Edge	19957 to 20393	19957	1.4MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			20393	1.4MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		19965 to 20385	19965	3MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			20385	3MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		19975 to 20375	19975	5MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			20375	5MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		20000 to 20350	20000	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			20350	10MHz	QPSK	1 RB / 49 RB Offset
						50 RB / 0 RB Offset
		20025 to 20325	20025	15MHz	QPSK	1 RB / 0 RB Offset
						75 RB / 0 RB Offset
			20325	15MHz	QPSK	1 RB / 74 RB Offset
						75 RB / 0 RB Offset
		20050 to 20300	20050	20MHz	QPSK	1 RB / 0 RB Offset
						100 RB / 0 RB Offset
			20300	20MHz	QPSK	1 RB / 99 RB Offset
						100 RB / 0 RB Offset
-	Conducted Emission	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 2 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 7 RB Offset
		19975 to 20375	20175	5MHz	QPSK	12 RB / 0 RB Offset
		20000 to 20350	20175	10MHz	QPSK	50 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	36 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	50 RB / 0 RB Offset
-	Radiated Emission	20050 to 20300	20175	20MHz	QPSK	1 RB / 99 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

LTE Band 13

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	ERP	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	1 RB / 24 RB Offset
-	Frequency Stability	23205 to 23255	23230	5MHz	QPSK	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK	1 RB / 24 RB Offset
-	Occupied Bandwidth	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Peak to Average Ratio	23205 to 23255	23205, 23230, 23255	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Band Edge	23205 to 23255	23205	5MHz	QPSK	1 RB / 0 RB Offset
			23255	5MHz	QPSK	25 RB / 0 RB Offset
		23230	23230	10MHz	QPSK	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
			23230	10MHz	QPSK	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
-	Conducted Emission	23205 to 23255	23230	5MHz	QPSK	1 RB / 0 RB Offset
		23230	23230	10MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission	23230	23230	10MHz	QPSK	1 RB / 24 RB Offset
						1 RB / 50 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP / EIRP	25deg. C, 65%RH	3.85Vdc	Gavin Wu
Frequency Stability	25deg. C, 65%RH	3.85Vdc	Carlos Chen
Occupied Bandwidth	25deg. C, 65%RH	3.85Vdc	Carlos Chen
Band Edge	25deg. C, 65%RH	3.85Vdc	Carlos Chen
Peak to Average Ratio	25deg. C, 65%RH	3.85Vdc	Carlos Chen
Condcudeted Emission	25deg. C, 65%RH	3.85Vdc	Carlos Chen
Radiated Emission	25deg. C, 65%RH	120Vac, 60Hz	Gavin Wu

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

Portable stations (hand-held devices) operating in the 777-787 MHz band are limited to 3 watts ERP

4.1.2 Test Procedures

EIRP / ERP Measurement:


- All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5MHz for WCDMA and 10MHz for LTE mode.
- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15\text{dBi}$.

Conducted Power Measurement:

- The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 Test Setup

EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



4.1.4 Test Results

CONDUCTED OUTPUT POWER (dBm)

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 19957	Mid Ch 20175	High Ch 20393		Low Ch 19957	Mid Ch 20175	High Ch 20393	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
4 / 1.4M	1	0	22.82	22.94	23.24	0	21.77	21.89	22.19	1
	1	2	23.17	23.29	23.59	0	22.12	22.24	22.54	1
	1	5	23.15	23.27	23.57	0	22.10	22.22	22.52	1
	3	0	23.14	23.26	23.56	0	22.09	22.21	22.51	1
	3	1	23.11	23.23	23.53	0	22.06	22.18	22.48	1
	3	3	21.64	21.76	22.06	0	20.59	20.71	21.01	1
	6	0	21.90	22.02	22.32	1	20.85	20.97	21.27	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 19965	Mid Ch 20175	High Ch 20385		Low Ch 19965	Mid Ch 20175	High Ch 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
4 / 3M	1	0	22.95	23.07	23.37	0	21.90	22.02	22.32	1
	1	7	23.30	23.42	23.72	0	22.25	22.37	22.67	1
	1	14	23.28	23.40	23.70	0	22.23	22.35	22.65	1
	8	0	23.27	23.39	23.69	1	22.22	22.34	22.64	2
	8	3	23.24	23.36	23.66	1	22.19	22.31	22.61	2
	8	7	21.77	21.89	22.19	1	20.72	20.84	21.14	2
	15	0	22.03	22.15	22.45	1	20.98	21.10	21.40	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 19975	Mid Ch 20175	High Ch 20375		Low Ch 19975	Mid Ch 20175	High Ch 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
4 / 5M	1	0	23.02	23.14	23.44	0	21.97	22.09	22.39	1
	1	12	23.37	23.49	23.79	0	22.32	22.44	22.74	1
	1	24	23.35	23.47	23.77	0	22.30	22.42	22.72	1
	12	0	23.34	23.46	23.76	1	22.29	22.41	22.71	2
	12	6	23.31	23.43	23.73	1	22.26	22.38	22.68	2
	12	13	21.84	21.96	22.26	1	20.79	20.91	21.21	2
	25	0	22.10	22.22	22.52	1	21.05	21.17	21.47	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20000	Mid Ch 20175	High Ch 20350		Low Ch 20000	Mid Ch 20175	High Ch 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
4 / 10M	1	0	23.08	23.20	23.50	0	22.03	22.15	22.45	1
	1	24	23.43	23.55	23.85	0	22.38	22.50	22.80	1
	1	49	23.41	23.53	23.83	0	22.36	22.48	22.78	1
	25	0	23.40	23.52	23.82	1	22.35	22.47	22.77	2
	25	12	23.37	23.49	23.79	1	22.32	22.44	22.74	2
	25	25	21.90	22.02	22.32	1	20.85	20.97	21.27	2
	50	0	22.16	22.28	22.58	1	21.11	21.23	21.53	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20025	Mid Ch 20175	High Ch 20325		Low Ch 20025	Mid Ch 20175	High Ch 20325	
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
4 / 15M	1	0	23.19	23.31	23.61	0	22.14	22.26	22.56	1
	1	37	23.54	23.66	23.96	0	22.49	22.61	22.91	1
	1	74	23.52	23.64	23.94	0	22.47	22.59	22.89	1
	36	0	23.51	23.63	23.93	1	22.46	22.58	22.88	2
	36	19	23.48	23.60	23.90	1	22.43	22.55	22.85	2
	36	39	22.01	22.13	22.43	1	20.96	21.08	21.38	2
	75	0	22.27	22.39	22.69	1	21.22	21.34	21.64	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20050	Mid Ch 20175	High Ch 20300		Low Ch 20050	Mid Ch 20175	High Ch 20300	
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
4 / 20M	1	0	23.31	23.43	23.73	0	22.26	22.38	22.68	1
	1	50	23.66	23.78	24.08	0	22.61	22.73	23.03	1
	1	99	23.64	23.76	24.06	0	22.59	22.71	23.01	1
	50	0	23.63	23.75	24.05	1	22.58	22.70	23.00	2
	50	25	23.60	23.72	24.02	1	22.55	22.67	22.97	2
	50	50	22.13	22.25	22.55	1	21.08	21.20	21.50	2
	100	0	22.39	22.51	22.81	1	21.34	21.46	21.76	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 23205	Mid Ch 23230	High Ch 23255		Low Ch 23205	Mid Ch 23230	High Ch 23255	
			779.5 MHz	782.0 MHz	784.5 MHz		779.5 MHz	782.0 MHz	784.5 MHz	
13 / 5M	1	0	23.08	23.28	23.72	0	22.01	22.21	22.65	1
	1	12	22.97	23.17	23.61	0	21.90	22.10	22.54	1
	1	24	22.71	22.91	23.35	0	21.64	21.84	22.28	1
	12	0	22.25	22.45	22.89	1	21.18	21.38	21.82	2
	12	6	22.16	22.36	22.80	1	21.09	21.29	21.73	2
	12	13	21.96	22.16	22.60	1	20.89	21.09	21.53	2
	25	0	22.13	22.33	22.77	1	21.06	21.26	21.70	2

Band / BW	RB Size	RB Offset	QPSK	3GPP MPR (dB)	16QAM	3GPP MPR (dB)
			Mid Ch 23230		Mid Ch 23230	
			782.0 MHz		782.0 MHz	
13 / 10M	1	0	23.60	0	22.55	1
	1	24	23.81	0	22.76	1
	1	49	23.50	0	22.45	1
	25	0	22.79	1	21.74	2
	25	12	22.77	1	21.72	2
	25	25	22.92	1	21.87	2
	50	0	22.73	1	21.68	2

ERP Power (dBm)

LTE Band 13							
Channel Bandwidth: 5MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23205	779.5	-9.56	32.24	20.53	112.98	H
	23230	782.0	-9.20	32.17	20.82	120.78	
	23255	784.5	-9.63	32.11	20.33	107.89	
	23205	779.5	-16.44	32.43	13.84	24.21	V
	23230	782.0	-16.03	32.42	14.24	26.55	
	23255	784.5	-16.08	32.46	14.23	26.49	

LTE Band 13							
Channel Bandwidth: 5MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23205	779.5	-10.49	32.24	19.60	91.20	H
	23230	782.0	-10.19	32.17	19.83	96.16	
	23255	784.5	-10.55	32.11	19.41	87.30	
	23205	779.5	-16.63	32.43	13.65	23.17	V
	23230	782.0	-16.29	32.42	13.98	25.00	
	23255	784.5	-16.55	32.46	13.76	23.77	

LTE Band 13							
Channel Bandwidth: 10MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23230	782.0	-9.26	32.17	20.76	119.12	H
	23230	782.0	-16.26	32.42	14.01	25.18	V

LTE Band 13							
Channel Bandwidth: 10MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
X	23230	782.0	-10.26	32.17	19.76	94.62	H
	23230	782.0	-16.39	32.42	13.88	24.43	V

EIRP Power (dBm)

LTE Band 4							
Channel Bandwidth: 1.4MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19957	1710.7	-18.34	36.45	18.11	64.71	H
	20175	1732.5	-19.37	36.80	17.43	55.32	
	20393	1754.3	-19.04	36.94	17.90	61.70	
	19957	1710.7	-14.13	37.28	23.15	206.40	V
	20175	1732.5	-15.22	37.63	22.41	174.18	
	20393	1754.3	-14.75	37.64	22.89	194.54	

LTE Band 4							
Channel Bandwidth: 1.4MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19957	1710.7	-19.58	36.45	16.87	48.64	H
	20175	1732.5	-20.77	36.80	16.03	40.08	
	20393	1754.3	-20.19	36.94	16.75	47.35	
	19957	1710.7	-15.35	37.28	21.93	155.85	V
	20175	1732.5	-16.06	37.63	21.57	143.55	
	20393	1754.3	-15.81	37.64	21.83	152.41	

LTE Band 4							
Channel Bandwidth: 3MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19965	1711.5	-18.48	36.45	17.97	62.66	H
	20175	1732.5	-19.13	36.80	17.67	58.47	
	20385	1753.5	-19.46	36.94	17.48	56.01	
	19965	1711.5	-14.48	37.28	22.80	190.41	V
	20175	1732.5	-14.87	37.63	22.76	188.80	
	20385	1753.5	-14.69	37.64	22.95	197.24	

LTE Band 4							
Channel Bandwidth: 3MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19965	1711.5	-19.85	36.45	16.60	45.71	H
	20175	1732.5	-20.74	36.80	16.06	40.36	
	20385	1753.5	-19.99	36.94	16.95	49.58	
	19965	1711.5	-15.59	37.28	21.69	147.47	V
	20175	1732.5	-16.39	37.63	21.24	133.05	
	20385	1753.5	-15.61	37.64	22.03	159.59	

LTE Band 4							
Channel Bandwidth: 5MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19975	1712.5	-18.45	36.45	18.00	63.10	H
	20175	1732.5	-18.99	36.80	17.81	60.38	
	20375	1752.5	-18.88	36.94	18.06	64.02	
	19975	1712.5	-14.49	37.28	22.79	189.98	V
	20175	1732.5	-14.92	37.63	22.71	186.64	
	20375	1752.5	-14.69	37.64	22.95	197.24	

LTE Band 4							
Channel Bandwidth: 5MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	19975	1712.5	-19.89	36.45	16.56	45.29	H
	20175	1732.5	-19.99	36.80	16.81	47.96	
	20375	1752.5	-20.03	36.94	16.91	49.12	
	19975	1712.5	-15.35	37.28	21.93	155.85	V
	20175	1732.5	-15.78	37.63	21.85	153.11	
	20375	1752.5	-15.68	37.64	21.96	157.04	

LTE Band 4							
Channel Bandwidth: 10MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20000	1715.0	-18.69	36.64	17.95	62.37	H
	20175	1732.5	-19.03	36.80	17.77	59.77	
	20350	1750.0	-18.78	36.80	18.02	63.39	
	20000	1715.0	-15.38	37.44	22.06	160.66	V
	20175	1732.5	-15.16	37.63	22.47	176.56	
	20350	1750.0	-14.66	37.64	22.98	198.38	

LTE Band 4							
Channel Bandwidth: 10MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20000	1715.0	-19.55	36.64	17.09	51.17	H
	20175	1732.5	-19.97	36.80	16.83	48.14	
	20350	1750.0	-20.25	36.80	16.55	45.19	
	20000	1715.0	-15.28	37.44	22.16	164.40	V
	20175	1732.5	-15.69	37.63	21.94	156.28	
	20350	1750.0	-15.77	37.64	21.87	153.64	

LTE Band 4							
Channel Bandwidth: 15MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20025	1717.5	-18.36	36.64	18.28	67.30	H
	20175	1732.5	-18.82	36.80	17.98	62.73	
	20325	1747.5	-18.99	36.80	17.81	60.39	
	20025	1717.5	-14.76	37.44	22.68	185.31	V
	20175	1732.5	-14.78	37.63	22.85	192.71	
	20325	1747.5	-14.50	37.64	23.14	205.83	

LTE Band 4							
Channel Bandwidth: 15MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20025	1717.5	-19.79	36.64	16.85	48.42	H
	20175	1732.5	-19.92	36.80	16.88	48.70	
	20325	1747.5	-19.89	36.80	16.91	49.09	
	20025	1717.5	-15.58	37.44	21.86	153.43	V
	20175	1732.5	-16.03	37.63	21.60	144.51	
	20325	1747.5	-15.58	37.64	22.06	160.51	

LTE Band 4							
Channel Bandwidth: 20MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20050	1720.0	-17.76	36.45	18.69	73.96	H
	20175	1732.5	-18.03	36.80	18.77	75.32	
	20300	1745.0	-18.76	36.94	18.18	65.81	
	20050	1720.0	-14.14	37.28	23.14	205.92	V
	20175	1732.5	-14.55	37.63	23.08	203.24	
	20300	1745.0	-14.58	37.64	23.06	202.30	

LTE Band 4							
Channel Bandwidth: 20MHz / 16QAM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Y	20050	1720.0	-18.45	36.45	18.00	63.10	H
	20175	1732.5	-19.30	36.80	17.50	56.22	
	20300	1745.0	-18.97	36.94	17.97	62.70	
	20050	1720.0	-14.36	37.28	22.92	195.75	V
	20175	1732.5	-14.74	37.63	22.89	194.54	
	20300	1745.0	-15.11	37.64	22.53	179.06	

4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ± 0.5 °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



4.2.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	Frequency Error (ppm)								Limit (ppm)
	LTE Band 4						LTE Band 13		
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	5MHz	10MHz	
3.85	0.0004	0.0010	0.0017	0.0001	0.0001	0.0014	0.00169	0.00004	2.5
3.5	0.0015	0.0008	0.0017	0.0015	0.0007	0.0009	0.00480	0.00381	2.5
4.44	0.0014	0.0012	0.0006	0.0013	0.0005	0.0012	0.00038	0.00321	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.6Vdc to 4.40Vdc.

Frequency Error vs. Temperature

Temp. (°C)	Frequency Error (ppm)								Limit (ppm)
	LTE Band 4						LTE Band 13		
	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz	5MHz	10MHz	
-30	0.0022	0.0011	0.0001	0.0006	0.0003	0.0013	0.00427	0.00471	2.5
-20	0.0014	0.0018	0.0015	0.0022	0.0019	0.0002	0.00432	0.00142	2.5
-10	0.0010	0.0003	0.0020	0.0020	0.0018	0.0021	0.00379	0.00005	2.5
0	0.0013	0.0017	0.0001	0.0019	0.0010	0.0016	0.00217	0.00343	2.5
10	0.0017	0.0013	0.0023	0.0023	0.0012	0.0016	0.00437	0.00182	2.5
20	-0.0019	-0.0019	-0.0007	-0.0015	-0.0012	-0.0005	-0.00409	-0.00274	2.5
30	-0.0023	-0.0020	-0.0006	-0.0023	-0.0022	-0.0005	-0.00317	-0.00221	2.5
40	-0.0010	-0.0006	-0.0006	-0.0019	-0.0021	-0.0014	-0.00174	-0.00040	2.5
50	-0.0001	-0.0012	-0.0005	-0.0009	-0.0009	-0.0015	-0.00349	-0.00338	2.5

4.3 Occupied Bandwidth Measurement


4.3.1 Limits Of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.3.2 Test Procedure


- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.3 Test Setup



4.3.4 Test Result

LTE Band 4							
Channel Bandwidth: 1.4MHz				Channel Bandwidth: 3MHz			
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	1.0988	1.0940	19965	1711.5	2.6971	2.6992
20175	1732.5	1.0959	1.0947	20175	1732.5	2.7007	2.6989
20393	1754.3	1.0982	1.0943	20385	1753.5	2.6995	2.7011



LTE Band 4


Channel Bandwidth: 5MHz

Channel Bandwidth: 10MHz


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	4.4934	4.4918	20000	1715.0	8.9785	8.9672
20175	1732.5	4.4991	4.4938	20175	1732.5	8.9785	8.9747
20375	1752.5	4.4922	4.4934	20350	1750.0	8.9724	8.9710

Spectrum Plot of Worst Value


5MHz / QPSK




5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



LTE BAND 4


Channel Bandwidth: 15MHz

Channel Bandwidth: 20MHz


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	13.463	13.461	20050	1720.0	17.952	17.947
20175	1732.5	13.453	13.447	20175	1732.5	17.917	17.935
20325	1747.5	13.448	13.430	20300	1745.0	17.890	17.890

Spectrum Plot of Worst Value


15MHz / QPSK




15MHz / 16QAM



20MHz / QPSK



20MHz / 16QAM



LTE Band 13


Channel Bandwidth: 5MHz

Channel Bandwidth: 10MHz


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
23205	779.5	4.4936	4.4884	23230	782.0	8.9637	8.9639
23230	782.0	4.4912	4.4918				
23255	784.5	4.4928	4.4928				

Spectrum Plot of Worst Value


5MHz / QPSK




5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM



4.4 Band Edge Measurement


4.4.1 Limits of Band Edge Measurement

For operations in the 777-787 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.

However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

For operations in the 1710–1755 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.


4.4.2 Test Setup



4.4.3 Test Procedures


- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 13kHz and VB of the spectrum is 51kHz (LTE Bandwidth 1.4MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz (LTE Bandwidth 3MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (LTE Bandwidth 5MHz/10MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 150kHz and VB of the spectrum is 470kHz (LTE Bandwidth 15MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 180kHz and VB of the spectrum is 560kHz (LTE Bandwidth 20MHz).
- Record the max trace plot into the test report.

4.4.4 Test Results






A D T






A D T






A D T






A D T






A D T






A D T





A D T




4.5 Peak To Average Ratio

4.5.1 Limits of Peak To Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.5.2 Test Setup




4.5.3 Test Procedures

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

4.5.4 Test Results

LTE Band 4							
Channel Bandwidth: 1.4MHz				Channel Bandwidth: 3MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
19957	1710.7	4.99	5.83	19965	1711.5	5.00	5.82
20175	1732.5	5.29	6.21	20175	1732.5	5.34	6.35
20393	1754.3	5.37	6.39	20385	1753.5	5.49	6.49



LTE Band 4


Channel Bandwidth: 5MHz

Channel Bandwidth: 10MHz


Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
19975	1712.5	5.62	6.07	20000	1715.0	5.10	6.05
20175	1732.5	5.73	6.29	20175	1732.5	5.27	6.10
20375	1752.5	5.76	6.30	20350	1750.0	5.23	6.16

Spectrum Plot of Worst Value


5MHz / QPSK




5MHz / 16QAM




10MHz / QPSK



10MHz / 16QAM



LTE BAND 4							
Channel Bandwidth: 5MHz				Channel Bandwidth: 10MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20025	1717.5	5.56	6.24	20050	1720.0	5.70	6.25
20175	1732.5	5.67	6.28	20175	1732.5	5.71	6.32
20325	1747.5	5.43	6.10	20300	1745.0	5.56	6.15



LTE Band 13


Channel Bandwidth: 5MHz

Channel Bandwidth: 10MHz


Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
23205	779.5	4.36	5.20	23230	782.0	4.16	4.92
23230	782.0	4.68	5.55				
23255	784.5	4.79	5.70				

Spectrum Plot of Worst Value


5MHz / QPSK




5MHz / 16QAM



10MHz / QPSK



10MHz / 16QAM




4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -13dBm.

4.6.2 Test Setup




4.6.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30 MHz to 8GHz for LTE Band 13 and from 30MHz to 18GHz for LTE Band 4. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

4.6.4 Test Results

Frequency Range: 30MHz~8GHz






A D T


Frequency Range: 30MHz~18GHz

LTE Band 4
Channel 20175


1.4MHz / QPSK




3MHz / QPSK




5MHz / QPSK




10MHz / QPSK



15MHz / QPSK



20MHz / QPSK



4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm.

4.7.2 Test Procedure


- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G
- $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15\text{dBi}.$

NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.7.3 Deviation from Test Standard

No deviation.

4.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results

LTE Band 4


Channel Bandwidth: 20MHz / QPSK



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 Chamber 5
Condition: PART27 3m HORIZONTAL
Remak : LTE Band 4_QPSK_20M(1.50)
Tested by: Gavin Wu
Plane : Z


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	122.07	-47.67	-38.05	-13.00	-34.67	-9.62	Peak
2	191.19	-49.79	-42.61	-13.00	-36.79	-7.18	Peak
3	238.71	-49.89	-43.43	-13.00	-36.89	-6.46	Peak
4	575.10	-66.25	-64.45	-13.00	-53.25	-1.80	Peak
5	680.80	-63.97	-63.57	-13.00	-50.97	-0.40	Peak
6	762.70	-63.62	-64.46	-13.00	-50.62	0.84	Peak
7 pp	3465.00	-43.66	-34.75	-13.00	-30.66	-8.91	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 Chamber 5
Condition: PART27 3m VERTICAL
Remak : LTE Band 4_QPSK_20M(1.50)
Tested by: Gavin Wu
Plane : Z

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	41.61	-39.04	-38.63	-13.00	-26.04	-0.41	Peak
2	159.60	-52.87	-48.03	-13.00	-39.87	-4.84	Peak
3	233.85	-51.87	-45.21	-13.00	-38.87	-6.66	Peak
4	375.60	-67.59	-61.50	-13.00	-54.59	-6.09	Peak
5	603.80	-65.20	-64.44	-13.00	-52.20	-0.76	Peak
6	759.90	-63.73	-64.58	-13.00	-50.73	0.85	Peak
7	3465.00	-47.74	-38.83	-13.00	-34.74	-8.91	Peak

LTE Band 13


Channel Bandwidth: 10MHz / QPSK



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 Chamber 5
Condition: PART27(B13) 3m HORIZONTAL
Remak : LTE Band 13_QPSK_10M(1.24)
Tested by: Gavin Wu
Plane : X


	Freq	Level	Read	Limit	Over		
	MHz	dBm/m	Level	Line	Limit	Factor	Remark
			dBm	dBm/m	dB	dB/m	
1	128.01	-49.74	-40.82	-13.00	-36.74	-8.92	Peak
2	176.34	-52.08	-45.36	-13.00	-39.08	-6.72	Peak
3	236.82	-50.28	-43.74	-13.00	-37.28	-6.54	Peak
4	353.20	-66.28	-60.06	-13.00	-53.28	-6.22	Peak
5	637.40	-66.77	-65.92	-13.00	-53.77	-0.85	Peak
6	760.60	-65.44	-66.29	-13.00	-52.44	0.85	Peak
7	1564.00	-53.65	-38.63	-40.00	-13.65	-15.02	Peak
8 pp	2346.00	-20.11	-9.67	-13.00	-7.11	-10.44	Peak
9	3910.00	-39.24	-32.03	-13.00	-26.24	-7.21	Peak
10	5474.00	-42.43	-41.09	-13.00	-29.43	-1.34	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 Chamber 5
Condition: PART27(B13) 3m VERTICAL
Remak : LTE Band 13_QPSK_10M(1.24)
Tested by: Gavin Wu
Plane : X


	Freq	Level	Read	Limit	Over		
	MHz	dBm/m	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	33.51	-41.35	-39.77	-13.00	-28.35	-1.58	Peak
2	40.53	-40.50	-40.62	-13.00	-27.50	0.12	Peak
3	57.00	-53.05	-46.18	-13.00	-40.05	-6.87	Peak
4	580.00	-66.70	-65.10	-13.00	-53.70	-1.60	Peak
5	634.60	-66.63	-65.79	-13.00	-53.63	-0.84	Peak
6	783.70	-65.08	-65.86	-13.00	-52.08	0.78	Peak
7	1564.00	-59.87	-44.85	-40.00	-19.87	-15.02	Peak
8 pp	2346.00	-29.26	-18.82	-13.00	-16.26	-10.44	Peak
9	3910.00	-40.53	-33.32	-13.00	-27.53	-7.21	Peak
10	5474.00	-37.04	-35.70	-13.00	-24.04	-1.34	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5



Site : 966 Chamber 5
Condition: PART27(B13) 3m HORIZONTAL
Remak : LTE Band 13_QPSK_10M(50.0)
Tested by: Gavin Wu
Plane : X


			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	1564.00	-65.54	-50.52	-40.00	-25.54	-15.02	Peak
2	2346.00	-38.72	-28.28	-13.00	-25.72	-10.44	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 6



Site : 966 Chamber 5
Condition: PART27(B13) 3m VERTICAL
Remak : LTE Band 13_QPSK_10M(50.0)
Tested by: Gavin Wu
Plane : X

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp	1564.00	-65.56	-50.54	-40.00	-25.56	-15.02	Peak
2	2346.00	-48.78	-38.34	-13.00	-35.78	-10.44	Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab/Telecom Lab

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---