

TEST REPORT

of

FCC Part 15 Subpart C §15.247

FCC ID: 2AYACBMOLS1


Equipment Under Test : BABYMONSTER OFFICIAL LIGHT STICK
Model Name : BABYMONSTER OFFICIAL LIGHT STICK
Variant Model Name(s) : -
Applicant : YG PLUS, INC.
Manufacturer : YG PLUS, INC.
Date of Receipt : 2024.08.20
Date of Test(s) : 2024.08.21 ~ 2024.11.21
Date of Issue : 2024.11.21

In the configuration tested, the EUT complied with the standards specified above.
This test report does not assure KOLAS accreditation.


- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.

We are responsible for all the information of this test report except for the data(※) provided by the customer

Tested by:


Hahyun Sung

Technical
Manager:


Jinhyoung Cho

SGS Korea Co., Ltd. Gunpo Laboratory

INDEX

Table of contents

| | |
|---|----|
| 1. General Information ----- | 3 |
| 2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emissions ----- | 8 |
| 3. 6 dB Bandwidth ----- | 23 |
| 4. Maximum Peak Conducted Output Power ----- | 26 |
| 5. Power Spectral Density ----- | 29 |
| 6. Antenna Requirement ----- | 32 |

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant : YG PLUS, INC.

Address : 10, Gukjegeumyung-ro, Yeongdeungpo-gu, Seoul, Republic of Korea

Contact Person : LEE, Dong-hun

Phone No. : +82-2-3140-4600

1.3. Details of Manufacturer

Company : Same as an applicant

Address : Same as an applicant

1.4. Description of EUT

| | |
|----------------------|---|
| Kind of Product | BABYMONSTER OFFICIAL LIGHT STICK |
| Model Name | BABYMONSTER OFFICIAL LIGHT STICK |
| Serial Number | Conducted Sample: C-001 Radiated Sample: R-001 |
| Power Supply | DC 4.5 V |
| Frequency Range | 2 402 MHz ~ 2 480 MHz (Bluetooth Low Energy) |
| Modulation Technique | GFSK |
| Number of Channels | 40 channels (Bluetooth Low Energy) |
| Antenna Type | PCB Pattern Antenna |
| Antenna Gain* | 4.32 dB i |
| H/W Version | 1.0 |
| S/W Version | 1.0 |

1.5. Test Equipment List

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Interval | Cal. Due |
|--------------------------|-----------------------------|--------------------------------------|------------------------|---------------|---------------|---------------|
| Signal Generator | R&S | SMA100B | 106887 | Oct. 11, 2024 | Annual | Oct. 11, 2025 |
| Spectrum Analyzer | R&S | FSV30 | 103211 | Dec. 06, 2023 | Annual | Dec. 06, 2024 |
| Spectrum Analyzer | Agilent | N9020A | MY53421758 | Sep. 10, 2024 | Annual | Sep. 10, 2025 |
| Attenuator | AEROFLEX / INMET | 40AH2W-10 | 40G-1 | Jun. 19, 2024 | Annual | Jun. 19, 2025 |
| High Pass Filter | Wainwright Instrument GmbH | WHKX3.0/18G-10SS | 21 | Jun. 07, 2024 | Annual | Jun. 07, 2025 |
| High Pass Filter | Wainwright Instrument GmbH | WHNX7.5/26.5G-6SS | 15 | Jun. 07, 2024 | Annual | Jun. 07, 2025 |
| Low Pass Filter | Mini-Circuits | NLP-1200+ | V 8979400903-2 | Feb. 07, 2024 | Annual | Feb. 07, 2025 |
| Power Sensor | Anritsu | MA24408A | 11838 | Aug. 09, 2024 | Annual | Aug. 09, 2025 |
| DC Power Supply | Agilent | U8002A | MY50070064 | Mar. 11, 2024 | Annual | Mar. 11, 2025 |
| Preamplifier | H.P. | 8447F | 2944A03909 | Aug. 09, 2024 | Annual | Aug. 09, 2025 |
| Signal Conditioning Unit | R&S | SCU-18F | 101058 | Dec. 07, 2023 | Annual | Dec. 07, 2024 |
| Pre Amplifier | MITEQ Inc. | JS44-18004000-35-8P | 1546891 | Oct. 14, 2024 | Annual | Oct. 14, 2025 |
| Loop Antenna | Schwarzbeck Mess-Elektronik | FMZB 1519 | 1519-039 | Aug. 21, 2023 | Biennial | Aug. 21, 2025 |
| Bilog Antenna | Schwarzbeck Mess-Elektronik | VULB 9163 | 9163-396 | Apr. 02, 2024 | Biennial | Apr. 02, 2026 |
| Horn Antenna | R&S | HF906 | 100326 | Feb. 19, 2024 | Annual | Feb. 19, 2025 |
| Horn Antenna | Schwarzbeck Mess-Elektronik | BBHA 9170 | 9170-540 | Dec. 05, 2023 | Annual | Dec. 05, 2024 |
| EMI Test Receiver | R&S | ESU26 | 100109 | Jan. 16, 2024 | Annual | Jan. 16, 2025 |
| Turn Table | Innco systems GmbH | DS 1200 S | N/A | N.C.R. | N/A | N.C.R. |
| Controller | Innco systems GmbH | CONTROLLER CO3000-4P | CO3000/963/383 30516/L | N.C.R. | N/A | N.C.R. |
| Antenna Mast | Innco systems GmbH | MA4640-XP-ET | MA4640/536/383 30516/L | N.C.R. | N/A | N.C.R. |
| Anechoic Chamber | SY Corporation | L x W x H (9.6 m x 6.4 m x 6.6 m) | N/A | N.C.R. | N/A | N.C.R. |
| Coaxial Cable | SENSORVIEW | NMST-13A26-NMST-5 m | TPC2402190004 | Oct. 04, 2024 | Semi-Annual | Apr. 04, 2025 |
| Coaxial Cable | SENSORVIEW | NMST-13A26-NMST-10 m | TPC2402190001 | Oct. 04, 2024 | Semi-Annual | Apr. 04, 2025 |
| Coaxial Cable | RFONE | PL360P-292M292M-1.5M-A | 20200324002 | Oct. 11, 2024 | Semi-Annual | Apr. 11, 2025 |

1.6. Declaration by the Manufacturer

- The EUT support BLE version 5.0 and only operates PHY 1M with 255 bytes.

1.7. Summary of Test Results

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part15 Subpart C | | |
|--|---|-------------------|
| Section | Test Item(s) | Result |
| 15.205(a) 15.209 15.247(d) | Transmitter Radiated Spurious Emissions and Conducted Spurious Emission | Pass |
| 15.247(a)(2) | 6 dB Bandwidth | Pass |
| 15.247(b)(3) | Maximum Peak Conducted Output Power | Pass |
| 15.247(e) | Power Spectral Density | Pass |
| 15.207 | AC Power Line Conducted Emission | N/A ¹⁾ |

Note;

1) The AC power line test was not performed because the EUT use battery power for operation and which do not operate from the AC power lines.

1.8. Test Procedure(s)

The measurement procedures described in the American National Standard of Procedure for Compliance Testing of unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 15.247 Meas Guidance v05r02 were used in the measurement of the DUT.

1.9. Sample Calculation

Where relevant, the following sample calculation is provided:

1.9.1. Conducted Test

Offset value (dB) = Attenuator (dB) + Cable loss (dB)

1.9.2. Radiation Test

Field strength level (dB μ V/m) = Measured level (dB μ V) + Antenna factor (dB/m) + Cable loss (dB) - Amplifier gain (dB) + Duty factor (dB)

1.10. Information of software for test

- Using the software of Non_Signaling_Test_v1.9 to testing of EUT.

1.11. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter | Uncertainty | |
|-------------------------------------|-------------|---------|
| Maximum Peak Conducted Output Power | 0.34 dB | |
| Power Spectral Density | 0.64 dB | |
| 6 dB Bandwidth | 0.07 MHz | |
| Conducted Spurious Emission | 0.80 dB | |
| Radiated Emission, 9 kHz to 30 MHz | H | 3.40 dB |
| | V | 3.40 dB |
| Radiated Emission, below 1 GHz | H | 4.60 dB |
| | V | 5.00 dB |
| Radiated Emission, above 1 GHz | H | 3.60 dB |
| | V | 3.60 dB |

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence.

1.12. Test Report Revision

| Revision | Report number | Date of Issue | Description |
|----------|----------------------|---------------|-------------|
| 0 | F690501-RF-RTL005580 | 2024.11.20 | Initial |

1.13. Duty Cycle of EUT

Regarding to KDB 558074 D01 15.247 Meas Guidance v05r02, 6, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below;


Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.

| Duty Cycle (%) | Correction factor (dB) |
|----------------|------------------------|
| 45.33 | 3.44 |

Remark;

- Duty Cycle (%) = (Tx on time / Tx on + off time) x 100
- Correction Factor (dB) = 10 log (1 / Duty Cycle)

- Test plot




2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emissions


2.1. Test Setup

2.1.1. Transmitter Radiated Spurious Emissions


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz emissions.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10th harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



2.1.2. Conducted Spurious Emissions



2.2. Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emission which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (μV/m) | Measurement Distance (Meters) |
|--------------------|--------------------------|----------------------------------|
| 0.009-0.490 | 2 400/F(kHz) | 300 |
| 0.490-1.705 | 24 000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100** | 3 |
| 88-216 | 150** | 3 |
| 216-960 | 200** | 3 |
| Above 960 | 500 | 3 |

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

2.3.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

2.3.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meters above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. For measurements below 1 GHz resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.
6. For measurements Above 1 GHz resolution bandwidth is set to 1 MHz, the video bandwidth is set to 3 MHz for peak measurements and as applicable for average measurements.

2.3.3. Test Procedures for Radiated Spurious Emissions

1. Unwanted Emissions into Non-Restricted Frequency Bands

- The Reference Level Measurement refer to section 11.11.2

Set analyzer center frequency to DTS channel center frequency, SPAN ≥ 1.5 times the DTS bandwidth, the RBW = 100 kHz and VBW $\geq 3 \times$ RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.

- Unwanted Emissions Level Measurement refer to section 11.11.3

Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 kHz and VBW $\geq 3 \times$ RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.

2. Unwanted Emissions into Restricted Frequency Bands

- Peak Power measurement procedure refer to section 11.12.2.4

Set RBW = as specified in Table 9, VBW $\geq 3 \times$ RBW, Detector = Peak, Sweep time = auto, Trace = Max hold.

Table 9 – RBW as a function of frequency

| Frequency | RBW |
|---------------------|--------------------|
| 9 kHz to 150 kHz | 200 Hz to 300 Hz |
| 0.15 MHz to 30 MHz | 9 kHz to 10 kHz |
| 30 MHz to 1 000 MHz | 100 kHz to 120 kHz |
| > 1 000 MHz | 1 MHz |

If the peak – detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

- Average Power measurements procedure refer to section 11.12.2.5.2

The EUT shall be configured to operate at the maximum achievable duty cycle.

Measure the duty cycle D of the transmitter output signal as described in section 11.6.

Set RBW = 1 MHz, VBW $\geq 3 \times$ RBW, Detector = RMS, if span / (# of points in sweep) \leq (RBW/2).

Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied then the detector mode shall be set to peak.

Averaging type = power (i.e., RMS).

As an alternative the detector and averaging type may be set for linear voltage averaging.

Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used. Sweep time = auto, Perform a trace average of at least 100 traces.

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is $[10 \log (1 / D)]$, where D is the duty cycle.
- 2) If a specific emission is demonstrated to be continuous (D \geq 98%) rather than turning ON and OFF with the transmit cycle, then no duty cycled correction is required for that emission.

3. Definition of DUT Axis.

The radiation test of the EUT was investigated in three orthogonal orientations X, Y, and Z described in the test setup photo. All radiated testing of EUT was performed with worst case axis.

2.3.4. Test Procedures for Conducted Spurious Emissions

Per the guidance of ANSI C63.10-2013, section 11.11.1 & 11.11.2 & 11.11.3, the reference level for out of band emissions is established from the plots of this section since the band edge emissions are measured with a RBW of 100 kHz. This reference level is then used as the limit in subsequent plots for out of band spurious emissions shown in section 2.4.3. The limit for out of band spurious emission at the band edge is 20 dB below the fundamental emission level measured in a 100 kHz bandwidth.

1. Conducted Emissions at Band Edge

- The Measurement refer to section 11.11.3

Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 kHz and VBW $\geq 3 \times$ RBW, Detector = Peak, Sweep time = Auto couple, Trace mode = Max hold, The trace was allowed to stabilize.

2. Conducted Spurious Emissions

- The Measurement refer to section 11.11.3

Start frequency was set to 9 kHz and stop frequency was set to 25 GHz (separated into two plots per channel), RBW = 1 MHz, VBW $\geq 3 \times$ RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold, The trace was allowed to stabilize.

3. TDF function

- For plots showing conducted spurious emissions from 9 kHz to 25 GHz, all path loss of wide frequency range was investigated and compensated to spectrum analyzer as TDF function.
 So, the reading values shown in plots were final result.

2.4. Test Results

Ambient temperature : $(23 \pm 1) ^\circ\text{C}$
Relative humidity : 47 % R.H.

2.4.1. Radiated Spurious Emissions below 1 000 MHz

The frequency spectrum from 9 kHz to 1 000 MHz was investigated. All reading values are peak values.


| Radiated Emissions | | | Ant | Correction (dB/m) | Total | Limit | |
|--------------------|-------------------------|----------------|------|----------------------|--------------------------|-------------------------|----------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| Below 1 000.00 | Not detected | - | - | - | - | - | |

Remark;


1. Spurious emissions for all channels were investigated and almost the same below 1 GHz.
2. Test from 30 MHz to 1 000 MHz was performed using the software of ELEKTRA(V5.02) from Rohde & Schwarz GmbH & Co. KG.
3. Reported spurious emissions are in **PHY 1M / 255 bytes / Low channel** as worst case among other mode and channels.
4. Radiated spurious emission measurement as below.
(Actual = Reading + AF + AMP + CL)
5. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

- Test plots


9 kHz – 150 kHz



150 kHz – 30 MHz



30 MHz – 1 GHz



2.4.2. Radiated Spurious Emissions above 1 000 MHz

The frequency spectrum above 1 000 MHz was investigated. All reading values are peak and average values.

Test mode: PHY 1M

Low Channel (2 402 MHz)

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *2 310.00 | 14.58 | Peak | V | 27.96 | 7.02 | - | 49.56 | 74.00 | 24.44 |
| *2 310.00 | 3.79 | Average | V | 27.96 | 7.02 | 3.44 | 42.21 | 54.00 | 11.79 |
| *2 355.32 | 16.55 | Peak | V | 28.19 | 6.96 | - | 51.70 | 74.00 | 22.30 |
| *2 355.32 | 3.53 | Average | V | 28.19 | 6.96 | 3.44 | 42.12 | 54.00 | 11.88 |
| *2 390.00 | 13.35 | Peak | V | 28.12 | 7.31 | - | 48.78 | 74.00 | 25.22 |
| *2 390.00 | 3.61 | Average | V | 28.12 | 7.31 | 3.44 | 42.48 | 54.00 | 11.52 |

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *4 803.94 | 42.54 | Peak | H | 32.72 | -28.69 | - | 46.57 | 74.00 | 27.43 |
| Above 4 900.00 | - | - | - | - | - | - | - | - | - |

Middle Channel (2 440 MHz)

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *4 879.98 | 42.99 | Peak | H | 33.02 | -28.75 | - | 47.26 | 74.00 | 26.74 |
| *7 319.98 | 43.67 | Peak | H | 36.14 | -26.50 | - | 53.31 | 74.00 | 20.69 |
| Above 7 400.00 | - | - | - | - | - | - | - | - | - |

High Channel (2 480 MHz)

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *2 483.50 | 14.23 | Peak | V | 28.33 | 7.36 | - | 49.92 | 74.00 | 24.08 |
| *2 483.50 | 3.92 | Average | V | 28.33 | 7.36 | 3.44 | 43.05 | 54.00 | 10.95 |
| *2 491.43 | 16.20 | Peak | V | 28.37 | 7.31 | - | 51.88 | 74.00 | 22.12 |
| *2 488.74 | 3.98 | Average | V | 28.35 | 7.33 | 3.44 | 43.10 | 54.00 | 10.90 |
| *2 500.00 | 13.95 | Peak | V | 28.40 | 7.24 | - | 49.59 | 74.00 | 24.41 |
| *2 500.00 | 4.01 | Average | V | 28.40 | 7.24 | 3.44 | 43.09 | 54.00 | 10.91 |


| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | DF (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *4 959.88 | 42.80 | Peak | H | 33.32 | -28.72 | - | 47.40 | 74.00 | 26.60 |
| *7 440.10 | 42.82 | Peak | H | 36.22 | -26.10 | - | 52.94 | 74.00 | 21.06 |
| Above 7 500.00 | - | - | - | - | - | - | - | - | - |

Remarks;


1. “*” means the restricted band.
2. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
3. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
4. Actual = Reading + AF + CL + (DF) or Reading + AF + AMP + CL + (DF).
5. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
6. The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.
7. AF = Antenna Factor, CL = Cable Loss, DF = Duty Correction Factor.

- Test plots


Low channel band edge (Peak)




Low channel band edge (Average)




Low channel 2nd harmonic (Peak)




Middle channel 2nd harmonic (Peak)




Middle channel 3rd harmonic (Peak)




High channel band edge (Peak)




High channel band edge (Average)



High channel 2nd harmonic (Peak)




High channel 3rd harmonic (Peak)




2.4.3. Plot of Conducted Spurious Emissions


Low Channel



Middle Channel



High Channel



3.6 dB Bandwidth

3.1. Test Setup



3.2. Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902-928 MHz, 2 400-2 483.5 MHz, and 5 725-5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3. Test Procedure

The test follows section 11.8 DTS bandwidth of ANSI C63.10-2013.
 Tests performed using section 11.8.1 Option 1.

- Option 1:

1. Set RBW to = 100 kHz.
2. Set the VBW \geq [3 x RBW].
3. Detector = peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4. Test Results

Ambient temperature : $(23 \pm 1) ^\circ\text{C}$
 Relative humidity : 47 % R.H.


- 6 dB Bandwidth

| Mode | Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Minimum Bandwidth (kHz) |
|------|---------|--------------------|-------------------------|----------------------------|
| GFSK | Low | 2 402 | 0.650 | 500 |
| | Middle | 2 440 | 0.659 | |
| | High | 2 480 | 0.656 | |


- Test plots

- 6 dB Bandwidth


Low Channel



Middle Channel




High Channel



4. Maximum Peak Conducted Output Power

4.1. Test Setup



4.2. Limit

According to §15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2 400-2 483.5 MHz, and 5 725-5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraph (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.3. Test Procedure

The test follows section 11.9.1.3 of ANSI C63.10-2013.

PKPM1 Peak-reading power meter method

- The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The test follows section 11.9.2.3.2 of ANSI C63.10-2013.

Method AVGPM-G (Measurement using a gated RF average-reading power meter)

- Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Test program: (S/W name: R&S Power Viewer, Version: 3.2.0)

1. Initially overall offset for attenuator and cable loss is measured per frequency.
2. Measured offset is inserted in test program in advance of measurement for output power.
3. Power for each frequency (channel) of device is investigated as final result.
4. Final result reported on this section from R&S power viewer program includes with several factors and test program shows only final result.


4.4. Test Results

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

| Mode | Channel | Frequency (MHz) | Average Power Result (dB m) | Peak Power Result (dB m) | Limit (dB m) |
|------|---------|--------------------|-----------------------------------|--------------------------------|-----------------|
| GFSK | Low | 2 402 | <u>-18.07</u> | <u>-16.94</u> | 30 |
| | Middle | 2 440 | -18.45 | -17.07 | |
| | High | 2 480 | -18.71 | -17.37 | |

5. Power Spectral Density

5.1. Test Setup



5.2. Limit

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

5.3. Test Procedure

The measurements are recorded using the PKPSD measurement procedure in section 11.10.2 of ANSI C63.10-2013.

- This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq [3 \times \text{RBW}]$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


5.4. Test Results

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.


| Mode | Channel | Frequency (MHz) | Measured PSD (dB m/3 kHz) | Limit (dB m/3 kHz) |
|------|---------|--------------------|------------------------------|-----------------------|
| GFSK | Low | 2 402 | -18.30 | 8 |
| | Middle | 2 440 | -18.73 | |
| | High | 2 480 | -18.54 | |

- Test plots


Low Channel



Middle Channel



High Channel



6. Antenna Requirement

6.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. And according to FCC 47 CFR Section §15.247(b) if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power shall be reduced appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.2. Antenna Connected Construction

Antenna used in this product is PCB Pattern Antenna with gain of 4.32 dBi.

- End of the Test Report -