



MPE Report

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance v06

FCC Part 2 §2.1091

1. Evaluation method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with HWB1BLE40AWH for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

2. Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

3. Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density



Compliance Certification Services (Shenzhen) Inc.

Report No: C180305Z03-RP_MPE

FCC ID: 2ADQOMDWF01

Date of Issue: March 23, 2018

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the maximum gain of the used 4.90dBi for 2.4GWLAN, the RF power density can be obtained.

Frequency Band	Antenna type and antenna number	Maximum antenna gain
2.4G	WLAN Antenna	4.90dBi

4. Estimation Result

4.1 Conducted Power Results

2.4GHz WIFI

Mode	Frequency(MHz)	Peak Conducted Output Power (dBm)
IEEE 802.11b	2412	17.76
	2437	18.26
	2462	18.72
IEEE 802.11g	2412	20.72
	2437	21.09
	2462	21.15
IEEE 802.11n HT20	2412	21.65
	2437	22.16
	2462	22.63
IEEE 802.11n HT40	2412	20.66
	2437	20.23
	2462	21.35

4.2 Manufacturing tolerance

2.4GHz WIFI

IEEE 802.11b			
Frequency(MHz)	2412	2437	2462
Maximum Output Power (dBm)	17.76	18.26	18.72

IEEE 802.11 g			
Frequency(MHz)	2412	2437	2462
Maximum Output Power (dBm)	20.72	21.09	21.15

IEEE 802.11n HT20			
Frequency(MHz)	2412	2437	2462
Maximum Output Power (dBm)	21.65	22.16	22.63



Compliance Certification Services (Shenzhen) Inc.

Report No: C180305Z03-RP_MPE

FCC ID: 2ADQOMDWF01

Date of Issue: March 23, 2018

IEEE 802.11n HT40			
Frequency(MHz)	2412	2437	2462
Maximum Output Power (dBm)	20.66	20.23	21.35

4.3 Measurement Results

4.3.1 Standalone MPE

2.4G WLAN

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	(dBm)	(mW)					
IEEE 802.11 b	18.72	74.4732	4.90	3.0903	100%	0.04581	1.0000
IEEE 802.11 g	21.15	130.3167	4.90	3.0903	100%	0.08016	1.0000
IEEE 802.11 n HT20	22.63	183.2314	4.90	3.0903	100%	0.11271	1.0000
IEEE 802.11 n HT40	21.35	136.4583	4.90	3.0903	100%	0.08394	1.0000

Remark:

1. Maximum average power including tune-up tolerance;
2. MPE use distance is 20cm from manufacturer declaration of user manual.
3. We choose 2412MHz (lowest frequency operate at 2.4GHz) to calculate MPE limit as higher frequency will have higher MPE limits

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- END OF REPORT-----