

RF Exposure Evaluation declaration

Product Name	Medical Cart Computer
Model No.	DT590B, DT592B, DT594B
FCC ID	YE3800G

Applicant	DT Research, Inc.
Address	6F, No. 1, NingPo E. St. Taipei, 100 Taiwan

Date of Receipt	Jan. 18, 2016
Date of Declaration	Mar. 09, 2016
Report No.	1610298R-RFUSP27V00-A

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : Medical Cart Computer
Test Item : RF Exposure Evaluation
Test Site : No.3 OATS

For 2.4GHz Band:

Operation Frequency	2412-2462MHz, 2422-2452MHz, 2402 – 2480MHz
Maximum Conducted output power	19.1 dBm
Antenna gain	1.51 dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
81.28305162	0.0229

Power density in column is much lower than the limit (1 mW/cm²).

For 5GHz Band:

Operation Frequency	5180-5240MHz,5260-5320MHz,5500-5700MHz, 5745-5825MHz,5190-5230MHz,5270-5310MHz, 5510-5670MHz,5755-5795MHz,5720 MHz, 5710MHz,5210-5290MHz,5530-5690MHz, 5775MHz
Maximum Conducted output power	18.39 dBm
Antenna gain	1.14 dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
69.02398038	0.0179

Power density in column is much lower than the limit (1 mW/cm²).