ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY **CFS8DL5882-4**
SYOSSET, NY 11791 **FCC ID#_____**

DATE: JUNE, 07, 2002 TESTED BY: GREG BARBATO APPROVED BY: KEN ADDY

TEST SAMPLE (model): ADEMCO 5882-4 (RECEIVER)

TEST METHOD: ANSI C63.4-1992
TEST SPECIFICATION: FCC PART 15, SUBPART C.

NOTES: 1) Fo= 355.7 MHZ
2) DETECTOR = PEAK.
3) FREQUENCY RANGE SCANNED TO 4 GHz.

4) CONVERTED READING = $10^{\left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20}\right]}$

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
59.283	V	5.83	0.50	10.78	7.17	------	7.17	100
118.566	V	18.00	0.67	11.21	31.19	------	31.19	150
177.850	H	20.33	0.83	13.55	54.38	------	54.38	150
237.137	H	15.33	1.17	15.69	31.08	------	31.08	200
296.410	V	14.33	1.50	18.05	36.35	------	36.35	200
355.700	V	20.83	1.67	16.60	65.01	------	65.01	200
414.983	V	5.00	1.67	17.36	10.91	------	10.91	200
474.266	V	5.00	1.67	19.96	14.39	------	14.39	200