


Measurement Data


TestMode	Freq(MHz)	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Hop	0.393	320	0.126	≤0.4	PASS
DH3	Hop	1.641	220	0.361	≤0.4	PASS
DH5	Hop	2.888	80	0.231	≤0.4	PASS
2DH1	Hop	0.403	330	0.133	≤0.4	PASS
2DH3	Hop	1.646	170	0.28	≤0.4	PASS
2DH5	Hop	2.887	100	0.289	≤0.4	PASS
3DH1	Hop	0.404	320	0.129	≤0.4	PASS
3DH3	Hop	1.646	110	0.181	≤0.4	PASS
3DH5	Hop	2.890	90	0.26	≤0.4	PASS

Remark:


The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s

Test plot as follows:






Date: 18.DEC.2024 13:09:58




Date: 18.DEC.2024 13:10:03

DH5_Ant1_Hop




Date: 18.DEC.2024 13:38:48




Date: 18.DEC.2024 13:38:54

2DH1_Ant1_Hop




Date: 18.DEC.2024 13:20:09




Date: 18.DEC.2024 13:20:15

2DH3_Ant1_Hop




Date: 18.DEC.2024 13:23:15




Date: 18.DEC.2024 13:23:21

2DH5_Ant1_Hop




Date: 18.DEC.2024 13:15:51




Date: 18.DEC.2024 13:15:57

3DH1_Ant1_Hop




Date: 18.DEC.2024 13:32:59




Date: 18.DEC.2024 13:33:04

3DH3_Ant1_Hop




Date: 18.DEC.2024 13:36:28




Date: 18.DEC.2024 13:36:33

3DH5_Ant1_Hop




Date: 18.DEC.2024 13:31:43



Date: 18 DEC 2024 13:31:49


5.8 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Test Setup:	 Remark: $Offset = cable\ loss + attenuation\ factor$.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

TestMode	ChName	Freq(MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Low	2402	0.46	-48.46	≤ -19.54	PASS
	High	2480	1.42	-51.43	≤ -18.58	PASS
	Low	Hop_2402	0.05	-51.57	≤ -19.95	PASS
	High	Hop_2480	0.66	-51.01	≤ -19.34	PASS
2DH5	Low	2402	0.45	-52.93	≤ -19.55	PASS
	High	2480	1.44	-50.89	≤ -18.56	PASS
	Low	Hop_2402	-1.00	-52.66	≤ -21	PASS
	High	Hop_2480	-0.11	-51.05	≤ -20.11	PASS
3DH5	Low	2402	0.07	-50.52	≤ -19.93	PASS
	High	2480	0.99	-51.25	≤ -19.01	PASS
	Low	Hop_2402	-3.27	-52.33	≤ -23.27	PASS
	High	Hop_2480	0.31	-50.79	≤ -19.69	PASS


Test plot as follows:






Date: 18.DEC.2024 12:55:45

DH5_Ant1_High_Hop_2480




Date: 18.DEC.2024 13:10:20

2DH5_Ant1_Low_2402




Date: 18.DEC.2024 12:34:43

2DH5_Ant1_High_2480




Date: 18.DEC.2024 12:44:11

2DH5_Ant1_Low_Hop_2402



Date: 18.DEC.2024 13:12:08

2DH5_Ant1_High_Hop_2480



Date: 18.DEC.2024 13:24:29

3DH5_Ant1_Low_2402