



**Test Report**  
**Spurious and EMC Emissions**

**AIR-CAP1532E-A-K9**

**FCC ID: LDK102089P**  
**IC: 2461B-102089P**

**5250 -5350 MHz**

**Against the following Specifications:**  
**CFR47 Part 15**

**Cisco Systems**  
170 West Tasman Drive  
San Jose, CA 95134

Test Engineer

A handwritten signature in dark ink, appearing to read "Bud Chilla", written over a horizontal line.

Date

12-13-13



This test report has been electronically authorized and archived using the CISCO Engineering Document Control system.

<b>SECTION 1: OVERVIEW .....</b>	<b>2</b>
<b>1.1 TEST SUMMARY.....</b>	<b>2</b>
<b>SECTION 2: ASSESSMENT INFORMATION .....</b>	<b>3</b>
<b>2.1 GENERAL .....</b>	<b>3</b>
<b>2.2 DATE OF TESTING .....</b>	<b>4</b>
<b>2.3 REPORT ISSUE DATE .....</b>	<b>4</b>
<b>2.4 TESTING FACILITIES.....</b>	<b>4</b>
<b>2.5 EQUIPMENT ASSESSED (EUT) .....</b>	<b>4</b>
<b>2.6 EUT DESCRIPTION.....</b>	<b>4</b>
<b>APPENDIX A:     EMISSION TEST RESULTS.....</b>	<b>6</b>
<b>APPENDIX B:     Test Equipment/Software Used to perform the test .....</b>	<b>17</b>

## Section 1: Overview

### 1.1 Test Summary

The samples were assessed against the tests detailed in section 3 under the requirements of the following specifications:

Emission	Immunity
CFR47 Part 15	N/A

The specifications listed above represent actual tests performed to demonstrate compliance against the specifications and basic standards listed on the front cover of this report. This list is not a one to one match to the front cover for one or more of the following reasons.

1. Basic standards call up many different test phenomena specifications such as the 61000-4-X series. The basic standards define which elements and levels shall be applied from these specifications and as such it is not appropriate to list the individual specifications on the front cover.
2. A Standard listed on the front cover may be required in a particular country but is not appropriate for the particular technologies included in the equipment under test. E.g. You cannot test a DC product to the mains Harmonics requirements in EN61000-3-2. See section 3.2.
3. Test results against a particular standard or specification may be included in a different test report. See section 3.2 for an EDCS reference of this data.
4. Where appropriate, Cisco may have substituted a later revision of a basic standard to those referenced in the specification on the front sheet of this test report. This decision was based upon improved test methodology and repeatability and/or where the newer revision represented a more stringent test.
5. Where relevant, testing has been carried out to the requirements of both EN and IEC Specifications. This was possible because of the similarities of the test methods involved and the Cisco EMC test procedures.
6. Testing may have been performed to an equivalent test that satisfies the requirements of the standards and specifications listed on the front cover of the report. See section 3.2.
7. Where radiated emissions testing has been performed to EN55022/CISPR22 the additional requirements of VCCI: V- 3/2006.04, EN55022: 1994 +A1/2 and CAN/CSA- CISPR 22-02 have also been evaluated unless otherwise stated.
8. Testing to the requirements of CFR47 Part 15 was performed against the CISPR22 limits. The results are therefore deemed satisfactory evidence of compliance with Industry Canada Interference Causing Equipment Standard ICES-003.
9. Where assessment has been performed to CISPR24, all the applicable test requirements may have not been covered. Refer to the results section for the tests performed.

#### Notes:

- 1) Where a specification listed on the front cover of this report has deviations from the basic standards listed above, the additional technical requirements of the specification were also assessed.
- 2) Where appropriate, Cisco may have substituted a later revision of a basic standard to those referenced in the specification on the front sheet of this test report. This decision was based upon improved test methodology and repeatability and/or where the newer revision represented a more stringent test.
- 3) Where relevant, testing has been carried out to the requirements of both EN and IEC Specifications. This was possible because of the similarities of the test methods involved and the Cisco EMC test procedures.



## **Section 2: Assessment Information**

### **2.1 General**

This report contains an assessment of an apparatus against Electromagnetic Compatibility Standards based upon tests carried out on the samples submitted. The testing was performed by and for the use of Cisco systems Inc.

With regard to this assessment, the following points should be noted:

- a) The results contained in this report relate only to the items tested and were obtained in the period between the date of the initial assessment and the date of issue of the report. Manufactured products will not necessarily give identical results due to production and measurement tolerances.
- b) The apparatus was set up and exercised using the configuration and modes of operation defined in the operations manual.
- c) Where relevant, the apparatus was only assessed using the susceptibility criteria defined in this report and the Test Assessment Plan (TAP).
- d) All testing was performed under the following environmental conditions:

Temperature	15°C to 35°C (54°F to 95°F)
Atmospheric Pressure	860mbar to 1060mbar (25.4" to 31.3")
Humidity	10% to 75*%

\*[Where applicable] For ESD testing the humidity limits used were 30% to 60% and for EFT/B tests the humidity limits used were 25% to 75%.
- e) All AC testing was performed at one or more of the following supply voltages:

110V 60 Hz (+/-20%)
220V 50 Hz (+/-20%)

**This report must not be reproduced except in full, without written approval of Cisco Systems.**



## **2.2 Date of testing**

15 July thru 31 October, 2013

## **2.3 Report Issue Date**

Cisco uses an electronic system to issue, store and control the revision of test reports. This system is called the Engineering Document Control System (EDCS). The actual report issue date is embedded into the original file on EDCS. Any copies of this report, either electronic or paper, that are not on EDCS must be considered uncontrolled.

## **2.4 Testing facilities**

This assessment was performed by:

### **Testing Laboratory**

Cisco Systems, Inc.,  
4125 Highlander Parkway  
Richfield, OH 44286  
USA

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134  
USA

## **Test Engineers**

Bud Chiller

## **2.5 Equipment Assessed (EUT)**

AIR-CAP1532E-A-K9

This report provides data supporting compliance with undesired emissions regulations stated in CFR47 Part 15 of the FCC Rules and Regulations.

## **2.6 EUT Description**

The AIR-CAP1532E-A-K9 is an 802.11n dual band mesh access point employing externally mounted antennas either directly on the RF port connectors or mounted separately to provide desired coverage.



## **Appendix A: Emission Test Results**

### **Radiated Spurious Emissions**

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Using Vasona, configure the spectrum analyzer as shown below (be sure to enter all losses between the transmitter output and the spectrum analyzer). Place the radio in continuous transmit mode.

Span:	1GHz – 18 GHz
Reference Level:	80 dBuV
Attenuation:	10 dB
Sweep Time:	Coupled
Resolution Bandwidth:	1MHz
Video Bandwidth:	1 MHz for peak, 10 Hz for average
Detector:	Peak

Maximize Turntable (find worst case table angle), Maximize Antenna (find worst case height)


Save 2 plots:    1) Average Plot (Vertical and Horizontal), Limit= 54dBuV @3m  
                     2) Peak plot (Vertical and Horizontal), Limit = 74dBuV @3m

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance.  
Also measure any emissions in the restricted bands.


This report represents the worst case data for all supported operating modes and antennas.  
There are no measurable emissions above 18 GHz.


## Transmitter Radiated Spurious Emissions

### Radiated Transmitter Spurs, 5280MHz, All Rates, All Modes, Average 1-18 GHz



### Radiated Transmitter Spurs, 5280MHz, All Rates, All Modes, Peak 1-18 GHz




**Radiated Transmitter Spurs, 5300MHz, All Rates, All Modes, Average 1-18 GHz****Radiated Transmitter Spurs, 5300MHz, All Rates, All Modes, Peak 1-18 GHz**




**Radiated Transmitter Spurs, 5320MHz, All Rates, All Modes, Average 1-18 GHz****Radiated Transmitter Spurs, 5320MHz, All Rates, All Modes, Peak 1-18 GHz**



## Radiated Transmitter Spurs, All Rates, All Modes, Average 18-26.5 GHz




## Radiated Transmitter Spurs, All Rates, All Modes, Peak 18-26.5 GHz






## Radiated Transmitter Spurs, All Rates, All Modes, Average 26.5-40 GHz



## Radiated Transmitter Spurs, All Rates, All Modes, Peak 26.5- 40GHz





## Receiver Radiated Spurious Emissions

### Radiated Receiver Spurs, All Rates, All Modes, Average



### Radiated Receiver Spurs, All Rates, All Modes, Peak






**Radiated Test Setup 1-18GHz**



**Radiated Test Setup 18-40GHz**

## Conducted Emissions




MHz	Raw dBuV	Cable Loss	Factors dB	Level dBuV	Measurement Type	Line	Limit dBuV	Margin dB	Pass /Fail
0.484234	55.5	0.1	9.5	65.1	Qp	RF	74.3	-9.2	Pass
0.774814	53.7	0.1	9.5	63.4	Qp	RF	74	-10.6	Pass
0.671719	50.9	0.1	9.5	60.5	Qp	RF	74	-13.5	Pass
0.872798	49	0.1	9.5	58.6	Qp	RF	74	-15.4	Pass
1.743	42.6	0.1	9.5	52.3	Qp	RF	74	-21.7	Pass
0.484913	54.9	0.1	9.5	64.5	Qp	RF	74.2	-9.8	Pass
0.484234	51.4	0.1	9.5	61	Av	RF	64.3	-3.3	Pass
0.774814	49.8	0.1	9.5	59.4	Av	RF	64	-4.6	Pass
0.671719	43.1	0.1	9.5	52.7	Av	RF	64	-11.3	Pass
0.872798	45	0.1	9.5	54.6	Av	RF	64	-9.4	Pass
1.743	37.6	0.1	9.5	47.3	Av	RF	64	-16.7	Pass
0.484913	50.5	0.1	9.5	60.1	Av	RF	64.2	-4.2	Pass

### Conducted Emission Test Setup






## Radiated emissions 30 – 1000 MHz



Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail
35.534	34.4	0.7	-10.9	24.2	Qp	V	342	14	30	-5.8	Pass
43.358	36.9	0.8	-16.8	20.8	Qp	V	104	124	30	-9.2	Pass
98.457	39.8	1.2	-17.8	23.3	Qp	V	121	324	30	-6.7	Pass
199.965	34	1.7	-14.5	21.1	Qp	V	113	121	30	-8.9	Pass
104.661	35.1	1.2	-15.8	20.5	Qp	V	127	18	30	-9.5	Pass
220.027	36.5	1.7	-16.4	21.9	Qp	V	150	198	30	-8.1	Pass





**Title:** Radiated Emissions 30-1000MHz Configuration Photograph

**Appendix B: Test Equipment/Software Used to perform the test**

Equip #	Manufacturer	Model	Description	Last Cal	Next Due
44940	Rohde & Schwarz	ESU	Spectrum Analyzer	15May13	15May14
40514	Agilent	E4440A	Spectrum Analyzer	12-NOV-12	12-NOV-13
3003	HP	8373B	Signal Generator	26Mar13	26Mar14
30654	Sunol Sciences	JB1	Combination Antenna	16Oct12	16Oct13
4882	EMCO	3115	Horn Antenna	28Jun13	28Jun14
41935	Newport	iBTHP-5-DB9	Temperature Probe	25MAR13	25MAR14
5691	Miteq	NSP1800-25-S1	1GHz to 18GHz Pre-Amplifier	01Feb13	01Feb14
41979	Cisco	1840	18-40GHz EMI Test Head	09Jul13	09Jul14
25658	Micro-Coax	UFB311A-1-0840-504504	RF Cable	13Feb13	13Feb14
47300	Agilent	MXE	EMI Receiver	13Nov12	13Nov13
8195	TTE	H613-150K-50-21378	Filter	04Jan13	04Jan14
8496	Fischer Custom	FCC-450B-2.4-N	Pulse limiter	20May13	20May14
39110	Coleman	RG-223	RF Cable, 25 ft., N	29Nov12	29Nov13
44023	Fischer	M2	CDN	16Nov12	16Nov13
25001	Micro-Coax	UFB197C-1-0240-504504	RF Cable, 2 ft.	24Mar13	24Mar14