



1. Bar code System: Code 128
2. Material: white ART paper
3. Printing color: Black and White.
The pink color content must be printed on the assembly line.
The green color content must be pre-printed in the label factory.
4. Tolerance: $\pm 0.2\text{mm}$
5. Print content: Use „DIN Next LT Pro“ as font for pre-printing in the label factory (font files are provided by snom)
 - A. Revision: RnX (provided by snom with PO), Printing Color: black
R:= indicates revision number (fixed information)
n:=1st revision index (major changes) (numeric)
X:=2nd revision index (minor changes) (capital letter)
 - B. Barcode: Serial No. (16 digits) (Code 128), Printing Color: black
XXX:= Country of Origin - ISO 3166-1 alpha-3 (3 digits)
YY:= Product of factory abbreviation - provided by snom (2 digits)
88888:= DDMMYY day, month, year (only last two digits)
99999:= Serial Number (5 digits, numeric)
 - C. Barcode: MAC Address (Code 128), Printing Color: black
 - D. Year of production, Printing Color: white
 - E. Country of Origin (English name), Printing Color: white
 - F. Factory Label ID (5 alpha-numeric digits), Printing Color: white
6. Attach onto the backside of the phone enclosure
7. Do not rip off the label and never re-use it!

company		revision	PS No.	ERP No.	scale	total pages	page
model		4	-	-	1:1	1	1
product		prepared by		Antonia Leven (antonia@pfefferminzgeschmack.de)			
filename		checked by		-			
created	2020-10-05	approved by		-			
last saved	2021-12-20	status		-			

Label Location Information

