



F2 Labs  
16740 Peters Road  
Middlefield, Ohio 44062  
United States of America  
[www.f2labs.com](http://www.f2labs.com)

## RADIO CERTIFICATION TEST REPORT

---

**Manufacturer:** Petropower, LLC  
3003 East 37th Street North, Suite 100  
Wichita, Kansas 67219 USA

**Applicant:** Same as Above

**Product Name:** T-Rex Smart Controller

**Product Description:** Edge computer platform used for oil field telemetry and control applications.

**Operating Voltage/Frequency:** 120VAC, 60 Hz

**Model(s):** 50003\*  
*\*Denotes actual model tested as worst-case representative of product family that includes models T-Rex Smart Controller 50003 and Well-EQ Uplink 11111. Model 11111 does not have BLE, NFC, or AC/DC power supply.*

**FCC ID:** 2BGG6PP11

**Testing Commenced:** 2024-05-29

**Testing Ended:** 2024-09-12

**Summary of Test Results:** In Compliance, with Modifications

The EUT complies with the EMC requirements when manufactured identically as the unit tested in this report, including any required modifications and/or manufacturer's statement. Any changes to the design or build of this unit subsequent to this testing may deem it non-compliant.

### Standards:

- ❖ FCC Part 15 Subpart C, Section 15.209
- ❖ FCC Part 15 Subpart C, Section 15.215(c) – Additional provisions to the general radiated emission limitations
- ❖ FCC Part 15 Subpart A, Section 15.31(e) – Measurement Standards
- ❖ FCC15.207 - Conducted Limits



Order No(s): F2P32071A

Applicant: Petropower, LLC  
Model(s): 50003

**Evaluation Conducted by:**

Julius Chiller, Senior Wireless Project Engineer

**Report Reviewed by:**

Ken Littell, Vice President of Operations

F2 Labs  
26501 Ridge Road  
Damascus, MD 20872  
Ph 301.253.4500

F2 Labs  
16740 Peters Road  
Middlefield, OH 44062  
Ph 440.632.5541

F2 Labs  
8583 Zionsville Road  
Indianapolis, IN 46268  
Ph 317.610.0611

This test report may be reproduced in full; partial reproduction only may be made with the written consent of F2 Labs. The results in this report apply only to the equipment tested.



## TABLE OF CONTENTS

1	<u>ADMINISTRATIVE INFORMATION</u>
2	<u>SUMMARY OF TEST RESULTS/MODIFICATIONS</u>
3	<u>TABLE OF MEASURED RESULTS</u>
4	<u>ENGINEERING STATEMENT</u>
5	<u>EUT INFORMATION AND DATA</u>
6	<u>LIST OF MEASUREMENT INSTRUMENTATION</u>
7	<u>OCCUPIED BANDWIDTH</u>
8	<u>FIELD STRENGTH OF EMISSIONS/RADIATED SPURIOUS EMISSIONS</u>
9	<u>VARIATION OF THE INPUT POWER</u>
10	<u>CONDUCTED EMISSIONS</u>
11	<u>TEST SETUP PHOTOGRAPH(S)</u>



## **1 ADMINISTRATIVE INFORMATION**

### **1.1 Measurement Location:**

F2 Labs in Middlefield, Ohio. Site description and attenuation data are on file with the FCC's Sampling and Measurement Branch at the FCC Laboratory in Columbia, MD.

### **1.2 Measurement Procedure:**

All measurements were performed according to ANSI C63.10 and recommended FCC procedure of measurement of equipment operating under Section 15.209. A list of the measurement equipment can be found in Section 6.



### 1.3 Uncertainty Budget:

The uncertainty in EMC measurements arises from several factors which affect the results, some associated with environmental conditions in the measurement room, the test equipment being used, and the measurement techniques adopted.

The measurement uncertainty budgets detailed below are calculated from the test and calibration data and are expressed with a 95% confidence factor using a coverage factor of  $k=2$ . The Uncertainty for a laboratory is referred to as  $U_{lab}$ . For Radiated and Conducted Emissions, the Expanded Uncertainty is compared to the  $U_{cispr}$  values to determine if a specific margin is required to deem compliance.

#### $U_{lab}$

Measurement Range	Combined Uncertainty	Expanded Uncertainty
Radiated Emissions <1 GHz @ 3m	2.54dB	5.07dB
Radiated Emissions <1 GHz @ 10m	2.55dB	5.09dB
Radiated Emissions 1 GHz to 2.7 GHz	1.81dB	3.62dB
Radiated Emissions 2.7 GHz to 18 GHz	1.55dB	3.10dB
AC Power Line Conducted Emissions, 150kHz to 30 MHz	1.38dB	2.76dB
AC Power Line Conducted Emissions, 9kHz to 150kHz	1.66dB	3.32dB

#### $U_{cispr}$

Measurement Range	Expanded Uncertainty
Radiated Emissions <1 GHz @ 3m	5.2dB
Radiated Emissions <1 GHz @ 10m	5.2dB
Radiated Emissions 1 GHz to 2.7 GHz	Under Consideration
Radiated Emissions 2.7 GHz to 18 GHz	Under Consideration
AC Power Line Conducted Emissions, 150kHz to 30 MHz	3.6dB
AC Power Line Conducted Emissions, 9kHz to 150kHz	4.0dB

If  $U_{lab}$  is less than or equal to  $U_{cispr}$ , then:

- compliance is deemed to occur if no measured disturbance exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cispr}$  in table 1, then:

- compliance is deemed to occur if no measured disturbance, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit.

Note: Only measurements listed in the tables above that relate to tests included in this Test Report are applicable.



Order No(s): F2P32071A

Applicant: Petropower, LLC  
Model(s): 50003

#### 1.4 Document History:

Document Number	Description	Issue Date	Approved By
F2P32071A-01E	First Issue	2024-09-12	K. Littell



## 2 SUMMARY OF TEST RESULTS

Test Name	Standard(s)	Results
Occupied Bandwidth	CFR 47 Part 15.215(c)	Complies
Field Strength of Emissions	CFR 47 Part 15.209	Complies
Radiated Spurious Emissions	CFR 47 Part 15.209	Complies
Variation of the Input Power	CFR 47 Part 15.31(e)	Complies
Conducted Emissions	CFR 47 Part 15.207(a)	Complies*

\*Complies with modifications.

### Modifications Made to the Equipment

The following modifications were made to meet Conducted Emissions requirements:

- 0.22 $\mu$ F capacitor placed from live AC input to PE.





### 3 TABLE OF MEASURED RESULTS

Test	13.56 MHz
Field Strength of Fundamental at 1m*	12.44 dB $\mu$ V/m
Field Strength of Fundamental corrected for 30m	-46.64 dB $\mu$ V/m
Limit for Fundamental at 30m	29.5 dB $\mu$ V/m
-20dB Occupied Bandwidth	1.015 kHz
99% Occupied Bandwidth	1.392 kHz
Variation of Input Power @ -15%	12.39 dB $\mu$ V/m
Variation of Input Power to @ +15%	12.61 dB $\mu$ V/m

*\*13.56 MHz Field Strength was measured at 1m. The dB $\mu$ A/m was converted to dB $\mu$ V/m by adding 51.5dB.*





#### **4 ENGINEERING STATEMENT**

This report has been prepared on behalf of Petropower, LLC to provide documentation for the testing described herein. This equipment has been tested and found to comply with part 15.209 of the FCC Rules using ANSI C63.10 and Part 15 standards. The test results found in this test report relate only to the items tested.



## 5 EUT INFORMATION AND DATA

### 5.1 Equipment Under Test:

Product: **T-Rex Smart Controller**

Model(s): **50003\***

*\*Denotes actual model tested as worst-case representative of product family that includes models T-Rex Smart Controller 50003 and Well-EQ Uplink 11111. Model 11111 does not have BLE, NFC, or AC/DC power supply.*

Serial No(s): CGGSEL

Firmware Version: 111

Hardware Version: 46066002

FCC ID: **2BGG6PP11**

5.2 Trade Name: **Petro Power, LLC**

### 5.3 Power Supply:

120VAC, 60 Hz

### 5.4 Applicable Rules:

CFR 47, Part 15.209

### 5.5 Antenna:

Integral

5.6 Accessories: None

### 5.7 Test Item Condition:

The equipment to be tested was received in good condition.

### 5.8 Testing Algorithm:

EUT was configured to transmit in continuous mode at 13.56 MHz.

**6 LIST OF MEASUREMENT INSTRUMENTATION**

Equipment Type	Asset Number	Manufacturer	Model	Serial Number	Calibration Due Date
Shielded Chamber	CL166-E	Albatross Projects	B83117-DF435-T261	US140023	2024-11-15
Receiver	CL151	Rohde & Schwarz	ESU40	100319	2025-04-09
Antenna, JB3 Combination	CL175	Sunol Sciences	JB3	A030315	2024-09-25
Amplifier w/18" Loop Antenna	CL163-Loop	AH Systems, Inc.	EHA-52B	100	2024-12-14
Low Loss Cable Set	CL315 / CL318	Fairview Microwave	FMC0202914-72/FMC0202914-240	None Spec.	2025-04-09 / 2025-04-10
Pre-Amplifier	CL284	A.H. Systems	PAM-1001	131	2025-04-10
Software:	Tile Version 3.4.B.3		Software Verified: 2024-05-29		
Software:	EMC 32, Version 8.53.0		Software Verified: 2024-05-29		
Spectrum Analyzer	0141	Hewlett Packard	8591E	3520A04145	2025-04-09
Transient Limiter	0202	Hewlett Packard	11947A	3107A00729	2025-04-09
LISN	CL181	Com-Power	LI-125A	191226	2026-11-20
LISN	CL182	Com-Power	LI-125A	191225	2026-11-21
Temp/Hum. Recorder	CL295	Thermpro	TP50	3	2026-04-27
Temp/Hum. Recorder	CL294	Thermpro	TP50	2	2026-04-27



## **7 OCCUPIED BANDWIDTH**

### **7.1 Requirements:**

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the -20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage.


Bandwidth measurements were made at the 13.56 MHz frequency. The 20dB bandwidth was measured using the Marker Delta method. The 99% bandwidth was measured using the analyzer's OBW measurement function. The 1-5% of OBW for RBW setting was not possible due to the nature of the signal.



## 7.2 Test Data - Occupied Bandwidth

Test Date(s):	2024-09-12	Test Engineer(s):	J. Chiller
Standards:	CFR 47 Part 15.215(c)	Air Temperature:	21.1°C
		Relative Humidity:	46%

## 13.56 MHz: 99% OBW




Date: 12.SEP.2024 15:35:57



Order No(s): F2P32071A

Applicant: Petropower, LLC  
Model(s): 50003

### 13.56 MHz: -20dB OBW



Date: 12.SEP.2024 15:35:25



## 8 FIELD STRENGTH OF EMISSIONS/RADIATED SPURIOUS EMISSIONS

At least 6 of the highest frequencies were measured per ANSI 63.4 in a 3-meter anechoic chamber. Frequencies below 1 GHz were measured using a quasi-peak detector. The antenna was raised between 1 and 4 meters and the EUT turntable was rotated 360 degrees to maximize the emissions. Some of the frequencies did not change with the EUT on or off. At those frequencies, the test distance was shortened to 1 meter and still no emissions from the EUT were visible or over the ambient or limit. Frequencies were scanned from 9kHz to 1000 MHz and the highest emissions are listed below.

Notes: Plots are peak, max hold pre-scan data included only to determine what frequencies to investigate and measure. During the pre-scan evaluation, the EUT was rotated in all possible directions and three orthogonal positions to find the maximum emissions. The orthogonal position that showed the highest emissions was used. At some frequencies, no emissions from the EUT were measurable over the ambient noise floor. The readings did not change with EUT on and EUT off.

In the following plots, the red line indicates the measurement with the EUT on. Emissions to be found by the EUT were measured and listed in the tables that follow.

Field strength was measured at 1 meter.

.




Order No(s): F2P32071A

Applicant: Petropower, LLC  
Model(s): 50003

Test Date(s):	2024-05-29	Test Engineer(s):	J. Chiller
Standards:	CFR 47 Part 15.209	Air Temperature:	22.1°C
Results:	Complies	Relative Humidity:	46%

**Field Strength, 13.56 MHz @ 1m:  
Characterization Scan, 0.15 MHz to 30 MHz (Loop Antenna)**








Order No(s): F2P32071A

Applicant: Petropower, LLC  
Model(s): 50003

Test Date(s):	2204-05-29	Test Engineer(s):	J. Chiller
Standards:	CFR 47 Part 15.209	Air Temperature:	22.1°C
Results:	Complies	Relative Humidity:	46%


**Radiated Spurious Emissions, 30 MHz to 1000 MHz**

Frequency (MHz)	Ant. Pol.	Ant. Height (cm)	Azimuth (degrees)	Reading (dBμV)	Cable Loss & Antenna Factor (dB)	Emission (dBμV/m)	Limit (dBμV/m)	Margin (dB)
32.040000	V	100.00	0.00	16.6	10.6	27.20	40.0	-12.8
35.480000	V	100.00	0.00	18.2	8.0	26.20	40.0	-13.8
45.280000	V	100.00	11.00	24.3	1.1	25.40	40.0	-14.6
54.240000	V	100.00	335.00	32.3	-1.7	30.60	40.0	-9.4
77.040000	V	100.00	172.00	27.6	-1.2	26.40	40.0	-13.6
103.400000	V	100.00	294.00	28.8	2.2	31.00	43.5	-12.5
103.920000	H	100.00	205.00	22.8	2.3	25.10	43.5	-18.4
142.800000	V	100.00	113.00	28.5	3.9	32.40	43.5	-11.1
144.560000	H	200.00	62.00	33.3	3.8	37.10	43.5	-6.4






### Radiated Spurious Emissions, 30 MHz to 1000 MHz - Vertical




### Radiated Spurious Emissions, 30 MHz to 1000 MHz - Horizontal






## Radiated Spurious Emissions, 0.009 MHz to 0.15 MHz - Loop Antenna



## Radiated Spurious Emissions, 0.15 MHz to 30.0 MHz - Loop Antenna





## **9 VARIATION OF THE INPUT POWER, 15.31(e)**

### **9.1 Requirements:**

For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.




## 9.2 Test Data – Variation of the Input Power

Test Date(s):	2024-05-29	Test Engineer(s):	J. Chiller
Standards:	CFR 47 Part 15.31(e)	Air Temperature:	22.3°C
Results:	Complies*	Relative Humidity:	48%

*\*The results show that the fundamental frequency did not move outside the frequency band and the field strength did not increase above the limit during the variations.*

### 13.56 MHz: Characterization Scan @ -15%






Order No(s): F2P32071A

Applicant: Petropower, LLC  
Model(s): 50003

### 13.56 MHz: Characterization Scan, Nominal






Order No(s): F2P32071A

Applicant: Petropower, LLC  
Model(s): 50003

### 13.56 MHz: Characterization Scan @ +15%





## 10 CONDUCTED EMISSIONS

### 10.1 Requirements

In accordance with FCC CFR 47 Part 15.207(a), "Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 10.2 Procedure

The EUT was placed on a 1.0 x 1.5 meter non-conductive table, 0.8 meter above a horizontal ground plane and 0.4 meter from a vertical ground plane. Power was provided to the EUT through a LISN bonded to a 3 x 2 meter ground plane. The LISN and peripherals were supplied power through a filtered AC power source. The output of the LISN was connected to the input of the receiver via a transient limiter, and emissions in the range 150 kHz to 30 MHz were measured. The measurements were recorded using the quasi-peak and average detectors as directed by the standard, and the resolution bandwidth during testing was 9 kHz. The raw measurements were corrected to allow for attenuation from the LISN, transient limiter and cables.







### 10.3 Conducted Emissions Test Data

Test Date:	2024-05-29	Test Engineer:	J. Chiller
Rule:	15.207	Air Temperature:	22.4° C
Test Results:	Complies, with Modifications	Relative Humidity:	48%

#### Conducted Test – Live: 0.15 MHz to 0.5 MHz




#### Conducted Test – Live: 0.5 MHz to 5.0 MHz






### Conducted Test – Live: 5.0 MHz to 30.0 MHz




**Note: Peak scans below AVG limit.**



### Conducted Test – Neutral: 0.15 MHz to 0.5 MHz




### Conducted Test – Neutral: 0.5 MHz to 5.0 MHz





## Conducted Test – Neutral: 5.0 MHz to 30.0 MHz




Top Discrete Measurements								
No.	Conductor	Frequency (MHz)	Detector	Level (dBμV)	Adjustment (dB)	Results (dBμV)	Limit (dBμV)	Margin (dB)
1	Neutral	0.1535	Quasi-Peak	45.33	12.227	57.56	65.810	-8.3
			Average	33.86	12.227	46.09	55.810	-9.7
2	Neutral	0.1579	Quasi-Peak	46.96	12.172	59.13	65.576	-6.4
			Average	34.49	12.172	46.66	55.576	-8.9
3	Neutral	0.169	Quasi-Peak	45.09	12.031	57.12	64.998	-7.9
			Average	34.14	12.031	46.17	54.998	-8.8
4	Neutral	0.177	Quasi-Peak	43.50	11.934	55.43	64.621	-9.2
			Average	31.17	11.934	43.10	54.621	-11.5
5	Neutral	0.193	Quasi-Peak	41.42	11.727	53.15	63.875	-10.7
			Average	27.57	11.727	39.30	53.875	-14.6
6	Neutral	0.223	Quasi-Peak	37.19	11.453	48.64	62.688	-14.0
			Average	21.83	11.453	33.28	52.688	-19.4
7	Neutral	0.246	Quasi-Peak	33.05	11.261	44.31	61.883	-17.6
			Average	19.07	11.261	30.33	51.883	-21.6




## 11 TEST SETUP PHOTOGRAPH(S)

Above 30 MHz






**Field Strength / Radiated Spurious Emissions / Occupied Bandwidth/  
Less than 30 MHz / Voltage Variations**





## Radiated Spurious Emissions: 30 MHz to 150 MHz



## Conducted Emissions

