

TEST REPORT

Product Name: WiFi/BT Module
Trade Mark: msi
Model No. / HVIN: MWH540S
Add. Model No. / HVIN: N/A
Report Number: 24112914988RFC-1
Test Standards: FCC 47 CFR Part 15 Subpart C
RSS-247 Issue 3
RSS-Gen Issue 5
FCC ID: I4L-MWH540S
IC: 3715A-MWH540S
Test Result: PASS
Date of Issue: January 7, 2025

Prepared for:

Micro-Star Int'l Co., Ltd.
No. 69, Lide St., Zhonghe Dist., New Taipei City 235, Taiwan

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6th, Baoneng Science and Technology Park,
Longhua Street, Longhua District, Shenzhen, China

TEL: +86-755-2823 0888

FAX: +86-755-2823 0886

Prepared by:

David Chen

David Chen
Senior Project Engineer

Reviewed by:

Henry Lu

Henry Lu
Team Leader

Approved by:

Robben Chen

Robben Chen
Assistant Manager

Date:

January 7, 2025

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

Version

Version No.	Date	Description
V1.0	January 7, 2025	Original



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	5
1.5 DESCRIPTION OF SUPPORT UNITS	5
1.6 TEST LOCATION	5
1.7 TEST FACILITY	5
1.8 DEVIATION FROM STANDARDS	6
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.11 MEASUREMENT UNCERTAINTY	6
2. TEST SUMMARY	7
3. EQUIPMENT LIST	8
4. TEST CONFIGURATION	9
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	9
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	9
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE	9
4.2 TEST CHANNELS	9
4.3 EUT TEST STATUS	9
4.4 TEST SETUP	10
4.4.1 FOR RADIATED EMISSIONS TEST SETUP	10
4.4.2 FOR CONDUCTED EMISSIONS TEST SETUP	11
4.4.3 FOR CONDUCTED RF TEST SETUP	12
4.5 SYSTEM TEST CONFIGURATION	12
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	13
5.1 REFERENCE DOCUMENTS FOR TESTING	13
5.2 ANTENNA REQUIREMENT	13
5.3 CONDUCTED PEAK OUTPUT POWER	14
5.4 RADIATED SPURIOUS EMISSIONS	15
5.5 BAND EDGE MEASUREMENTS (RADIATED)	22
APPENDIX 1 PHOTOS OF TEST SETUP	31
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	31

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Micro-Star Int'l Co., Ltd.
Address of Applicant:	No. 69, Lide St., Zhonghe Dist., New Taipei City 235, Taiwan
Manufacturer:	Micro-Star Int'l Co., Ltd.
Address of Manufacturer:	No. 69, Lide St., Zhonghe Dist., New Taipei City 235, Taiwan

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	WiFi/BT Module		
Model No. / HVIN:	MWH540S		
Add. Model No. / HVIN:	N/A		
Trade Mark:	msi		
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	IEEE 802.11b/g/n	
		Bluetooth V5.0	
	5 GHz U-NII Bands:	5 150 MHz to 5 350 MHz	IEEE 802.11a/n/ac
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac
		5 725 MHz to 5 875 MHz	IEEE 802.11a/n/ac
Software Version:	N/A (Provided by the customer)		
Hardware Version:	V3.00 (Provided by the customer)		
Sample Received Date:	November 11, 2024		
Sample Tested Date:	December 11, 2024 to December 27, 2024		
Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.			

1.2.2 Description of Accessories

None.

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth 5.0 (LE/2LE/LE Code)
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Antenna Type: (Provided by the customer)	Tube Antenna
Antenna Gain: (Provided by the customer)	3.38 dBi
Normal Test Voltage:	3.3 Vdc

1.4 OTHER INFORMATION

Operation Frequency Each of Channel	
$f = 2402 + 2k \text{ MHz, } k = 0, \dots, 39$	
Note:	
f	is the operating frequency (MHz);
k	is the operating channel.

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	DELL	Inspiron 5593	N/A	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.2 Meter	UnionTrust

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China, China 518109

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	±4.7 dB
4	Radiated emission 30MHz-1GHz	±4.6 dB
5	Radiated emission 1GHz-18GHz	±4.4 dB
6	Radiated emission 18GHz-26GHz	±4.6 dB
7	Radiated emission 26GHz-40GHz	±4.6 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.68 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	2.4 GHz: ± 6.5 × 10 ⁻⁸
12	Transmission Time	± 0.19 %

2. TEST SUMMARY

Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (b)(4) RSS-Gen Issue 5, Section 6.8	N/A	PASS ^{NOTE 1}
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207 RSS-Gen Issue 5, Section 8.8	ANSI C63.10-2013 Clause 6.2	VERIFIED ^{NOTE 1}
Conducted Peak Output Power	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3) RSS-247 Issue 3, Section 5.4(d)	ANSI C63.10-2013 Clause 11.9.1.3	PASS ^{NOTE 1}
6dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2) RSS-247 Issue 3, Section 5.2(a)	ANSI C63.10-2013 Clause 11.8.1	VERIFIED ^{NOTE 1}
Occupied Bandwidth	RSS-Gen Issue 5, Section 6.7	RSS-Gen Issue 5, Section 6.7	VERIFIED ^{NOTE 1}
Power Spectral Density	FCC 47 CFR Part 15 Subpart C Section 15.247 (e) RSS-247 Issue 3, Section 5.2(b)	ANSI C63.10-2013 Clause 11.10.2	VERIFIED ^{NOTE 1}
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d) RSS-247 Issue 3, Section 5.5	ANSI C63.10-2013 Clause 11.11	VERIFIED ^{NOTE 1}
Radiated Spurious Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209 RSS-Gen Issue 5, Section 6.13/8.9/8.10	ANSI C63.10-2013 Clause 11.11 & Clause 11.12	PASS ^{NOTE 1}
Band Edge Measurements (Radiated)	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209 RSS-247 Issue 3, Section 5.5	ANSI C63.10-2013 Clause 11.13	PASS ^{NOTE 1}
Note: 1) This report base on previous reports no.: SRTC2024-9004(F)-24032606(E) Issued by The State Radio_monitoring_center Testing Center (SRTC). Change Antenna, after evaluation, all data refer to previous reports except for the EIRP calculation and verifying the all Radiated Spurious Emissions and Band Edge Measurements (Radiated) tests.			
Disclaimer and Explanations: The declared of product specification and data (e.g., antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.			

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	3m SAC	ETS-LINDGREN	3M	Euroshiedpn-CT001270-1317	11-Nov-2023	10-Nov-2026
☒	Receiver	R&S	ESIB26	100114	25-Oct-2024	24-Oct-2025
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	28-Oct-2024	27-Oct-2025
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	29-Oct-2024	28-Oct-2025
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	29-Oct-2024	28-Oct-2025
☒	Preamplifier	HP	8447F	2805A02960	25-Oct-2024	24-Oct-2025
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	01-Apr-2024	31-Mar-2025
☒	Pre-amplifier	ETS-LINDGREN	00118385	00201874	01-Apr-2024	31-Mar-2025
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	28-Oct-2024	27-Oct-2025
☒	Pre-amplifier	ETS-LINDGREN	00118384	00202652	28-Oct-2024	27-Oct-2025
☒	Band Rejection Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G590	17-Jan-2024	16-Jan-2025
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

RF Conducted Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	29-Mar-2024	28-Mar-2025
☐	EXA Spectrum Analyzer	KEYSIGHT	N9020A	MY51286807	25-Oct-2024	24-Oct-2025
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	25-Oct-2024	24-Oct-2025

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	3.3	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temp. (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
Radiated Spurious Emissions Band Edge Measurements (Radiated)	21.1	31.6	100.6	S202410304552-PJA01	Jackson Wu

4.2 TEST CHANNELS

Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
GFSK	2402 MHz to 2480 MHz	Lowest(L)	Middle(M)	Highest(H)
		Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

4.3 EUT TEST STATUS

Type of Modulation	Tx Function	Description
GFSK	1Tx	1. Keep the EUT in continuously transmitting with modulation test single.

Test Software (Provided by the customer)
MPTool

4.4 TEST SETUP

4.4.1 For Radiated Emissions test setup




Figure 1. Below 30MHz







Figure 2. 30MHz to 1GHz



4.4.2 For Conducted Emissions test setup



4.4.3 For Conducted RF test setup



4.5 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 3.3 VDC. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in orientation.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	RSS-247 Issue 3	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
4	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
5	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
6	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi. RSS-Gen Issue 5, Section 6.8 requirement: According to RSS-Gen Issue 5, Section 6.8, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns.
EUT Antenna: The antenna adopts IPEX interface and no consideration of replacement. The gain of the antenna is 3.38 dBi.

5.3 CONDUCTED PEAK OUTPUT POWER

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3)

Test Method: ANSI C63.10-2013 Clause 11.9.1.3

Limit: For systems using digital modulation in the 2400-2483.5 MHz bands: 1 Watt.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter.
2. Measure out each test modes' peak or average output power, record the power level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.4.3 for details.

Instruments Used: Refer to section 3 for details

Test Results: Pass

Mode	Frequency	Max. Peak Power	Peak Power Limit	Peak EIRP	Peak EIRP Limit	Max. Avg. Power	Result
	(MHz)	(dBm)	(dBm)	(dBm)	(dBm)	(dBm)	
LE	2402	5.40	30	8.78	36.02	3.42	Pass
	2440	6.01	30	9.39	36.02	3.52	Pass
	2480	6.16	30	9.54	36.02	4.13	Pass
2LE	2402	5.57	30	8.95	36.02	0.83	Pass
	2440	6.20	30	9.58	36.02	0.98	Pass
	2480	6.32	30	9.70	36.02	1.48	Pass
LE Code 125k	2402	5.65	30	9.03	36.02	4.66	Pass
	2440	6.45	30	9.83	36.02	6.03	Pass
	2480	6.53	30	9.91	36.02	6.42	Pass
LE Code 500k	2402	5.37	30	8.75	36.02	3.56	Pass
	2440	5.96	30	9.34	36.02	2.15	Pass
	2480	6.10	30	9.48	36.02	3.55	Pass

Note:

1). The antenna gain of 3.38 dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.

5.4 RADIATED SPURIOUS EMISSIONS

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209
RSS-Gen Issue 5, Section 6.13/8.9/8.10

Test Method: ANSI C63.10-2013 Clause 11.11 & Clause 11.12

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

Spurious Emissions

Frequency	Field strength (microvolt/meter)	Limit (dB μ V/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.4.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

- 1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

2. Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter (Above 18GHz the distance is 1 meter and table is 1.5 meter).

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1

- 2) Test the EUT in the lowest channel, middle channel, the Highest channel
- 3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the Y axis positioning which it is worse case.
- 4) Repeat above procedures until all frequencies measured was complete.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:


Radiated Emission Test Data (9 KHz ~ 30 MHz):

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value need not be reported.


Radiated Emission Test Data (30 MHz ~ 1 GHz):

Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.000	26.99	-4.08	22.91	40.00	-17.09	Peak
2	51.176	36.88	-14.01	22.87	40.00	-17.13	Peak
3	135.916	36.53	-15.36	21.17	43.50	-22.33	Peak
4	266.839	42.12	-10.12	32.00	46.00	-14.00	Peak
5	401.105	34.79	-4.73	30.06	46.00	-15.94	Peak
6	838.887	32.51	3.71	36.22	46.00	-9.78	Peak



Radiated Emission Test Data (Above 1GHz):								
LE_Lowest Channel:								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804	35.27	-2.08	33.19	54.00	-20.81	Average	Horizontal
2	4804	47.42	-2.08	45.34	74.00	-28.66	Peak	Horizontal
3	7206	33.37	1.30	34.67	54.00	-19.33	Average	Horizontal
4	7206	46.05	1.30	47.35	74.00	-26.65	Peak	Horizontal
5	4804	35.32	-2.08	33.24	54.00	-20.76	Average	Vertical
6	4804	48.23	-2.08	46.15	74.00	-27.85	Peak	Vertical
7	7206	33.43	1.30	34.73	54.00	-19.27	Average	Vertical
8	7206	45.54	1.30	46.84	74.00	-27.16	Peak	Vertical
LE_Middle Channel:								
1	4880	35.15	-2.05	33.10	54.00	-20.90	Average	Horizontal
2	4880	46.55	-2.05	44.50	74.00	-29.50	Peak	Horizontal
3	7320	34.86	1.31	36.17	54.00	-17.83	Average	Horizontal
4	7320	47.00	1.31	48.31	74.00	-25.69	Peak	Horizontal
5	4880	35.25	-2.05	33.20	54.00	-20.80	Average	Vertical
6	4880	46.94	-2.05	44.89	74.00	-29.11	Peak	Vertical
7	7320	34.91	1.31	36.22	54.00	-17.78	Average	Vertical
8	7320	47.48	1.31	48.79	74.00	-25.21	Peak	Vertical
LE_Highest Channel:								
1	4960	34.62	-2.02	32.60	54.00	-21.40	Average	Horizontal
2	4960	46.67	-2.02	44.65	74.00	-29.35	Peak	Horizontal
3	7440	34.75	1.32	36.07	54.00	-17.93	Average	Horizontal
4	7440	47.27	1.32	48.59	74.00	-25.41	Peak	Horizontal
5	4960	34.62	-2.02	32.60	54.00	-21.40	Average	Vertical
6	4960	47.04	-2.02	45.02	74.00	-28.98	Peak	Vertical
7	7440	34.73	1.32	36.05	54.00	-17.95	Average	Vertical
8	7440	46.97	1.32	48.29	74.00	-25.71	Peak	Vertical

2LE_ Lowest Channel:								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804	35.25	-2.08	33.17	54.00	-20.83	Average	Horizontal
2	4804	46.84	-2.08	44.76	74.00	-29.24	Peak	Horizontal
3	7206	33.47	1.30	34.77	54.00	-19.23	Average	Horizontal
4	7206	46.07	1.30	47.37	74.00	-26.63	Peak	Horizontal
5	4804	35.27	-2.08	33.19	54.00	-20.81	Average	Vertical
6	4804	46.66	-2.08	44.58	74.00	-29.42	Peak	Vertical
7	7206	33.47	1.30	34.77	54.00	-19.23	Average	Vertical
8	7206	45.96	1.30	47.26	74.00	-26.74	Peak	Vertical
2LE_ Middle Channel:								
1	4880	35.15	-2.05	33.10	54.00	-20.90	Average	Horizontal
2	4880	46.81	-2.05	44.76	74.00	-29.24	Peak	Horizontal
3	7320	34.83	1.31	36.14	54.00	-17.86	Average	Horizontal
4	7320	47.70	1.31	49.01	74.00	-24.99	Peak	Horizontal
5	4880	35.22	-2.05	33.17	54.00	-20.83	Average	Vertical
6	4880	46.83	-2.05	44.78	74.00	-29.22	Peak	Vertical
7	7320	34.81	1.31	36.12	54.00	-17.88	Average	Vertical
8	7320	47.95	1.31	49.26	74.00	-24.74	Peak	Vertical
2LE_ Highest Channel:								
1	4960	34.64	-2.02	32.62	54.00	-21.38	Average	Horizontal
2	4960	46.19	-2.02	44.17	74.00	-29.83	Peak	Horizontal
3	7440	34.83	1.32	36.15	54.00	-17.85	Average	Horizontal
4	7440	46.86	1.32	48.18	74.00	-25.82	Peak	Horizontal
5	4960	34.54	-2.02	32.52	54.00	-21.48	Average	Vertical
6	4960	46.10	-2.02	44.08	74.00	-29.92	Peak	Vertical
7	7440	34.75	1.32	36.07	54.00	-17.93	Average	Vertical
8	7440	47.00	1.32	48.32	74.00	-25.68	Peak	Vertical

LE Code (S=2)_ Lowest Channel:								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804	35.27	-2.08	33.19	54.00	-20.81	Average	Horizontal
2	4804	47.78	-2.08	45.70	74.00	-28.30	Peak	Horizontal
3	7206	33.43	1.30	34.73	54.00	-19.27	Average	Horizontal
4	7206	45.94	1.30	47.24	74.00	-26.76	Peak	Horizontal
5	4804	35.27	-2.08	33.19	54.00	-20.81	Average	Vertical
6	4804	47.35	-2.08	45.27	74.00	-28.73	Peak	Vertical
7	7206	33.43	1.30	34.73	54.00	-19.27	Average	Vertical
8	7206	46.06	1.30	47.36	74.00	-26.64	Peak	Vertical
LE Code (S=2)_ Middle Channel:								
1	4880	35.17	-2.05	33.12	54.00	-20.88	Average	Horizontal
2	4880	47.48	-2.05	45.43	74.00	-28.57	Peak	Horizontal
3	7320	34.86	1.31	36.17	54.00	-17.83	Average	Horizontal
4	7320	47.00	1.31	48.31	74.00	-25.69	Peak	Horizontal
5	4880	35.07	-2.05	33.02	54.00	-20.98	Average	Vertical
6	4880	46.85	-2.05	44.80	74.00	-29.20	Peak	Vertical
7	7320	34.91	1.31	36.22	54.00	-17.78	Average	Vertical
8	7320	47.30	1.31	48.61	74.00	-25.39	Peak	Vertical
LE Code (S=2)_ Highest Channel:								
1	4960	34.54	-2.02	32.52	54.00	-21.48	Average	Horizontal
2	4960	46.45	-2.02	44.43	74.00	-29.57	Peak	Horizontal
3	7440	34.75	1.32	36.07	54.00	-17.93	Average	Horizontal
4	7440	47.90	1.32	49.22	74.00	-24.78	Peak	Horizontal
5	4960	34.56	-2.02	32.54	54.00	-21.46	Average	Vertical
6	4960	46.71	-2.02	44.69	74.00	-29.31	Peak	Vertical
7	7440	34.83	1.32	36.15	54.00	-17.85	Average	Vertical
8	7440	47.04	1.32	48.36	74.00	-25.64	Peak	Vertical

LE Code (S=8)_ Lowest Channel:								
No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804	35.30	-2.08	33.22	54.00	-20.78	Average	Horizontal
2	4804	47.67	-2.08	45.59	74.00	-28.41	Peak	Horizontal
3	7206	33.56	1.30	34.86	54.00	-19.14	Average	Horizontal
4	7206	46.11	1.30	47.41	74.00	-26.59	Peak	Horizontal
5	4804	35.42	-2.08	33.34	54.00	-20.66	Average	Vertical
6	4804	46.65	-2.08	44.57	74.00	-29.43	Peak	Vertical
7	7206	33.47	1.30	34.77	54.00	-19.23	Average	Vertical
8	7206	45.79	1.30	47.09	74.00	-26.91	Peak	Vertical
LE Code (S=8)_ Middle Channel:								
1	4880	35.22	-2.05	33.17	54.00	-20.83	Average	Horizontal
2	4880	47.84	-2.05	45.79	74.00	-28.21	Peak	Horizontal
3	7320	34.94	1.31	36.25	54.00	-17.75	Average	Horizontal
4	7320	47.56	1.31	48.87	74.00	-25.13	Peak	Horizontal
5	4880	35.10	-2.05	33.05	54.00	-20.95	Average	Vertical
6	4880	48.15	-2.05	46.10	74.00	-27.90	Peak	Vertical
7	7320	34.86	1.31	36.17	54.00	-17.83	Average	Vertical
8	7320	47.07	1.31	48.38	74.00	-25.62	Peak	Vertical
LE Code (S=8)_ Highest Channel:								
1	4960	34.72	-2.02	32.70	54.00	-21.30	Average	Horizontal
2	4960	46.93	-2.02	44.91	74.00	-29.09	Peak	Horizontal
3	7440	34.65	1.32	35.97	54.00	-18.03	Average	Horizontal
4	7440	46.74	1.32	48.06	74.00	-25.94	Peak	Horizontal
5	4960	34.62	-2.02	32.60	54.00	-21.40	Average	Vertical
6	4960	46.67	-2.02	44.65	74.00	-29.35	Peak	Vertical
7	7440	34.70	1.32	36.02	54.00	-17.98	Average	Vertical
8	7440	47.04	1.32	48.36	74.00	-25.64	Peak	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

5.5 BAND EDGE MEASUREMENTS (RADIATED)

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209
RSS-247 Issue 3, Section 5.5

Test Method: ANSI C63.10-2013 Clause 11.13

Limits:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Frequency	Limit (dBμV/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

Test Setup: Refer to section 4.4.1 for details.

Test Procedures:

Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).


1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.



Equipment Used: Refer to section 3 for details.



Test Result: Pass

The measurement data as follows:

Test Channel:	Lowest Channel	Ant. Polar. :	Horizontal		
Frequency (MHz)	Peak level (dB μ V/m)	Peak Limit (dB μ V/m)	AV level (dB μ V/m)	AV Limit (dB μ V/m)	Conclusion
2390.000	84.40	74.00	35.17	54.00	Pass





2LE Mode:

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com



<http://www.uttlab.com>

UTTR-RF-RSS247-V1.1






Test Channel:	Lowest Channel	Ant. Polar. :	Horizontal		
Frequency (MHz)	Peak level (dB μ V/m)	Peak Limit (dB μ V/m)	AV level (dB μ V/m)	AV Limit (dB μ V/m)	Conclusion
2390.000	49.09	74.00	36.04	54.00	Pass





Test Channel:	Lowest Channel	Ant. Polar. :	Horizontal		
Frequency (MHz)	Peak level (dB μ V/m)	Peak Limit (dB μ V/m)	AV level (dB μ V/m)	AV Limit (dB μ V/m)	Conclusion
2390.000	49.24	74.00	35.48	54.00	Pass





APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
