



Report No.: T180523N07-MF  
Page 1 of 6 Rev. 00  
FCC ID: XEG-TN180BT-C

**IEEE C95.1  
KDB 447498 D03  
47 C.F.R. Part 1, Subpart I, Section 1.1310  
47 C.F.R. Part 2, Subpart J, Section 2.1091  
TEST REPORT**

**RF EXPOSURE REPORT**

**For  
ANALOG PLAYER  
Model: TN-180BT  
Data Applies To: N/A  
Trade Name: TEAC**

*Issued to*  
**TEAC CORPORATION  
1-47 Ochiai, Tama-shi, Tokyo 206-8530, Japan**

**Issued By  
Compliance Certification Services Inc.  
Tainan Laboratory  
No.8, Jiucengling, Xinhua Dist., Tainan City  
712, Taiwan (R.O.C.)  
TEL: 886-6-580-2201  
FAX: 886-6-580-2202  
<http://www.ccsrf.com>  
E-Mail : [service@ccsrf.com](mailto:service@ccsrf.com)  
Issued Date: June 26, 2018**



Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



## **Revision History**

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	June 26, 2018	Initial Issue	ALL	Sunny Chang



## TABLE OF CONTENTS

1. LIMIT .....	4
2. EUT SPECIFICATION .....	4
3. TEST RESULTS .....	5
4. MAXIMUM PERMISSIBLE EXPOSURE .....	6

## 1. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

## 2. EUT SPECIFICATION

<b>EUT</b>	ANALOG PLAYER		
<b>Model</b>	TN-180BT		
<b>RF Module</b>	BRITO	<b>Model:</b>	BLTTM8670
<b>Frequency band (Operating)</b>	<input type="checkbox"/> 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz 802.11n HT40: 2.422GHz ~ 2.452GHz 802.11a/n HT20: 5.180GHz ~ 5.240GHz / 5.745 ~ 5.825GHz 802.11n HT40: 5.190GHz ~ 5.230GHz / 5.755~ 5.795GHz 802.11ac VHT80: 5.210GHz / 5.775GHz <input checked="" type="checkbox"/> Others		
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others		
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )		
<b>Antenna Specification</b>	Dipole Antenna / Gain: 2.04 dBi (Numeric gain: 1.60) worst		
<b>Maximum Average output power</b>	Bluetooth 3.0: 5.813 dBm (3.813 mW) Bluetooth 4.0: 5.038 dBm (3.190 mW)		
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A		

### 3. TEST RESULTS

**No non-compliance noted.**

#### Calculation

Given  $E = \frac{\sqrt{30 \times P \times G}}{d}$  &  $S = \frac{E^2}{377}$

Where  $E$  = Field strength in Volts / meter

$P$  = Power in Watts

$G$  = Numeric antenna gain

$d$  = Distance in meters

$S$  = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where  $d$  = Distance in cm

$P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW / cm<sup>2</sup>

## 4. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using  $d = 20$  cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where  $P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power density in mW / cm<sup>2</sup>

### Bluetooth 3.0 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)	Result
Mid	2441	3.813	1.60	20	0.0012	1	Pass

### Bluetooth 4.0 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm <sup>2</sup>	Limit (mW/cm2)	Result
High	2480	3.190	1.60	20	0.0010	1	Pass