



KSIGN Testing Co., Ltd.

Building 5, No. 316, Jianghong South Road Binjiang District, Hangzhou 310052, China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website:www.gdkesign.com

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description:	Key Programmer
Model Name:	TOP KEY
FCC ID:	2AVYW-TOPKEY

2. EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f ²)*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

*Note:

1. f= Frequency in MHz * Plane-wave Equivalent Power Density
2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

$$S=PG/4\pi R^2$$

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



KSIGN Testing Co., Ltd.

Building 5, No. 316, Jianghong South Road Binjiang District, Hangzhou 310052, China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website:www.gdkesign.com

3. CALCULATION

A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated.

WIFI PART(Can not transmit at different band simultaneously)

Antenna Gain=2.0dBi (Numeric 1.58), $\pi=3.14$

Mode	Frequency (MHz)	Output Power (dBm)	Tune-up power (dBm)	Output Power (mW)	Power Density (mW/cm ²)	Power Density Limit (mW/cm ²)
DH5	2402	1.35	0.5 ± 1	1.413	0.0004	1
	2441	0.92	0.5 ± 1	1.413	0.0004	1
	2480	-0.19	0.5 ± 1	1.413	0.0004	1
2DH5	2402	1.07	0.5 ± 1	1.413	0.0004	1
	2441	0.6	0.5 ± 1	1.413	0.0004	1
	2480	-0.26	0.5 ± 1	1.413	0.0004	1
3DH5	2402	1.22	0.5 ± 1	1.413	0.0004	1
	2441	0.69	0.5 ± 1	1.413	0.0004	1
	2480	-0.23	0.5 ± 1	1.413	0.0004	1
BLE	2402	-1.4	-2 ± 1	0.794	0.0003	1
	2440	-1.48	-2 ± 1	0.794	0.0003	1
	2480	-2.59	-2 ± 1	0.794	0.0003	1

Conclusion:

For the max result: $0.004 \leq 1$ for FCC SAR, No RF exposure evaluation is required.

--THE END--