



规格:50*50mm

TOPSTAR EV CHARGER

Model Number:
TSE240V/32AUS-H01R002

Input:
208-240VAC, single phase,60Hz,32A

Output:
208-240VAC,60Hz,32A max

Temperature Rating:
-22°F to 122°F(-30°C to 50°C)

Enclosure Rating:
NEMA Type 4

Date Code: XXXXXX
Serial Number: XXXX
CCID: XXXXXXXXXX



Conforms to UL std UL 2594
Certified to CSA std C22.2 No. 280.



Contains FCC ID: 2AC7Z-ESPC3WROOM
Contains IC: 21098-ESPC3WROOM
FCC ID: 2A9FM-TSE240VAUS
IC: 29702-TSE240VAUS

TOPSTAR EV CHARGER

Model Number:
TSE240V/40AUS-H01R002

Input:
208-240VAC, single phase,60Hz,40A

Output:
208-240VAC,60Hz,40A max

Temperature Rating:
-22°F to 122°F(-30°C to 50°C)

Enclosure Rating:
NEMA Type 4

Date Code: XXXXXX
Serial Number: XXXX
CCID: XXXXXXXXXX



Conforms to UL std UL 2594
Certified to CSA std C22.2 No. 280.



Contains FCC ID: 2AC7Z-ESPC3WROOM
Contains IC: 21098-ESPC3WROOM
FCC ID: 2A9FM-TSE240VAUS
IC: 29702-TSE240VAUS

TOPSTAR EV CHARGER

Model Number:
TSE240V/48AUS-H01R002

Input:
208-240VAC, single phase,60Hz,48A

Output:
208-240VAC,60Hz,48A max

Temperature Rating:
-22°F to 122°F(-30°C to 50°C)

Enclosure Rating:
NEMA Type 4

Date Code: XXXXXX
Serial Number: XXXX
CCID: XXXXXXXXXX



Conforms to UL std UL 2594
Certified to CSA std C22.2 No. 280.



Contains FCC ID: 2AC7Z-ESPC3WROOM
Contains IC: 21098-ESPC3WROOM
FCC ID: 2A9FM-TSE240VAUS
IC: 29702-TSE240VAUS

TOPSTAR EV CHARGER

Model Number:
TSE240V/32AUS-C01R001

Input:
208-240VAC, single phase,60Hz,32A

Output:
208-240VAC,60Hz,32A max

Temperature Rating:
-22°F to 122°F(-30°C to 50°C)

Enclosure Rating:
NEMA Type 4

Date Code: XXXXXX
Serial Number: XXXX
CCID: XXXXXXXXXX



Conforms to UL std UL 2594
Certified to CSA std C22.2 No. 280.



Contains FCC ID: 2AC7Z-ESPC3WROOM
Contains FCC ID: XMR201909EC25AFX
Contains IC: 21098-ESPC3WROOM
Contains IC: 10224A-2019EC25AFX
FCC ID: 2A9FM-TSE240VAUS
IC: 29702-TSE240VAUS

TOPSTAR EV CHARGER

Model Number:
TSE240V/40AUS-C01R001

Input:
208-240VAC, single phase,60Hz,40A

Output:
208-240VAC,60Hz,40A max

Temperature Rating:
-22°F to 122°F(-30°C to 50°C)

Enclosure Rating:
NEMA Type 4

Date Code: XXXXXX
Serial Number: XXXX
CCID: XXXXXXXXXX



Conforms to UL std UL 2594
Certified to CSA std C22.2 No. 280.



Contains FCC ID: 2AC7Z-ESPC3WROOM
Contains FCC ID: XMR201909EC25AFX
Contains IC: 21098-ESPC3WROOM
Contains IC: 10224A-2019EC25AFX
FCC ID: 2A9FM-TSE240VAUS
IC: 29702-TSE240VAUS

TOPSTAR EV CHARGER

Model Number:
TSE240V/48AUS-C01R001

Input:
208-240VAC, single phase,60Hz,48A

Output:
208-240VAC,60Hz,48A max

Temperature Rating:
-22°F to 122°F(-30°C to 50°C)

Enclosure Rating:
NEMA Type 4

Date Code: XXXXXX
Serial Number: XXXX
CCID: XXXXXXXXXX



Conforms to UL std UL 2594
Certified to CSA std C22.2 No. 280.



Contains FCC ID: 2AC7Z-ESPC3WROOM
Contains FCC ID: XMR201909EC25AFX
Contains IC: 21098-ESPC3WROOM
Contains IC: 10224A-2019EC25AFX
FCC ID: 2A9FM-TSE240VAUS
IC: 29702-TSE240VAUS

TOPSTAR EV CHARGER

Model Number:
TTSE240V/32AUS-C01R002

Input:
208-240VAC, single phase,60Hz,32A

Output:
208-240VAC,60Hz,32A max

Temperature Rating:
-22°F to 122°F(-30°C to 50°C)

Enclosure Rating:
NEMA Type 4

Date Code: XXXXXX
Serial Number: XXXX
CCID: XXXXXXXXXX



Conforms to UL std UL 2594
Certified to CSA std C22.2 No. 280.



Contains FCC ID: 2AC7Z-ESPC3WROOM
Contains IC: 21098-ESPC3WROOM
FCC ID: 2A9FM-TSE240VAUS
IC: 29702-TSE240VAUS

TOPSTAR EV CHARGER

Model Number:
TSE240V/40AUS-C01R002

Input:
208-240VAC, single phase,60Hz,40A

Output:
208-240VAC,60Hz,40A max

Temperature Rating:
-22°F to 122°F(-30°C to 50°C)

Enclosure Rating:
NEMA Type 4

Date Code: XXXXXX
Serial Number: XXXX
CCID: XXXXXXXXXX



Conforms to UL std UL 2594
Certified to CSA std C22.2 No. 280.



Contains FCC ID: 2AC7Z-ESPC3WROOM
Contains IC: 21098-ESPC3WROOM
FCC ID: 2A9FM-TSE240VAUS
IC: 29702-TSE240VAUS

TOPSTAR EV CHARGER

Model Number:
TSE240V/48AUS-C01R002

Input:
208-240VAC, single phase,60Hz,48A

Output:
208-240VAC,60Hz,48A max

Temperature Rating:
-22°F to 122°F(-30°C to 50°C)

Enclosure Rating:
NEMA Type 4

Date Code: XXXXXX
Serial Number: XXXX
CCID: XXXXXXXXXX



Conforms to UL std UL 2594
Certified to CSA std C22.2 No. 280.



Contains FCC ID: 2AC7Z-ESPC3WROOM
Contains IC: 21098-ESPC3WROOM
FCC ID: 2A9FM-TSE240VAUS
IC: 29702-TSE240VAUS