



C-MAC Engineering
21 Richardson Side rd
Kanata ON K2K 2C1 · Canada
Tel 613 763 7847
Fax 613 763 8091

www.cmac.com

Denis Lalonde
Radio Compliance Specialist.

December 1, 2000

American TCB, Inc.
6731 Whittier Avenue
Suite C110
McLean, VA 22101

Re: AB6NTHV5XD

Dear Sir or Madam:

This document describes the method used for determining the minimum separation distance between the iBWA System 3200 and the general public in order to prevent RF exposure as per paragraph 1.1310.

The minimum separation distance was determined with calculations. They were done using FCC OST/OET Bulletin 65 ("Evaluating Compliance with FCC Specified Guidelines for Human Exposure to Radiofrequency Radiation"). The aperture antenna equations for predicting RF fields from that document were used. The iBWA System 3200 will be deployed using antennas of 3 different dimension: 60 cm, 90 cm, and 120 cm. The aperture antenna equations were used to evaluate the power density levels of all 3 antennas. The worst case results are recorded below.

The power density of the 18 GHz iBWA System 3200:

- at the surface of the 60 cm antenna is 0.14 mW/cm^2 (OST/OET Bulletin 65 equation 11)
- in the near field ($R < 5.6 \text{ m}$ from the 60 cm antenna) is less than 0.08 mW/cm^2 (equation 12, 13, 14)
- in the transition region ($5.6 \text{ m} < R < 13.5 \text{ m}$ from the 60 cm antenna) is less than 0.08 mW/cm^2 (equation 16, 17)
- in the far field ($R > 13.5 \text{ m}$ from the 60 cm antenna) is less than 0.035 mW/cm^2 (equation 18)

Power = 20.0 dBm

Antenna diameter = 60 cm, 90 cm, or 120 cm

Frequency = 18700 MHz

Antenna gain = 39 dBi (60 cm), 42.4 (90 cm), and 44.9 dBi (120 cm)

The FCC General Population limit is 1 mW/cm^2 , hence the 18 GHz iBWA System 3200 meets the requirement at any distance.

Regards,

Denis Lalonde
Product Integrity
email: dlalonde@kan.cmac.com
C-MAC Engineering