



GENERAL TOLERANCE					
	G	H	J	K	L
~ 8	±0.1	±0.1	±0.2	±0.3	±0.4
8up ~ 25	±0.15	±0.15	±0.3	±0.3	±0.6
25up ~ 80	±0.2	±0.25	±0.4	±0.5	±0.8
80up ~ 250	±0.3	±0.4	±0.6	±0.8	±1.2
250over	±0.6	±0.8	±1.0	±1.5	±2.0

DO NOT SCALE DRAWING

47 ±0.3

4-R2

RoadKing
MODEL: RKCBBT
FCC ID: AMWUT427Z
IC: 513C-UT427Z
MADE IN VIETNAM

SERIAL NO.: XXXXXXXX

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION.

RoadKing
MODEL: RKCBBT
FCC ID: AMWUT427Z
IC: 513C-UT427Z
MADE IN VIETNAM

SERIAL NO.: XXXXXXXX

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION.

Actual Size

INDICATION OF SERIAL NO.

XXXXXXXXXX

SEE NOTE.6
6 FIGURES
SERIAL No. 000001~999999
STARTS FROM 000001 EVERY YEAR

XXXXXXXXXX

SEE NOTE.6
COUNTRY CODE
VIETNAM---8 , CHINA---4

XXXXXXXXXX

SEE NOTE.6
THE END OF A.D.(YEAR)
EX: 2011---1
2012---2
2020---0

NOTE

1. MATERIAL : POLYESTER TACK FORM(MATT) SILVER t=0.05
UL RECOGNIZED COMPONENT UNDER THE CATEGORY OF MARKING AND LABELING SYSTEMS (PGDQ2)
2. PRINT COLOR : BLACK (LETTERS)
SILVER (BACKGROUND)
3. ARTWORK : D37294
4. LAMINATE : POLYPROPYLENE(MATT) or PET(MATT) CLEAR t=0.025mm
5. ADHESIVE STRENGTH : MORE THAN 1000g/25mm² (180° PEEL OFF TEST)
6. SERIAL NO. : MUST BE FOLLOWED PURCHASE OFFICIAL INFORMATION (SERIAL NO. IS DECIDED BY PC DEPARTMENT.)

CAUTION :
MATERIAL MUST BE MET DIRECTIVE 94/62/EC AS FOLLOWS :
THE FOLLOWING SUBSTANCE TOTAL CONTENTS SHOULD BE LESS THAN 100ppm
(1) Cadmium and Cadmium Compounds
(2) Hexavalent Chromium Compounds
(3) Lead and Lead Compounds
(4) Mercury and Mercury Compounds
MATERIAL MUST BE MET DIRECTIVE 2002/95/EC(RoHS) AS FOLLOWS
THE FOLLOWING SUBSTANCE EACH CONTENT SHOULD BE LESS THAN 1000ppm
(5) Polybrominated Biphenyls(PBBs)
(6) Polybrominated Diphenyl ethers(PBDEs)
At the time of parts approval request you have to prove and gurantee
that the material comply with the above requirement by attaching SAMPLE and
'GREEN PROCUREMENT BASIC INFORMATION SURVEY (CHEMICAL SUBSTANCES) TABLE'
When material is changed after parts approval, it is necessary to do some thing again.

UL 指定材料
納品時添付材料証明書
UL ONLY
SUPPLY COPY OF MATERIAL
IDENTIFICATION SHEET
要厳守注記

△	△	△	CAUTION: Approval sample must be submitted for Uniden(ENG) approval. Using any materials in this drawing before Uniden(ENG) approval is prohibited.					
REV.MARK	CONTENS	REVISED	CHECKED	APPV'D	APPROVED BY	CHECKED BY	DESIGNED BY	DRAWN BY
DRAWING ISSUE STAMP <div style="border: 1px solid black; padding: 5px; text-align: center;"> </div>		ENG'G. DIM. REQMT. FOR UNIDEN IQC INSP		YES NO	EBASHI Nov.25'19	KURIH Nov.25'19		KURIH Nov.25'19
ANGLE 		UNITS mm	TOLERANCE 	SCALE 2:1	MODEL UT427Z		PARTS NAME LABEL ID	
MOLD CAVITIES pcs		TOOL CODE		BASIC MODEL		BASIC PARTS CODE		PARTS CODE PLD111660ZZ
ISSUE DATE : 2019.11.26								