

<u>TEST REPORT</u>

	Ref. Report No.
	06-1341-033-1
Nome and address of the applicant	
<u>Test item(s)</u> ;	
UHF –Band RFID	Tag
5F. Ace Techno Tower B/D. 684-1 Deungchon-Dong. (Digital Transmiss)	ion Transmitter)
Gangseo-Gu, Seoul 157-030, Korea	
Model/type ref. ;	
IDA245	
Standard / Test regulation	
FCC Part 15, Subpart C Manufacturer :	
<u>rest result</u>	
Page	
Additional inform	nation ;
-Required Authoriza	tion : Certification
Incoming date · Sep 21 2006 -FCC ID. : OYUIDA	245
incoming date . Sep 21, 2000	
Test date : Sep 21, 2006 ~ Sep 27, 2006 Issue date : Sep 27,	2006

This test report only responds to the tested sample and shall not be reproduced except in full without written approval of the Korea Testing Laboratory.

Tested and reported by

Sung-Kyu Cho, Engineer

Reviewed by

5. J. Kim 22

Seok-Jin Kim, Telecommunication Team Manager

KOREA TESTING LABORATORY

222-13, Guro-Dong Guro-Gu Seoul Korea 152-053

http://www.ktl.re.kr

Page 2 of 20

TABLE OF CONTENTS

I. (GENERAL INFORMATION	4
1.	Applicant's Name and Mailing Address	
2.	Manufacturer's Name and Mailing Address	
3.	Equipment Descriptions	
4.	Rules and Regulations	
5.	Measuring Procedure	
6.	Place of Measurement	
7.	Date of Measurement	
Π.	GENERAL REQUIREMENTS OF THE EUT	5
1.	Labeling Requirement (Section 15.19)	
2.	Information to User (Sections 15.21)	
3.	Special Accessories (Section 15.27)	
Ш.	RADIATED EMISSION MEASUREMENT (Section 15.209)	_6
1.	Test Procedure	
2.	Photograph for the test configuration	
3.	Sample Calculation	
4.	Measurement Data	
V.	6 dB BANDWIDTH (Section 15.247(a))	<u>14</u>
1.	Test standard	
2.	Measurement Data	
3.	Measurement Plot	
VI.	OUTPUT POWER MEASUREMENT (Section 15.247(b))	15
1.	Test standard	
2.	Measurement Data	
3.	Measurement Plot	

VII.	100 kHz BANDWIDTH OF BAND EDGES (Section 15.247(c))			
1.	Test standard			
2.	Measurement Data			
3.	Measurement Plot			
VIII.	POWER SPECTRAL DENSITY (Section 15.247(e))	17		
1.	Test standard			
2.	Measurement Data			
3.	Measurement Plot			
IX.	TEST EQUIPMENTS USED FOR MEASUREMENTS	20		

Page 4 of 20

I. GENERAL INFORMATION

1. Applicant's Name and	:	IDTECK CO., LTD.
Mailing Address		5F, Ace Techno Tower B/D. 684-1 Deungchon-Dong,
		Gangseo-Gu, Seoul 157-030, Korea

2. Manufacturer's Name and Mailing Address : IDTECK CO., LTD. 5F, Ace Techno Tower B/D. 684-1 Deungchon-Dong, Gangseo-Gu, Seoul 157-030, Korea

3. Equipment Descriptions

3.1 Operating Frequency :	2,402 MHz
3.2 Maximum Antenna gain :	6 dBi
3.2 Power Supply :	DC 3 V (Battery)

- 4. Rules and Regulations : FCC Part 15, Subpart C
 5. Measuring Procedure : ANSI C63.4-2003
 6. Place of Measurement : Absorber-lined room(3-Meter) of KTL
- 7. Date of Measurement : Sep 21, 2006 ~ Sep 27, 2006

II. GENERAL REQUIREMENTS OF THE EUT

1. Labelling Requirement (Section 15.19)

This device complies with Part 15 of the FCC Rules. Operation is subject to following two condition : (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

1.1 Location of Label : User's Guide Manual 1.2 How Applied : Printed

2. Information to User (Section 15.21)

The following or similar statements were provided in the manual for user instruction. Please refer page 9 of the attached manual for details.

CAUTION : Any changes or modifications in construction of this device which are not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

3. Sp	ecial.	Accessories	(Section	15.27)
-------	--------	-------------	----------	--------

3.1 Were the special Accessories provided?	[] yes, [х] no
--	---	----------	---	------

- 3.2 If yes, details for the special accessories are as follows :
- 3.3 If yes, were the appropriate instructions provided on the first page of the text concerned with the device?
 - ſ] yes, [] no
- 3.4 Are these accessories provided of the type which can be readily obtained from multiple retail outlets ?] no] yes, [Т

And therefore does the manual specify what additional components or accessories are required to used in order to comply with the Rules? ſ

] yes, [] no

III. RADIATED EMISSION MEASUREMENT (Section 15.209)

1. Test Procedure

1.1 Preliminary Testing for Reference

The EUT was designed to transmit on 2,402 MHz. Therefore measurements were performed with the equipment operating on 2,402 MHz.

Preliminary testing was performed in a KTL absorber-lined room to determine the emission characteristics of the EUT. The EUT was placed on the wooden table which has dimensions of 0.8 meters in height, 1 meter in length and 1.5 meters in width. Receiving antenna (Biconi-Log antenna : 30 to 1000 MHz or Horn Antenna : 1 to 25 GHz) was placed at the distance of 1 meter from the EUT.

An attempt was made to maximize the emission level with the various configurations of the EUT. Emission levels from the EUT with various configurations were examined on a spectrum analyzer connected with a RF amplifier and graphed by a plotter.

1.2 Final Radiated Emission Test at an Absorber-Lined Room

The final measurement of radiated field strength was carried out in a KTL absorber-lined Room that was listed up at FCC according to the "Radiated Emissions Testing" procedure specified by ANSI C63.4.

Based on the test results in preliminary test, measurement was made in same test set up and configurations where produced maximum emission level. Receiving antenna was installed at 3-meter distance from the EUT, and was connected to an EMI receiver or spectrum analyzer with a RF amplifier.

Turntable was rotated through 360 degrees and receiving antenna height was varied from 1 to 4 meters above the ground plane with horizontal and vertical polarization to read maximum emission level.

If necessary, the radiated emission measurements could be performed at a closer distance than specified distance to ensure higher accuracy and their results were extrapolated to the specified distance using an inverse linear distance extrapolation factor(20dB/decade) as per Section 15.31(f).

The maximum emission level from the EUT occurred in such configuration as shown in the following photograph.

2. Photograph of the test configuration



3. Sample Calculation

The emission level measured in decibels above one microvolt (dB μN) was calculated as shown in following sample calculation.

For example :

Measured Value at 2,401.8 MHz	57.8 dB µN
+ Antenna Factor & Cable Loss	31.4 dB/m
– Preamplifier	-29.6 dB
 Distance Correction Factor * 	0.0 dB
= Radiated Emission	59.6 dB µN/m

* Extrapolated from the measured distance to the specified distance by an inverse linear distance extrapolation.

Page 8 of 20

4. Measurement Data

- Intentional Spurious Emission
- Resolution Bandwidth : <u>x</u> CISPR Quasi-Peak (6dB Bandwidth : 120kHz for below 1GHz)
 <u>x</u> Peak (3dB Bandwidth : 1MHz for above 1GHz)
- Measurement Distance : 3 Meter

c Fre	hannel equency (MHz)	* D.M.	* A.P.	Measured Value (dBµV/m)	* A.F. + C.L (dB)	* A.G. (dB)	* D.C.F. (dB)	Emission Level (dBµN/m)	Limit (dBµV/m)	** Margin (dB)
	2,401.8	Р	V	57.8	31.4	-29.6		59.6	114.0	-54.4
	2,401.8	Α	V	25.6	31.4	-29.6		27.4	94.0	-66.6
	*** 4,804.0	Р	V	49.7	37.6	-26.7	-9.5	51.1	74.0	-22.9
	*** 4,804.0	Α	V	22.6	37.6	-26.7	-9.5	24.0	54.0	-30.0
	**** 7,206.0	Р	H/V	<35.0	42.1	-26.0	-9.5	<41.6	74.0	>-32.4
2,402	**** 7,2 <u>0</u> 6.0	Α	H/V	<20.0	42.1	-26.0	-9.5	<26.6	54.0	>-27.4
MHZ										
Note *	Note * D.M. : Detect Mode (P : Peak, Q : Quasi-Peak, A : Average) A.P. : Antenna Polarization (H : Horizontal, V : Vertical) A.F. : Antenna Factor C.L. : Cable Loss A.G. : Amplifier Gain D.C.F. : Distance Correction Factor									
**	Margin (dB) = I	Emissio	n Level (dB)	- Limit	(dB)				
***	In the cas sensitivit	se of th y of m	iese frec easuren	quencies, the nent system.	EUT wa	is measi	ured at 1.	0m distance f	or sufficient	
****	 < means RF prean 	less tha	an, > m r was 35	eans bigger t 5.0 dBuV and	than. The 1 25.0 dF	e observ BuV in p	ed specti beak and	rum analyzer average mode	noise floor le respectively	evel with

Note;

(1) Fundamental emissions from the intentional radiators were not located within any of frequency bands described in section 15.205(a) listed below ;

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.25
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.1775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	
13.36-13.41			

The field strength of emissions appearing within above frequency bands did not exceed the limits shown in section 15.209. At frequency equal to or less than 1000 MHz, compliance with the limits section 15.209 was demonstrated using measurement employing a CISPR quasi-peak detector. Above 1000 MHz, demonstrated based on the average value of the measured emissions.

- (2) If the intentional radiator was operated under the radiated emission limits of the general requirements of section 15.209, it's fundamental emissions were not located in the frequency bands 54-72MHz, 76-88 MHz, 174-216 MHz, 470-860 MHz.
- (3) The level of any unwanted emissions from an intentional radiator did not exceed the level of the fundamental emission.
- (4) Radiated and spurious emissions were checked from 30 MHz to 24 GHz. And all other emissions not reported on data were more than 20 dB below the permitted level.

🔆 Ag	j ilent 09	:49:16	Jul 25	i, 2006							Peak Search
Ref 88 #Peak	.39 dBj	٧u	#Attei	n 0 dB				Mkr1	2.377 57.74	87 GHz dB µ V	Next Peak
Log 10 dB/ Offet											Next Pk Right
31.4 dB DI	-Mark	/~~~ er	the source of	-vu-noten	duadhing	himahad	aphric hallby	nnan	1 mmlunh		Next Pk Left
74.0 dB µ V LgAv	2.37 57.	7870 74 d	0000 BµV	GHz							Min Search
M1 S2 S3 FC AA											Pk-Pk Search
£ (f): FTun Swp											Mkr → CF
Start 2 #Res B	L 2.310 0 W 1 MH	0 GHz z		 #V	 BW 1 M	 Hz	Si	Stop weep 1	2.390 ms (60	00 GHz 1 pts)	More 1 of 2
File 0	File Operation Status, A:\VP.GIF file saved										

< Restricted Band edge (PEAK), Horizontal >

🔆 Ag	j ilent 09	:50:25	Jul 25	, 2006							Peak Search
Ref 68 #Peak	.39 dBj	٧u	#Attei	n 0 dB				Mkr1	2.390 45.52	00 GHz dB µ V	Next Peak
Log 10 dB/ Offst										1	Next Pk Right
31.4 dB DI 54.0	₋Mark	er									Next Pk Left
dBµV LgAv	2.39 45.	0000 52 d	0000 BµV	GHz							Min Search
M1 S2 S3 FC AA											Pk-Pk Search
£(f): F⊤un Swp											Mkr → CF
Start 2 #Res B	L 2.310 0 W 1 MH	0 GHz z		 #\	BW 10	 Hz	Swee	Stop p 6.23	 2.390 (8 s (60	00^GHz 1 pts)	More 1 of 2
File 0	peratio	in Stat	tus, A:	\HP.GI	F file :	saved					

< Restricted Band edge (AVG), Horizontal >

Page 11 of 20

🔆 Ag	j ilent 09	:47:50	Jul 25	,2006							File
Ref 88 #Peak	.39 dBj	٧u	#Atter	n Ø dB				Mkr1	2.352 58.63	40 GHz dB µ V	Catalog•
Log 10 dB/ Offet											Save
31.4 dB DI	Mark	er	an all and a second	vhatantine	en falter og so	1 Vited (Institute	aphienter and	dattire picasi	pulsiphon	a	Load⊦
74.0 dB µ V LgAv	2.35 58.	2400 63 d	0000 BµV	GHz							Delete•
M1 S2 S3 FC AA											Сору
£ (f): FTun Swp											Rename⊦
Start 2 #Res B	L 2.310 0 W 1 MH	0 GHz z		 #V	BW 1 M	Hz	S1	Stop weep 1	2.390 ms (60	00 GHz 1 pts)	More 1 of 2
File 0	peratio	in Stat	tus, A:'	\VA.GI	F file	saved					

< Restricted Band edge (PEAK), Vertical >

🔆 Ag	j ilent 09	:46:45	Jul 25	, 2006							Peak Search
Ref 88 #Peak	.39 dB	٧u	#Atter	n 0 dB				Mkr1	2.390 45.55	00 GHz dB µ V	Next Peak
Log 10 dB/ Offet											Next Pk Right
31.4 dB DI	Mark	er								1	Next Pk Left
54.0 dB µ V LgAv	2.39 45.	0000 55 d	0000 BµV	GHz							Min Search
M1 S2 S3 FC AA											Pk-Pk Search
£ (f): FTun Swp											Mkr → CF
Start 2 #Res B	L 2.310 0 W 1 MH	0 GHz z		 #V	BW 10	 Hz	 Swee	Stop 9p 6.23	 2.390 (8 s (60	00 GHz 1 pts)	More 1 of 2
Data c	orrupt	or st	ale, NF	RAM co	py of	FL_5_4	UNPR_1	0DB_P	AOFF_D	00	

< Restricted Band edge (AVG), Vertical >

Mkr1 2.492 77 GHz Next Peak Log 10 1	🔆 Ag	jilent 09	:54:59	Jul 25	,2006							Peak Search
Log 10 <	Ref 88 #Peak	.39 dBj	٧u	#Atter	n 0 dB				Mkr1	2.492 59.54	77 GHz dB µ V	Next Peak
31.4 1 1 Next Pk Le DI 74.0 Marker Min Search Min Search DI 74.0 59.54 dBµV Min Search Min Search LgAv 59.54 dBµV Pk-Pk Search Pk-Pk Search M1 S2 S3 FC Min Search Mkr → C AA Min Search Mkr → C Start 2 483 50 GHz Start 2 500 00 GHz Mor	Log 10 dB/ Offet											Next Pk Right
74.0 1000000000000000000000000000000000000	31.4 dB DI	Mark	er	and and the second	an tayahir a shiraya	mound	1 Annellan	q distant	-man-botypes	howa	a desperient pradaction	Next Pk Left
M1 S2 S3 FC AA Pk-Pk Search AA AA AA AA £(f): FTun AA AA Swp AA AA AA Start 2 483 50 GHz Start 2 500 00 GHz Mor	74.0 dB µ V LgAv	2.49 59.	2770 54 d	9000 BµV	GHz							Min Search
€(f): FTun Swp Start 2,483,50,GHz Start 2,483,50,GHz Mor	M1 S2 S3 FC AA											Pk-Pk Search
Start 2,483,50, GHz Mor	£ (f): FTun Swp											Mkr → CF
start 2.465 36 612 *VBW 1 MHz Stop 2.366 66 612 1 of *Res BW 1 MHz Sweep 1 ms (601 pts) 1 of	Start 2 #Res B	L 2.483 5 3W 1 MH	0 GHz z		 #V	 BW 1 M	 Hz	SI	Stop weep 1	2.500 (ms (60	00 GHz 1 pts)	More 1 of 2

< Restricted Band edge (PEAK), Horizontal >

🔆 Ag	j ilent 09	:53:57	Jul 25	, 2006							Peak Search
Ref 68 #Peak	.39 dB	٧u	#Attei	n 0 dB				Mkr1	2.489 46.39	99 GHz dB µ V	Next Peak
Log 10 dB/ Offst				1	 						Next Pk Right
31.4 dB DI 54.0	-Mark	er—									Next Pk Left
dBµV LgAv	2.48 46.	9990 39 d	000 Βμν Ι	GHz							Min Search
M1 S2 S3 FC AA											Pk-Pk Search
€(f): FTun Swp											Mkr → CF
Start 2 #Res B	L 2.483 5 W 1 MH	0 ĜHz z		#\	 'BW 10	Hz	Swee	Stop p 1.28	 2.500 (7 s (60	00 GHz 1 pts)	More 1 of 2
File O	peratio	n Stat	tus, A:	\HV.GI	r tile	saved					

< Restricted Band edge (AVG), Horizontal >

🔆 Ag	ilent 09	:56:02	Jul 25	5,2006							Peak Search
Ref 88 #Peak	.39 dB	٧u	#Attei	n 0 dB				Mkr1	2.496 58.74	34 GHz dBµV	Next Peak
Log 10 dB/											Next Pk Right
dB DI	-Mark	۰ er—	Versientiller	alang was not	- Anna Martine	Uppermaned		1 Anthropology	liden.governinai	Mar Martine	Next Pk Left
74.0 dB µ V LgAv	2.49 58.	6340 74 d	9000 BµV	GHz							Min Search
M1 S2 S3 FC AA											Pk-Pk Search
€(f): FTun Swp											Mkr → CF
Start 2 #Res B	.483 5 W 1 MH	0 GHz z		 #V	 BW 1 M	 Hz	SI	Stop Weep 1	2.500 (ms (60	00 GHz 1 pts)	More 1 of 2
File O	peratio	n Stat	tus, A:	\HP2.6	IF file	saved	l				

< Restricted Band edge (PEAK), Vertical >

🔆 Ag	j ilent 09	:56:45	Jul 25	,2006							Peak Search
Ref 78 #Peak	.39 dBj	٧u	#Atter	n 0 dB				Mkr1	2.490 46.32	32 GHz dB µ V	Next Peak
Log 10 dB/ Offet											Next Pk Right
31.4 dB DI	Mark	er			1 \$						Next Pk Left
54.0 dBµV LgAv	2.49 46.	0320 32 d	0000 BµV	GHz							Min Search
M1 S2 S3 FC AA											Pk-Pk Search
£ (f): FTun Swp											Mkr → CF
Start 2 #Res B	L 2.483 5 W 1 MH	0 ĜHz z		 #\	 'BW 10	 Hz	Swee	Stop p 1.28	 2.500 (7 s (60	00 GHz 1 pts)	More 1 of 2
File O	peratio	n Stat	tus, A:	\VP2.6	IF file	save	3				

< Restricted Band edge (AVG), Vertical >

VI. 6 dB BANDWIDTH (Section 15.247(a))

1. Test Standards

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB Bandwidth shall be at least 500 kHz

2. Test Procedure

The EUT was set to transmit at its maximum data rate. The EUT was connected to a spectrum analyzer through a 50 ohm RF cable. Analyzer RES BW was set to 100 kHz.

3.6 dB Bandwidth

Frequency	Measured Value	Limit	Result
(MHz)	(kHz)	(kHz)	
2,402	728.0	At least 500	Pass

4. Measurement Plot



(6 dB Bandwidth)

V. OUTPUT POWER MEASUREMENT (Section 15.247(b))

1. Test Standards

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands using antennas with gains of 6 dBi or less, maximum allowed transmitter output power is 1 Watt. For antennas with gains greater than 6 dBi, the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

2. Test Procedure

The EUT was connected to a spectrum analyzer through a 50 ohm RF cable. External attenuation and cable loss were compensated for using the offset function of the analyzer. Analyzer RES BW was set to 1 MHz..

3. Measurement Data

Frequency (MHz)	Measured Value (uW)	Limit (Watt)	Result
2,402	17.49	1	Pass

4. Measurement Plot



(Maximum Conducted Output Power)

Korea Testing Laboratory Telecommunication Team 222-13, Guro3-dong, Guro-gu, Seoul Korea 152-848

VI. 100 kHz BANDWIDTH OF BAND EDGES (Section 15.247(c))

1. Test Standards

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum of digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in section 15.209(a) is not required.

2. Test Procedure

The EUT was connected to a spectrum analyzer through a 50 ohm RF cable. External attenuation and cable loss were compensated for using the offset function of the analyzer.

3. Measurement data

Frequency	Measured Value	Limit	Result
(MHz)	(dBc)	(dBc)	
2,402	31.43	20	Pass

4. Measurement Plot



(Out of band Conducted Emissions, 30 MHz ~ 1 GHz)

Korea Testing Laboratory Telecommunication Team 222-13, Guro3-dong, Guro-gu, Seoul Korea 152-848



(Out of band Conducted Emissions, 1 GHz ~ 8 GHz)



(Out of band Conducted Emissions, 8 GHz ~ 15 GHz)



(Out of band Conducted Emissions, 15 GHz ~ 25 GHz)

VII. POWER SPECTRAL DENSITY (Section 15.247(e))

1. Test Standards

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any tie interval of continuous transmission.

2. Test Procedure

The EUT was connected to a spectrum analyzer through a 50 ohm RF cable. External attenuation and cable loss were compensated for using the offset function of the analyzer. The spectrum analyzer RES BW was set to 3 kHz. The Start and Stop frequencies were set to band edges of the maximum output passband. Total sweep time was calculated as follows:

SWEEP TIME (SEC) = (Fstop, kHz – Fstart, kHz) / 3 kHz

3. Measurement data

Frequency	Measured Value	Limit	Result
(MHz)	(dBm)	(dBm)	
2,402	-35.26	8	Pass

4. Measurement Plot



(Power Spectral Density)

Page 20 of 20

VII. TEST EQUIPMENTS USED FOR MEASUREMENTS

Equipment	Model No.	Manufacturer	Serial No.	Effective Cal. Duration
[x] EMI Receiver (20 MHz-1 GHz)	ESVS30	R & S	830516/002	04/04/06-04/04/07
[x] EMI Receiver (20 Hz-7 GHz)	ESI	R & S	835571/004	10/14/05-10/14/06
[x] Spectrum Analyzer (9 kHz-26.5 GHz)	8563A	Н. Р.	3222A02069	05/15/06-05/15/07
[x] Spectrum Analyzer (3 Hz-50 GHz)	E4448A	Agilent	MY43360322	03/16/06-03/16/07
[x] Pre-Amplifier (0.1-3000 MHz, 30 dB)	8347A	Н. Р.	2834A00543	05/19/06-05/19/07
[x] Pre-Amplifier (1-26.5 GHz, 35 dB)	8449B	Н. Р.	3008A00302	06/14/06-06/14/07
[] Signal Generator (250 kHz-20 GHz)	E8257D	Agilent	MY44320379	12/26/05-12/26/06
[] LISN(50 Ω , 50 μH) (10 kHz-100 MHz)	ESH3-Z5	R & S	826789/009	05/16/06-05/16/07
[] Plotter	7470A	Н. Р.	3104A21292	-
[] Tuned Dipole Ant. (30 MHz-300 MHz)	VHA 9103	Schwarzbeck	-	*
[] Tuned Dipole Ant. (300 MHz-1 GHz)	UHA 9105	Schwarzbeck	-	*
[x] BiConi-Log Ant. (30 MHz -1 GHz)	VULB9168	Schwarzbeck	9168-167	*
[x] Horn Ant. (1 GHz-18 GHz)	3115	EMCO	-	*
[] Horn Ant. (18 GHz-40 GHz)	3116	EMCO	-	*
[] Active Loop Ant. (9 kHz-30 MHz)	6502	EMCO	2532	*
[] DC Power Supply	6260B	H.P.	1145A04822	-
[] Shielded Room (5.0 m x 4.5 m)	-	SIN-MYUNG	-	-

* Each set of antennas has been calibrated to ensure correlation with ANSI C63.5 standard. The calibration of antennas is traceable to Korea Standard Research Institute(KSRI)