



RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Test Result of RF Exposure Evaluation

BT Mode							
Mode	Frequency (MHz)	Output power to antenna (dBm)	Output power to antenna (mW)	Antenna Gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
GFSK	2441	8.433	6.97	1.73	0.002065	1.0	PASS
$\pi/4$ -DQPSK	2441	6.093	4.07	1.73	0.001205	1.0	PASS
8-DPSK	2441	6.237	4.20	1.73	0.001244	1.0	PASS

2.4G WI-FI Mode							
Mode	Frequency (MHz)	Output power to antenna (dBm)	Output power to antenna (mW)	Antenna Gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b	2412	14.911	30.98	1.73	0.009180	1.0	PASS
802.11g	2412	13.755	23.74	1.73	0.007034	1.0	PASS
802.11n20	2462	13.122	20.52	1.73	0.006080	1.0	PASS

5.2G WI-FI Mode							
Mode	Frequency (MHz)	Output power to antenna (dBm)	Output power to antenna (mW)	Antenna Gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11a	5180	10.659	11.64	3.64	0.005354	1.0	PASS
802.11n20	5180	10.405	10.98	3.64	0.005049	1.0	PASS
802.11ac20	5180	10.476	11.16	3.64	0.005133	1.0	PASS

Note: The device can not transmit with 2.4GWI-FI and 5.2GWI-FI and BT simultaneously.