



**FCC CFR47 PART 15 SUBPART C
CERTIFICATION
TEST REPORT**

FOR

2.4 GHz 802.11 b/g MINI PCI CARD

MODEL NUMBER: SR2

FCC ID: SWX-SR2

REPORT NUMBER: 05U3280-1

ISSUE DATE: MAY 9, 2005

Prepared for
**UBIQUITI NETWORKS
1111 WEYBURN LANE, SUITE 41
SAN JOSE, CA 95129
U.S.A.**

Prepared by
**COMPLIANCE ENGINEERING SERVICES, INC.
d.b.a.
COMPLIANCE CERTIFICATION SERVICES
561F MONTEREY ROAD,
MORGAN HILL, CA 95037, USA
TEL: (408) 463-0885
FAX: (408) 463-0888**

NVLAP[®]
LAB CODE:200065-0

Revision History

<u>Rev.</u>	<u>Revisions</u>	<u>Revised By</u>
-------------	------------------	-------------------

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
3.1. ACCREDITED TESTS	5
3.2. UNACCREDITED TESTS.....	5
4. CALIBRATION AND UNCERTAINTY.....	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. MEASUREMENT UNCERTAINTY.....	6
5. EQUIPMENT UNDER TEST.....	6
5.1. DESCRIPTION OF EUT	6
5.2. MAXIMUM OUTPUT POWER	6
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	7
5.4. SOFTWARE AND FIRMWARE	7
5.5. WORST-CASE CONFIGURATION AND MODE.....	7
5.6. DESCRIPTION OF TEST SETUP	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. LIMITS AND RESULTS	11
7.1. CHANNEL TESTS FOR THE 2400 TO 2483.5 MHz BAND	11
7.1.1. 6 dB BANDWIDTH	11
7.1.2. 99% BANDWIDTH.....	18
7.1.3. PEAK OUTPUT POWER	25
7.1.4. MAXIMUM PERMISSIBLE EXPOSURE.....	33
7.1.5. AVERAGE POWER.....	36
7.1.6. PEAK POWER SPECTRAL DENSITY	37
7.1.7. CONDUCTED SPURIOUS EMISSIONS.....	44
7.2. RADIATED EMISSIONS.....	57
7.2.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS	57
7.2.2. TRANSMITTER ABOVE 1 GHz FOR 2400 TO 2483.5 MHz BAND	60
7.2.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz.....	78
7.3. POWERLINE CONDUCTED EMISSIONS	82
8. SETUP PHOTOS.....	86

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: UBIQUITI NETWORKS
1111 WEYBURN LANE, #41
SAN JOSE, CA 95129
U.S.A.

EUT DESCRIPTION: 802.11b/g MINI PCI CARD

MODEL: SR2

SERIAL NUMBER: NLT9 Proto 3

DATE TESTED: MARCH 7 – APRIL 19, 2005

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	NO NON-COMPLIANCE NOTED

Compliance Certification Services, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document. No part of this report may be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any government agency.

Approved & Released For CCS By:



YAN ZHENG
EMC SUPERVISOR
COMPLIANCE CERTIFICATION SERVICES

Tested By:



DAVID GARCIA
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2003, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

3.1. ACCREDITED TESTS

Except as specified below in clause 3.2, the test sites and measurement facilities used to collect data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

3.2. UNACCREDITED TESTS

Channel test data included in this test report was provided by Ubiquity Networks and is not covered by the NVLAP accreditation.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz	+/- 3.3 dB
Radiated Emission, 200 to 1000 MHz	+4.5 / -2.9 dB
Radiated Emission, 1000 to 2000 MHz	+4.5 / -2.9 dB
Power Line Conducted Emission	+/- 2.9 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is an 802.11b/g Mini PCI transceiver card.

The radio module is manufactured by Ubiquiti Networks.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

2400 to 2483.5 MHz Authorized Band

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2412 - 2462	802.11b	27.73	592.93
2412 - 2462	802.11g	28.49	706.32

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a single dipole antenna with a maximum gain of 3.0 dBi.

5.4. SOFTWARE AND FIRMWARE

The test utility software used during testing was ART, rev. 5.2.

5.5. WORST-CASE CONFIGURATION AND MODE

The worst-case channel is determined as the channel with the highest output power. The highest measured output power was at 2437 MHz.

The worst-case data rate for this channel is determined to be 11 Mb/s, based on previous experience with 802.11b/g WLAN product design architectures.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Laptop	HP	ZE4900	CNF440Y77	DoC
AC Adapter	HP	PK0080	n/a	n/a


I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	AC	1	AC	Unshielded	1.8 m	N
2	DC	1	DC	Unshielded	1.8 m	N

TEST SETUP

The EUT is installed in a host laptop computer via a cardbus-to-miniPCI adapter / extension board during the tests. Test software exercised the radio card.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	Cal Due
Spectrum Analyzer 3 Hz ~ 44 GHz	Agilent	E4446A	US42510266	8/25/2005
EMI Test Receiver	R & S	ESIB40	100192	5/9/2006
EMI Test Receiver	R & S	ESHS 20	827129/006	10/22/2005
Antenna, Horn 1 ~ 18 GHz	EMCO	3115	6717	6/12/2005
Antenna, Horn, 18 ~ 26 GHz	ARA	MWH-1826/B	1013	9/12/2005
Antenna, Bilog 30MHz ~ 2Ghz	Sunol Sciences	JB1	A121003	9/22/2005
Preamplifier, 1 ~ 26 GHz	Miteq	NSP2600-SP	924341	12/23/2005
LISN, 10 kHz ~ 30 MHz	Solar	8012-50-R-24-BNC	8379443	10/21/2005
Site A Line Stabilizer/Conditioner	Tripplite	LC-1800a	A005181	CNR
LISN, 10 kHz ~ 30 MHz	FCC	LISN-50/250-25-2	2023	8/30/2005
4.0 High Pass Filter	Micro Tronics	HPM13351	3	N/A

7. LIMITS AND RESULTS

7.1. CHANNEL TESTS FOR THE 2400 TO 2483.5 MHz BAND

The data in this section was provided by Ubiquity Networks and is not covered by the NVLAP accreditation. Levels used are based on power level settings that were used to pass radiated emissions tests.

7.1.1. 6 dB BANDWIDTH

LIMIT

§15.247 (a) (2) For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

No non-compliance noted:


802.11b Mode


Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Limit (kHz)	Margin (kHz)
Low	2412	12150	500	11650
Middle	2437	12050	500	11550
High	2462	11100	500	10600


802.11g Mode

Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Limit (kHz)	Margin (kHz)
Low	2412	16250	500	15750
Middle	2437	16100	500	15600
High	2462	15750	500	15250


6 DB BANDWIDTH (802.11b MODE)









6 DB BANDWIDTH (802.11g MODE)







7.1.2. 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

No non-compliance noted:


802.11b Mode


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	15.7141
Middle	2437	16.1061
High	2462	15.2613


802.11g Mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	16.5106
Middle	2437	16.6028
High	2462	16.3312


99% BANDWIDTH (802.11b MODE)









99% BANDWIDTH (802.11g MODE)







7.1.3. PEAK OUTPUT POWER

PEAK POWER LIMIT

§15.247 (b) The maximum peak output power of the intentional radiator shall not exceed the following:

§15.247 (b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz , and 5725-5850 MHz bands: 1 watt.

§15.247 (b) (4) Except as shown in paragraphs (b)(4) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§15.247 (b) (4) (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer and the analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth.

RESULTS

The maximum antenna gain is 3 dBi for other than fixed, point-to-point operations, therefore the limit is 30 dBm.

No non-compliance noted:

Test Setup: The antenna output is connected into the spectrum analyzer. RBW is set to 1 MHz; Video BW is set to 3 MHz. The channel power function is used on the spectrum analyzer with a 20 MHz channel bandwidth (equal to the 802.11 carrier transmission bandwidth). Cable/connector loss of 1.5dB at 2.4GHz was added to all raw measurements.


802.11b Mode


Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	2412	27.73	30	-2.27
Middle	2437	27.65	30	-2.35
High	2462	27.59	30	-2.41


802.11g Mode

Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	2412	28.05	30	-1.95
Middle	2437	28.49	30	-1.51
High	2462	27.96	30	-2.04


OUTPUT POWER (802.11b MODE)









OUTPUT POWER (802.11g MODE)







7.1.4. MAXIMUM PERMISSIBLE EXPOSURE

LIMITS

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

CALCULATIONS

Given

$$E = \sqrt{(30 * P * G) / d}$$

and

$$S = E^2 / 3770$$

where

E = Field Strength in Volts/meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts/square centimeter

Combining equations and rearranging the terms to express the distance as a function of the remaining variables yields:

$$d = \sqrt{((30 * P * G) / (3770 * S))}$$

Changing to units of Power to mW and Distance to cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = 100 * d \text{ (m)}$$

yields

$$d = 100 * \sqrt{((30 * (P / 1000) * G) / (3770 * S))}$$

$$d = 0.282 * \sqrt{(P * G / S)}$$

where

d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW/cm²

Substituting the logarithmic form of power and gain using:

$$P \text{ (mW)} = 10^{(P \text{ (dBm)} / 10)} \text{ and}$$

$$G \text{ (numeric)} = 10^{(G \text{ (dBi)} / 10)}$$

yields

$$d = 0.282 * 10^{((P + G) / 20)} / \sqrt{S} \quad \text{Equation (1)}$$

where

d = MPE distance in cm

P = Power in dBm

G = Antenna Gain in dBi

S = Power Density Limit in mW/cm²

Equation (1) and the measured peak power is used to calculate the MPE distance.

LIMITS

From §1.1310 Table 1 (B), $S = 1.0 \text{ mW/cm}^2$

RESULTS

No non-compliance noted:

Mode	Power Density Limit (mW/cm²)	Output Power (dBm)	Antenna Gain (dBi)	MPE Distance (cm)
802.11b	1.0	27.73	3.00	9.70
802.11g	1.0	28.49	3.00	10.59

NOTE: For mobile or fixed location transmitters, the minimum separation distance is 20 cm, even if calculations indicate that the MPE distance would be less.

7.1.5. AVERAGE POWER

AVERAGE POWER LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

No non-compliance noted:

Test Setup: The antenna output is connected into the spectrum analyzer. RBW is set to 1 MHz; Video BW is set to 3 MHz. The channel power function is used on the spectrum analyzer with a 20 MHz channel bandwidth (equal to the 802.11 carrier transmission bandwidth). Cable/connector loss of 1.5dB at 2.4GHz was added to all raw measurements.

802.11b Mode

Channel	Frequency (MHz)	Power (dBm)
Low	2412	24.52
Middle	2437	24.49
High	2462	24.78

802.11g Mode

Channel	Frequency (MHz)	Power (dBm)
Low	2412	23.03
Middle	2437	23.11
High	2462	23.09

7.1.6. PEAK POWER SPECTRAL DENSITY

LIMIT

§15.247 (d) For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer, the maximum level in a 3 kHz bandwidth is measured with the spectrum analyzer using RBW = 3 kHz and VBW > 3 kHz, sweep time = span / 3 kHz, and video averaging is turned off. The PPSD is the highest level found across the emission in any 3 kHz band.

RESULTS

No non-compliance noted:


802.11b Mode


Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	2.551	8	-5.45
Middle	2437	2.604	8	-5.40
High	2462	3.891	8	-4.11


802.11g Mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	4.751	8	-3.25
Middle	2437	5.067	8	-2.93
High	2462	4.893	8	-3.11


PEAK POWER SPECTRAL DENSITY (802.11b MODE)









PEAK POWER SPECTRAL DENSITY (802.11g MODE)







7.1.7. CONDUCTED SPURIOUS EMISSIONS

LIMITS

§15.247 (c) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

RESULTS


No non-compliance noted:


SPURIOUS EMISSIONS, LOW CHANNEL (802.11b MODE)







SPURIOUS EMISSIONS, MID CHANNEL (802.11b MODE)







SPURIOUS EMISSIONS, HIGH CHANNEL (802.11b MODE)







SPURIOUS EMISSIONS, LOW CHANNEL (802.11g MODE)







SPURIOUS EMISSIONS, MID CHANNEL (802.11g MODE)





SPURIOUS EMISSIONS, HIGH CHANNEL (802.11g MODE)





7.2. RADIATED EMISSIONS

7.2.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS

LIMITS

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each 5 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


7.2.2. TRANSMITTER ABOVE 1 GHz FOR 2400 TO 2483.5 MHz BAND


RESTRICTED BANDEDGE (b MODE, LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (b MODE, LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (b MODE, HIGH CHANNEL, VERTICAL)







HARMONICS AND SPURIOUS EMISSIONS (b MODE)


03/10/05 High Frequency Measurement																	
Compliance Certification Services, Morgan Hill Open Field Site																	
Test Engr:		David Garcia															
Project #:		05U3280-1															
Company:		Ubiquity Networks															
EUT Descrip.:		802.11 b/g Mini PCI Card module															
EUT M/N:		SR2															
Test Target:		FCC 15.247															
Mode Oper:		11b mode, transmitting, 3 dBi Dipole Antenna															
Test Equipment:																	
EMCO Horn 1-18GHz				Pre-amplifier 1-26GHz				Pre-amplifier 26-40GHz				Horn > 18GHz					
T73; S/N: 6717 @3m				T86 Miteq 924341								T39; ARA 18-26GHz; S/N:1013					
Hi Frequency Cables																	
2 foot cable				3 foot cable				4 foot cable				12 foot cable				HPF	Reject Filter
4_David				12_Yan				HPF_ 4.0GHz									
Peak Measurements RBW=VBW=1MHz																	
Average Measurements RBW=1MHz ; VBW=10Hz																	
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fldr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)		
2412 Channel																	
4.824	3.0	48.6	36.3	32.9	4.8	-44.0	0.0	0.6	42.9	30.6	74	54	-31.1	-23.4	V		
12.060	3.0	48.4	40.7	38.8	8.5	-44.0	0.0	0.9	52.6	44.9	74	54	-21.4	-9.1	V		
4.824	3.0	47.8	35.0	32.9	4.8	-44.0	0.0	0.6	42.1	29.3	74	54	-31.9	-24.7	H		
12.060	3.0	50.4	40.6	38.8	8.5	-44.0	0.0	0.9	54.6	44.8	74	54	-19.4	-9.2	H		
2437 Channel																	
4.874	3.0	48.5	36.6	32.9	4.9	-44.1	0.0	0.6	42.8	30.9	74	54	-31.2	-23.1	V		
7.311	3.0	50.0	40.4	35.8	6.0	-45.0	0.0	0.6	47.4	37.8	74	54	-26.6	-16.2	V		
12.185	3.0	48.9	39.6	38.8	8.5	-44.2	0.0	0.9	53.0	43.7	74	54	-21.0	-10.3	V		
4.874	3.0	48.0	36.2	32.9	4.9	-44.1	0.0	0.6	42.3	30.5	74	54	-31.7	-23.5	H		
7.311	3.0	47.8	37.1	35.8	6.0	-45.0	0.0	0.6	45.2	34.5	74	54	-28.8	-19.5	H		
12.185	3.0	47.9	38.1	38.8	8.5	-44.2	0.0	0.9	52.0	42.2	74	54	-22.0	-11.8	H		
2462 Channel																	
4.924	3.0	48.7	37.1	33.0	4.9	-44.2	0.0	0.6	43.0	31.4	74	54	-31.0	-22.6	V		
7.386	3.0	51.3	42.2	36.0	6.0	-45.0	0.0	0.6	48.9	39.8	74	54	-25.1	-14.2	V		
4.924	3.0	48.3	36.7	33.0	4.9	-44.2	0.0	0.6	42.6	31.0	74	54	-31.4	-23.0	H		
7.386	3.0	50.3	38.8	36.0	6.0	-45.0	0.0	0.6	47.9	36.4	74	54	-26.1	-17.6	H		
No further emissions were detected above the noise floor of the test receiver.																	
f	Measurement Frequency					Amp	Preamp Gain					Avg Lim	Average Field Strength Limit				
Dist	Distance to Antenna					D Corr	Distance Correct to 3 meters					Pk Lim	Peak Field Strength Limit				
Read	Analyzer Reading					Avg	Average Field Strength @ 3 m					Avg Mar	Margin vs. Average Limit				
AF	Antenna Factor					Peak	Calculated Peak Field Strength					Pk Mar	Margin vs. Peak Limit				
CL	Cable Loss					HPF	High Pass Filter										


RESTRICTED BANDEDGE (g MODE, LOW CHANNEL, HORIZONTAL)







RESTRICTED BANDEDGE (g MODE, LOW CHANNEL, VERTICAL)







RESTRICTED BANDEDGE (g MODE, HIGH CHANNEL, HORIZONTAL)





RESTRICTED BANDEDGE (g MODE, HIGH CHANNEL, VERTICAL)





HARMONICS AND SPURIOUS EMISSIONS (g MODE)

03/10/05 High Frequency Measurement															
Compliance Certification Services, Morgan Hill Open Field Site															
Test Engr:		David Garcia													
Project #:		05U3280-1													
Company:		Ubiquity Networks													
EUT Descrip.:		802.11 b/g Mini PCI Card module													
EUT M/N:		SR2													
Test Target:		FCC 15.247													
Mode Oper:		11g mode, transmitting, 3 dBi Dipole Antenna													
Test Equipment:															
EMCO Horn 1-18GHz		Pre-amplifier 1-26GHz		Pre-amplifier 26-40GHz		Horn > 18GHz									
T73; S/N: 6717 @3m		T86 Miteq 924341				T39; ARA 18-26GHz; S/N:1013									
Hi Frequency Cables															
2 foot cable		3 foot cable		4 foot cable		12 foot cable		HPF		Reject Filter		Peak Measurements RBW=VBW=1MHz			
				4_David		12_Yan		HPF_4.0GHz				Average Measurements RBW=1MHz ; VBW=10Hz			
f GHz	Dist (m)	Read Pk dBuV	Read Avg. dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fldr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)
2412 Channel															
4.824	3.0	48.2	36.0	32.9	4.8	-44.0	0.0	0.6	42.5	30.3	74	54	-31.5	-23.7	V
12.060	3.0	50.0	39.1	38.8	8.5	-44.0	0.0	0.9	54.2	43.3	74	54	-19.8	-10.7	V
4.824	3.0	48.0	35.0	32.9	4.8	-44.0	0.0	0.6	42.3	29.3	74	54	-31.7	-24.7	H
12.060	3.0	49.6	38.5	38.8	8.5	-44.0	0.0	0.9	53.8	42.7	74	54	-20.2	-11.3	H
2437 Channel															
4.874	3.0	48.2	36.0	32.9	4.9	-44.1	0.0	0.6	42.5	30.3	74	54	-31.5	-23.7	V
7.311	3.0	50.5	38.7	35.8	6.0	-45.0	0.0	0.6	47.9	36.1	74	54	-26.1	-17.9	V
4.874	3.0	48.0	35.8	32.9	4.9	-44.1	0.0	0.6	42.3	30.1	74	54	-31.7	-23.9	H
2462 Channel															
4.924	3.0	48.4	36.9	33.0	4.9	-44.2	0.0	0.6	42.7	31.2	74	54	-31.3	-22.8	V
4.924	3.0	48.2	36.3	33.0	4.9	-44.2	0.0	0.6	42.5	30.6	74	54	-31.5	-23.4	H
No further emissions were detected above the noise floor of the test receiver.															
f	Measurement Frequency					Amp	Preamp Gain					Avg Lim	Average Field Strength Limit		
Dist	Distance to Antenna					D Corr	Distance Correct to 3 meters					Pk Lim	Peak Field Strength Limit		
Read	Analyzer Reading					Avg	Average Field Strength @ 3 m					Avg Mar	Margin vs. Average Limit		
AF	Antenna Factor					Peak	Calculated Peak Field Strength					Pk Mar	Margin vs. Peak Limit		
CL	Cable Loss					HPF	High Pass Filter								

7.2.3. WORST-CASE RADIATED EMISSIONS BELOW 1 GHz


SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)

HORIZONTAL PLOT



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 20 File#: 05U3280.EMI Date: 03-09-2005 Time: 15:37:36



(Auxiliary ATC)

Trace:

Ref Trace:

Condition: FCC CLASS-B HORIZONTAL
Test Operator: : David Garcia
Project #: : 05U3280-1
Company: : Ubiquiti Networks
EUT: : 802.11b/g Mini-PCI WLAN Module
Model No : SR2
Configuration: : EUT/H-P Laptop; SMA Antenna
Target of Test: : FCC Class B
Mode of Operation: TX

Page: 1

HORIZONTAL DATA

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	98.870	57.30	-16.71	40.59	43.50	-2.91	Peak
2	131.850	53.50	-12.70	40.80	43.50	-2.70	Peak
3 *	164.830	60.30	-14.11	46.19	43.50	2.69	Peak
4	164.830	54.80	-14.11	40.69	43.50	-2.81	QP
5	238.550	54.30	-14.18	40.12	46.00	-5.88	Peak
6	599.390	48.90	-5.51	43.39	46.00	-2.61	QP
7	599.390	50.70	-5.51	45.19	46.00	-0.81	Peak
8	996.120	50.90	-0.48	50.42	54.00	-3.58	Peak


SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)

VERTICAL PLOT



561F Monterey Road
Morgan Hill, CA 95037
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 12 File#: 05U3280.EMI Date: 03-09-2005 Time: 15:05:58



(Auxiliary ATC)

Trace:

Ref Trace:

Condition: FCC CLASS-B VERTICAL
Test Operator: : David Garcia
Project #: : 05U3280-1
Company: : Ubiquiti Networks
EUT: : 802.11b/g Mini-PCI WLAN Module
Model No : SR2
Configuration: : EUT/H-P Laptop; SMA Antenna
Target of Test: : FCC Class B
Mode of Operation: TX

Page: 1

VERTICAL DATA

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1	165.800	53.00	-14.15	38.85	43.50	-4.65	Peak
2	198.780	48.90	-13.27	35.63	43.50	-7.87	Peak
3	455.830	46.90	-8.15	38.75	46.00	-7.25	Peak
4	527.610	46.00	-6.77	39.23	46.00	-6.77	Peak
5	533.430	44.80	-6.67	38.13	46.00	-7.87	Peak
6	597.450	45.10	-5.53	39.57	46.00	-6.43	Peak

7.3. POWERLINE CONDUCTED EMISSIONS

LIMIT

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The resolution bandwidth is set to 9 kHz for both peak detection and quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

No non-compliance noted:

6 WORST EMISSIONS


CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq.	Reading			Closs	Limit	FCC B	Margin		Remark
(MHz)	PK (dBuV)	QP (dBuV)	AV (dBuV)	(dB)	QP	AV	QP (dB)	AV (dB)	L1 / L2
0.15	52.20	--	--	0.00	65.78	55.78	-13.58	-3.58	L1
0.34	37.58	--	--	0.00	59.30	49.30	-21.72	-11.72	L1
0.54	32.68	--	--	0.00	56.00	46.00	-23.32	-13.32	L1
0.20	47.88	--	--	0.00	63.61	53.61	-15.73	-5.73	L2
0.34	40.17	--	--	0.00	59.28	49.28	-19.11	-9.11	L2
0.40	38.54	--	--	0.00	57.77	47.77	-19.23	-9.23	L2
6 Worst Data									

LINE 1 RESULTS



561F Monterey Road
Morgan Hill, CA 95037 USA
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 28 File#: 05U3280.EMI Date: 03-08-2005 Time: 16:40:38
Level (dBuV) Compliance Certification Services



Trace: 26
Project No. : 05U3280-1
Test Engr : David Garcia
Company : Ubiquiti Networks
EUT : 802.11b/g Mini PCI card
Model No. : SR2
Test Config.: EUT w/extender card to HP Laptop
Type of Test: FCC CLASS B
Mode of Op. : Tx (Worst Channel)
AC Mains : L1: Peak(Black); Average (Green)
: 115VAC, 60Hz


Ref Trace:

LINE 2 RESULTS



561F Monterey Road
Morgan Hill, CA 95037 USA
Tel: (408) 463-0888
Fax: (408) 463-0885

Data#: 21 File#: 05U3280.EMI Date: 03-08-2005 Time: 16:30:45
Level (dBuV) Compliance Certification Services




Trace: 19
Project No. : 05U3280-1
Test Engr : David Garcia
Company : Ubiquiti Networks
EUT : 802.11 b/g Mini PCI card
Model No. : SR2
Test Config.: EUT w/extender card to HP Laptop
Type of Test: FCC CLASS B
Mode of Op. : Tx (Worst Channel)
AC Mains : L2: Peak(Black); Average (Green)
: 115VAC, 60Hz


Ref Trace:

8. SETUP PHOTOS

ANTENNA PORT CONDUCTED RF MEASUREMENT SETUP




RADIATED RF MEASUREMENT SETUP



RADIATED BACK PHOTO



POWERLINE CONDUCTED EMISSIONS MEASUREMENT SETUP



LINE CONDUCTED BACK PHOTO



END OF REPORT