

FCC ID:2ASBQ-75AMVF60

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

B.3 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	1,920 R ²
1.34	–	30	35.6 m	–	1.6 m	3,450 R ² / f^2
30	–	300	1.6 m	–	159 mm	3.83 R ²
300	–	1,500	159 mm	–	31.8 mm	0.0128 R ² / f
1,500	–	100,000	31.8 mm	–	0.5 mm	19.2R ²

Subscripts L and H are low and high; λ is wavelength.
 From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

1.1 Friis transmission formula: $P_d = 3450 R^2 / f^2$

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body. the 13.56 MHz does not effect the overall RF Exposure and there was no need to evaluate for these bands.

1.2 Measurement Result

RFID 13.56MHz, Antenna Gain: 0dBi

Mode	Emission Level(dBu V/m)	ERP (dBm)	Limits (dBm)
13.56MHz	58.33	-36.90	28.76

Note: Refer to report No. ENS2406280304W00101R and ENS2406280304W00102R.

Limits: $3450 * 0.2^2 / 13.56^2 = 0.751 \text{ W} = 28.76 \text{ dBm}$