

RF Exposure Report

Report No.: SA150424E08A

FCC ID: RRK-CS3202

Test Model: CS-3202

Received Date: Apr. 24, 2015

Test Date: July 29, 2015

Issued Date: Sep. 25, 2015

Applicant: Alpha Networks Inc.

Address: No.8 Li-shing 7th Rd., Science-based Industrial Park, Hsinchu, Taiwan,

R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin

Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin

Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin

Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Report No.: SA150424E08A Page No. 1 / 5 Report Format Version: 6.1.1 Reference No.: 150630E03



Table of Contents

Relea	ase Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
2.1	Limits for Maximum Permissible Exposure (MPE)	5
2.2	MPE Calculation Formula	5
2.3	Classification	5
2.4	Antenna Gain	5
3	Calculation Result of Maximum Conducted Power	5



Release Control Record

Issue No.	Description	Date Issued
SA150424E08A	Original release.	Sep. 25, 2015

Report No.: SA150424E08A Page No. 3 / 5 Report Format Version: 6.1.1

Report No.: SA150424E08A Reference No.: 150630E03



1 Certificate of Conformity

Product: 720P Wireless Baby Camera

Brand: ALPHA

Test Model: CS-3202

Sample Status: ENGINEERING SAMPLE

Applicant: Alpha Networks Inc.

Test Date: July 29, 2015

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :		, Date:	Sep. 25, 2015	
	Claire Kuan / Specialist			

May Chen/Manager

Date: Sep. 25, 2015

Report No.: SA150424E08A Reference No.: 150630E03

Approved by:

Page No. 4 / 5



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)	
Limits For General Population / Uncontrolled Exposure					
300-1500			F/1500	30	
1500-100,000			1.0	30	

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

The antenna provided to the EUT, please refer to the following table:

Ant. Gain(dBi)	Frequency Range (GHz to GHz)	Ant. Type	Connecter Type	Cable Length (mm)
2.93	2.4~2.5	PIFA	I-pex	55

3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm²)
2412-2462	71.614	2.93	20	0.02797	1

--- END ---

Report No.: SA150424E08A Page No. 5 / 5 Report Format Version: 6.1.1

Reference No.: 150630E03