



SISTRAID
IP-0204-PD20-801



SE1_System_Spec_for_TUV_SUD
E392304 Rev. 03 (2024-03-25)

3.1.3 Print Format of Packaging Bag for SE1 Sensor

Please refer to EDB document **9351020** for details.

SE1 Sensor for (refer to Table 1)

SICK

SE1

Safety Switch
SE1-ST1A20

Product ID
pid.sick.com/

P/N 1132196/
S/N 24050001




Safe Switch On (Front) : 15
Safe Switch On (Top/Bottom) : 6
Safe Switch Off : 30

FCC ID : 2AHDRSE1, IC : 21147SE1

Type 1, Class 2

Safety Parameters : Cat. 4, PL e (EN ISO 13849)
SIL 3 (IEC 61508)

Enclosure Rating : IP67, IP69K
Operating Temperature : -10 °C to +70 °C
Power Supply : DC 24 V / 35 mA
Operating Instruction : 8028531



handle it with care
Fragile

SICK	 SISTRAID IP-0204-PD20-801	 SE1_System_Spec_for_TUV_SUD E392304 Rev. 03 (2024-03-25)
-------------	---	---

3.1.4 Print Format of Packaging Bag for SE1 Actuator

Please refer to EDB document **9351020** for details.

SE1 Actuator (refer to Table 4)

SICK

SE1

Safety Switch
SE1-AM01

Product ID
pid.sick.com /

P/N 1132271/
S/N 24050001



 **US**
LISTED
PROXIMITY SWITCH
4LP4

