

供应商: **Videostrong Technology Co., Ltd**
 Address: 604, Lushi industrial Building, 28 District,
 Bao' an District, Shenzhen, China

SPECIFICATION FOR APPROVAL

X X X 料號
 SOREDE P/N _____
 品 名 / 規 格
 DESCRIPTION _____ 2.4G antenna _____
 X X X 送樣編號 _____
 送樣日期: _____

MANUFACTURER/制造商

APPROVED BY	QC DEPT	CHECKED BY	TESTED BY
核 准	品 管	审 核	检 测

客户: **Videostrong Technology Co., Ltd**

CUSTOMER P/N 视壮料号: _____

CUSTOMER 视壮名称: _____

DESCRIPTION 品名/规格: _____


CUSTOMER APPROVAL/客户审核

APPROVED BY	QC DEPT	CHECKED BY	TESTED BY
核准	品管	审核	检测

Product Number:

Product Name: Wire Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency 频率	2400-2500MHz
S.W.R.驻波比	<= 2.0
Antenna Gain 增益	1 dBi
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm
B. Material & Mechanical Characteristics	
Material of Radiator	Cu
Material of Plastic 塑胶材质	/
Cable Type 线材规格	/
Connector Type 连接器规格	/
Connector Pull Test	/
Connector Torque Test	/
C. Environmental	
Operation Temperature 存储温度	- 40 °C ~ + 80 °C
Storage Temperature 存储温度	- 40 °C ~ + 80 °C

2. Characteristics and Reliability Test

Test Items		Test Condition and Procedure	Requirements
C1	S.W.R.	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification
C2	Antenna Gain	Set DUT on Antenna Chamber; make individual calibration to test	Directive DUT specification
M1	Vibration	MIL-STD-202G, 201A Amplitude: 0.03 inch (0.76mm); Freq: 10 to 55 Hz 3 directions; 2 hours for each direction	1. No Visual Damage 2. Frequency Tol.<= 5%


Product Number:

Product Name: Wire Antenna

M2	Random Drop	Height: 1.5 Meter; 3 directions; 1 time for each direction	1. No parts separated 2. Frequency Tol.<= 5%
M3	Solderability	MIL-STD-202G, 210F, cond. A Solder iron: 350±10°C; Duration: 5 seconds	1. Mounted on PCB 2. No Visual Damage
M4	Terminal-Pull Test	MIL-STD-202G, 211A, cond. A Holding with individual specification; force applied to axis of terminal	1. Directive DUT specification 2. Frequency Tol.<= 5%
M5	Terminal-Torque Test	MIL-STD-202G, 211A, cond. E Holding with individual specification; applied clockwise and counterclockwise to the axis of terminal	1. Directive DUT specification 2. Frequency Tol.<= 5%
M6	Dimension	Inspection of dimension, color, material, package, surface process	Directive DUT specification
E1	Salt Spray	MIL-STD-202G, 101E, cond. B Temp: 405°C; RH: >= 95%; NaCl solution: >= 5%; Time: 48 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E2	Humidity	MIL-STD-202G, 103B, cond. B Temp: 40°C; RH: >= 95%; Time: 48 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E3	Thermal Shock	1 Cycle: - 40°C (30 minutes) to + 80°C (30 minutes) Cycles: 24	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E4	Life (High Temp.)	MIL-STD-202G, 108A, cond. A Temp: 80°C; Time: 96 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
R1	RoHS	With Reference to IEC 62321:2008 with flow chart	Directive RoHS 2020/863/EU

3. Antenna - S Parameter Test Data

Product Number:
Product Name: Wire Antenna




4. Antenna - Radiation Pattern Test Data

Frequency ID	1	6	11
Frequency (MHz)	2400	2450	2500
Gain (dBi)	1dBi	0.84dBi	0.98dBi
Efficiency (%)	50.08	50.54	47.83

Product Number:
Product Name: Wire Antenna

2400MHz



5. Mechanical Drawing (See attached files)

Product Number:
Product Name: Wire Antenna

