



12. Radio Frequency Exposure

12.1.Applicable Standards

☐ §1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.																																										
☐ §1.1307(b)(3)(i)(c)	ERP is below a threshold calculated based on the distance , R between the person and t antenna / radiating structure, where $R > \lambda / 2 \pi$. TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION <table><tr><th colspan="3">RF Source Frequency</th><th colspan="2">Minimum Distance</th><th>Threshold ERP</th></tr><tr><th>f_L MHz</th><th></th><th>f_H MHz</th><th>$\lambda_L / 2\pi$</th><th>$\lambda_H / 2\pi$</th><th>W</th></tr><tr><td>0.3</td><td>–</td><td>1.34</td><td>159 m</td><td>–</td><td>35.6 m</td></tr><tr><td>1.34</td><td>–</td><td>30</td><td>35.6 m</td><td>–</td><td>1.6 m</td></tr><tr><td>30</td><td>–</td><td>300</td><td>1.6 m</td><td>–</td><td>159 mm</td></tr><tr><td>300</td><td>–</td><td>1,500</td><td>159 mm</td><td>–</td><td>31.8 mm</td></tr><tr><td>1,500</td><td>–</td><td>100,000</td><td>31.8 mm</td><td>–</td><td>0.5 mm</td></tr></table> Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.	RF Source Frequency			Minimum Distance		Threshold ERP	f_L MHz		f_H MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W	0.3	–	1.34	159 m	–	35.6 m	1.34	–	30	35.6 m	–	1.6 m	30	–	300	1.6 m	–	159 mm	300	–	1,500	159 mm	–	31.8 mm	1,500	–	100,000	31.8 mm	–	0.5 mm
RF Source Frequency			Minimum Distance		Threshold ERP																																						
f_L MHz		f_H MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W																																						
0.3	–	1.34	159 m	–	35.6 m																																						
1.34	–	30	35.6 m	–	1.6 m																																						
30	–	300	1.6 m	–	159 mm																																						
300	–	1,500	159 mm	–	31.8 mm																																						
1,500	–	100,000	31.8 mm	–	0.5 mm																																						
☒ § 1.1307(b)(3)(i)(B).	Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$ $P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ Where $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ and $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ d = the separation distance (cm);																																										

**12.2.EUT Specification**

Frequency band (Operating)	☐ WLAN: 2412MHz ~ 2462MHz ☒ WLAN: 5150MHz ~ 5250MHz ☒ WLAN: 5250MHz ~ 5350MHz ☒ WLAN: 5470MHz ~ 5725MHz ☒ WLAN: 5725MHz ~ 5850MHz ☐ Bluetooth: 2402MHz ~ 2480MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☐ Blanket 1 mW Blanket Exemption ☒ MPE-based Exemption ☐ SAR-based Exemption
Remark: The maximum conducted output power is <u>17.86 dBm (61.094mW)</u> at <u>5785MHz</u> (with <u>3.80dBi antenna gain.</u>)	

12.3.Result

Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Max.Tune up e.r.p. Power (dBm)	Max. Tune up e.r.p power (mW)	Limit (mW)
5180-5240	16.09	16.59	3.8	18.24	66.68	3060
5260-5320	16.32	16.82	3.8	18.47	70.31	3060
5500-5700	16.91	17.41	2.4	17.66	58.34	3060
5745-5825	17.86	18.36	0.9	17.11	51.40	3060

No non-compliance noted.

Maximum Permissible Exposure (Co-location)

WCN3680 WIFI 5G + Nordic BLE

Modulation Type	Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Distance (cm)	Max.Tune up e.r.p. Power(mW)	Limit (mW)	MPE Ratio
11ac VHT20	5260-5320	16.32	16.82	3.8	20	70.31	3060.00	0.023
GFSK(1Mbps)	2402-2480	3.68	4.18	4.9	20	4.93	3060.00	0.002
Co-location Total								0.025
Σ MPE ratios Limit								1.000

-----THE END OF REPORT-----