



775 Montague Expressway
 Milpitas, CA 95035
 Tel: 408-526-1188
 Fax: 408-526-1088
 Email: sales.eaw@us.bureauveritas.com

Modular Approval Declaration Letter

Reason for Amendment (current / obsolete)	Revision History		Approved Date
	From	To	
Initial Release (Obsolete)	1.0	1.0	Dec-04-2006
Added IC Modular Letter (Obsolete)	1.0	2.0	Feb 16 2009
Add LMA and MA option (Obsolete)	2.0	3.0	April 14 2010
Revised per RSS Gen issue 3.0 (Obsolete)	3.0	4.0	Jan 12 2011
Removed Foot(2) (obsolete)	4.0	5.0	July 19 2011
Adding New note per KDB996369 D01 V01R03 (obsolete)	5.0	6.0	August 29 2011
Updated company template & Added text box (obsolete)	6.0	7.0	Jan-31-2012
Updated modular requirement (obsolete)	7.0	8.0	Sept 05 2014
Updated template to meet RSP 100 issue 10 (obsolete)	8.0	9.0	Nov 20 2014
Updated template to meet RSP 100 issue 11 (obsolete))	9.0	10.0	March 19 2015
Revised the Modular Requirement statements (obsolete)	10.0	11.0	July 28, 2016
Updated template with BV logo (current)	11.0	12.0	June 26, 2019



(Date) April 06, 2020

(Product name) FCC ID: 2AJE7SMC-WEX02

is seeking FCC Authorization as a ☒ **Single Modular Transmitter** / ☐ **Single Limited Modular Transmitter** (Please check one)

The EUT meets the requirements for ☒ **Single Modular Approval** / ☐ **Single Limited Modular Approval** (Please check one)

as detailed in KDB 996369. Compliance to each of the requirements is described below:

Item	Modular requirement	Yes	No	Please provide a detailed explanation if the answer is "No."
1	Have its own RF shielding	Yes		
2	Have buffered modulation/data inputs (if such inputs are provided)	Yes		
3	The modular transmitter must have its own power supply regulation.	Yes		
4	Meet the antenna requirements of section 15.203	Yes		
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing.	Yes		
6	Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	Yes		
7	The modular transmitter is manufactured so that the user can not influence the operation of the transmitter that will operate outside of the scope of the regulations.	Yes		
8	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093.	Yes		

Note:

- (1) LMA may be granted when one or more of the requirements in the table above cannot be demonstrated.
LMA will also be issued in those instances where applicants can demonstrate that they will retain control over the final installation of the device, such that compliance of the end product is assured. In such cases, an operating condition on the LMA for the module must state that the module is only approved for use when installed in devices produced by a specific manufacturer.
When LMA is sought, the application for equipment certification must specifically state how control of the end product into which the module will be installed, and will be maintained, such that full compliance of the end product is always ensured.
- (2) Please provide Clear and specific instructions describing the conditions, limitations and procedures for third-parties to use and/or integrate the module into a host device.
- (3) For non-Software Defined Radio transmitter modules where software is used to ensure compliance of the device, technical description of how such control is implemented to ensure prevention of third party modification must be provided (see KDB 594280).

Note 1: Compliance of a module in its final configuration is the responsibility of the applicant. A host device will not be considered certified if the instructions regarding antenna configuration provided in the original description, of one or more separately certified modules it contains, were not followed.

Note 2: This equipment should be installed and operated with a minimum distance of 20cm between the radiator and the user's body.


Note 3: "Contains FCC ID: 2AJE7SMC-WEX02" should be labelled on the outside of a host device. When it is not possible, such information should be contained in the user manual.

Example:

3.3VDC should be supplied to the module. The module can be controlled via SPI interface.

Do not disassemble, modify (including changing the printed circuit board) or repair.

A separately certified transceiver module which is housed in an industrial device or peripheral does not require the overall system to be recertified, if the industrial device or peripheral, as a stand-alone unit, complies with all applicable technical standards.



Client's signature

Client's name / title : Akira Nishigori / Assistant manager

Contact information / address : 4-2-2, Kinunodai, Tsukubamirai-shi, Ibaraki-ken, Japan

Telephone: +81-297-52-6665

Fax No.: +81-297-20-5003

E-mail: nishigori.akira@smcjp.co.jp