APPENDIX B - SAR PLOTS

Test Plot 1#: GSM 850 Mid Head Left Cheek

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic GPRS-4 slots (0); Frequency: 836.6 MHz;Duty Cycle: 1:2 Medium parameters used: f = 836.6 MHz; $\sigma = 0.931$ S/m; $\epsilon_r = 41.904$; $\rho = 1000$ kg/m³ Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(6.68, 6.68, 6.68) @ 836.6 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.366 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.017 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.409 W/kg

SAR(1 g) = 0.361 W/kg; SAR(10 g) = 0.307 W/kg

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid (> 16 mm)

Ratio of SAR at M2 to SAR at M1 = 90.8%

Maximum value of SAR (measured) = 0.375 W/kg



0 dB = 0.375 W/kg = -4.26 dBW/kg

Test Plot 2#: GSM 850 Mid Body Back

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic GPRS-4 slots (0); Frequency: 836.6 MHz;Duty Cycle: 1:2 Medium parameters used: f = 836.6 MHz; $\sigma = 0.931$ S/m; $\varepsilon_r = 41.904$; $\rho = 1000$ kg/m³ Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(6.68, 6.68, 6.68) @ 836.6 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.393 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 19.87 V/m; Power Drift = -0.19 dB Peak SAR (extrapolated) = 0.512 W/kg SAR(1 g) = 0.347 W/kg; SAR(10 g) = 0.224 W/kg Smallest distance from peaks to all points 3 dB below = 10.7 mm Ratio of SAR at M2 to SAR at M1 = 72.6%Maximum value of SAR (measured) = 0.387 W/kg



0 dB = 0.387 W/kg = -4.12 dBW/kg

Test Plot 3#: PCS 1900 Mid Head Left Cheek

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic GPRS-4 slots (0); Frequency: 1880 MHz;Duty Cycle: 1:2 Medium parameters used: f = 1880 MHz; σ = 1.437 S/m; ϵ_r = 39.406; ρ = 1000 kg/m³ Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(5.24, 5.24, 5.24) @ 1880 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.142 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 4.859 V/m; Power Drift = -0.05 dB Peak SAR (extrapolated) = 0.177 W/kg SAR(1 g) = 0.135 W/kg; SAR(10 g) = 0.100 W/kg Smallest distance from peaks to all points 3 dB below = 20.5 mm Ratio of SAR at M2 to SAR at M1 = 78.2%Maximum value of SAR (measured) = 0.148 W/kg



0 dB = 0.148 W/kg = -8.30 dBW/kg

Test Plot 4#: PCS 1900 Mid Body Back

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic GPRS-4 slots (0); Frequency: 1880 MHz;Duty Cycle: 1:2 Medium parameters used: f = 1880 MHz; $\sigma = 1.437$ S/m; $\epsilon_r = 39.406$; $\rho = 1000$ kg/m³ Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(5.24, 5.24, 5.24) @ 1880 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.532 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 12.18 V/m; Power Drift = -0.08 dB Peak SAR (extrapolated) = 0.641 W/kg SAR(1 g) = 0.460 W/kg; SAR(10 g) = 0.301 W/kg Smallest distance from peaks to all points 3 dB below = 15.1 mm Ratio of SAR at M2 to SAR at M1 = 74.3%Maximum value of SAR (measured) = 0.513 W/kg



0 dB = 0.513 W/kg = -2.90 dBW/kg

Test Plot 5#: WCDAM Band 2 Mid Head Left Cheek

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: WCDMA (0); Frequency: 1880 MHz;Duty Cycle: 1:1 Medium parameters used: f = 1880 MHz; σ = 1.437 S/m; ϵ_r = 39.406; ρ = 1000 kg/m³ Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(5.24, 5.24, 5.24) @ 1880 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.174 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 5.353 V/m; Power Drift = 0.07 dB Peak SAR (extrapolated) = 0.223 W/kg SAR(1 g) = 0.163 W/kg; SAR(10 g) = 0.118 W/kg Smallest distance from peaks to all points 3 dB below = 16.8 mm Ratio of SAR at M2 to SAR at M1 = 74.7%Maximum value of SAR (measured) = 0.187 W/kg



0 dB = 0.187 W/kg = -7.28 dBW/kg

Test Plot 6#: WCDAM Band 2 Mid Body Back

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: WCDMA (0); Frequency: 1880 MHz;Duty Cycle: 1:1 Medium parameters used: f = 1880 MHz; σ = 1.437 S/m; ϵ_r = 39.406; ρ = 1000 kg/m³ Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(5.24, 5.24, 5.24) @ 1880 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.723 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 10.04 V/m; Power Drift = 0.09 dB Peak SAR (extrapolated) = 0.926 W/kg SAR(1 g) = 0.662 W/kg; SAR(10 g) = 0.433 W/kg Smallest distance from peaks to all points 3 dB below = 15.7 mm Ratio of SAR at M2 to SAR at M1 = 73.2%Maximum value of SAR (measured) = 0.761 W/kg



0 dB = 0.761 W/kg = -1.19 dBW/kg

Test Plot 7#: WCDMA Band 5 Mid Head Left Cheek

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: WCDMA (0); Frequency: 836.6 MHz;Duty Cycle: 1:1 Medium parameters used: f = 836.6 MHz; $\sigma = 0.931$ S/m; $\epsilon_r = 41.904$; $\rho = 1000$ kg/m³ Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(6.68, 6.68, 6.68) @ 836.6 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.295 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.126 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.327 W/kg

SAR(1 g) = 0.288 W/kg; SAR(10 g) = 0.244 W/kg

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid (> 16 mm)

Ratio of SAR at M2 to SAR at M1 = 90.2%

Maximum value of SAR (measured) = 0.301 W/kg



0 dB = 0.301 W/kg = -5.21 dBW/kg

Test Plot 8#: WCDMA Band 5 Mid Body Back

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: WCDMA (0); Frequency: 836.6 MHz;Duty Cycle: 1:1 Medium parameters used: f = 836.6 MHz; $\sigma = 0.931$ S/m; $\epsilon_r = 41.904$; $\rho = 1000$ kg/m³ Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(6.68, 6.68, 6.68) @ 836.6 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.572 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 18.98 V/m; Power Drift = -0.14 dB Peak SAR (extrapolated) = 0.722 W/kg SAR(1 g) = 0.479 W/kg; SAR(10 g) = 0.302 W/kg Smallest distance from peaks to all points 3 dB below = 11.7 mm Ratio of SAR at M2 to SAR at M1 = 69.4% Maximum value of SAR (measured) = 0.564 W/kg



0 dB = 0.564 W/kg = -2.49 dBW/kg

Test Plot 9#: LTE Band 2 1RB Mid Head Left Tilt

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic FDD-LTE (0); Frequency: 1880 MHz;Duty Cycle: 1:1 Medium parameters used: f = 1880 MHz; $\sigma = 1.437$ S/m; $\epsilon_r = 39.406$; $\rho = 1000$ kg/m³ Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(5.24, 5.24, 5.24) @ 1880 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.141 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 6.274 V/m; Power Drift = 0.06 dB Peak SAR (extrapolated) = 0.170 W/kg SAR(1 g) = 0.131 W/kg; SAR(10 g) = 0.096 W/kg Smallest distance from peaks to all points 3 dB below = 16.3 mm Ratio of SAR at M2 to SAR at M1 = 79.2%Maximum value of SAR (measured) = 0.144 W/kg



0 dB = 0.144 W/kg = -8.42 dBW/kg

Test Plot 10#: LTE Band 2 1RB Low Body Back

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic FDD-LTE (0); Frequency: 1860 MHz;Duty Cycle: 1:1 Medium parameters used: f = 1860 MHz; $\sigma = 1.429$ S/m; $\epsilon_r = 39.425$; $\rho = 1000$ kg/m³ Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(5.24, 5.24, 5.24) @ 1860 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.823 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 16.16 V/m; Power Drift = -0.03 dB Peak SAR (extrapolated) = 1.26 W/kg SAR(1 g) = 0.871 W/kg; SAR(10 g) = 0.559 W/kg Smallest distance from peaks to all points 3 dB below = 13.7 mm Ratio of SAR at M2 to SAR at M1 = 70.3%Maximum value of SAR (measured) = 1.01 W/kg



0 dB = 1.01 W/kg = 0.04 dBW/kg

Test Plot 11#: LTE Band 4 1RB Mid Head Left Tilt

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic FDD-LTE (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1 Medium parameters used: f = 1732.5 MHz; $\sigma = 1.368$ S/m; $\epsilon_r = 39.444$; $\rho = 1000$ kg/m³ Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(5.53, 5.53, 5.53) @ 1732.5 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.207 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mmReference Value = 8.621 V/m; Power Drift = -0.06 dB Peak SAR (extrapolated) = 0.235 W/kg SAR(1 g) = 0.191 W/kg; SAR(10 g) = 0.144 W/kg Smallest distance from peaks to all points 3 dB below = 16 mm Ratio of SAR at M2 to SAR at M1 = 82% Maximum value of SAR (measured) = 0.206 W/kg



0 dB = 0.206 W/kg = -6.86 dBW/kg

Test Plot 12#: LTE Band 4 1RB Mid Body Bottom

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic FDD-LTE (0); Frequency: 1732.5 MHz;Duty Cycle: 1:1 Medium parameters used: f = 1732.5 MHz; $\sigma = 1.368$ S/m; $\epsilon_r = 39.444$; $\rho = 1000$ kg/m³ Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(5.53, 5.53, 5.53) @ 1732.5 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.590 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 18.45 V/m; Power Drift = -0.06 dB Peak SAR (extrapolated) = 1.10 W/kg SAR(1 g) = 0.637 W/kg; SAR(10 g) = 0.367 W/kg Smallest distance from peaks to all points 3 dB below = 10.7 mm Ratio of SAR at M2 to SAR at M1 = 60.2%Maximum value of SAR (measured) = 0.787 W/kg



0 dB = 0.787 W/kg = -1.04 dBW/kg

Test Plot 13#: LTE Band 5 1RB Mid Head Left Cheek

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic FDD-LTE (0); Frequency: 836.5 MHz;Duty Cycle: 1:1 Medium parameters used: f = 836.5 MHz; $\sigma = 0.931$ S/m; $\epsilon_r = 41.905$; $\rho = 1000$ kg/m³ Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(6.68, 6.68, 6.68) @ 836.5 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (8x9x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.270 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.523 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.290 W/kg

SAR(1 g) = 0.261 W/kg; SAR(10 g) = 0.224 W/kg

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid (> 16 mm)

Ratio of SAR at M2 to SAR at M1 = 90%

Maximum value of SAR (measured) = 0.275 W/kg



0 dB = 0.275 W/kg = -5.61 dBW/kg

Test Plot 14#: LTE Band 5 1RB Mid Body Back

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic FDD-LTE (0); Frequency: 836.5 MHz;Duty Cycle: 1:1 Medium parameters used: f = 836.5 MHz; $\sigma = 0.931$ S/m; $\epsilon_r = 41.905$; $\rho = 1000$ kg/m³ Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(6.68, 6.68, 6.68) @ 836.5 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (measured) = 0.244 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 12.81 V/m; Power Drift = 0.07 dB Peak SAR (extrapolated) = 0.330 W/kg SAR(1 g) = 0.219 W/kg; SAR(10 g) = 0.150 W/kg Smallest distance from peaks to all points 3 dB below = 16.1 mm Ratio of SAR at M2 to SAR at M1 = 68.4%Maximum value of SAR (measured) = 0.250 W/kg



0 dB = 0.250 W/kg = -6.02 dBW/kg

Test Plot 15#: LTE Band 7 1RB Mid Head Left Cheek

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic FDD-LTE (0); Frequency: 2535 MHz;Duty Cycle: 1:1 Medium parameters used: f = 2535 MHz; $\sigma = 1.911$ S/m; $\epsilon_r = 40.185$; $\rho = 1000$ kg/m³ Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(4.83, 4.83, 4.83) @ 2535 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (10x10x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.390 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mmReference Value = 4.542 V/m; Power Drift = 0.19 dB Peak SAR (extrapolated) = 0.587 W/kg SAR(1 g) = 0.384 W/kg; SAR(10 g) = 0.246 W/kg Smallest distance from peaks to all points 3 dB below = 14.2 mm Ratio of SAR at M2 to SAR at M1 = 69.6% Maximum value of SAR (measured) = 0.454 W/kg



0 dB = 0.454 W/kg = -3.43 dBW/kg

Test Plot 16#: LTE Band 7 1RB Mid Body Back

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: Generic FDD-LTE (0); Frequency: 2535 MHz;Duty Cycle: 1:1 Medium parameters used: f = 2535 MHz; $\sigma = 1.911$ S/m; $\epsilon_r = 40.185$; $\rho = 1000$ kg/m³ Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(4.83, 4.83, 4.83) @ 2535 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (10x17x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.600 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mmReference Value = 8.247 V/m; Power Drift = -0.12 dB Peak SAR (extrapolated) = 0.993 W/kg SAR(1 g) = 0.578 W/kg; SAR(10 g) = 0.316 W/kg Smallest distance from peaks to all points 3 dB below = 10 mm Ratio of SAR at M2 to SAR at M1 = 63.3% Maximum value of SAR (measured) = 0.708 W/kg



0 dB = 0.708 W/kg = -1.50 dBW/kg

Test Plot 17#: 2.4G WLAN Mid Head Left Cheek

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: 802.11b (0); Frequency: 2437 MHz;Duty Cycle: 1:1 Medium parameters used: f = 2437 MHz; σ = 1.825 S/m; ϵ_r = 40.545; ρ = 1000 kg/m³ Phantom section: Left Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(4.83, 4.83, 4.83) @ 2437 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (9x9x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.107 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mmReference Value = 5.432 V/m; Power Drift = 0.09 dB Peak SAR (extrapolated) = 0.137 W/kg SAR(1 g) = 0.102 W/kg; SAR(10 g) = 0.079 W/kg Smallest distance from peaks to all points 3 dB below = 17.1 mm Ratio of SAR at M2 to SAR at M1 = 84.4% Maximum value of SAR (measured) = 0.110 W/kg



0 dB = 0.110 W/kg = -9.59 dBW/kg

Test Plot 18#: 2.4G WLAN Mid Body Front

DUT: Mobile Phone; Type: S500; Serial: 30JH-1

Communication System: 802.11b (0); Frequency: 2437 MHz;Duty Cycle: 1:1 Medium parameters used: f = 2437 MHz; $\sigma = 1.825$ S/m; $\epsilon_r = 40.545$; $\rho = 1000$ kg/m³ Phantom section: Flat Section

DASY5 Configuration:

- Probe: ES3DV3 SN3220; ConvF(4.83, 4.83, 4.83) @ 2437 MHz; Calibrated: 2024/10/15
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2025/2/17
- Phantom: SAM (30deg probe tilt) with CRP v5.0_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.14 (7501)

Area Scan (10x17x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.0681 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.945 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.0720 W/kg

SAR(1 g) = 0.067 W/kg; SAR(10 g) = 0.065 W/kg

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid (> 15 mm)

Ratio of SAR at M2 to SAR at M1 = 89.8%

Maximum value of SAR (measured) = 0.0722 W/kg



0 dB = 0.0722 W/kg = -11.41 dBW/kg