

**EMC Technologies Pty Ltd**

ABN 82 057 105 549
176 Harrick Road
Keilor Park
Victoria Australia 3042

Ph: + 613 9365 1000
Fax: + 613 9331 7455
email: melb@emctech.com.au

SAR Test Report

Report Number: M150814_FCC_EM7355 WWAN_8260NGW
WLAN_Multiband

Host PC: Portable T SERIES LIFEBOOK
CONVERTIBLE Computer

Radio Modules: Sierra EM7355 WWAN module and Intel
8260NGW WLAN/Bluetooth module

Host PC Model Number: T936

Host FCC ID: EJE-WB0096

WWAN FCC ID: EJE-EM7355D

Host IC ID: 337J-WB0096

WWAN IC ID: 337J-EM7355D

Date of Issue: 21st September 2015

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

CONTENTS

1.0 GENERAL INFORMATION.....	3
2.0 INTRODUCTION.....	4
3.0 TEST SAMPLE TECHNICAL INFORMATION.....	5
3.1 DUT (WLAN) Details	5
3.2 DUT (Bluetooth) Details	9
3.3 DUT (T series LifeBook Convertible PC) Details	10
3.4 Test sample Accessories	10
3.4.1 Battery Types	10
4.0 TEST SIGNAL, FREQUENCY AND OUTPUT POWER.....	11
4.1 Battery Status.....	11
5.0 DETAILS OF TEST LABORATORY	12
5.1 Location	12
5.2 Accreditations.....	12
5.3 Environmental Factors	12
6.0 CALIBRATION AND VERIFICATION PROCEDURES AND DATA	13
6.1 System verification	13
6.1.1 System verification Results @ 5GHz.....	13
6.1.2 Liquid Temperature and Humidity.....	13
7.0 SAR MEASUREMENT PROCEDURE USING DASY5	14
8.0 MEASUREMENT UNCERTAINTY	15
9.0 EQUIPMENT LIST AND CALIBRATION DETAILS.....	18
10.0 TEST METHODOLOGY.....	19
10.1 Position	19
10.1.1 "Lap Held" Position Definition (0mm spacing).....	19
10.1.2 "Edge On" Position (Portrait or Landscape).....	19
10.1.3 "Bystander" Position (25mm spacing).....	19
10.2 List of All Test Cases (Antenna In/Out, Test Frequencies, User Modes).....	20
11.0 SAR MEASUREMENT RESULTS	21
11.1 5GHz Band SAR Results	21
12.0 COMPLIANCE STATEMENT	29
13.0 MULTIBAND EVALUATION CONSIDERATIONS.....	30
APPENDIX A1 TEST SAMPLE PHOTOGRAPHS	32
APPENDIX A2 TEST SAMPLE PHOTOGRAPHS	40
APPENDIX A3 TEST SAMPLE PHOTOGRAPHS	40
APPENDIX A4 TEST SETUP PHOTOGRAPHS	40
APPENDIX A5 TEST SETUP PHOTOGRAPHS	40
APPENDIX A6 TEST SETUP PHOTOGRAPHS	40
APPENDIX A7 TEST SETUP PHOTOGRAPHS	40
APPENDIX A8 TEST SETUP PHOTOGRAPHS	40
APPENDIX B PLOTS OF THE SAR MEASUREMENTS	40
APPENDIX C DESCRIPTION OF SAR MEASUREMENT SYSTEM	177
APPENDIX D CALIBRATION DOCUMENTS	181



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

SAR TEST REPORT**Report Number: M150814_FCC_8260NGW_SAR_5.6****Host FCC ID: EJE-WB0096; WWAN FCC ID: EJE-EM7355D****Host IC ID: 337J-WB0096; WWAN IC ID: 337J-EM7355D****1.0 GENERAL INFORMATION**

Test Sample: Portable T SERIES LIFEBOOK CONVERTIBLE Computer
Model Name: T936
Radio Modules: WLAN and Bluetooth 8260NGW
Interface Type: M.2 Wireless LAN Module
Device Category: Portable Transmitter
Test Device: Pre-Production Unit
FCC System ID: EJE-WB0096
PC System IC: 337J-WB0096
RF exposure Category: General Population/Uncontrolled

Manufacturer: Fujitsu Limited


Test Standard/s:


1. KDB 248227 D01 SAR measurements for 802.11 a b g v02r01
 KDB 447498 D01 General RF Exposure Guidance v05r02
 KDB 616217 D04 SAR for laptop and tablets v01r01
 KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
 KDB 865664 D02 RF Exposure Reporting v01r01
2. Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), RSS-102
3. **EN 62209-2:2010**
 Human exposure to radio frequency fields from hand-held and bodymounted wireless communication devices. Human models, instrumentation, and procedures.
Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)
4. **IEEE 1528: 2013**
 Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.
 The Fujitsu T SERIES LIFEBOOK CONVERTIBLE Computer T936 with Sierra EM7355 WWAN module and Intel 8260NGW WLAN/Bluetooth module complied with the FCC General public/uncontrolled RF exposure limits of 1.6mW/g per requirements of 47CFR2.1093(d). It also complied with IC RSS-102 requirements.

Statement Of Compliance: The Fujitsu T SERIES LIFEBOOK CONVERTIBLE Computer T936 with Sierra EM7355 WWAN module and Intel 8260NGW WLAN/Bluetooth module complied with the FCC General public/uncontrolled RF exposure limits of 1.6mW/g per requirements of 47CFR2.1093(d). It also complied with IC RSS-102 requirements.

Highest Reported SAR: 5 GHz WLAN Band: 1.242 mW/g

Test Dates: 25th August 2015 to 3rd September 2015

Test Officer: 
 Peter Jakubiec

Authorised Signature: 
 Chris Zombolas
 Technical Director



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

SAR TEST REPORT
Portable T SERIES LIFEBOOK CONVERTIBLE Computer
Model: T936
Report Number: M150814_FCC_8260NGW_SAR_5.6

Table 1

Table of Revisions				
Report Number	Revision Number	Description	Pages affected	Date
M150814_FCC_8260NGW_SAR_5.6	1	Original	N/A	15th September 2015

2.0 INTRODUCTION

Testing was performed on the Fujitsu T SERIES LIFEBOOK CONVERTIBLE PC, Model: T936 with M.2 integrated Wireless LAN & Bluetooth Module (INTEL SNOWFIELD PEAK 802.11a/b/g/n/ac), Model: 8260NGW. The 8260NGW WLAN module was originally certified by INTEL Corporation as a modular approval under FCC ID: PD98260NG. The Fujitsu T SERIES LIFEBOOK CONVERTIBLE PC can be equipped with WWAN transmitter in addition to WLAN/Bluetooth module. Report No. FA491525-02_ issued by Sporton international inc. includes WWAN module SAR measurement; report M150814_FCC_8260NGW_SAR_2.4 issued by EMC includes 2.4 GHz WLAN SAR measurement.

The INTEL SNOWFIELD PEAK module is an OEM product was tested in the dedicated host – LIFEBOOK T SERIES, Model T936. The system tested will be referred to as the DUT throughout this report.

The Wireless LAN Module incorporates Bluetooth Transmitter, which can only transmit via Antenna B (2), the Bluetooth maximum power was 7dBm (including tune-up) therefore it did not require SAR testing as a stand-alone transmitter. This is in accordance with KDB 447498 section 4.3.1 exemption formula:

The shortest distance between the BT antenna (Antenna 2) and the user is 5.37mm. The closest distance between WLAN 1 and WLAN2 antennas was 268 mm

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR Result} - [(5.01)/(5.37\text{mm})] \cdot [\sqrt{f(2.45\text{GHz})}] = 1.46$$

The measurement test results mentioned hereon only apply to the 5GHz frequency band; an additional report titled "M150814_FCC_8260NGW_SAR_2.4" applies to the 2450MHz frequency range.

Table 2

Applicable Head Configurations	: None
Applicable Body Configurations	: Lap Held Position
	: Edge On Position
	: Bystander Position



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

3.0 TEST SAMPLE TECHNICAL INFORMATION

(Information supplied by the client)

3.1 DUT (WLAN) Details

Table 3

Transmitter:	M.2 Wireless LAN Module (WLAN parts)
Wireless Module:	WLAN 2x2 IEEE802.11ac/abgn
Model Number:	8260NGW
Manufacturer:	Intel Corporation
Wi-Fi standard	802.11ac 2x2
Wi-Fi TX/RX chains	2x2 chains
Supported Bands	2.4GHz, 5GHz
Antenna Allocation	Main: Wi-Fi only, Aux: Shared Wi-Fi, BT
Wi-Fi TX/RX Throughput	660 Mbps
Bluetooth Core	BT4.1(BDR/EDR/AFH/BLE)
Antenna Types:	Nissei Inverted F antenna Model: refer to WLAN antenna data Location: refer to Antenna location file For BT: use Aux(2: left side connect on module)
Power Supply:	3.3 VDC from PCI bus



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Table 4 Channels and Output power setting**2.4 GHz (802.11b, 802.11g and 802.11n/ac)**

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)		
					Ch A		Ch B	Power Control Tx A	Power Control Tx B	Tx A	Tx B
802.11 b 2.4 GHz	1	2412	CCK 1	20MHz 99%D C	15.0		15.0	15.375	15.500	15.01	15.05
	6	2437						15.375	15.375	15.07	15.01
	7	2442						15.250	15.625	15.01	15.05
	11	2462									
	12	2467			12.0	10.0	15.250	15.125	15.01	15.07	
	13	2472					12.375	10.125	12.01	10.02	
802.11 g 2.4 GHz	1	2412	OFDM 6	20MHz 99%D C	15.0		15.0	-	-	-	-
	2	2417						-	-	-	-
	6	2437						-	-	-	-
	10	2457						-	-	-	-
	11	2462						-	-	-	-
	12	2467			13.5	13.5	-	-	-	-	
	13	2472			2.0	1.0	-	-	-	-	
802.11 n 2.4 GHz	3F	2422	CCK HT0	40 98%D C	15.0		15.0	15.250	15.375	15.04	15.04
	4F	2427									
	5F	2432									
	6F	2437						15.250	15.375	15.06	15.09
	7F	2442						15.250	15.250	15.08	15.02
	8F	2447									
	9F	2452									
	10F	2457			12.0	10.0	15.250	15.375	15.09	15.01	
	11F	2462									
	3F	2422	OFDM HT0	40 98%D C	14.0		15.0	-	-	-	-
	4F	2427			15.0		15.0	-	-	-	-
	5F	2432						-	-	-	-
	6F	2437						-	-	-	-
	7F	2442						-	-	-	-
8F	2447	-						-	-	-	
9F	2452	-						-	-	-	
10F	2457	12.5			12.5	-	-	-	-		
11F	2462	1.0			0.0	-	-	-	-		

5 GHz (802.11a)

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)		
					Ch A	Ch B	Power Control Tx A	Power Control Tx B	Tx A	Tx B	
802.11a	5.2 GHz		OFDM 6	20 99%DC	13.5	13.5					
	36	5180					-	-	-	-	
	40	5200					-	-	-	-	
	44	5220					-	-	-	-	
	48	5240					-	-	-	-	
	5.3 GHz				13.5	13.5					
	52	5260					-	-	-	-	
	56	5280					-	-	-	-	
	60	5300					-	-	-	-	
	64	5320					-	-	-	-	
	5.6 GHz				13.5	13.5					
	100	5500					-	-	-	-	
	104	5520					-	-	-	-	
	108	5540					-	-	-	-	
	112	5560					-	-	-	-	
	116	5580					-	-	-	-	
	120	5600					-	-	-	-	
	124	5620					-	-	-	-	
	128	5640					-	-	-	-	
	5.65 to 5.835 GHz	132					5660	-	-	-	-
		136					5680	-	-	-	-
		140					5700	-	-	-	-
		5.8 GHz					13.5	13.5			
		149			5745	-			-	-	-
	153	5765			-	-			-	-	
	157	5785			-	-			-	-	
	161	5805			-	-			-	-	
	165	5825			-	-	-	-			



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

5 GHz (802.11n)

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)		
					Ch A	Ch B	Power Control Tx A	Power Control Tx B	Tx A	Tx B	
802.11n	5.2 GHz		OFDM HT0	20 99%DC							
	36	5180			13.5	13.5	-	-	-	-	
	40	5200					-	-	-	-	
	44	5220					-	-	-	-	
	48	5240					-	-	-	-	
	5.3 GHz										
	52	5260			13.5	13.5	-	-	-	-	
	56	5280					-	-	-	-	
	60	5300					13.250	-	13.50	-	
	64	5320					13.125	-	13.57	-	
	5.6 GHz										
	100	5500			13.5	13.5	13.750	13.375	13.53	13.54	
	104	5520					-	-	-	-	
	108	5540					-	-	-	-	
	112	5560					-	-	-	-	
	116	5580					-	-	-	-	
	120	5600					13.875	13.375	13.50	13.53	
	124	5620					-	-	-	-	
	128	5640					-	-	-	-	
	5.65 to 5.835 GHz	132					5660	-	-	-	-
		136			5680	-	-	-	-		
		140			5700	-	-	-	-		
		5.8 GHz									
		149			5745	13.5	13.5	-	-	-	-
		153			5765			-	-	-	-
		157			5785			-	-	-	-
	161	5805			-			-	-	-	
	165	5825			-			-	-	-	
	5.2 GHz										
	38	5190		13.5	13.5	-	-	-	-		
	46	5230				-	-	-	-		
	5.3 GHz										
	54	5270		13.5	13.5	13.750	13.625	13.56	13.57		
	62	5310		13.0	13.5	13.5	13.500		13.58		
	5.6 GHz										
	102	5510		13.5	13.5	13.5	13.625	13.375	13.50	13.59	
	110	5550		13.5			13.375	13.500	13.57	13.60	
	118	5590		-			-	-	-		
	126	5630		-			-	-	-		
	5.65 to 5.835 GHz	134		5670			-	-	-	-	
		142		5710	-	-	-	-			
		5.8 GHz									
	151	5755		13.5	13.5	-	-	-	-		
	159	5795				-	-	-	-		



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

5 GHz (802.11ac)

Mode	Channel	Frequency (MHz)	Data Rate (Mbps)	Tx BW (MHz)	Average Power Target (dBm)		Power Control		Average Power Measured (dBm)			
					Ch A	Ch B	Power Control Tx A	Power Control Tx B	Tx A	Tx B		
802.11 ac	5.2 GHz		HT0									
	42	5210				13.5	13.625	13.875	13.53	13.58		
	5.3 GHz											
	58	5290		12.0		10.0	-	-	-	-		
	5.6 GHz											
	106	5530		13.0		13.5	-	13.625	13.05	13.52		
	122	5610		13.5		13.5	13.875	13.500	13.52	13.56		
	5.65 to 5.835 GHz	138		5690	13.5		13.5	13.500	13.500	13.50	13.61	
		5.8 GHz										
		155		5775	13.5		13.5	13.875	13.625	13.57	13.59	

NOTE: For 2450 MHz SAR results refer to report titled "M150814_FCC_8260NGW_SAR_2.4".

3.2 DUT (Bluetooth) Details

Table 5

Transmitter:	WLAN / BT Combo Module
Network Standard:	Bluetooth™ RF Test Specification
Modulation Type:	Frequency Hopping Spread Spectrum (FHSS)
Frequency Range:	2402 MHz to 2480 MHz
Number of Channels:	79
Carrier Spacing:	1.0 MHz
Antenna Types:	Nissei Inverted F antenna BT: Antenna B (2)
Max. Output Power:	7 dBm
Reference Oscillator:	16 MHz (Built-in)
Power Supply:	3.3 VDC from host.

Table 6

Channel Number	Frequency (MHz)	Bluetooth Utility power setting
1	2402	7 dBm
2	2403	
-	-	
39	2440	
40	2441	
41	2442	
-	-	
78	2479	
79	2480	



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

3.3 DUT (T series LifeBook Convertible PC) Details

Table 7

Host Notebook :	LifeBook T series
Model Name:	T936
Serial Number:	Pre-production Sample
Manufacturer:	FUJITSU LIMITED
CPU Type and Speed:	Core i7 2.6GHz
LCD	13.3"QHD: LQ133T1JW17, FHD: LQ133M1JW01
Graphics chip	Non
Wired LAN:	Intel I219LM : 10 Base-T/100 Base-TX/1000Base-T
Modem:	Non
Port Replicator Model:	FPCPR245xx
AC Adapter Model:	90W: A13-090P1A(Chicony), A13-090P2A(Chicony) ADP-90BE D(Delta), ADP-90BE C(Delta) 80W: ADP-80SB A(Delta), ADP-80SB B(Delta) 65W: ADP-65MD B(Delta), ADP-65MD C(Delta) A13-065N2A(Chicony), A13-065N3A(Chicony)
Voltage:	19 V
Current Specs:	4.74A / 4.22A / 3.42A
Watts:	90W / 80W / 65W
Battery type	Li-Polymer
Brand	FUJITSU
Manufacturer	Sony
Rating	3150mAh, 14.4Vdc, 45Wh

3.4 Test sample Accessories

3.4.1 Battery Types

One type of Fujitsu Lithium Ion battery is used to power the DUT.

Table 8 Battery Details

Model	FPCBP425
V/mAh	14.4V/3150mAh



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

4.0 TEST SIGNAL, FREQUENCY AND OUTPUT POWER

INTEL's DRTU test tool was used to configure the WLAN for testing. The DUT Wireless LAN operates in 2 modes, OFDM and DSSS. For the SAR measurements the device was operating in continuous transmit mode using programming codes supplied by Fujitsu.

The test results mentioned in this report only apply to the 5.6 GHz frequency range. An additional report titled 'M150814_FCC_8260NGW_SAR_2.4' is specific to the 2450MHz range.

The DUT is capable of using two antennas transmitting simultaneously however in this mode; the power level is 3dB lower (50%) than if a single antenna was transmitting, There were no wires or other connections to the DUT during the SAR measurements.

At the beginning of the SAR tests, the conducted power of the device was measured after temporary modification of antenna connector inside the device's TX RX compartment. Measurements were performed with a calibrated Power Meter, and the result of the measurements includes the tune up tolerance of 1 dB. The Transmitter power was set to be equal or higher than power specified by the manufacturer including tune-up.

Table 9 Frequency and Conducted Power Results Bluetooth

Channel	Channel Frequency MHz	Data Rate (Mbps)	Maximum Conducted Output Power Measured (dBm)
Channel 40	2441	N/A	6.4

4.1 Battery Status

The DUT battery was fully charged prior to commencement of measurement. The battery condition was monitored by measuring the RF field at a defined position inside the phantom before the commencement of each test and again after the completion of the test. It was not possible to perform conducted power measurements at the output of the DUT, at the beginning and end of each scan due to lack of a suitable antenna port. The uncertainty associated with the power drift was less than 5% and was assessed in the uncertainty budget.



5.0 DETAILS OF TEST LABORATORY

5.1 Location

EMC Technologies Pty Ltd
176 Harrick Road
Keilor Park, (Melbourne) Victoria
Australia 3042

Telephone: +61 3 9365 1000
Facsimile: +61 3 9331 7455
email: melb@emctech.com.au
website: www.emctech.com.au

5.2 Accreditations

EMC Technologies Pty. Ltd. is accredited by the National Association of Testing Authorities, Australia (NATA).
NATA Accredited Laboratory Number: 5292

EMC Technologies Pty Ltd is NATA accredited for the following standards:

AS/NZS 2772.2 2011:	RF and microwave radiation hazard measurement
ACMA:	Radio communications (Electromagnetic Radiation - Human Exposure) Standard 2014
EN 50360: 2001	Product standard to demonstrate the compliance of Mobile Phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz – 3 GHz)
EN 62209-1:2006	Human exposure to radio frequency fields from hand-held and body-mounted devices-Human models, instrumentation and procedures. Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range 300 MHz to 3 GHz)
EN 62209-2:2010	Human Exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models instrumentation and procedures Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)
IEEE 1528: 2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.

Refer to NATA website www.nata.asn.au for the full scope of accreditation.

5.3 Environmental Factors

The measurements were performed in a shielded room with no background RF signals. The temperature in the laboratory was controlled to within $21 \pm 1^\circ\text{C}$, the humidity was in the range 37% to 49%. The liquid parameters are measured daily prior to the commencement of each test. Tests were performed to check that reflections within the environment did not influence the SAR measurements. DASY5 SAR measurement system using either the EX3DV4 or ET3DV6 E-field probe is less than $5\mu\text{V}$ in both air and liquid mediums.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

6.0 CALIBRATION AND VERIFICATION PROCEDURES AND DATA

6.1 System verification

6.1.1 System verification Results @ 5GHz

The following table lists the results of the System Verification. The forward power into the reference dipole for SAR System Verification was adjusted to 100 mW.

The SPEAG calibration reference SAR value is the SAR system verification result obtained in a specific dielectric liquid using the validation dipole (D5GHzV2) during calibration. The measured one-gram SAR should be within 10% of the expected target reference values shown in below.

Table 10 Deviation from reference system verification values in 5.6 GHz band

Frequency and Date	Measured SAR 1g (mW/g)	Measured SAR 1g (Normalized to 1W)	SPEAG Calibration reference SAR Value 1g (mW/g)	Deviation From SPEAG Reference 1g (%)	Last Validation Date
5200MHz 25 th August 2015	7.65	76.50	75.1	1.86	22/05/2015
5200MHz 26 th August 2015	7.27	72.70	75.1	-3.20	22/05/2015
5200MHz 27 th August 2015	7.58	75.80	75.1	0.93	22/05/2015
5500MHz 31 st August 2015	8.63	86.30	81.3	6.15	25/05/2015
5800MHz 2nd September 2015	7.75	77.50	76.7	1.04	27/05/2015
5800MHz 3rd September 2015	8.05	80.50	76.7	4.95	27/05/2015

NOTE: All reference system verification values are referenced to 1W input power.

6.1.2 Liquid Temperature and Humidity

The humidity and dielectric/ambient temperatures were recorded during the assessment of the tissue material dielectric parameters. The difference between the ambient temperature of the liquid during the dielectric measurement and the temperature during tests was less than $|2|^\circ\text{C}$.

Table 11 Temperature and Humidity recorded for each day

Date	Ambient Temperature (°C)	Liquid Temperature (°C)	Humidity (%)
25th August 2015	21.3	21.0	40
26th August 2015	21.5	21.1	38
27th August 2015	20.7	20.5	49
31st August 2015	21.7	21.3	37
2nd September 2015	21.6	21.3	37
3rd September 2015	21.6	21.5	38



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

7.0 SAR MEASUREMENT PROCEDURE USING DASY5

The SAR evaluation was performed with the SPEAG DASY5 system. A summary of the procedure follows:

- a) A measurement of the SAR value at a fixed location is used as a reference value for assessing the power drop of the DUT. The SAR at this point is measured at the start of the test, and then again at the end of the test.
- b) The SAR distribution at the exposed flat section of the flat phantom is measured at a distance of 2.0 mm from the inner surface of the shell. The area covers the entire dimension of the DUT and the horizontal grid spacing is 10 mm x 10 mm. The actual Area Scan has dimensions of 60 mm x 90 mm surrounding the test device. Based on this data, the area of the maximum absorption is determined by Spline interpolation.
- c) Around this point, a volume of 24 mm x 24 mm x 22 mm is assessed by measuring 7 x 7 x 12 points. On the basis of this data set, the spatial peak SAR value is evaluated with the following procedure:
 - (i) The data at the surface are extrapolated, since the centre of the dipoles is 1.0 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 2.0 mm. The extrapolation is based on a least square algorithm. A polynomial of the fourth order is calculated through the points in z-axes. This polynomial is then used to evaluate the points between the surface and the probe tip.
 - (ii) The maximum interpolated value is searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g and 10 g) are computed using the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one-dimensional splines with the "Not a knot"- condition (in x, y and z-direction). The volume is integrated with the trapezoidal – algorithm. One thousand points (10 x 10 x 10) are interpolated to calculate the averages.
 - (iii) All neighbouring volumes are evaluated until no neighbouring volume with a higher average value is found.
 - (iv) The SAR value at the same location as in Step (a) is again measured to evaluate the actual power drift.



8.0 MEASUREMENT UNCERTAINTY

The uncertainty analysis is based on the template listed in the IEEE Std 1528-2013 for both device SAR tests and Validation uncertainty. The measurement uncertainty of a specific device is evaluated independently.

Table 12 Uncertainty Budget for DASY5 Version 52 – DUT SAR test 5GHz

Error Description	Uncert. Value	Prob. Dist.	Div.	C _i (1g)	C _i (10g)	1g u _i	10g u _i	v _i
Measurement System								
Probe Calibration	6.55	N	1.00	1	1	6.55	6.55	∞
Axial Isotropy	4.7	R	1.73	0.7	0.7	1.90	1.90	∞
Hemispherical Isotropy	9.6	R	1.73	0.7	0.7	3.88	3.88	∞
Boundary Effects	2	R	1.73	1	1	1.15	1.15	∞
Linearity	4.7	R	1.73	1	1	2.71	2.71	∞
System Detection Limits	1	R	1.73	1	1	0.58	0.58	∞
Modulation response	2.4	R	1.73	1	1	1.39	1.39	∞
Readout Electronics	0.3	N	1.00	1	1	0.30	0.30	∞
Response Time	0.8	R	1.73	1	1	0.46	0.46	∞
Integration Time	2.6	R	1.73	1	1	1.50	1.50	∞
RF Ambient Noise	3	R	1.73	1	1	1.73	1.73	∞
RF Ambient Reflections	3	R	1.73	1	1	1.73	1.73	∞
Probe Positioner	0.8	R	1.73	1	1	0.46	0.46	∞
Probe Positioning	6.7	R	1.73	1	1	3.87	3.87	∞
Post Processing	4	R	1.73	1	1	2.31	2.31	∞
Test Sample Related								
Power Scaling	0	R	1.73	1	1	0.00	0.00	∞
Test Sample Positioning	2.9	N	1.00	1	1	2.90	2.90	145
Device Holder Uncertainty	3.6	N	1.00	1	1	3.60	3.60	5
Output Power Variation – SAR Drift Measurement	4.71	R	1.73	1	1	2.72	2.72	∞
Phantom and Setup								
Phantom Uncertainty	7.6	R	1.73	1	1	4.39	4.39	∞
SAR Correction	1.9	R	1.73	1	0.84	1.10	0.92	∞
Liquid Conductivity – Measurement uncertainty	2.5	N	1.00	0.64	0.71	1.60	1.78	∞
Liquid Permittivity – Measurement uncertainty	2.5	N	1.00	0.6	0.26	1.50	0.65	∞
Temp.unc. - Conductivity	3.4	R	1.73	0.78	0.71	0.77	0.70	∞
Temp. unc. - Permittivity	0.4	R	1.73	0.23	0.26	0.04	0.05	∞
Combined standard Uncertainty (u _c)						12.50	12.43	
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k= 2			25.00	24.86	

Estimated total measurement uncertainty for the DASY5 measurement system was $\pm 12.5\%$. The extended uncertainty ($K = 2$) was assessed to be $\pm 25\%$ based on 95% confidence level. The uncertainty is not added to the measurement result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Table 13 Uncertainty Budget for DASY5 Version 52 – DUT SAR test 5GHz**IEC 62209-2 UNCERTAINTY FOR RSS-102**

Error Description	Uncert. Value	Prob. Dist.	Div.	C _i (1g)	C _i (10g)	1g u _i	10g u _i	v _i
Measurement System								
Probe Calibration	6.55	N	1	1	1	6.55	6.55	∞
Axial Isotropy	4.7	R	1.73	0.7	0.7	1.90	1.90	∞
Hemispherical Isotropy	9.6	R	1.73	0.7	0.7	3.88	3.88	∞
Linearity	4.7	R	1.73	1	1	2.71	2.71	∞
Modulation Response	2.4	R	1.73	1	1	1.39	1.39	∞
System Detection Limits	1	R	1.73	1	1	0.58	0.58	∞
Boundary Effects	2	R	1.73	1	1	1.15	1.15	∞
Readout Electronics	0.3	N	1.00	1	1	0.30	0.30	∞
Response Time	0.8	R	1.73	1	1	0.46	0.46	∞
Integration Time	2.6	R	1.73	1	1	1.50	1.50	∞
RF Ambient Noise	3	R	1.73	1	1	1.73	1.73	∞
RF Ambient Reflections	3	R	1.73	1	1	1.73	1.73	∞
Probe Positioner	0.8	R	1.73	1	1	0.46	0.46	∞
Probe Positioning	6.7	R	1.73	1	1	3.87	3.87	∞
Post Processing	4	R	1.73	1	1	2.31	2.31	∞
Test Sample Related								
Device Holder	3.6	N	1.00	1	1	3.60	3.60	5
Test Sample Positioning	2.9	N	1.00	1	1	2.90	2.90	145
Power Scaling	0	R	1.73	1	1	0.00	0.00	∞
Power Drift	4.72	R	1.73	1	1	2.73	2.73	∞
Phantom and Setup								
Phantom Uncertainty	7.6	R	1.73	1	1	4.39	4.39	∞
SAR Correction	1.9	R	1.73	1	0.84	1.10	0.92	∞
Liquid Conductivity – Measurement uncertainty	2.5	N	1.00	0.78	0.71	1.95	1.78	∞
Liquid Permittivity – Measurement uncertainty	2.5	N	1.00	0.26	0.26	0.65	0.65	∞
Temp.unc. - Conductivity	3.4	R	1.73	0.78	0.71	1.53	1.39	∞
Temp. unc. - Permittivity	0.4	R	1.73	0.23	0.26	0.05	0.06	∞
Combined standard Uncertainty (u _c)						12.55	12.49	748
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k= 2			25.09	24.98	

Estimated total measurement uncertainty for the DASY5 measurement system was $\pm 12.55\%$. The extended uncertainty ($K = 2$) was assessed to be $\pm 25.09\%$ based on 95% confidence level. The uncertainty is not added to the measurement result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Table 14 Uncertainty Budget for DASY5 Version 52 – System verification 5GHz

Error Description	Uncert. Value	Prob. Dist.	Div.	C _i (1g)	C _i (10g)	1g u _i	10g u _i	v _i
Measurement System								
Probe Calibration	6.55	N	1.00	1	1	6.55	6.55	∞
Axial Isotropy	4.7	R	1.73	1	1	2.71	2.71	∞
Hemispherical Isotropy	9.6	R	1.73	0	0	0.00	0.00	∞
Boundary Effects	1	R	1.73	1	1	0.58	0.58	∞
Linearity	4.7	R	1.73	1	1	2.71	2.71	∞
System Detection Limits	1	R	1.73	1	1	0.58	0.58	∞
Modulation response	0	R	1.73	1	1	0.00	0.00	∞
Readout Electronics	0.3	N	1.00	1	1	0.30	0.30	∞
Response Time	0	R	1.73	1	1	0.00	0.00	∞
Integration Time	0	R	1.73	1	1	0.00	0.00	∞
RF Ambient Noise	1	R	1.73	1	1	0.58	0.58	∞
RF Ambient Reflections	1	R	1.73	1	1	0.58	0.58	∞
Probe Positioner	0.8	R	1.73	1	1	0.46	0.46	∞
Probe Positioning	6.7	R	1.73	1	1	3.87	3.87	∞
Post Processing	2	R	1.73	1	1	1.15	1.15	∞
Dipole Related								
Deviation of exp. dipole	5.5	R	1.73	1	1	3.18	3.18	∞
Dipole Axis to Liquid Dist.	2	R	1.73	1	1	1.15	1.15	∞
Input power & SAR drift	3.40	R	1.73	1	1	1.96	1.96	∞
Phantom and Setup								
Phantom Uncertainty	4	R	1.73	1	1	2.31	2.31	∞
Liquid Conductivity – Deviation from target values	5	R	1.73	0.64	0.43	1.85	1.24	∞
Liquid Permittivity – Deviation from target values	5	R	1.73	0.6	0.49	1.73	1.41	∞
Liquid Conductivity – Measurement uncertainty	2.5	N	1.00	0.78	0.71	1.95	1.78	∞
Liquid Permittivity – Measurement uncertainty	2.5	N	1.00	0.26	0.26	0.65	0.65	∞
Temp.unc. - Conductivity	3.4	R	1.73	0.78	0.71	0.77	0.70	∞
Temp. unc. - Permittivity	0.4	R	1.73	0.23	0.26	0.04	0.05	∞
Combined standard Uncertainty (u _c)						10.36	10.19	
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k= 2			20.73	20.37	

Estimated total measurement uncertainty for the DASY5 measurement system was $\pm 10.36\%$. The extended uncertainty ($K = 2$) was assessed to be $\pm 20.73\%$ based on 95% confidence level. The uncertainty is not added to the measurement result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

9.0 EQUIPMENT LIST AND CALIBRATION DETAILS

Table 15 SPEAG DASY5 Version 52

Equipment Type	Manufacturer	Model Number	Serial Number	Calibration Due	Used For this Test?
Robot - Six Axes	Staubli	RX90BL	N/A	Not applicable	✓
Robot Remote Control	SPEAG	CS7MB	RX90B	Not applicable	✓
SAM Phantom	SPEAG	N/A	1260	Not applicable	
SAM Phantom	SPEAG	N/A	1060	Not applicable	
Flat Phantom	AndreT	10.1	P 10.1	Not Applicable	
Flat Phantom	AndreT	9.1	P 9.1	Not Applicable	
Flat Phantom	SPEAG	ELI 4.0	1101	Not Applicable	✓
Data Acquisition Electronics	SPEAG	DAE3 V1	359	06-June-2015	
Data Acquisition Electronics	SPEAG	DAE3 V1	442	03-Dec-2015	✓
Probe E-Field - Dummy	SPEAG	DP1	N/A	Not applicable	
Probe E-Field	SPEAG	ET3DV6	1380	11-Dec-2015	
Probe E-Field	SPEAG	ET3DV6	1377	10-June-2015	
Probe E-Field	SPEAG	ES3DV6	3029	Not Used	
Probe E-Field	SPEAG	EX3DV4	3956	13-June-2015	
Probe E-Field	SPEAG	EX3DV4	7358	11-Dec-2015	✓
Validation Source 150 MHz	SPEAG	CLA150	4003	3-Dec-2016	
Antenna Dipole 300 MHz	SPEAG	D300V3	1012	11-Dec-2015	
Antenna Dipole 450 MHz	SPEAG	D450V3	1074	11-Dec-2015	
Antenna Dipole 750 MHz	SPEAG	D750V2	1051	13-Dec-2016	
Antenna Dipole 900 MHz	SPEAG	D900V2	047	09-Dec-2017	
Antenna Dipole 1640 MHz	SPEAG	D1640V2	314	05-Dec-2017	
Antenna Dipole 1800 MHz	SPEAG	D1800V2	242	05-Dec-2017	
Antenna Dipole 1950 MHz	SPEAG	D1950V3	1113	6-Dec -2015	
Antenna Dipole 2300 MHz	SPEAG	D2300V2	1032	22-Aug-2016	
Antenna Dipole 2450 MHz	SPEAG	D2450V2	724	04-Dec-2015	
Antenna Dipole 2600 MHz	SPEAG	D2600V2	1044	13-Dec-2016	
Antenna Dipole 3500 MHz	SPEAG	D3500V2	1002	13-July-2013	
Antenna Dipole 5600 MHz	SPEAG	D5GHzV2	1008	16-Dec-2016	✓
RF Amplifier	EIN	603L	N/A	*In test	
RF Amplifier	Mini-Circuits	ZHL-42	N/A	*In test	
RF Amplifier	Mini-Circuits	ZVE-8G	N/A	*In test	✓
Synthesized signal generator	Hewlett Packard	86630A	3250A00328	*In test	
RF Power Meter	Hewlett Packard	437B	3125012786	*In test	✓
RF Power Sensor 0.01 - 18 GHz	Hewlett Packard	8481H	1545A01634	02-Sept-2015	✓
RF Power Meter	Rohde & Schwarz	NRP	101415	30-Sept-2015	
RF Power Sensor	Rohde & Schwarz	NRP - Z81	100174	30-Sept-2015	
RF Power Meter Dual	Hewlett Packard	435A	1733A05847	*In test	✓
RF Power Sensor	Hewlett Packard	8482A	2349A10114	*In test	✓
Network Analyser	Hewlett Packard	8714B	GB3510035	14-Oct-2015	
Network Analyser	Hewlett Packard	8753ES	JP39240130	10-Nov-2015	✓
Dual Directional Coupler	Hewlett Packard	778D	1144 04700	*In test	
Dual Directional Coupler	NARDA	3022	75453	*In test	✓

* Calibrated during the test for the relevant parameters.

10.0 TEST METHODOLOGY

T series LifeBook Convertibles should be evaluated in normal use positions, typical for lap-held bottom-face only. However the number of positions will depend on the number of configurations the laptop can be operated in. The “LIFEBOOK T SERIES” can be used in either a conventional laptop position (see Appendix A) or a Tablet configuration. The antenna location in the “LIFEBOOK T SERIES” is closest to the top of the screen when used in a conventional laptop configuration and due to the separation distances involved between the phantom and the laptop antenna, testing is not required in this position.

10.1 Position

10.1.1 “Lap Held” Position Definition (0mm spacing)

The DUT was tested in the 2.00 mm flat section of the ELI4 Flat phantom for the “Lap Held” position. The Transceiver was placed at the bottom of the phantom and suspended in such way that the back of the DUT was touching the phantom. This device orientation simulates the PC’s normal use – being held on the lap of the user. A spacing of 0mm ensures that the SAR results are conservative and represent a worst-case position.

10.1.2 “Edge On” Position (Portrait or Landscape)

The DUT was tested in the (2.00 mm) flat section of the ELI4 Flat phantom for the “Edge On” position. The Antenna edge of the Transceiver was placed underneath the flat section of the phantom and suspended until the edge touched the phantom. *Refer to Appendix A for photos of measurement positions.*

10.1.3 “Bystander” Position (25mm spacing)

The DUT was tested in the 2.00 mm flat section of the ELI4 Flat phantom for the “Bystander” position. The Transceiver was placed at the bottom of the phantom and suspended in such way that the back of it’s LCD screen was parallel to phantom and at 25mm distance. This orientation simulates use of the device in a way that allows occasional RF exposure of the nearby person (Bystander).

10.2 List of All Test Cases (Antenna In/Out, Test Frequencies, User Modes)

The DUT has fixed antennas. Depending on the measured SAR level up to three test channels with the test sample operating at maximum power were recorded. The following table represents the matrix used to determine what testing was required. All relevant provisions of KDB 447498 and KDB 616217 are applied for SAR measurements of the host system.

Table 16 Testing configurations

Phantom Configuration	*Device Mode	Antenna	Test Configurations		
			Channel (Remaining)	Channel (Highest)	Channel (Remaining)
Lap Held	OFDM 5GHz All Bands	A		X	
		B		X	
Bystander	OFDM 5GHz All Bands	A		X	
		B		X	
Edge On	OFDM 5GHz All Bands	A		X	
		B		X	

Legend

X	Testing Required in this configuration
	Testing required in this configuration only if SAR of middle channel is more than 3dB below the SAR limit or it is the worst case.

NOTE: Throughout this report, Antenna A and B refer to Tx1 and Tx2 in the host respectively.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

11.0 SAR MEASUREMENT RESULTS

The SAR values averaged over 1g tissue masses were determined for the sample DUT for all test configurations listed in section 10.2.

11.1 5GHz Band SAR Results

Table 17 SAR MEASUREMENT RESULTS Lower Band – OFDM Mode

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.8 $\pm 5\%$ 46.36 to 51.24)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Body Bystander ANT 1 WWAN Ant. IN (OFDM) 25-Aug-2015	1.	OFDM 5 GHz HTO (20 MHz)	60	5300	0.037	0.11	48.13	5.499	0.037
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.9 $\pm 5\%$ 46.46 to 51.35)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Body Bystander ANT 2 WWAN Ant. IN (OFDM) 25-Aug-2015	2.	OFDM 5 GHz HTO (40 MHz)	54	5270	0.019	0.13	48.23	5.457	0.020
Body Lap Held ANT 1 WWAN Ant. IN (OFDM) 26-Aug-2015	3.	OFDM 5 GHz HTO (80 MHz)	42	5210	0.040	-0.18	49.27	5.192	0.042
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.9 $\pm 5\%$ 46.46 to 51.35)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 1 WWAN Ant. IN (OFDM) 26-Aug-2015	4.	OFDM 5 GHz HTO (40 MHz)	54	5270	0.025	0.16	49.1	5.309	0.025
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.8 $\pm 5\%$ 46.36 to 51.24)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 1 WWAN Ant. IN (OFDM) 26-Aug-2015	5.	OFDM 5 GHz HTO (20 MHz)	60	5300	0.021	-0.03	48.99	5.37	0.021
Body Lap Held ANT 1 WWAN Ant. IN (OFDM) 26-Aug-2015	6.	OFDM 5 GHz HTO (20 MHz)	64	5320	0.025	-0.17	48.92	5.403	0.025
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.9 $\pm 5\%$ 46.46 to 51.35)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 2 WWAN Ant. IN (OFDM) 26-Aug-2015	7.	OFDM 5 GHz HTO (80 MHz)	42	5210	0.026	0.01	49.27	5.192	0.027
Body Lap Held ANT 2 WWAN Ant. IN (OFDM) 26-Aug-2015	8.	OFDM 5 GHz HTO (40 MHz)	54	5270	0.028	-0.17	49.1	5.309	0.028
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.8 $\pm 5\%$ 46.36 to 51.24)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 2 WWAN Ant. IN (OFDM) 26-Aug-2015	9.	OFDM 5 GHz HTO (40 MHz)	62	5310	0.031	0.02	48.96	5.385	0.032



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.9 $\pm 5\%$ 46.46 to 51.35)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 2 WWAN Ant. OUT (OFDM) 26-Aug-2015	10.	OFDM 5 GHz HTO (40 MHz)	54	5270	0.027	-0.19	49.1	5.309	0.027
Edge 1 ANT 1 WWAN Ant. IN (OFDM) 26-Aug-2015	11.	OFDM 5 GHz HTO (80 MHz)	42	5210	0.759	-0.14	49.27	5.192	0.799
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.9 $\pm 5\%$ 46.46 to 51.35)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 1 WWAN Ant. IN (OFDM) 26-Aug-2015	12.	OFDM 5 GHz HTO (40 MHz)	54	5270	0.766	-0.14	49.1	5.309	0.782
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.8 $\pm 5\%$ 46.36 to 51.24)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 1 WWAN Ant. IN (OFDM) 26-Aug-2015	13.	OFDM 5 GHz HTO (20 MHz)	60	5300	0.788	-0.13	48.99	5.37	0.796
Edge 1 ANT 1 WWAN Ant. IN (OFDM) 26-Aug-2015	14.	OFDM 5 GHz HTO (20 MHz)	64	5320	0.891	-0.14	48.92	5.403	0.900
Edge 1 ANT 1 WWAN Ant. IN Variability (OFDM) 26-Aug-2015	15.	OFDM 5 GHz HTO (20 MHz)	64	5320	0.907	0.00	48.92	5.403	0.916
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.9 $\pm 5\%$ 46.46 to 51.35)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 2 WWAN Ant. IN (OFDM) 27-Aug-2015	16.	OFDM 5 GHz HTO (80 MHz)	42	5210	0.636	-0.09	48.13	5.321	0.669
Edge 1 ANT 2 WWAN Ant. IN (OFDM) 27-Aug-2015	17.	OFDM 5 GHz HTO (40 MHz)	54	5270	0.876	-0.02	47.95	5.435	0.894
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.8 $\pm 5\%$ 46.36 to 51.24)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 2 WWAN Ant. IN (OFDM) 27-Aug-2015	18.	OFDM 5 GHz HTO (40 MHz)	62	5310	0.930	-0.04	47.82	5.506	0.949
Edge 1 ANT 2 WWAN Ant. IN Variability (OFDM) 27-Aug-2015	19.	OFDM 5 GHz HTO (40 MHz)	62	5310	1.040	-0.06	47.82	5.506	1.061
Edge 2 ANT 1 WWAN Ant. IN (OFDM) 27-Aug-2015	20.	OFDM 5 GHz HTO (20 MHz)	60	5300	0.154	0.03	47.85	5.486	0.156
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.9 $\pm 5\%$ 46.46 to 51.35)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Edge 4 ANT 2 WWAN Ant. IN (OFDM) 27-Aug-2015	21.	OFDM 5 GHz HTO (40 MHz)	54	5270	0.036	-0.01	47.95	5.435	0.037
Edge 4 ANT 2 WWAN Ant. OUT (OFDM) 27-Aug-2015	-	OFDM 5 GHz HTO (80 MHz)	42	5210	Noise floor	-	48.13	5.321	Noise floor
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.9 $\pm 5\%$ 46.46 to 51.35)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Edge 4 ANT 2 WWAN Ant. OUT (OFDM) 27-Aug-2015	22.	OFDM 5 GHz HTO (40 MHz)	54	5270	0.042	-0.17	47.95	5.435	0.043



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.8 $\pm 5\%$ 46.36 to 51.24)	σ (target 5.4 $\pm 5\%$ 5.13 to 5.67)	Tune Up and DC SAR (mW/g)
Edge 4 ANT 2 WWAN Ant. OUT (OFDM) 27-Aug-2015	23.	OFDM 5 GHz HT0 (40 MHz)	62	5310	0.049	-0.17	47.82	5.506	0.050
Test Position	Plot	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 49.0 $\pm 5\%$ 46.55 to 51.45)	σ (target 5.3 $\pm 5\%$ 5.04 to 5.57)	Tune Up and DC SAR (mW/g)
System Performance Check with D5GHzV2 Dipole 25-Aug-2015	24.	CW	0	5200	7.650	0.03	48.43	5.34	-
System Performance Check with D5GHzV2 Dipole 26-Aug-2015	25.	CW	0	5200	7.270	0.02	49.29	5.179	-
System Performance Check with D5GHzV2 Dipole 27-Aug-2015	26.	CW	0	5200	7.580	0.01	48.16	5.313	-

NOTE: The measurement uncertainty of 25.09% for 5GHz testing is not added to the result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Table 18 SAR MEASUREMENT RESULTS Middle Band – OFDM Mode

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.6 $\pm 5\%$ 46.17 to 51.03)	σ (target 5.6 $\pm 5\%$ 5.32 to 5.88)	Tune Up and DC SAR (mW/g)
Body Bystander ANT 1 WWAN Ant. IN (OFDM) 28-Aug-15	27.	OFDM 5 GHz HT0 (40 MHz)	110	5550	0.029	-0.06	47.31	5.800	0.030
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.5 $\pm 5\%$ 46.08 to 50.93)	σ (target 5.77 $\pm 5\%$ 5.48 to 6.06)	Tune Up and DC SAR (mW/g)
Body Bystander ANT 2 WWAN Ant. IN (OFDM) 28-Aug-2015	28.	OFDM 5 GHz HT0 (80 MHz)	122	5610	0.056	0.15	47.13	5.902	0.059
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.6 $\pm 5\%$ 46.17 to 51.03)	σ (target 5.6 $\pm 5\%$ 5.32 to 5.88)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 1 WWAN Ant. IN (OFDM) 28-Aug-2015	29.	OFDM 5 GHz HT0 (40 MHz)	102	5510	0.022	-0.12	47.44	5.736	0.022
Body Lap Held ANT 1 WWAN Ant. IN (OFDM) 28-Aug-2015	30.	OFDM 5 GHz HT0 (40 MHz)	110	5550	0.026	0.14	47.31	5.800	0.026
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.5 $\pm 5\%$ 46.08 to 50.93)	σ (target 5.77 $\pm 5\%$ 5.48 to 6.06)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 1 WWAN Ant. IN (OFDM) 28-Aug-2015	31.	OFDM 5 GHz HT0 (80 MHz)	122	5610	0.025	0.12	47.13	5.902	0.027
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.6 $\pm 5\%$ 46.17 to 51.03)	σ (target 5.6 $\pm 5\%$ 5.32 to 5.88)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 2 WWAN Ant. IN (OFDM) 28-Aug-2015	32.	OFDM 5 GHz HT0 (80 MHz)	106	5530	0.052	0.07	47.36	5.765	0.055
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.5 $\pm 5\%$ 46.08 to 50.93)	σ (target 5.77 $\pm 5\%$ 5.48 to 6.06)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 2 WWAN Ant. IN (OFDM) 28-Aug-2015	33.	OFDM 5 GHz HT0 (80 MHz)	122	5610	0.049	-0.05	47.13	5.902	0.051
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.6 $\pm 5\%$ 46.17 to 51.03)	σ (target 5.6 $\pm 5\%$ 5.32 to 5.88)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 2 WWAN Ant. OUT (OFDM) 28-Aug-2015	34.	OFDM 5 GHz HT0 (80 MHz)	106	5530	0.041	0.07	47.36	5.765	0.043
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.5 $\pm 5\%$ 46.08 to 50.93)	σ (target 5.77 $\pm 5\%$ 5.48 to 6.06)	Tune Up and DC SAR (mW/g)



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Body Lap Held ANT 2 WWAN Ant. OUT (OFDM) 28-Aug-2015	35.	OFDM 5 GHz HTO (80 MHz)	122	5610	0.045	-0.07	47.13	5.902	0.048
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.6 $\pm 5\%$ 46.17 to 51.03)	σ (target 5.6 $\pm 5\%$ 5.32 to 5.88)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 1 WWAN Ant. IN (OFDM) 28-Aug-2015	36.	OFDM 5 GHz HTO (40 MHz)	102	5510	0.973	-0.05	47.44	5.736	0.993
Edge 1 ANT 1 WWAN Ant. IN (OFDM) 31-Aug-2015	37.	OFDM 5 GHz HTO (40 MHz)	110	5550	1.030	0.20	47.32	5.726	1.051
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.5 $\pm 5\%$ 46.08 to 50.93)	σ (target 5.77 $\pm 5\%$ 5.48 to 6.06)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 1 WWAN Ant. IN (OFDM) 31-Aug-2015	38.	OFDM 5 GHz HTO (80 MHz)	122	5610	1.180	-0.18	47.07	5.825	1.242
Edge 1 ANT 1 WWAN Ant. IN Variability (OFDM) 31- Aug-2015	39.	OFDM 5 GHz HTO (80 MHz)	122	5610	1.180	-0.13	47.07	5.825	1.242
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.6 $\pm 5\%$ 46.17 to 51.03)	σ (target 5.6 $\pm 5\%$ 5.32 to 5.88)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 2 WWAN Ant. IN (OFDM) 31-Aug-2015	40.	OFDM 5 GHz HTO (80 MHz)	106	5530	1.090	-0.03	47.35	5.699	1.147
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.5 $\pm 5\%$ 46.08 to 50.93)	σ (target 5.77 $\pm 5\%$ 5.48 to 6.06)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 2 WWAN Ant. IN (OFDM) 31-Aug-2015	41.	OFDM 5 GHz HTO (80 MHz)	122	5610	1.000	-0.03	47.07	5.825	1.053
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.6 $\pm 5\%$ 46.17 to 51.03)	σ (target 5.6 $\pm 5\%$ 5.32 to 5.88)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 2 WWAN Ant. IN Variability (OFDM) 31- Aug-2015	42.	OFDM 5 GHz HTO (80 MHz)	106	5530	1.070	0.00	47.35	5.699	1.126
Edge 2 ANT 1 WWAN Ant. IN (OFDM) 31-Aug-2015	43.	OFDM 5 GHz HTO (40 MHz)	110	5550	0.109	0.12	47.32	5.726	0.111
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.5 $\pm 5\%$ 46.08 to 50.93)	σ (target 5.77 $\pm 5\%$ 5.48 to 6.06)	Tune Up and DC SAR (mW/g)
Edge 4 ANT 2 WWAN Ant. IN (OFDM) 31-Aug-2015	44.	OFDM 5 GHz HTO (80 MHz)	122	5610	0.055	-0.09	47.07	5.825	0.058
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.6 $\pm 5\%$ 46.17 to 51.03)	σ (target 5.6 $\pm 5\%$ 5.32 to 5.88)	Tune Up and DC SAR (mW/g)
Edge 4 ANT 2 WWAN Ant. OUT (OFDM) 31-Aug-2015	45.	OFDM 5 GHz HTO (80 MHz)	106	5530	0.082	0.17	47.35	5.699	0.086
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.5 $\pm 5\%$ 46.08 to 50.93)	σ (target 5.77 $\pm 5\%$ 5.48 to 6.06)	Tune Up and DC SAR (mW/g)
Edge 4 ANT 2 WWAN Ant. OUT (OFDM) 31-Aug-2015	46.	OFDM 5 GHz HTO (80 MHz)	122	5610	0.097	-0.01	47.07	5.825	0.102



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Position	Plot	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.6 $\pm 5\%$ 46.17 to 51.03)	σ (target 5.6 $\pm 5\%$ 5.32 to 5.88)	Tune Up and DC SAR (mW/g)
System Performance Check with D5GHzV2 Dipole 28-Aug-2015	47.	System Check (0)	1	5600	8.61	0.07	47.15	5.884	-
System Performance Check with D5GHzV2 Dipole 31-Aug-2015	48.	System Check (0)	1	5600	8.63	0.05	47.11	5.811	-

NOTE: The measurement uncertainty of 25.09% for 5GHz testing is not added to the result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Table 19 SAR MEASUREMENT RESULTS Upper Band – OFDM Mode

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.2 $\pm 5\%$ 45.79 to 50.61)	σ (target 6.0 $\pm 5\%$ 5.7 to 6.3)	Tune Up and DC SAR (mW/g)
Body Bystander ANT 1 WWAN Ant. IN (OFDM) 03-Sept-2015	49.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.023	-0.09	46.03	6.194	0.024
Body Bystander ANT 2 WWAN Ant. IN (OFDM) 03-Sept-2015	50.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.027	-0.12	46.03	6.194	0.028
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.3 $\pm 5\%$ 45.89 to 50.72)	σ (target 5.9 $\pm 5\%$ 5.61 to 6.20)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 1 WWAN Ant. IN (OFDM) 02-Sept-2015	51.	OFDM 5 GHz HT0 (80 MHz)	138	5690	0.015	0.14	47.23	6.03	0.016
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.2 $\pm 5\%$ 45.79 to 50.61)	σ (target 6.0 $\pm 5\%$ 5.7 to 6.3)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 1 WWAN Ant. IN (OFDM) 02-Sept-2015	52.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.021	0.12	46.94	6.146	0.022
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.3 $\pm 5\%$ 45.89 to 50.72)	σ (target 5.9 $\pm 5\%$ 5.61 to 6.20)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 2 WWAN Ant. IN (OFDM) 02-Sept-2015	53.	OFDM 5 GHz HT0 (80 MHz)	138	5690	0.038	-0.12	47.23	6.03	0.040
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.2 $\pm 5\%$ 45.79 to 50.61)	σ (target 6.0 $\pm 5\%$ 5.7 to 6.3)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 2 WWAN Ant. IN (OFDM) 02-Sept-2015	54.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.034	0.14	46.94	6.146	0.036
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.3 $\pm 5\%$ 45.89 to 50.72)	σ (target 5.9 $\pm 5\%$ 5.61 to 6.20)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 2 WWAN Ant. OUT (OFDM) 02-Sept-2015	55.	OFDM 5 GHz HT0 (80 MHz)	138	5690	0.035	-0.16	47.23	6.03	0.037
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.2 $\pm 5\%$ 45.79 to 50.61)	σ (target 6.0 $\pm 5\%$ 5.7 to 6.3)	Tune Up and DC SAR (mW/g)
Body Lap Held ANT 2 WWAN Ant. OUT (OFDM) 02-Sept-2015	56.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.032	-0.06	46.94	6.146	0.034
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.3 $\pm 5\%$ 45.89 to 50.72)	σ (target 5.9 $\pm 5\%$ 5.61 to 6.20)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 1 WWAN Ant. IN (OFDM) 03-Sept-2015	57.	OFDM 5 GHz HT0 (80 MHz)	138	5690	0.941	0.09	46.25	6.067	0.991



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.2 $\pm 5\%$ 45.79 to 50.61)	σ (target 6.0 $\pm 5\%$ 5.7 to 6.3)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 1 WWAN Ant. IN (OFDM) 03-Sept-2015	58.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.822	-0.13	46.03	6.194	0.865
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.3 $\pm 5\%$ 45.89 to 50.72)	σ (target 5.9 $\pm 5\%$ 5.61 to 6.20)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 1 WWAN Ant. IN Variability (OFDM) 03-Sept-2015	59.	OFDM 5 GHz HT0 (80 MHz)	138	5690	0.902	-0.02	46.25	6.067	0.949
Edge 1 ANT 2 WWAN Ant. IN (OFDM) 03-Sept-2015	60.	OFDM 5 GHz HT0 (80 MHz)	138	5690	0.840	-0.20	46.25	6.067	0.884
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.2 $\pm 5\%$ 45.79 to 50.61)	σ (target 6.0 $\pm 5\%$ 5.7 to 6.3)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 2 WWAN Ant. IN (OFDM) 03-Sept-2015	61.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.662	-0.13	46.03	6.194	0.697
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.3 $\pm 5\%$ 45.89 to 50.72)	σ (target 5.9 $\pm 5\%$ 5.61 to 6.20)	Tune Up and DC SAR (mW/g)
Edge 1 ANT 2 WWAN Ant. IN Variability (OFDM) 03-Sept-2015	62.	OFDM 5 GHz HT0 (80 MHz)	138	5690	0.841	-0.18	46.25	6.067	0.885
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.2 $\pm 5\%$ 45.79 to 50.61)	σ (target 6.0 $\pm 5\%$ 5.7 to 6.3)	Tune Up and DC SAR (mW/g)
Edge 2 ANT 1 WWAN Ant. IN (OFDM) 03-Sept-2015	63.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.038	-0.21	46.03	6.194	0.040
Edge 4 ANT 2 WWAN Ant. IN (OFDM) 03-Sept-2015	64.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.027	0.06	46.03	6.194	0.029
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.3 $\pm 5\%$ 45.89 to 50.72)	σ (target 5.9 $\pm 5\%$ 5.61 to 6.20)	Tune Up and DC SAR (mW/g)
Edge 4 ANT 2 WWAN Ant. OUT (OFDM) 03-Sept-2015	65.	OFDM 5 GHz HT0 (80 MHz)	138	5690	0.029	-0.06	46.25	6.067	0.030
Test Position	Plot No.	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.2 $\pm 5\%$ 45.79 to 50.61)	σ (target 6.0 $\pm 5\%$ 5.7 to 6.3)	Tune Up and DC SAR (mW/g)
Edge 4 ANT 2 WWAN Ant. OUT (OFDM) 03-Sept-2015	66.	OFDM 5 GHz HT0 (80 MHz)	155	5775	0.021	-0.08	46.03	6.194	0.022
Test Position	Plot	Test Mode	Test Ch.	Test Freq. (MHz)	SAR (1g) mW/g	Drift (dB)	ϵ_r (target 48.2 $\pm 5\%$ 45.79 to 50.61)	σ (target 6.0 $\pm 5\%$ 5.7 to 6.3)	Tune Up and DC SAR (mW/g)
System Performance Check with D5GHzV2 Dipole 02-Sept-2015	67.	CW	2	5800	7.75	-0.05	46.84	6.181	-
System Performance Check with D5GHzV2 Dipole 03-Sept-2015	68.	CW	2	5800	8.05	-0.09	45.96	6.221	-

NOTE: The measurement uncertainty of 25.09% for 5GHz testing is not added to the result.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

12.0 COMPLIANCE STATEMENT

The Fujitsu T SERIES LIFEBOOK CONVERTIBLE PC, Model: T936 with Sierra EM7355 WWAN module and Intel 8260NGW WLAN/Bluetooth module was found to comply with the FCC and RSS-102 SAR requirements.

The highest Measured SAR level was 1.18 mW/g for a 1g cube. The manufacturer's duty cycle is 95%. Scaling the SAR value, the maximum Reported SAR value is 1.242 mW/g. This value was measured at 5610 MHz (channel 122) in the "Edge 1 ANT 1 WWAN Ant. IN" position in OFDM (HT0 80MHz bandwidth) modulation mode at the antenna 1. This was below the limit of 1.6 mW/g for uncontrolled exposure, even taking into account the measurement uncertainty of 25.09 %.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

13.0 MULTIBAND EVALUATION CONSIDERATIONS

Fujitsu **T SERIES LIFEBOOK CONVERTIBLE PC**, Model: **T936** can be equipped with WWAN transmitter in addition to WLAN/Bluetooth module. Report No. FA491525-02 issued by Sporton international inc. includes WWAN module SAR measurement; report M150814_FCC_8260NGW_SAR_2.4 issued by **EMC Technologies** includes 2.4 WLAN SAR measurement.

For the simultaneous transmission of Bluetooth according to the section 4.3.2 the estimated SAR is given by formula:

(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm) · $[\sqrt{f(2.45\text{GHz})/x}]$ W/kg

Result - $[(5.01)/(5.37\text{mm})] \cdot [\sqrt{f(\text{GHz})/7.5}] = 0.195\text{W/kg}$.

The highest SAR for the antenna A (1) was 1.242 mW/g so the sum of the simultaneously transmitting Bluetooth and WLAN (Ant. B) was 0.195 mW/g which was below the SAR limit of 1.6mW/g.

Position	Ant 1	Ant 2		WWAN antenna	Summed SAR	
	WLAN	WLAN	Bluetooth		Ant 1 +WWAN	Ant 2 +WWAN
Lap Held	0.075	0.148	0.195	1.402	1.477	1.597
Bystander	0.037	0.059	0.195	-	-	-
Edge 1	1.242	1.147	0.195	0.236	1.478	1.383
Edge 2	0.207	-	0.195	-	-	-
Edge 4	-	0.341	0.195	0.688	-	1.029

According to the FCC SAR evaluation procedures mentioned in KDB447498, when the sum of 1-g SAR of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit, SAR test exclusion applies to that simultaneous transmission configuration.

