



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Tait International Limited

Address: 245 Wooldridge Road, Harewood, P.O. Box 1645 Christchurch 8051
New Zealand

FCC ID: CASTPEH7G

Product Name: TP3350 Two Way Radio

Type Code/HVIN: TPEH7G

Test Model: T03-00313-HCAA, T03-00313-HAAA,
T03-00313-HBAA

Standard(s): FCC PART 22, 74 and 90
ANSI C63.26-2015
TIA-603-E-2016

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR21120026-00D

Date Of Issue: 2022-02-16

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)
No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 DESCRIPTION OF TEST CONFIGURATION.....	7
1.2.2 Support Equipment List and Details	7
1.2.3 Support Cable List and Details	7
1.2.4 Block Diagram of Test Setup.....	7
1.3 MEASUREMENT UNCERTAINTY	8
2. SUMMARY OF TEST RESULTS	9
3. REQUIREMENTS AND TEST PROCEDURES	10
3.1 RF OUTPUT POWER	10
3.1.1 Applicable Standard.....	10
3.1.2 Test Procedure	10
3.2 MODULATION CHARACTERISTIC:.....	10
3.2.1 Applicable Standard.....	10
3.2.2 Test Procedure	10
3.3 OCCUPIED BANDWIDTH & EMISSION MASK:	10
3.3.1 Applicable Standard.....	10
3.3.2 Test Procedure	10
3.4 SPURIOUS EMISSIONS AT ANTENNA TERMINALS:	11
3.4.1 Applicable Standard.....	11
3.4.2 Test Procedure	11
3.5 RADIATED SPURIOUS EMISSIONS:	11
3.5.1 Applicable Standard.....	11
3.5.2 Test Procedure	11
3.6 FREQUENCY STABILITY:.....	11
3.6.1 APPLICABLE STANDARD.....	11
3.6.2 Test Procedure	11
3.7 TRANSIENT FREQUENCY BEHAVIOR.....	12
3.7.1 Applicable Standard.....	12
3.7.2 TEST PROCEDURE	12
4. TEST DATA AND RESULTS	13
4.1 RF OUTPUT POWER	13
4.2 MODULATION CHARACTERISTIC:.....	20

4.3 OCCUPIED BANDWIDTH & EMISSION MASK:26

4.4 SPURIOUS EMISSIONS AT ANTENNA TERMINALS:38

4.5 RADIATED SPURIOUS EMISSIONS:43

4.6 FREQUENCY STABILITY:.....51

4.7 TRANSIENT FREQUENCY BEHAVIOR.....55

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	TP3350 Two Way Radio
EUT Model:	T03-00313-HCAA, T03-00313-HAAA, T03-00313-HBAA
Multiple Model:	T03-00313-HXXX ("XXX" please refer to the DoS)
Operation Frequency:	450-520 MHz
Modulation Type:	FM, 4FSK
Channel Spacing:	12.5 kHz /25 kHz
Rated Output Power: (Conducted)	High Power Level: 4W Low Power Level: 1W
Rated Input Voltage:	DC 7.4V from battery or DC 12V from Charger
Serial Number:	CR21120026-RF-S1(Model: T03-00313-HCAA) CR21120026-RF -S2(Model: T03-00313-HAAA) CR21120026-RF -S3(Model: T03-00313-HBAA)
EUT Received Date:	2021.12.25
EUT Received Status:	Good
Note: The Multiple models are electrically identical with model T03-00313-HCAA, please refer to the declaration letter for more detail, which was provided by manufacturer. Test was performed at model: T03-00313-HCAA, except radiated emissions test with all models.	

Antenna Information Detail ▲:

Antenna	Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
1	Tait International Limited	Helical	50	2.5 dBi/450-520MHz
2	Tait International Limited	Helical	50	3.5 dBi/450-520MHz

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter	Shenzhen Shi Ying Yuan Electronics Co., Ltd.	ICP30-120-2000	Input: 100-240V~50/60Hz 0.8A Output: 12V 2A
Charger	Tait International Limited	T03-00322-AAA	Not Applicable
Headset		T03-00047-BAAA	Not Applicable
Belt Clip		Not Applicable	Not Applicable

Test Frequency Detail:

Per C63.26-2015, section 5.1, the lowest frequency, middle frequency, and highest frequency was performed the test as below:

Modulation/ Channel Bandwidth	Test Channel	Frequency (MHz)	Rule Part
FM 12.5kHz	Lowest	450.0125	For Part 90
	Middle	480.0125	For Part 90
	Highest	519.9875	For Federal
	Additional	454.0125	For Part 22
	Additional	455.0125	For Part 74
4FSK 12.5kHz	Lowest	450.0125	For Part 90
	Middle	480.0125	For Part 90
	Highest	519.9875	For Federal
	Additional	454.0125	For Part 22
	Additional	455.0125	For Part 74
FM 25kHz	Additional	454.0125	For Part 22
	Additional	455.0125	For Part 74

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer.
Equipment Modifications:	No
EUT Exercise Software:	No


1.2.2 Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
WEINSCHEL Corp	Load	50oml	50oml Load

1.2.3 Support Cable List and Details

Cable Description	Shielding Cable	Ferrite Core	Length (m)	From Port	To
\	\	\	\	\	\

1.2.4 Block Diagram of Test Setup



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
RF Frequency	±0.082×10 ⁻⁶

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§2.1046; § 22.727; §74.461; §90.205	RF Output Power	Compliant
§2.1047	Modulation Characteristic	Compliant
§2.1049; §22.357; § 22.731; §74.462; §90.209; §90.210	Occupied Bandwidth & Emission Mask	Compliant
§2.1051; §22.861; §74.462; §90.210	Spurious Emission at Antenna Terminal	Compliant
§2.1053; §22.861; §74.462; §90.210	Spurious Radiated Emissions	Compliant
§2.1055; § 22.355; §74.464; §90.213	Frequency Stability	Compliant
§90.214	Transient Frequency Behavior	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 RF OUTPUT POWER

3.1.1 Applicable Standard

FCC §2.1046, § 22.727, §74.461 and §90.205

3.1.2 Test Procedure

Conducted RF Output Power:

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Spectrum Analyzer Setting:

R B/W	Video B/W
100 kHz	300 kHz

3.2 MODULATION CHARACTERISTIC:

3.2.1 Applicable Standard

FCC §2.1047

- (a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.
- (b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

3.2.2 Test Procedure

Test Method: TIA-603-E 2.2.3

3.3 OCCUPIED BANDWIDTH & EMISSION MASK:

3.3.1 Applicable Standard

FCC §2.1049, §22.357, § 22.731, §74.462, §90.209 and §90.210

3.3.2 Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 100 Hz or 300 Hz and the spectrum was recorded in the frequency band ± 50 kHz from the carrier frequency.

3.4 SPURIOUS EMISSIONS AT ANTENNA TERMINALS:

3.4.1 Applicable Standard

FCC §2.1051, §22.861, §74.462, and §90.210

3.4.2 Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.

3.5 RADIATED SPURIOUS EMISSIONS:

3.5.1 Applicable Standard

FCC §2.1053, §22.861, §74.462, and §90.210

3.5.2 Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to teeth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001)-the absolute level

3.6 FREQUENCY STABILITY:

3.6.1 Applicable Standard

FCC §2.1055, § 22.355, §74.464 and §90.213

3.6.2 Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a frequency counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.


3.7 TRANSIENT FREQUENCY BEHAVIOR

3.7.1 Applicable Standard

Regulations: FCC §90.214

3.7.2 Test Procedure

- a) Connect the EUT and test equipment as shown on the following block diagram.
- b) Set the Spectrum Analyzer to measure FM deviation, and tune the RF frequency to the transmitter assigned frequency.
- c) Set the signal generator to the assigned transmitter frequency and modulate it with a 1 kHz tone at ± 12.5 kHz deviation and set its output level to -100dBm.
- d) Turn on the transmitter.
- e) Supply sufficient attenuation via the RF attenuator to provide an input level to the Spectrum Analyzer that is 40 dB below the maximum allowed input power when the transmitter is operating at its rated power level. Note this power level on the Spectrum Analyzer as P_0 .
- f) Turn off the transmitter.
- g) Adjust the RF level of the signal generator to provide RF power equal to P_0 . This signal generator RF level shall be maintained throughout the rest of the measurement.
- h) Remove the attenuation 1, so the input power to the Spectrum Analyzer is increased by 30 dB when the transmitter is turned on.
- i) Adjust the vertical amplitude control of the spectrum analyzer to display the 1000 Hz at ± 4 divisions vertically centered on the display. Set trigger mode of the Spectrum Analyzer to “Video”, and tune the “trigger level” on suitable level. Then set the “trigger offset” to -10ms for turn on and -15ms for turn off.
- j) Turn on the transmitter and the transient wave will be captured on the screen of Spectrum Analyzer. Observe the stored display. The instant when the 1 kHz test signal is completely suppressed is considered to be t_{on} . The trace should be maintained within the allowed divisions during the period t_1 and t_2 .
- k) Then turn off the transmitter, and another transient wave will be captured on the screen of Spectrum Analyzer. The trace should be maintained within the allowed divisions during the period t_3 .



4. TEST DATA AND RESULTS

4.1 RF OUTPUT POWER

Serial Number:	CR21120026-RF-S1	Test Date:	2022/01/12~2022/02/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Morpheus Shi	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	20~21.2	Relative Humidity: (%)	52~56	ATM Pressure: (kPa)	101.4~101.6

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2021-07-22	2022-07-21
YINSAIGE	Coaxial Cable	SS402	SJ0100004	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100003	Each time	N/A
Weinschel	Power splitter	1515	RA915	Each time	N/A
HP	RF Communications Test Set	8920A	3438A05209	2021-07-22	2022-07-21

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*


Test Data:

Channel Separation	Test Modulation	Test Channel	Test Frequency (MHz)	Conducted Output Power (dBm)		Limit (dBm)	
				High Power Level	Low Power Level	High Power Level	Low Power Level
12.5kHz	FM	Low	450.0125	35.86	30.69	36.81	30.79
		Middle	480.0125	36.00	29.88	36.81	30.79
		High	519.9875	36.14	30.70	36.81	30.79
		Additional	455.0125	35.80	30.46	36.81	30.79
		Additional	454.0125	35.80	30.52	36.81	30.79
	4FSK	Low	450.0125	35.85	30.37	36.81	30.79
		Middle	480.0125	36.16	30.52	36.81	30.79
		High	519.9875	36.20	30.45	36.81	30.79
		Additional	455.0125	35.77	30.27	36.81	30.79
		Additional	454.0125	35.78	30.28	36.81	30.79
25kHz	FM	Additional	455.0125	35.74	30.48	36.81	30.79
		Additional	454.0125	35.79	30.53	36.81	30.79


Note:

The high rated power level is 4W(36dBm), and low rated power level is 1W(30dBm).


The output power shall not exceed by more than 20 percent the manufacturer's rated output power for the particular transmitter specifically listed on the authorization.

FM, 12.5kHz:**Low Channel, 450.0125 MHz High Power**


Date: 12.JAN.2022 10:39:10

Low Channel, 450.0125 MHz Low Power


Date: 12.JAN.2022 10:39:38

Middle Channel, 480.0125 MHz High Power


Date: 15.FEB.2022 10:11:30

Middle Channel, 480.0125 MHz Low Power


Date: 15.FEB.2022 10:11:51

High Channel, 519.9875 MHz High Power


Date: 12.JAN.2022 10:45:25

High Channel, 519.9875 MHz Low Power


Date: 12.JAN.2022 10:46:13

Additional, For Part 22, 454.0125 MHz High Power


Date: 12.JAN.2022 10:50:52

Additional, For Part 22, 454.0125 MHz Low Power


Date: 12.JAN.2022 10:51:14

Additional, For Part 74, 455.0125 MHz High Power


Date: 12.JAN.2022 10:47:22

Additional, For Part 74, 455.0125 MHz Low Power


Date: 12.JAN.2022 10:47:46

4FSK, 12.5kHz:**Low Channel, 450.0125 MHz High Power**


Date: 12.JAN.2022 11:41:55

Low Channel, 450.0125 MHz Low Power


Date: 12.JAN.2022 11:43:30

Middle Channel, 480.0125 MHz High Power


Date: 15.FEB.2022 10:12:20

Middle Channel, 480.0125 MHz Low Power


Date: 15.FEB.2022 10:12:36

High Channel, 519.9875 MHz High Power


Date: 12.JAN.2022 11:51:03

High Channel, 519.9875 MHz Low Power


Date: 12.JAN.2022 11:46:25

Additional, For Part 22, 454.0125 MHz High Power


Date: 12.JAN.2022 11:49:36

Additional, For Part 22, 454.0125 MHz Low Power


Date: 12.JAN.2022 11:47:38

Additional, For Part 74, 455.0125 MHz High Power


Date: 12.JAN.2022 11:50:22

Additional, For Part 74, 455.0125 MHz Low Power


Date: 12.JAN.2022 11:47:05

FM, 25kHz:**Additional Channel, Part 74, 455.0125 MHz High Power**


Date: 12.JAN.2022 10:48:51

Additional Channel, Part 74, 455.0125 MHz Low Power

Date: 12.JAN.2022 10:49:34

Additional Channel, Part 22, 454.0125 MHz High Power

Date: 12.JAN.2022 10:52:03

Additional Channel, Part 22, 454.0125 MHz Low Power

Date: 12.JAN.2022 10:52:22

4.2 MODULATION CHARACTERISTIC:

Serial Number:	CR21120026-RF-S1	Test Date:	2022/01/12~2022/02/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Morpheus Shi	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	20~21.2	Relative Humidity: (%)	52~56	ATM Pressure: (kPa)	101.4~101.6
----------------------	---------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
YINSAIGE	Coaxial Cable	SS402	SJ0100004	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A
HP	RF Communications Test Set	8920A	3438A05209	2021-07-22	2022-07-21

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*


Test Data:

Audio Frequency Response – High Power

Carrier Frequency: 480.0125 MHz	
Channel Spacing: 12.5kHz	
Modulation Frequency (Hz)	Response data (dB)
300	-12.89
400	-9.37
500	-6.94
600	-4.98
700	-3.35
800	-2.16
900	-1.01
1000	0.00
1200	1.54
1400	2.78
1600	3.77
1800	4.71
2000	5.61
2200	6.44
2400	7.38
2600	8.79
2800	9.59
3000	9.27




Carrier Frequency: 455.0125 MHz	
Channel Spacing: 25kHz	
Modulation Frequency (Hz)	Response data (dB)
300	-13.78
400	-9.85
500	-7.19
600	-5.20
700	-3.54
800	-2.20
900	-1.07
1000	0.00
1200	1.49
1400	2.72
1600	3.78
1800	4.74
2000	5.63
2200	6.47
2400	7.36
2600	8.51
2800	9.26
3000	8.88




Modulation Limiting – High Power



Channel Spacing: 12.5kHz		Carrier Frequency: 480.0125 MHz			
Audio Frequency (Hz)	Instantaneous		Steady-state		Limit [kHz]
	Deviation (@+20dB) [kHz]	Deviation (@-20dB) [kHz]	Deviation (@+20dB) [kHz]	Deviation (@-20dB) [kHz]	
300	1.556	0.129	1.535	0.114	2.5
400	1.732	0.133	1.724	0.126	2.5
500	1.744	0.143	1.736	0.153	2.5
600	1.768	0.162	1.752	0.167	2.5
700	1.792	0.182	1.782	0.178	2.5
800	1.729	0.206	1.711	0.197	2.5
900	1.786	0.203	1.764	0.208	2.5
1000	1.817	0.229	1.825	0.214	2.5
1200	1.678	0.247	1.633	0.236	2.5
1400	1.724	0.267	1.705	0.254	2.5
1600	1.764	0.296	1.754	0.278	2.5
1800	1.759	0.318	1.746	0.302	2.5
2000	1.764	0.338	1.775	0.335	2.5
2200	1.792	0.359	1.812	0.367	2.5
2400	1.862	0.404	1.884	0.389	2.5
2600	1.987	0.457	1.974	0.425	2.5
2800	2.119	0.505	2.136	0.494	2.5
3000	2.071	0.489	2.025	0.462	2.5



Channel Spacing: 25kHz		Carrier Frequency: 455.0125 MHz			
Audio Frequency (Hz)	Instantaneous		Steady-state		Limit [kHz]
	Deviation (@+20dB) [kHz]	Deviation (@-20dB) [kHz]	Deviation (@+20dB) [kHz]	Deviation (@-20dB) [kHz]	
300	3.235	0.114	3.224	0.111	5
400	3.556	0.152	3.547	0.146	5
500	3.501	0.174	3.517	0.182	5
600	3.546	0.212	3.578	0.225	5
700	3.563	0.238	3.574	0.246	5
800	3.529	0.265	3.545	0.275	5
900	3.637	0.304	3.621	0.314	5
1000	3.627	0.322	3.611	0.328	5
1200	3.358	0.395	3.384	0.402	5
1400	3.475	0.436	3.492	0.458	5
1600	3.554	0.491	3.581	0.502	5
1800	3.573	0.557	3.591	0.572	5
2000	3.526	0.616	3.503	0.634	5
2200	3.535	0.651	3.557	0.674	5
2400	3.660	0.734	3.681	0.746	5
2600	3.904	0.835	3.926	0.845	5
2800	4.212	0.916	4.227	0.936	5
3000	4.065	0.882	4.025	0.871	5



Audio Frequency Low Pass Filter Response – High Power



4.3 OCCUPIED BANDWIDTH & EMISSION MASK:

Serial Number:	CR21120026-RF-S1	Test Date:	2022/01/12~2022/02/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Morpheus Shi	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	20~21.2	Relative Humidity: (%)	52~56	ATM Pressure: (kPa)	101.4~101.6
----------------------	---------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2021-07-22	2022-07-21
YINSAIGE	Coaxial Cable	SS402	SJ0100004	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100003	Each time	N/A
Weinschel	Power splitter	1515	RA915	Each time	N/A
HP	RF Communications Test Set	8920A	3438A05209	2021-07-22	2022-07-21

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Mode	Test Channel	Test Frequency (MHz)	High Power Level		Low Power Level	
			99% Occupied Bandwidth (kHz)	26dB Emission Bandwidth (kHz)	99% Occupied Bandwidth (kHz)	26dB Emission Bandwidth (kHz)
FM 12.5kHz	Low	450.0125	5.300	10.240	5.300	10.288
	Middle	480.0125	5.286	10.347	5.286	10.347
	High	519.9875	7.853	10.401	9.776	10.401
	Additional	454.0125	5.288	10.321	5.288	10.321
	Additional	455.0125	5.208	10.401	5.208	10.321
4FSK 12.5kHz	Low	450.0125	6.170	7.917	6.010	7.917
	Middle	480.0125	6.286	8.930	6.571	8.505
	High	519.9875	6.490	9.279	6.571	9.119
	Additional	454.0125	6.490	9.439	6.010	8.397
	Additional	455.0125	6.250	8.397	6.410	8.558
FM 25kHz	Additional	454.0125	10.737	15.817	10.737	15.880
	Additional	455.0125	10.897	15.994	10.737	15.994

Note: Emission bandwidth was based on calculation method instead of measurement.

Emission Designator: Per CFR 47 §2.201& §2.202, BW = 2M + 2D

For FM Mode (Channel Spacing: 12.5 kHz)

Emission Designator: 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = 11K0$

F3E portion of the designator represents an FM voice transmission

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

For FM Mode (Channel Spacing: 25 kHz)

Emission Designator: 16K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 5.0 kHz deviation.

$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 5.0 \text{ kHz}) = 16 \text{ kHz} = 16K0$

F3E portion of the designator represents an FM voice transmission

Therefore, the entire designator for 25 kHz channel spacing FM mode is 16K0F3E.

For Digital Mode (Channel Spacing: 12.5 kHz)

Emission Designator: 7K60F1D and 7K60F1E


The 99% energy rule (title 47CFR 2.1049) was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.60 kHz. The emission mask was obtained from 47CFR 90.210(d).

F1D and F1E portion of the designator indicates digital information.


Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1E.

FM, 12.5kHz, High Power:

Low Channel




Date: 12.JAN.2022 14:26:56




Date: 12.JAN.2022 15:12:35

Middle Channel




Date: 15.FEB.2022 10:53:48




Date: 15.FEB.2022 11:08:17

High Channel




Date: 12.JAN.2022 15:22:58




Date: 12.JAN.2022 16:23:34

Additional Channel Part 74, 455.0125 MHz




Date: 12.JAN.2022 15:31:51




Date: 12.JAN.2022 16:26:54


Additional Channel Part 22, 454.0125 MHz




Date: 12.JAN.2022 15:44:04




Date: 12.JAN.2022 19:47:00

FM, 12.5kHz, Low Power:**Low Channel**


Date: 12.JAN.2022 14:39:00




Date: 12.JAN.2022 15:14:26

Middle Channel


Date: 15.FEB.2022 10:56:37



Date: 15.FEB.2022 11:09:43


High Channel

Date: 12.JAN.2022 15:24:42




Date: 12.JAN.2022 16:24:41

Additional Channel Part 74, 455.0125 MHz




Date: 12, JAN, 2022 15:33:58




Date: 12, JAN, 2022 16:28:05


Additional Channel Part 22, 454.0125 MHz




Date: 12, JAN, 2022 15:46:13




Date: 12, JAN, 2022 19:45:15

4FSK, 12.5kHz, High Power:**Low Channel**


Date: 12.JAN.2022 17:58:58




Date: 12.JAN.2022 19:23:16

Middle Channel


Date: 15.FEB.2022 11:25:45



Date: 15.FEB.2022 11:06:50


High Channel

Date: 12.JAN.2022 18:15:31




Date: 12.JAN.2022 19:34:54

Additional Channel Part 74, 455.0125 MHz




Date: 12, JAN, 2022 19:07:42




Date: 12, JAN, 2022 19:36:48

Additional Channel Part 22, 454.0125 MHz




Date: 12, JAN, 2022 19:11:10




Date: 12, JAN, 2022 19:42:29

4FSK, 12.5kHz, Low Power:

Low Channel




Date: 12.JAN.2022 18:01:28




Date: 12.JAN.2022 19:25:30

Middle Channel




Date: 15.FEB.2022 10:59:31




Date: 15.FEB.2022 11:05:27

High Channel




Date: 12.JAN.2022 18:18:20




Date: 12.JAN.2022 19:32:52

Additional Channel Part 74, 455.0125 MHz




Date: 12.JAN.2022 18:21:11




Date: 12.JAN.2022 19:38:19

Additional Channel Part 22, 454.0125 MHz




Date: 12.JAN.2022 19:13:51




Date: 12.JAN.2022 19:43:59

FM, 25 kHz, High Power:

Additional Channel Part 74, 455.0125 MHz




Date: 12, JAN, 2022 15:37:27




Date: 12, JAN, 2022 16:30:19

Additional Channel Part 22, 454.0125 MHz




Date: 12, JAN, 2022 15:51:25




Date: 12, JAN, 2022 19:48:36

FM, 25 kHz, Low Power:

Additional Channel Part 74, 455.0125 MHz




Date: 12.JAN.2022 15:38:47




Date: 12.JAN.2022 16:31:23

Additional Channel Part 22, 454.0125 MHz



Date: 12.JAN.2022 16:07:19



Date: 12.JAN.2022 19:49:25

4.4 SPURIOUS EMISSIONS AT ANTENNA TERMINALS:

Serial Number:	CR21120026-RF-S1	Test Date:	2022/01/12~2022/02/15
Test Site:	RF	Test Mode:	Transmitting (High power was tested)
Tester:	Morpheus Shi	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	20~21.2	Relative Humidity: (%)	52~56	ATM Pressure: (kPa)	101.4~101.6
----------------------	---------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2021-07-22	2022-07-21
YINSAIGE	Coaxial Cable	SS402	SJ0100004	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100003	Each time	N/A
Weinschel	Power splitter	1515	RA915	Each time	N/A
E-Microwave	Band Rejector Filter	OBF-ZP-400-520-NF	OE0120256	2021-01-23	2022-01-22
HP	RF Communications Test Set	8920A	3438A05209	2021-07-22	2022-07-21


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:


Note: Test performed at high power level with Band Rejector Filter, please refer to the following table.

FM, 12.5kHz:

Low Channel, 450.0125 MHz




Date: 12.JAN.2022 20:03:14




Date: 12.JAN.2022 20:42:31

Middle Channel, 480.0125 MHz




Date: 15.FEB.2022 13:12:02




Date: 15.FEB.2022 13:16:36

High Channel, 519.9875 MHz




Date: 12.JAN.2022 20:05:08




Date: 12.JAN.2022 20:40:19

4FSK, 12.5kHz:

Low Channel, 450.0125 MHz




Date: 12.JAN.2022 20:14:36




Date: 12.JAN.2022 20:32:23

Middle Channel, 480.0125 MHz




Date: 15.FEB.2022 13:17:43




Date: 15.FEB.2022 13:16:12

High Channel, 519.9875 MHz




Date: 12.JAN.2022 20:16:57




Date: 12.JAN.2022 20:30:01

Part 74:

FM,12.5kHz, 455.0125 MHz




Date: 12. JAN. 2022 20:06:07




Date: 12. JAN. 2022 20:40:56

FM,25kHz, 455.0125 MHz




Date: 12. JAN. 2022 20:12:14




Date: 12. JAN. 2022 20:37:35

4FSK,12.5kHz, 455.0125 MHz




Date: 12. JAN. 2022 20:17:52




Date: 12. JAN. 2022 20:22:22

Part 22:

FM,12.5kHz, 454.0125 MHz (All emission is under limit -13dBm)




Date: 12.JAN.2022 20:09:11




Date: 12.JAN.2022 20:34:38

FM,25kHz, 454.0125 MHz (All emission is under limit -13dBm)




Date: 12.JAN.2022 20:10:36




Date: 12.JAN.2022 20:33:46

4FSK,12.5kHz, 454.0125 MHz (All emission is under limit -13dBm)



Date: 12.JAN.2022 20:19:12



Date: 12.JAN.2022 20:21:15

4.5 RADIATED SPURIOUS EMISSIONS:

Serial Number:	CR21120026-RF-S1	Test Date:	2022/01/27
Test Site:	966-1/966-2	Test Mode:	Transmitting (High power was tested)
Tester:	Great Qiao, Tommy Luo	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	19.4~19.5	Relative Humidity: (%)	58~59	ATM Pressure: (kPa)	101.1
----------------------	-----------	---------------------------	-------	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020-10-19	2023-10-18
R&S	EMI Test Receiver	ESR3	102724	2021-07-22	2022-07-21
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2021-07-18	2022-07-17
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2021-07-18	2022-07-17
Sonoma	Amplifier	310N	186165	2021-07-18	2022-07-17
EMCO	Adjustable Dipole Antenna	3121C	9109-756	N/A	N/A
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2021-07-25	2022-07-24
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
R&S	Spectrum Analyzer	FSV40	101591	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2021-08-08	2022-08-07
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021-11-10	2022-11-09
AH	Double Ridge Guide Horn Antenna	SAS-571	1396	2021-10-18	2024-10-17
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2021-07-25	2022-07-24
Agilent	Signal Generator	E8247C	MY43321352	2021-04-25	2022-04-24

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Note:

Test only performed with High power level. The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis, the worst orientation was photographed and it's data was recorded.

All models T03-00313-HCAA, T03-00313-HBAA, T03-00313-HAAA were pre-scanned, T03-00313-HCAA showed the worst case test data as shown in the below.

30MHz - 5GHz:**Part 90**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
FM, Frequency: 450.0125MHz-12.5 kHz								
900.03	H	52.31	-46.99	0.00	0.63	-47.62	-20.00	27.62
900.03	V	55.85	-40.58	0.00	0.63	-41.21	-20.00	21.21
1350.04	H	38.92	-64.30	8.08	0.79	-57.01	-20.00	37.01
1350.04	V	40.50	-62.97	8.08	0.79	-55.68	-20.00	35.68
1800.05	H	39.13	-64.37	8.86	0.90	-56.41	-20.00	36.41
1800.05	V	39.97	-63.72	8.86	0.90	-55.76	-20.00	35.76
2250.06	H	37.41	-64.72	9.25	0.93	-56.40	-20.00	36.40
2250.06	V	37.71	-64.36	9.25	0.93	-56.04	-20.00	36.04
2700.08	H	47.96	-52.02	9.72	1.04	-43.34	-20.00	23.34
2700.08	V	46.60	-53.34	9.72	1.04	-44.66	-20.00	24.66
3150.09	H	36.64	-60.70	10.26	1.14	-51.58	-20.00	31.58
3150.09	V	36.94	-60.22	10.26	1.14	-51.10	-20.00	31.10
3600.10	H	40.20	-57.35	10.50	1.24	-48.09	-20.00	28.09
3600.10	V	40.02	-57.39	10.50	1.24	-48.13	-20.00	28.13
4050.11	H	42.39	-53.50	10.87	1.32	-43.95	-20.00	23.95
4050.11	V	40.17	-55.60	10.87	1.32	-46.05	-20.00	26.05
4500.13	H	44.69	-51.09	10.60	1.38	-41.87	-20.00	21.87
4500.13	V	41.42	-54.10	10.60	1.38	-44.88	-20.00	24.88
4FSK, Frequency: 450.0125MHz-12.5 kHz								
900.03	H	58.15	-41.15	0.00	0.63	-41.78	-20.00	21.78
900.03	V	61.13	-35.30	0.00	0.63	-35.93	-20.00	15.93
1350.04	H	38.76	-64.46	8.08	0.79	-57.17	-20.00	37.17
1350.04	V	42.28	-61.19	8.08	0.79	-53.90	-20.00	33.90
1800.05	H	38.48	-65.02	8.86	0.90	-57.06	-20.00	37.06
1800.05	V	39.62	-64.07	8.86	0.90	-56.11	-20.00	36.11
2250.06	H	38.48	-63.65	9.25	0.93	-55.33	-20.00	35.33
2250.06	V	39.11	-62.96	9.25	0.93	-54.64	-20.00	34.64
2700.08	H	47.29	-52.69	9.72	1.04	-44.01	-20.00	24.01
2700.08	V	44.07	-55.87	9.72	1.04	-47.19	-20.00	27.19
3150.09	H	34.71	-62.63	10.26	1.14	-53.51	-20.00	33.51
3150.09	V	35.85	-61.31	10.26	1.14	-52.19	-20.00	32.19
3600.10	H	43.18	-54.37	10.50	1.24	-45.11	-20.00	25.11
3600.10	V	43.28	-54.13	10.50	1.24	-44.87	-20.00	24.87
4050.11	H	43.67	-52.22	10.87	1.32	-42.67	-20.00	22.67
4050.11	V	41.48	-54.29	10.87	1.32	-44.74	-20.00	24.74
4500.13	H	42.11	-53.67	10.60	1.38	-44.45	-20.00	24.45
4500.13	V	43.53	-51.99	10.60	1.38	-42.77	-20.00	22.77

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
FM, Frequency: 480.0125MHz-12.5 kHz								
906.43	H	56.84	-42.27	0.00	0.55	-42.82	-20.00	22.82
906.43	V	56.72	-39.57	0.00	0.55	-40.12	-20.00	20.12
1440.04	H	39.46	-64.14	8.33	0.74	-56.55	-20.00	36.55
1440.04	V	41.96	-61.71	8.33	0.74	-54.12	-20.00	34.12
1920.05	H	39.60	-63.20	9.00	0.86	-55.06	-20.00	35.06
1920.05	V	39.83	-62.57	9.00	0.86	-54.43	-20.00	34.43
2400.06	H	36.47	-64.58	9.34	0.98	-56.22	-20.00	36.22
2400.06	V	37.89	-62.90	9.34	0.98	-54.54	-20.00	34.54
2880.08	H	47.28	-52.29	10.01	1.07	-43.35	-20.00	23.35
2880.08	V	45.01	-54.61	10.01	1.07	-45.67	-20.00	25.67
3360.09	H	37.01	-60.30	10.34	1.17	-51.13	-20.00	31.13
3360.09	V	36.91	-60.30	10.34	1.17	-51.13	-20.00	31.13
3840.10	H	37.37	-58.57	10.74	1.28	-49.11	-20.00	29.11
3840.10	V	37.66	-58.17	10.74	1.28	-48.71	-20.00	28.71
4320.11	H	43.33	-52.82	10.71	1.35	-43.46	-20.00	23.46
4320.11	V	40.05	-56.00	10.71	1.35	-46.64	-20.00	26.64
4800.13	H	43.43	-50.68	10.96	1.44	-41.16	-20.00	21.16
4800.13	V	41.49	-52.42	10.96	1.44	-42.90	-20.00	22.90
4FSK, Frequency: 480.0125MHz -12.5 kHz								
960.03	H	56.84	-40.65	0.00	0.62	-41.27	-20.00	21.27
960.03	V	56.72	-38.40	0.00	0.62	-39.02	-20.00	19.02
1440.04	H	42.16	-61.44	8.33	0.74	-53.85	-20.00	33.85
1440.04	V	43.41	-60.26	8.33	0.74	-52.67	-20.00	32.67
1920.05	H	38.46	-64.34	9.00	0.86	-56.20	-20.00	36.20
1920.05	V	39.25	-63.15	9.00	0.86	-55.01	-20.00	35.01
2400.06	H	38.16	-62.89	9.34	0.98	-54.53	-20.00	34.53
2400.06	V	38.63	-62.16	9.34	0.98	-53.80	-20.00	33.80
2880.08	H	49.05	-50.52	10.01	1.07	-41.58	-20.00	21.58
2880.08	V	46.23	-53.39	10.01	1.07	-44.45	-20.00	24.45
3360.09	H	35.86	-61.45	10.34	1.17	-52.28	-20.00	32.28
3360.09	V	36.22	-60.99	10.34	1.17	-51.82	-20.00	31.82
3840.10	H	43.47	-52.47	10.74	1.28	-43.01	-20.00	23.01
3840.10	V	42.93	-52.90	10.74	1.28	-43.44	-20.00	23.44
4320.11	H	44.75	-51.40	10.71	1.35	-42.04	-20.00	22.04
4320.11	V	39.82	-56.23	10.71	1.35	-46.87	-20.00	26.87
4800.13	H	41.45	-52.66	10.96	1.44	-43.14	-20.00	23.14
4800.13	V	42.95	-50.96	10.96	1.44	-41.44	-20.00	21.44

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
FM, Frequency: 519.9875MHz-12.5 kHz								
76.03	H	35.94	-71.46	-1.99	0.16	-73.61	-20.00	53.61
53.74	V	44.67	-58.35	-13.18	0.13	-71.66	-20.00	51.66
1039.98	H	38.19	-64.71	7.21	0.65	-58.15	-20.00	38.15
1039.98	V	41.57	-61.64	7.21	0.65	-55.08	-20.00	35.08
1559.96	H	36.19	-67.81	8.57	0.80	-60.04	-20.00	40.04
1559.96	V	37.90	-66.16	8.57	0.80	-58.39	-20.00	38.39
2079.95	H	41.68	-60.25	9.15	0.91	-52.01	-20.00	32.01
2079.95	V	40.92	-60.84	9.15	0.91	-52.60	-20.00	32.60
2599.94	H	38.63	-61.30	9.56	1.02	-52.76	-20.00	32.76
2599.94	V	35.93	-63.86	9.56	1.02	-55.32	-20.00	35.32
3119.93	H	39.82	-57.66	10.25	1.13	-48.54	-20.00	28.54
3119.93	V	41.33	-56.00	10.25	1.13	-46.88	-20.00	26.88
3639.91	H	49.36	-48.10	10.54	1.22	-38.78	-20.00	18.78
3639.91	V	49.09	-48.28	10.54	1.22	-38.96	-20.00	18.96
4159.90	H	45.86	-50.11	10.80	1.29	-40.60	-20.00	20.60
4159.90	V	40.36	-55.58	10.80	1.29	-46.07	-20.00	26.07
4679.89	H	39.72	-55.23	10.82	1.41	-45.82	-20.00	25.82
4679.89	V	39.52	-55.42	10.82	1.41	-46.01	-20.00	26.01
4FSK, Frequency: 519.9875MHz-12.5 kHz								
256.27	H	39.94	-71.81	0.00	0.30	-72.11	-20.00	52.11
52.77	V	44.91	-57.64	-13.63	0.13	-71.40	-20.00	51.40
1039.98	H	38.71	-64.19	7.21	0.65	-57.63	-20.00	37.63
1039.98	V	40.15	-63.06	7.21	0.65	-56.50	-20.00	36.50
1559.96	H	37.58	-66.42	8.57	0.80	-58.65	-20.00	38.65
1559.96	V	38.27	-65.79	8.57	0.80	-58.02	-20.00	38.02
2079.95	H	39.47	-62.46	9.15	0.91	-54.22	-20.00	34.22
2079.95	V	37.27	-64.49	9.15	0.91	-56.25	-20.00	36.25
2599.94	H	43.48	-56.45	9.56	1.02	-47.91	-20.00	27.91
2599.94	V	42.08	-57.71	9.56	1.02	-49.17	-20.00	29.17
3119.93	H	39.58	-57.90	10.25	1.13	-48.78	-20.00	28.78
3119.93	V	40.93	-56.40	10.25	1.13	-47.28	-20.00	27.28
3639.91	H	50.58	-46.88	10.54	1.22	-37.56	-20.00	17.56
3639.91	V	50.62	-46.75	10.54	1.22	-37.43	-20.00	17.43
4159.90	H	53.80	-42.17	10.80	1.29	-32.66	-20.00	12.66
4159.90	V	52.01	-43.93	10.80	1.29	-34.42	-20.00	14.42
4679.89	H	45.35	-49.60	10.82	1.41	-40.19	-20.00	20.19
4679.89	V	45.65	-49.29	10.82	1.41	-39.88	-20.00	19.88

Part 74

art 74

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
FM, Frequency: 455.0125MHz-12.5 kHz								
910.03	H	56.99	-42.01	0.00	0.54	-42.55	-20.00	22.55
910.03	V	59.00	-37.21	0.00	0.54	-37.75	-20.00	17.75
1365.04	H	39.12	-64.25	8.12	0.77	-56.90	-20.00	36.90
1365.04	V	42.18	-61.37	8.12	0.77	-54.02	-20.00	34.02
1820.05	H	39.87	-63.52	8.88	0.90	-55.54	-20.00	35.54
1820.05	V	40.33	-63.15	8.88	0.90	-55.17	-20.00	35.17
2275.06	H	36.53	-65.50	9.27	0.96	-57.19	-20.00	37.19
2275.06	V	37.23	-64.66	9.27	0.96	-56.35	-20.00	36.35
2730.08	H	48.20	-51.76	9.77	1.06	-43.05	-20.00	23.05
2730.08	V	45.99	-53.91	9.77	1.06	-45.20	-20.00	25.20
3185.09	H	37.05	-60.14	10.27	1.12	-50.99	-20.00	30.99
3185.09	V	37.58	-59.38	10.27	1.12	-50.23	-20.00	30.23
3640.10	H	34.99	-62.47	10.54	1.22	-53.15	-20.00	33.15
3640.10	V	36.75	-60.62	10.54	1.22	-51.30	-20.00	31.30
4095.11	H	43.39	-52.61	10.84	1.27	-43.04	-20.00	23.04
4095.11	V	38.96	-57.00	10.84	1.27	-47.43	-20.00	27.43
4550.13	H	43.17	-52.44	10.66	1.36	-43.14	-20.00	23.14
4550.13	V	42.25	-53.15	10.66	1.36	-43.85	-20.00	23.85
FM, Frequency: 455.0125MHz-25 kHz								
910.03	H	56.95	-42.05	0.00	0.54	-42.59	-13.00	29.59
910.03	V	58.69	-37.52	0.00	0.54	-38.06	-13.00	25.06
1365.04	H	41.10	-62.27	8.12	0.77	-54.92	-13.00	41.92
1365.04	V	42.84	-60.71	8.12	0.77	-53.36	-13.00	40.36
1820.05	H	40.11	-63.28	8.88	0.90	-55.30	-13.00	42.30
1820.05	V	40.23	-63.25	8.88	0.90	-55.27	-13.00	42.27
2275.06	H	36.29	-65.74	9.27	0.96	-57.43	-13.00	44.43
2275.06	V	37.19	-64.70	9.27	0.96	-56.39	-13.00	43.39
2730.08	H	48.49	-51.47	9.77	1.06	-42.76	-13.00	29.76
2730.08	V	45.72	-54.18	9.77	1.06	-45.47	-13.00	32.47
3185.09	H	35.95	-61.24	10.27	1.12	-52.09	-13.00	39.09
3185.09	V	37.69	-59.27	10.27	1.12	-50.12	-13.00	37.12
3640.10	H	36.02	-61.44	10.54	1.22	-52.12	-13.00	39.12
3640.10	V	38.12	-59.25	10.54	1.22	-49.93	-13.00	36.93
4095.11	H	44.02	-51.98	10.84	1.27	-42.41	-13.00	29.41
4095.11	V	39.74	-56.22	10.84	1.27	-46.65	-13.00	33.65
4550.13	H	42.39	-53.22	10.66	1.36	-43.92	-13.00	30.92
4550.13	V	43.07	-52.33	10.66	1.36	-43.03	-13.00	30.03

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
4FSK, Frequency: 455.0125MHz-12.5 kHz								
910.03	H	61.10	-37.90	0.00	0.54	-38.44	-20.00	18.44
910.03	V	63.08	-33.13	0.00	0.54	-33.67	-20.00	13.67
1365.04	H	41.04	-62.33	8.12	0.77	-54.98	-20.00	34.98
1365.04	V	43.28	-60.27	8.12	0.77	-52.92	-20.00	32.92
1820.05	H	40.07	-63.32	8.88	0.90	-55.34	-20.00	35.34
1820.05	V	40.67	-62.81	8.88	0.90	-54.83	-20.00	34.83
2275.06	H	38.24	-63.79	9.27	0.96	-55.48	-20.00	35.48
2275.06	V	36.91	-64.98	9.27	0.96	-56.67	-20.00	36.67
2730.08	H	49.05	-50.91	9.77	1.06	-42.20	-20.00	22.20
2730.08	V	45.70	-54.20	9.77	1.06	-45.49	-20.00	25.49
3185.09	H	36.09	-61.10	10.27	1.12	-51.95	-20.00	31.95
3185.09	V	36.53	-60.43	10.27	1.12	-51.28	-20.00	31.28
3640.10	H	44.02	-53.44	10.54	1.22	-44.12	-20.00	24.12
3640.10	V	42.83	-54.54	10.54	1.22	-45.22	-20.00	25.22
4095.11	H	44.30	-51.70	10.84	1.27	-42.13	-20.00	22.13
4095.11	V	41.92	-54.04	10.84	1.27	-44.47	-20.00	24.47
4550.13	H	42.09	-53.52	10.66	1.36	-44.22	-20.00	24.22
4550.13	V	41.70	-53.70	10.66	1.36	-44.40	-20.00	24.40

Part 22

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
FM, Frequency: 454.0125MHz-12.5 kHz								
908.03	H	57.68	-41.38	0.00	0.54	-41.92	-13.00	28.92
908.03	V	58.69	-37.57	0.00	0.54	-38.11	-13.00	25.11
1362.04	H	39.80	-63.54	8.11	0.77	-56.20	-13.00	43.20
1362.04	V	43.23	-60.31	8.11	0.77	-52.97	-13.00	39.97
1816.05	H	39.00	-64.41	8.88	0.90	-56.43	-13.00	43.43
1816.05	V	39.47	-64.05	8.88	0.90	-56.07	-13.00	43.07
2270.06	H	37.52	-64.53	9.26	0.95	-56.22	-13.00	43.22
2270.06	V	38.10	-63.83	9.26	0.95	-55.52	-13.00	42.52
2724.08	H	46.88	-53.09	9.76	1.05	-44.38	-13.00	31.38
2724.08	V	45.24	-54.67	9.76	1.05	-45.96	-13.00	32.96
3178.09	H	36.01	-61.21	10.27	1.12	-52.06	-13.00	39.06
3178.09	V	36.21	-60.79	10.27	1.12	-51.64	-13.00	38.64
3632.10	H	38.08	-59.40	10.53	1.22	-50.09	-13.00	37.09
3632.10	V	39.66	-57.72	10.53	1.22	-48.41	-13.00	35.41
4086.11	H	43.59	-52.39	10.85	1.28	-42.82	-13.00	29.82
4086.11	V	39.55	-56.37	10.85	1.28	-46.80	-13.00	33.80
4540.13	H	43.59	-52.06	10.65	1.36	-42.77	-13.00	29.77
4540.13	V	43.47	-51.95	10.65	1.36	-42.66	-13.00	29.66
FM, Frequency: 454.0125MHz-25 kHz								
908.03	H	57.83	-41.23	0.00	0.54	-41.77	-13.00	28.77
908.03	V	58.62	-37.64	0.00	0.54	-38.18	-13.00	25.18
1362.04	H	41.98	-61.36	8.11	0.77	-54.02	-13.00	41.02
1362.04	V	43.40	-60.14	8.11	0.77	-52.80	-13.00	39.80
1816.05	H	38.73	-64.68	8.88	0.90	-56.70	-13.00	43.70
1816.05	V	39.53	-63.99	8.88	0.90	-56.01	-13.00	43.01
2270.06	H	36.96	-65.09	9.26	0.95	-56.78	-13.00	43.78
2270.06	V	37.77	-64.16	9.26	0.95	-55.85	-13.00	42.85
2724.08	H	47.96	-52.01	9.76	1.05	-43.30	-13.00	30.30
2724.08	V	45.54	-54.37	9.76	1.05	-45.66	-13.00	32.66
3178.09	H	35.37	-61.85	10.27	1.12	-52.70	-13.00	39.70
3178.09	V	36.77	-60.23	10.27	1.12	-51.08	-13.00	38.08
3632.10	H	39.61	-57.87	10.53	1.22	-48.56	-13.00	35.56
3632.10	V	40.17	-57.21	10.53	1.22	-47.90	-13.00	34.90
4086.11	H	43.33	-52.65	10.85	1.28	-43.08	-13.00	30.08
4086.11	V	38.87	-57.05	10.85	1.28	-47.48	-13.00	34.48
4540.13	H	42.76	-52.89	10.65	1.36	-43.60	-13.00	30.60
4540.13	V	43.61	-51.81	10.65	1.36	-42.52	-13.00	29.52

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
4FSK,Frequency: 454.0125MHz-12.5 kHz								
908.03	H	61.79	-37.27	0.00	0.54	-37.81	-13.00	24.81
908.03	V	57.42	-38.84	0.00	0.54	-39.38	-13.00	26.38
1362.04	H	42.24	-61.10	8.11	0.77	-53.76	-13.00	40.76
1362.04	V	43.16	-60.38	8.11	0.77	-53.04	-13.00	40.04
1816.05	H	38.53	-64.88	8.88	0.90	-56.90	-13.00	43.90
1816.05	V	38.51	-65.01	8.88	0.90	-57.03	-13.00	44.03
2270.06	H	37.01	-65.04	9.26	0.95	-56.73	-13.00	43.73
2270.06	V	37.73	-64.20	9.26	0.95	-55.89	-13.00	42.89
2724.08	H	47.96	-52.01	9.76	1.05	-43.30	-13.00	30.30
2724.08	V	46.79	-53.12	9.76	1.05	-44.41	-13.00	31.41
3178.09	H	35.45	-61.77	10.27	1.12	-52.62	-13.00	39.62
3178.09	V	36.91	-60.09	10.27	1.12	-50.94	-13.00	37.94
3632.10	H	44.81	-52.67	10.53	1.22	-43.36	-13.00	30.36
3632.10	V	45.19	-52.19	10.53	1.22	-42.88	-13.00	29.88
4086.11	H	43.94	-52.04	10.85	1.28	-42.47	-13.00	29.47
4086.11	V	43.13	-52.79	10.85	1.28	-43.22	-13.00	30.22
4540.13	H	43.18	-52.47	10.65	1.36	-43.18	-13.00	30.18
4540.13	V	42.96	-52.46	10.65	1.36	-43.17	-13.00	30.17

Note 1: The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

Note 2:

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

4.6 FREQUENCY STABILITY:

Serial Number:	CR21120026-RF-S1	Test Date:	2022/01/17~2022/02/16
Test Site:	RF	Test Mode:	Transmitting
Tester:	Morpheus Shi	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	20.9~21.8	Relative Humidity: (%)	55~60	ATM Pressure: (kPa)	101.1~101.6
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200256	2021-07-22	2022-07-21
YINSAIGE	Coaxial Cable	SS402	SJ0100004	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100003	Each time	N/A
Weinschel	Power splitter	1515	RA915	Each time	N/A
HP	RF Communications Test Set	8920A	3438A05209	2021-07-22	2022-07-21
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A
UNI-T	Multimeter	UT39A+	C210582554	2021-09-30	2022-09-29
BACL	TEMP&HUMI Test Chamber	BTH-150	30026	2021-07-22	2022-07-22

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:**FCC Part 90:**

FM,12.5kHz, Reference Frequency: 480.0125 MHz, Limit: ± 2.5 ppm			
Temperature (°C)	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
-30	7.4	480.012636	0.28
-20		480.012531	0.06
-10		480.012646	0.30
0		480.012566	0.14
10		480.012468	-0.07
20		480.012729	0.48
30		480.012652	0.32
40		480.012522	0.05
50		480.012554	0.11
20	6.2	480.012477	-0.05
20	8.4	480.012455	-0.09

4FSK, 12.5kHz, Reference Frequency: 480.0125MHz, Limit: ± 2.5 ppm			
Temperature (°C)	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
-30	7.4	480.012474	-0.05
-20		480.012554	0.11
-10		480.012716	0.45
0		480.012580	0.17
10		480.012505	0.01
20		480.012801	0.63
30		480.012597	0.20
40		480.012667	0.35
50		480.012561	0.13
20	6.2	480.012552	0.11
20	8.4	480.012612	0.23

FCC Part 74:

FM, 12.5kHz, Reference Frequency: 455.0125 MHz, Limit: ± 5.0 ppm			
Temperature (°C)	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
-30	7.4	455.012645	0.32
-20		455.012467	-0.07
-10		455.012540	0.09
0		455.012574	0.16
10		455.012521	0.05
20		455.012700	0.44
30		455.012721	0.49
40		455.012733	0.51
50		455.012452	-0.11
20	6.2	455.012672	0.38
20	8.4	455.012570	0.15

4FSK, 12.5kHz, Reference Frequency: 455.0125 MHz, Limit: ± 5.0 ppm			
Temperature (°C)	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
-30	7.2	455.012733	0.51
-20		455.012451	-0.11
-10		455.012643	0.31
0		455.012663	0.36
10		455.012685	0.41
20		455.012860	0.79
30		455.012689	0.42
40		455.012709	0.46
50		455.012517	0.04
20	6.2	455.012620	0.26
20	8.4	455.012514	0.03

FM, 25kHz, Reference Frequency: 455.0125 MHz, Limit: ± 5.0 ppm			
Temperature (°C)	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
-30	7.4	455.012653	0.34
-20		455.012499	0.00
-10		455.012452	-0.11
0		455.012552	0.11
10		455.012579	0.17
20		455.012700	0.44
30		455.012669	0.37
40		455.012633	0.29
50		455.012519	0.04
20	6.2	455.012586	0.19
20	8.4	455.012718	0.48

FCC Part 22:

FM, 12.5kHz, Reference Frequency: 454.0125MHz, Limit: ± 5.0 ppm			
Temperature (°C)	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
-30	7.4	454.012631	0.29
-20		454.012472	-0.06
-10		454.012701	0.44
0		454.012479	-0.05
10		454.012669	0.37
20		454.012740	0.53
30		454.012728	0.50
40		454.012585	0.19
50		454.012701	0.44
20	6.2	454.012547	0.10
20	8.4	454.012632	0.29

4FSK,12.5kHz, Reference Frequency: 454.0125MHz, Limit: ± 5.0 ppm			
Temperature (°C)	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
-30	7.4	454.012561	0.13
-20		454.012738	0.52
-10		454.012477	-0.05
0		454.012655	0.34
10		454.012477	-0.05
20		454.012766	0.59
30		454.012655	0.34
40		454.012580	0.18
50		454.012483	-0.04
20	6.2	454.012521	0.05
20	8.4	454.012594	0.21

FM, 25kHz, Reference Frequency: 454.0125MHz, Limit: ± 5.0 ppm			
Temperature (°C)	Voltage Supplied (V _{DC})	Measured Frequency (MHz)	Frequency Error (ppm)
-30	7.4	454.012544	0.10
-20		454.012687	0.41
-10		454.012576	0.17
0		454.012501	0.00
10		454.012558	0.13
20		454.012700	0.44
30		454.012558	0.13
40		454.012698	0.44
50		454.012458	-0.09
20	6.2	454.012746	0.54
20	8.4	454.012734	0.52

4.7 TRANSIENT FREQUENCY BEHAVIOR

Serial Number:	CR21120026-RF-S1	Test Date:	2022/02/16
Test Site:	RF	Test Mode:	Transmitting
Tester:	Morpheus Shi	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	21.8	Relative Humidity: (%)	55	ATM Pressure: (kPa)	101.1
----------------------	------	------------------------------	----	------------------------	-------



Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Signal Analyzer	FSIQ26	831929/006	2021-07-22	2022-07-21
YINSAIGE	Coaxial Cable	SS402	SJ0100004	Each time	N/A
YINSAIGE	Coaxial Cable	SS402	SJ0100003	Each time	N/A
Weinschel	Power splitter	1515	RA915	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A
HP	RF Communications Test Set	8920A	3438A05209	2021-07-22	2022-07-21

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Channel Spacing (kHz)	Transient Period (ms)	Transient Frequency	Result
12.5	10(t ₁)	±12.5 kHz	Pass
	25(t ₂)	±6.25 kHz	
	10(t ₃)	±12.5 kHz	



***** END OF REPORT *****