




EUT Name	soundcore Boom 2, SOUNDCORE BOOM 2	Model Name	A3138
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 7.3V
Test Mode	Mode 6	Antenna Polarity	Horizontal

Test Graph for Peak Measurement








RESULT: Pass




EUT Name	soundcore Boom 2, SOUNDCORE BOOM 2	Model Name	A3138
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 7.3V
Test Mode	Mode 6	Antenna Polarity	Vertical

Test Graph for Peak Measurement









RESULT: Pass




EUT Name	soundcore Boom 2, SOUNDCORE BOOM 2	Model Name	A3138
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 7.3V
Test Mode	Mode 7	Antenna Polarity	Horizontal

Test Graph for Peak Measurement









RESULT: Pass




EUT Name	soundcore Boom 2, SOUNDCORE BOOM 2	Model Name	A3138
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 7.3V
Test Mode	Mode 7	Antenna Polarity	Vertical

Test Graph for Peak Measurement









RESULT: Pass




EUT Name	soundcore Boom 2, SOUNDCORE BOOM 2	Model Name	A3138
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 7.3V
Test Mode	Mode 9	Antenna Polarity	Horizontal

Test Graph for Peak Measurement









RESULT: Pass




EUT Name	soundcore Boom 2, SOUNDCORE BOOM 2	Model Name	A3138
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 7.3V
Test Mode	Mode 9	Antenna Polarity	Vertical

Test Graph for Peak Measurement







RESULT: Pass

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



Page 72 of 84

10. Number of Hopping Frequency Measurement

10.1 Provisions Applicable


This frequency hopping system must employ a minimum of 15 hopping channels.

10.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:


- 1. Span = The frequency band of operation. Depending on the number of channels the device
- 2. supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- 3. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 4. VBW ≥ RBW
- 5. Sweep time = Auto couple
- 6. Detector = Peak
- 7. Trace mode = Max hold
- 8. Allow the trace to stabilize

10.3 Measurement Setup (Block Diagram of Configuration)




10.4 Measurement Result

Test Data of Number of Hopping Frequency				
Test Mode	Limits	Pass or Fail		
8DPSK Hopping	>=15	Pass		





Test Graphs of Number of Hopping Frequency



Note: The 8DPSK modulation is the worst case and recorded in the report.

Report No.: AGC01110231036FR02 Page 74 of 84

11. Time of Occupancy (Dwell Time) Measurement

11.1 Provisions Applicable


The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.

11.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:


- 1. Span = Zero span, centered on a hopping channel.
- 2. RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- 3. VBW ≥ RBW
- 4. Sweep time = As necessary to capture the entire dwell time per hopping channel
- 5. Detector = Peak
- 6. Trace mode = Free Run
- 7. Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time. An oscilloscope may be used instead of a spectrum analyzer. The EUT shall show compliance with the appropriate regulatory limit for the number of hopping channels. A plot of the data shall be included in the test report.

11.3 Measurement Setup (Block Diagram of Configuration)




11.4 Measurement Result

	Test Data of Dwell Time							
Channel	Time of Pulse for 3DH5 (ms)	Number of hops in the period specified in the requirements	Sweep Time (ms)	Limit (ms)	Pass or Fail			
2402	2.879	27.0*4	310.932	400	Pass			
2441	2.879	27.0*4	310.932	400	Pass			
2480	2.879	26.0*4	299.416	400	Pass			






Test Graphs of Dwell Time




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test_Graph_EDR_HOP_ANT1_NA_3Mbps_2402_Time per Burst

Web: http://www.agccert.com/










Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/





Note: All mode rates are testedand evaluated, the 8DPSK modulation is the worst case and recorded in the report.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 78 of 84

12. Frequency Separation Measurement

12.1 Provisions Applicable

When the power is less than 0.125W: The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.


When the power is less than 1W: The minimum permissible channel separation for this system is 20dB BW.

12.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:


- 1. Span: Wide enough to capture the peaks of two adjacent channels.
- 2. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- 3. Video (or average) bandwidth (VBW) ≥ RBW.
- 4. Sweep: Auto.
- 5. Detector function: Peak.
- 6. Trace: Max hold. g) Allow the trace to stabilize.
- 7. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

12.3 Measurement Setup (Block Diagram of Configuration)




12.4 Measurement Result

Test Data of Frequency Separation					
Test Mode Channel Separation (MHz) Limits(MHz) Pass or Fail					
8DPSK Hopping	1.001	>= 0.828	Pass		







Note: All mode rates are testedand evaluated, The 8DPSK modulation is the worst case and recorded in the report.



13. AC Power Line Conducted Emission Test


13.1 Measurement Limit

Fraguenay	Maximum RF Line Voltage			
Frequency	Q.P. (dBµV)	Average (dBμV)		
150kHz~500kHz	66-56	56-46		
500kHz~5MHz	56	46		
5MHz~30MHz	60	50		

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

13.2 Measurement Setup (Block Diagram of Configuration)





Page 81 of 84

13.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

13.4 Final Procedure of Line Conducted Emission Test

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

13.5 Measurement Results






MEASUREMENT RESULT: "agc_fin"

2023/12/12 10:01							
	Frequency MHz	Level dBµV		Limit dBµV	Margin dB	Detector	Line
	0.710000	21.50	6.2	56	34.5	QP	L1
	0.770000	23.90	6.2	56	32.1	QP	L1
	1.102000	22.10	6.2	56	33.9	QP	L1
	1.362000	21.70	6.2	56	34.3	QP	L1
	1.438000	21.30	6.2	56	34.7	QP	L1
	12.326000	27.40	6.8	60	32.6	OP	L1

MEASUREMENT RESULT: "agc_fin2"

2023/12/12 10:01							
Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line		
18.30	6.1	49	30.4	AV	L1		
20.00	6.2	46	26.0	AV	L1		
16.20	6.2	46	29.8	AV	L1		
12.10	6.3	46	33.9	AV	L1		
20.50	6.8	50	29.5	AV	L1		
19.30	6.8	50	30.7	AV	L1		
	Level dBµV 18.30 20.00 16.20 12.10 20.50	Level Transd dB	Level Transd Limit dBμV dB dBμV 18.30 6.1 49 20.00 6.2 46 16.20 6.2 46 12.10 6.3 46 20.50 6.8 50	Level Transd Limit Margin dBμV dB dBμV dB 18.30 6.1 49 30.4 20.00 6.2 46 26.0 16.20 6.2 46 29.8 12.10 6.3 46 33.9 20.50 6.8 50 29.5	Level Transd Limit Margin Detector dBμV dB dBμV dB 18.30 6.1 49 30.4 AV 20.00 6.2 46 26.0 AV 16.20 6.2 46 29.8 AV 12.10 6.3 46 33.9 AV 20.50 6.8 50 29.5 AV		





MEASUREMENT RESULT: "agc_fin"

2023/12/12 9:58										
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line				
0.158000	26.50	6.1	66	39.1	QP	N				
0.346000	22.60	6.1	59	36.5	QP	N				
0.778000	29.00	6.2	56	27.0	QP	N				
1.042000	22.10	6.2	56	33.9	QP	N				
1.374000	22.70	6.2	56	33.3	QP	N				
12.218000	27.30	6.8	60	32.7	QP	N				

MEASUREMENT RESULT: "agc fin2"

2023/12/12 9:58										
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line				
0.778000	22.30	6.2	46	23.7	AV	N				
1.206000	16.90	6.2	46	29.1	AV	N				
3.162000	15.80	6.3	46	30.2	AV	N				
10.970000	16.80	6.7	50	33.2	AV	N				
12.234000	20.10	6.8	50	29.9	AV	N				
13.262000	20.30	6.8	50	29.7	AV	N				



Page 84 of 84

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC01110231036AP02

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC01110231036AP03

----End of Report----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.