

# **RF Exposure Report**

#### For

**Applicant Name:** Address: EUT Name:

Brand Name:

Model Number: Series Model Number:

#### **GoPlus Corp**

11250 Poplar Ave, Fontana, CA 92337 Active plastic speaker

### ISONART

FP10766 P1915A, PP-1915A, PP-1915

## **Issued By**

#### **Company Name:**

Address:

FCC ID:

Test Date:

BTF Testing Lab (Shenzhen) Co., Ltd. F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

**Report Number:** BTF240314R00803 Test Standards: 2BE5D-FP10766 **Test Conclusion:** Pass 2024-04-03

Prepared By:

Date of Issue:

Date:

Approved By:

Date:

47 CFR Part 2 Subpart J Section 2.1091 2024-03-14 to 2024-04-02



Ryan.CJ / EMC Manager 2024-04-03


Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Total or partial reproduction of this document without permission of the Laboratory is not allowed. BTF Testing Lab (Shenzhen) Co., Ltd. F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Page 1 of 7




| Revision History                     |                       |  |  |  |  |
|--------------------------------------|-----------------------|--|--|--|--|
| Version Issue Date Revisions Content |                       |  |  |  |  |
| R_V0                                 | 2024-04-03            | Original   |  |  |  |
|                                      |                       |  |  |  |  |
| Note:                                | Once the revision has | Once the revision has been made, then previous versions reports are invalid. |  |  |  |





#### **Table of Contents**

| 1. | Introd | Juction  |   |
|----|--------|--|---|
|    | 1.1    | Identification of Testing Laboratory               | 4 |
|    | 1.2    | Identification of the Responsible Testing Location | 4 |
|    | 1.3    | Laboratory Condition                               | 4 |
|    | 1.4    | Announcement                                       | 4 |
| 2. | Produ  | uct Information                                    | 5 |
|    | 2.1    | Application Information                            | 5 |
|    | 2.2    | Manufacturer Information                           | 5 |
|    | 2.3    | Factory Information                                |   |
|    | 2.4    | General Description of Equipment under Test (EUT)  | 5 |
| 3. |        | Requirement  |   |
|    | 3.1    | Assessment Result                                  |   |





# 1. Introduction

### 1.1 Identification of Testing Laboratory

| Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.  |                   |
|---|-------------------|
| Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Community, Songgang Street, Bao'an District, Shenzhen, China |                   |
| Phone Number:   | +86-0755-23146130 |
| Fax Number:   | +86-0755-23146130 |

#### **1.2 Identification of the Responsible Testing Location**

| Test Location:           | BTF Testing Lab (Shenzhen) Co., Ltd.  |  |  |
|--------------------------|---|--|--|
| Address:                 | F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China   |  |  |
| Description:             | All measurement facilities used to collect the measurement data are located at F101,201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China |  |  |
| FCC Registration Number: | 518915  |  |  |
| Designation Number:      | CN1330  |  |  |

#### **1.3 Laboratory Condition**

| Ambient Temperature:       | 20℃ to 25℃         |
|----------------------------|--------------------|
| Ambient Relative Humidity: | 45% to 55%         |
| Ambient Pressure:          | 100 kPa to 102 kPa |

#### **1.4 Announcement**

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.



# 2. Product Information

#### 2.1 Application Information

| Company Name: | GoPlus Corp                         |
|---------------|-------------------------------------|
| Address:      | 11250 Poplar Ave, Fontana, CA 92337 |

#### 2.2 Manufacturer Information

| Company Name: | Ningbo Polinata Electronics Co., Ltd.   |
|---------------|---|
| Address:      | 9#, Xinrui Rd,Longxing Village, Wuxiang Town, Yinzhou District, Ningbo<br>City, Zhejiang Province, China. |

### 2.3 Factory Information

| Company Name: | Ningbo Polinata Electronics Co., Ltd.   |
|---------------|---|
| Address:      | 9#, Xinrui Rd,Longxing Village, Wuxiang Town, Yinzhou District, Ningbo<br>City, Zhejiang Province, China. |

## 2.4 General Description of Equipment under Test (EUT)

| EUT Name                                   | Active plastic speaker  |
|--|---|
| Under Test Model Name                      | FP10766   |
| Series Model Number:                       | P1915A, PP-1915A, PP-1915   |
| Description of Model name differentiation: | All the models are identical to each other except for model name. |



# 3. Test Requirement

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b), Limits for Maximum Permissible Exposure (MPE),

| E   |                |                            | D I I                  | A              |  |  |
|---|----------------|----------------------------|------------------------|----------------|--|--|
| Frequency range   | Electric field | Magnetic field strength    | Power density          | Averaging time |  |  |
| (MHz)   | strength(V/m)  | (A/m)                      | (mW/cm <sup>2</sup> )  | (minutes)      |  |  |
|   | (A) Limits f   | or Occupational/Controllec | Exposures              |                |  |  |
| 0.3-3.0   | 614            | 1.63                       | *(100)                 | 6              |  |  |
| 3.0-30  | 1842/f         | 4.89/f                     | *(900/f <sup>2</sup> ) | 6              |  |  |
| 30–300  | 61.4           | 0.163                      | 1.0                    | 6              |  |  |
| 300-1500  | -              | -                          | f/300                  | 6              |  |  |
| 1500-100,000  | -              | -                          | 5                      | 6              |  |  |
| (B) Limits for General Population/Uncontrolled Exposure |                |                            |                        |                |  |  |
| 0.3-1.34  | 614            | 1.63                       | *(100)                 | 30             |  |  |
| 1.34–30   | 824/f          | 2.19/f                     | *(180/f <sup>2</sup> ) | 30             |  |  |
| 30-300  | 27.5           | 0.073                      | 0.2                    | 30             |  |  |
| 300-1500  | -              | -                          | f/1500                 | 30             |  |  |
| 1500-100,000  | -              | -                          | 1.0                    | 30             |  |  |

Note: f = frequency in MHz

#### **EVALUATION METHOD**

Transmission formula: Pd = (Pout\*G)/(4\*pi\*r<sup>2</sup>)

Where

Pd = power density in mW/cm<sup>2</sup>, Pout = output power to antenna in mW, G = gain of antenna in linear scale; Pi = 3.1416, R = distance between observation point and center of the radiator in cm

#### 3.1 Assessment Result

⊠ Passed

Not Applicable

| Frequency<br>(MHz) | Туре | Conducted<br>Power (dBm) | Maximum Tune-<br>up (dBm) | Power<br>Density<br>(mW/cm2) | Limit<br>(mW/cm2) | Result |
|--------------------|------|--------------------------|---------------------------|------------------------------|-------------------|--------|
| 2480               | EDR  | -4.19                    | -4                        | 0.00001                      | 1.0000            | Pass   |
| 2480               | BLE  | -0.27                    | 0                         | 0.00017                      | 1.0000            | Pass   |

Note: The exposure evaluation safety distance is 20cm.



Test Report Number: BTF240219R00201



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

www.btf-lab.com

## --END OF REPORT--