




TEST REPORT

Report Reference No..... : CHTEW19080128 Report verification: 

Project No..... : SHT1907059701EW

FCC ID..... : ZSW-30-091

Applicant's name..... : b mobile HK Limited

Address..... : Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong

Manufacturer..... : b mobile HK Limited

Address..... : Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong

Test item description : Mobile Phone

Trade Mark : Bmobile

Model/Type reference..... : X10

Listed Model(s) : -

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample..... : Jul 19, 2019

Date of testing..... : Jul 20, 2019- Aug 20 , 2019

Date of issue..... : Aug 21 , 2019

Result..... : PASS

Compiled by
(Position+Printed name+Signature): File administrators Silvia Li

Supervised by
(Position+Printed name+Signature): Project Engineer Aaron Fang

Approved by
(Position+Printed name+Signature): RF Manager Hans Hu

Silvia Li

Aaron Fang

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

| | | |
|-----------|--|-----------|
| 1. | TEST STANDARDS AND REPORT VERSION | 3 |
| 1.1. | Test Standards | 3 |
| 1.2. | Report version | 3 |
| 2. | TEST DESCRIPTION | 4 |
| 3. | SUMMARY | 5 |
| 3.1. | Client Information | 5 |
| 3.2. | Product Description | 5 |
| 3.3. | Operation state | 6 |
| 3.4. | EUT configuration | 6 |
| 3.5. | Modifications | 6 |
| 4. | TEST ENVIRONMENT | 7 |
| 4.1. | Address of the test laboratory | 7 |
| 4.2. | Test Facility | 7 |
| 4.3. | Environmental conditions | 8 |
| 4.4. | Statement of the measurement uncertainty | 8 |
| 4.5. | Equipments Used during the Test | 9 |
| 5. | TEST CONDITIONS AND RESULTS | 11 |
| 5.1. | Antenna requirement | 11 |
| 5.2. | Conducted Emissions (AC Main) | 12 |
| 5.3. | Conducted Peak Output Power | 15 |
| 5.4. | 20 dB Bandwidth | 19 |
| 5.5. | Carrier Frequencies Separation | 23 |
| 5.6. | Hopping Channel Number | 25 |
| 5.7. | Dwell Time | 27 |
| 5.8. | Pseudorandom Frequency Hopping Sequence | 34 |
| 5.9. | Restricted band (radiated) | 35 |
| 5.10. | Band edge and Spurious Emissions (conducted) | 37 |
| 5.11. | Spurious Emissions (radiated) | 53 |
| 6. | TEST SETUP PHOTOS | 57 |
| 7. | EXTERANAL AND INTERNAL PHOTOS | 58 |

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 15.247 Meas Guidance v05r01](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

| Revision No. | Date of issue | Description |
|--------------|---------------|-------------|
| N/A | 2019-08-21 | Original |
| | | |
| | | |
| | | |
| | | |

2. TEST DESCRIPTION

| Test Item | Section in CFR 47 | Result | Test Engineer |
|---|-------------------|--------|---------------|
| Antenna Requirement | 15.203/15.247 (c) | PASS | Kang Yang |
| AC Power Line Conducted Emissions | 15.207 | PASS | Kang Yang |
| Conducted Peak Output Power | 15.247 (b)(1) | PASS | Bruce Wong |
| 20 dB Bandwidth | 15.247 (a)(1) | PASS | Bruce Wong |
| Carrier Frequencies Separation | 15.247 (a)(1) | PASS | Bruce Wong |
| Hopping Channel Number | 15.247 (a)(1) | PASS | Bruce Wong |
| Dwell Time | 15.247 (a)(1) | PASS | Bruce Wong |
| Pseudorandom Frequency Hopping Sequence | 15.247(b)(4) | PASS | Bruce Wong |
| Restricted band | 15.247(d)/15.205 | PASS | Tony Duan |
| Radiated Emissions | 15.247(d)/15.209 | PASS | Tony Duan |

Note: The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

| | |
|---------------|---|
| Applicant: | b mobile HK Limited |
| Address: | Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong |
| Manufacturer: | b mobile HK Limited |
| Address: | Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong |

3.2. Product Description

| | |
|----------------------|--|
| Name of EUT: | Mobile Phone |
| Trade Mark: | Bmobile |
| Model No.: | X10 |
| Listed Model(s): | - |
| IMEI: | Conducted: 352378094738832 Radiated: 352378094738857 |
| Power supply: | DC 3.8V |
| Adapter information: | Input:100-240Va.c., 50/60Hz, 0.2A Output:5.0Vd.c., 1.0A |
| Hardware version: | Bmobile_X10_HW_V1.0 |
| Software version: | Bmobile_X10_TEM_MX_V001 |
| Bluetooth | |
| Version: | Supported BT4.0+EDR |
| Modulation: | GFSK, $\pi/4$ DQPSK, 8DPSK |
| Operation frequency: | 2402MHz~2480MHz |
| Channel number: | 79 |
| Channel separation: | 1MHz |
| Antenna type: | PIFA Antenna |
| Antenna gain: | 1.2dBi |

3.3. Operation state

➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

| Channel | Frequency (MHz) |
|---------|-----------------|
| 00 | 2402 |
| 01 | 2403 |
| : | : |
| 39 | 2441 |
| : | : |
| 77 | 2479 |
| 78 | 2480 |

➤ TEST MODE

| |
|--|
| For RF test items: |
| The engineering test program was provided and enabled to make EUT continuous transmit |
| For AC power line conducted emissions: |
| The EUT was set to connect with the Bluetooth instrument under large package sizes transmission. |
| For Radiated suprious emissions test item: |
| The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data recorded in the report. |

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

| | | |
|---|---------------|---|
| / | Manufacturer: | / |
| | Model No.: | / |
| / | Manufacturer: | / |
| | Model No.: | / |

3.5. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

4.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

IC-Registration No.:5377A

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377A.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| | |
|--------------------|-------------|
| Temperature: | 15~35°C |
| Relative Humidity: | 30~60 % |
| Air Pressure: | 950~1050mba |

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

| Test Items | Measurement Uncertainty | Notes |
|---|-------------------------|-------|
| Transmitter power conducted | 0.51 dB | (1) |
| Conducted spurious emissions 9kHz~40GHz | 0.51 dB | (1) |
| Conducted Disturbance 150kHz~30MHz | 3.02 dB | (1) |
| Radiated Emissions below 1GHz | 4.90 dB | (1) |
| Radiated Emissions above 1GHz | 4.96 dB | (1) |
| Occupied Bandwidth | 70 Hz | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$

4.5. Equipments Used during the Test

| ● Conducted Emission | | | | | | |
|----------------------|----------------------------------|--------------------|-----------------|------------|---------------------------|---------------------------|
| Used | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) |
| ● | Shielded Room | Albatross projects | N/A | N/A | 2018/09/28 | 2023/09/27 |
| ● | EMI Test Receiver | R&S | ESCI | 101247 | 2018/10/27 | 2019/10/26 |
| ● | Artificial Mains | SCHWARZBECK | NNLK 8121 | 573 | 2018/10/27 | 2019/10/26 |
| ● | Pulse Limiter | R&S | ESH3-Z2 | 100499 | 2018/10/27 | 2019/10/26 |
| ● | RF Connection Cable | HUBER+SUHNER | EF400 | N/A | 2018/11/15 | 2019/11/14 |
| ● | Test Software | R&S | ES-K1 | N/A | N/A | N/A |
| ○ | Single Balanced Telecom Pair ISN | FCC | FCC-TLISN-T2-02 | 20371 | 2018/10/28 | 2019/10/27 |
| ○ | Two Balanced Telecom Pairs ISN | FCC | FCC-TLISN-T4-02 | 20373 | 2018/10/28 | 2019/10/27 |
| ○ | Four Balanced Telecom Pairs ISN | FCC | FCC-TLISN-T8-02 | 20375 | 2018/10/28 | 2019/10/27 |
| ○ | V-Network | R&S | ESH3-Z6 | 100211 | 2018/10/27 | 2019/10/26 |
| ○ | V-Network | R&S | ESH3-Z6 | 100210 | 2018/10/27 | 2019/10/26 |
| ○ | 2-Line V-Network | R&S | ESH3-Z5 | 100049 | 2018/10/27 | 2019/10/26 |

| ● Radiated Emission-6th test site | | | | | | |
|-----------------------------------|-------------------------|--------------------|--------------|------------|---------------------------|---------------------------|
| Used | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) |
| ● | Semi-Anechoic Chamber | Albatross projects | SAC-3m-02 | N/A | 2018/09/30 | 2021/09/29 |
| ● | EMI Test Receiver | R&S | ESCI | 100900 | 2018/10/28 | 2019/10/27 |
| ● | Loop Antenna | R&S | HFH2-Z2 | 100020 | 2017/11/20 | 2020/11/19 |
| ● | Ultra-Broadband Antenna | SCHWARZBECK | VULB9163 | 546 | 2017/04/05 | 2020/04/04 |
| ● | Pre-Amplifier | SCHWARZBECK | BBV 9742 | N/A | 2018/11/15 | 2019/11/14 |
| ● | RF Connection Cable | HUBER+SUHNER | N/A | N/A | 2018/09/28 | 2019/09/27 |
| ● | RF Connection Cable | HUBER+SUHNER | SUCOFLEX104 | 501184/4 | 2018/09/28 | 2019/09/27 |
| ● | Test Software | R&S | ES-K1 | N/A | N/A | N/A |
| ● | Turntable | Maturo Germany | TT2.0-1T | N/A | N/A | N/A |
| ● | Antenna Mast | Maturo Germany | CAM-4.0-P-12 | N/A | N/A | N/A |

| ● Radiated emission-7th test site | | | | | | |
|-----------------------------------|-------------------------|--------------------|-------------|------------|---------------------------|---------------------------|
| Used | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) |
| ● | Semi-Anechoic Chamber | Albatross projects | SAC-3m-01 | N/A | 2018/09/30 | 2021/09/29 |
| ● | Spectrum Analyzer | R&S | FSP40 | 100597 | 2018/10/27 | 2019/10/26 |
| ● | Horn Antenna | SCHWARZBECK | 9120D | 1011 | 2017/03/27 | 2020/03/26 |
| ● | Pre-amplifier | BONN | BLWA0160-2M | 1811887 | 2018/11/14 | 2019/11/13 |
| ● | Pre-amplifier | CD | PAP-0102 | 12004 | 2018/11/14 | 2019/11/13 |
| ● | Broadband Pre-amplifier | SCHWARZBECK | BBV 9718 | 9718-248 | 2019/04/26 | 2020/04/25 |
| ● | RF Connection Cable | HUBER+SUHNER | RE-7-FH | N/A | 2018/11/15 | 2019/11/14 |
| ● | RF Connection Cable | HUBER+SUHNER | RE-7-FL | N/A | 2018/11/15 | 2019/11/14 |
| ● | Test Software | Audix | E3 | N/A | N/A | N/A |

| | | | | | | |
|---|--------------|----------------|--------------|-----|-----|-----|
| ● | Turntable | Maturo Germany | TT2.0-1T | N/A | N/A | N/A |
| ● | Antenna Mast | Maturo Germany | CAM-4.0-P-12 | N/A | N/A | N/A |

● **RF Conducted Method**

| Used | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) |
|------|------------------------------|--------------|-----------------|------------|------------------------------|------------------------------|
| ● | Signal and spectrum Analyzer | R&S | FSV40 | 100048 | 2018/10/28 | 2019/10/27 |
| ● | Spectrum Analyzer | Agilent | N9020A | MY50510187 | 2018/09/29 | 2019/09/28 |
| ○ | Radio communication tester | R&S | CMW500 | 137688-Lv | 2018/09/29 | 2019/09/28 |
| ○ | Test software | Tonscend | JS1120-1(LTE) | N/A | N/A | N/A |
| ○ | Test software | Tonscend | JS1120-2(WIFI) | N/A | N/A | N/A |
| ○ | Test software | Tonscend | JS1120-3(WCDMA) | N/A | N/A | N/A |
| ○ | Test software | Tonscend | JS1120-4(GSM) | N/A | N/A | N/A |

5. TEST CONDITIONS AND RESULTS

5.1. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Test Result:

☒ **Passed** ☐ **Not Applicable**

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. Conducted Emissions (AC Main)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

| Frequency range (MHz) | Limit (dBuV) | |
|-----------------------|--------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS


☒ Passed ☐ Not Applicable

Note:

- 1) Transd= Cable lose + Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit - Level

Test Line:

L

**MEASUREMENT RESULT: "GM1907225021_fin"**

7/22/2019 2:06PM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.514500 | 45.50 | 9.9 | 56 | 10.5 | QP | L1 | GND |
| 0.519000 | 43.50 | 9.9 | 56 | 12.5 | QP | L1 | GND |
| 1.185000 | 42.90 | 9.9 | 56 | 13.1 | QP | L1 | GND |
| 4.924500 | 40.50 | 10.0 | 56 | 15.5 | QP | L1 | GND |
| 5.145000 | 22.20 | 10.0 | 60 | 37.8 | QP | L1 | GND |
| 15.162000 | 36.40 | 10.2 | 60 | 23.6 | QP | L1 | GND |


MEASUREMENT RESULT: "GM1907225021_fin2"

7/22/2019 2:06PM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.357000 | 28.30 | 9.9 | 49 | 20.5 | AV | L1 | GND |
| 0.514500 | 31.80 | 9.9 | 46 | 14.2 | AV | L1 | GND |
| 1.243500 | 29.70 | 9.9 | 46 | 16.3 | AV | L1 | GND |
| 4.996500 | 28.40 | 10.0 | 46 | 17.6 | AV | L1 | GND |
| 5.131500 | 26.50 | 10.0 | 50 | 23.5 | AV | L1 | GND |
| 15.211500 | 25.40 | 10.2 | 50 | 24.6 | AV | L1 | GND |

Test Line:

N

**MEASUREMENT RESULT: "GM1907225020_fin"**

7/22/2019 2:03PM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.177000 | 38.20 | 9.9 | 65 | 26.4 | QP | N | GND |
| 0.294000 | 41.30 | 9.9 | 60 | 19.1 | QP | N | GND |
| 0.501000 | 27.70 | 9.9 | 56 | 28.3 | QP | N | GND |
| 0.591000 | 42.10 | 9.9 | 56 | 13.9 | QP | N | GND |
| 0.888000 | 39.80 | 9.9 | 56 | 16.2 | QP | N | GND |
| 4.942500 | 34.30 | 10.0 | 56 | 21.7 | QP | N | GND |

MEASUREMENT RESULT: "GM1907225020_fin2"

7/22/2019 2:03PM

| Frequency MHz | Level dBμV | Transd dB | Limit dBμV | Margin dB | Detector | Line | PE |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.177000 | 37.40 | 9.9 | 55 | 17.2 | AV | N | GND |
| 0.591000 | 29.60 | 9.9 | 46 | 16.4 | AV | N | GND |
| 0.964500 | 22.50 | 9.9 | 46 | 23.5 | AV | N | GND |
| 2.368500 | 21.90 | 9.9 | 46 | 24.1 | AV | N | GND |
| 5.181000 | 18.30 | 10.0 | 50 | 31.7 | AV | N | GND |
| 17.236500 | 19.00 | 10.2 | 50 | 31.0 | AV | N | GND |

5.3. Conducted Peak Output Power


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1):

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.

For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the pathloss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
 Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 RBW \geq the 20 dB bandwidth of the emission being measured, VBW \geq RBW
 Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.


TEST MODE:


Please refer to the clause 3.3


TEST RESULTS

☒ Passed ☐ Not Applicable

| Modulation type | Channel | Peak Output power (dBm) | Average Output power (dBm) | Limit (dBm) | Result |
|-----------------|---------|-------------------------|----------------------------|--------------|--------|
| GFSK | 00 | 4.97 | 4.90 | ≤ 30.00 | Pass |
| | 39 | 6.55 | 6.48 | | |
| | 78 | 4.86 | 4.81 | | |
| $\pi/4$ DQPSK | 00 | 4.26 | 3.72 | ≤ 21.00 | Pass |
| | 39 | 5.78 | 5.19 | | |
| | 78 | 4.17 | 3.64 | | |
| 8DPSK | 00 | 4.42 | 3.71 | ≤ 21.00 | Pass |
| | 39 | 5.95 | 5.21 | | |
| | 78 | 4.32 | 3.63 | | |








5.4. 20 dB Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.


TEST MODE:


Please refer to the clause 3.3


TEST RESULTS

☒ Passed ☐ Not Applicable

| Modulation type | Channel | 20 dB Bandwidth (MHz) | Limit (MHz) | Result |
|-----------------|---------|-----------------------|-------------|--------|
| GFSK | 00 | 0.93 | - | Pass |
| | 39 | 0.93 | | |
| | 78 | 0.93 | | |
| $\pi/4$ DQPSK | 00 | 1.30 | - | Pass |
| | 39 | 1.29 | | |
| | 78 | 1.30 | | |
| 8DPSK | 00 | 1.29 | - | Pass |
| | 39 | 1.29 | | |
| | 78 | 1.29 | | |








5.5. Carrier Frequencies Separation

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels
RBW \geq 1% of the span, VBW \geq RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable


| Modulation type | Channel | Carrier Frequencies Separation (MHz) | Limit (MHz) * | Result |
|-----------------|---------|--------------------------------------|---------------|--------|
| GFSK | 39 | 1.00 | ≥ 0.93 | Pass |
| $\pi/4$ DQPSK | 39 | 1.00 | ≥ 0.87 | Pass |
| 8DPSK | 39 | 1.00 | ≥ 0.86 | Pass |

Note:

*: GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the section 5.4.

$\pi/4$ DQPSK limit = $2/3$ * The maximum 20 dB Bandwidth for $\pi/4$ DQPSK modulation on the section 5.4.

8DPSK limit = $2/3$ * The maximum 20 dB Bandwidth for 8DPSK modulation on the section 5.4




5.6. Hopping Channel Number

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW \geq 1% of the span, VBW \geq RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:



Please refer to the clause 3.3

TEST RESULTS


☒ Passed ☐ Not Applicable

| Modulation type | Channel number | Limit | Result |
|-----------------|----------------|--------------|--------|
| GFSK | 79 | ≥ 15.00 | Pass |
| $\pi/4$ DQPSK | 79 | | |
| 8DPSK | 79 | | |

GFSK

 $\pi/4$ DQPSK

8DPSK




5.7. Dwell Time

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): The average time of occupancy on any channel shall not be greater than 0.4 seconds within a pe-riod of 0.4 seconds multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW \geq RBW
Sweep = as necessary to capture the entire dwell time per hopping channel,
Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS


☒ Passed ☐ Not Applicable

| Modulation type | Channel | Burst Width [ms/hop/ch] | Total Hops[hop*ch] | Dwell time (Second) | Limit (Second) | Result |
|-----------------|---------|-------------------------|--------------------|---------------------|----------------|--------|
| GFSK | DH1 | 0.38 | 315.00 | 0.12 | ≤ 0.40 | Pass |
| | DH3 | 1.63 | 162.00 | 0.26 | | |
| | DH5 | 2.88 | 107.00 | 0.31 | | |
| $\pi/4$ DQPSK | 2DH1 | 0.39 | 315.00 | 0.12 | ≤ 0.40 | Pass |
| | 2DH3 | 1.64 | 162.00 | 0.27 | | |
| | 2DH5 | 2.88 | 112.00 | 0.32 | | |
| 8DPSK | 3DH1 | 0.39 | 317.00 | 0.12 | ≤ 0.40 | Pass |
| | 3DH3 | 1.63 | 158.00 | 0.26 | | |
| | 3DH5 | 2.89 | 117.00 | 0.34 | | |


DH3
Burst number




DH5
Burst width




DH5
Burst number







2DH3
Burst number




2DH5
Burst width




2DH5
Burst number







3DH3
Burst number



3DH5
Burst width



3DH5
Burst number



5.8. Pseudorandom Frequency Hopping Sequence


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo-randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally on the average by each transmitter.

The system receiver has input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.


5.9. Restricted band (radiated)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
RBW=1 MHz, VBW=3 MHz Peak detector for Peak value
RBW=1 MHz, VBW=10 Hz Peak detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Note:

- 1) Final level= Read level + Factor.
- 2) Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.
- 3) The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.

| Test channel: | | | | CH00 | | | |
|-----------------|-------------------|---------------|----------------|---------------------|-------------|--------------|------------|
| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Margin (dB) | Polarization | Test value |
| 2310.00 | 53.05 | -2.34 | 50.71 | 74.00 | 23.29 | Horizontal | Peak |
| 2390.00 | 53.67 | -2.41 | 51.26 | 74.00 | 22.74 | Horizontal | Peak |
| 2310.00 | 52.31 | -2.34 | 49.97 | 74.00 | 24.03 | Vertical | Peak |
| 2390.00 | 52.24 | -2.41 | 49.83 | 74.00 | 24.17 | Vertical | Peak |
| 2310.00 | 42.29 | -2.34 | 39.95 | 54.00 | 14.05 | Horizontal | Average |
| 2390.00 | 41.81 | -2.41 | 39.40 | 54.00 | 14.60 | Horizontal | Average |
| 2310.00 | 42.28 | -2.34 | 39.94 | 54.00 | 14.06 | Vertical | Average |
| 2390.00 | 41.86 | -2.41 | 39.45 | 54.00 | 14.55 | Vertical | Average |

| Test channel: | | | | CH78 | | | |
|-----------------|-------------------|---------------|----------------|---------------------|-------------|--------------|------------|
| Frequency (MHz) | Read Level (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Margin (dB) | Polarization | Test value |
| 2483.50 | 59.19 | -2.15 | 57.04 | 74.00 | 16.96 | Horizontal | Peak |
| 2500.00 | 53.13 | -2.10 | 51.03 | 74.00 | 22.97 | Horizontal | Peak |
| 2483.50 | 58.29 | -2.15 | 56.14 | 74.00 | 17.86 | Vertical | Peak |
| 2500.00 | 52.54 | -2.10 | 50.44 | 74.00 | 23.56 | Vertical | Peak |
| 2483.50 | 48.39 | -2.15 | 46.24 | 54.00 | 7.76 | Horizontal | Average |
| 2500.00 | 42.06 | -2.10 | 39.96 | 54.00 | 14.04 | Horizontal | Average |
| 2483.50 | 46.28 | -2.15 | 44.13 | 54.00 | 9.87 | Vertical | Average |
| 2500.00 | 42.07 | -2.10 | 39.97 | 54.00 | 14.03 | Vertical | Average |

5.10. Band edge and Spurious Emissions (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
RBW = 100 kHz, VBW \geq RBW, scan up through 10th harmonic.
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable




CH78
Hopping mode




| Test Item: | Band edge | Modulation type: | $\pi/4$ DQPSK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------------------|--|------------------|---------------|------------|----------|-----------------|---------|---------|----------|-----------------|----|---|--|--------------|----------|--|--|----|---|--|------------|------------|--|--|----|---|--|----------|------------|--|--|----|---|--|--------------|------------|--|--|----|---|--|--------------|------------|--|--|
| CH00 No hopping mode | <div><div>Spectrum</div><div><div>Ref Level 20.00 dBm</div><div>Offset 1.00 dB</div><div>RBW 100 kHz</div><div>Att 30 dB</div><div>SWT 1.1 ms</div><div>VBW 300 kHz</div><div>Mode Auto Sweep</div><div>Count 500/500</div></div><div><div>1PK Max</div><div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>M1[1]</div><div>M2[1]</div><div>M3</div><div>M4</div></div><div><div>3.10 dBm</div><div>2.402180 GHz</div><div>-51.02 dBm</div><div>2.400000 GHz</div></div></div><div><div>Start 2.31 GHz</div><div>691 pts</div><div>Stop 2.405 GHz</div></div><div><div>Marker</div><table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.40218 GHz</td><td>3.10 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-51.02 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-55.37 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-55.81 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.399906 GHz</td><td>-52.05 dBm</td><td></td><td></td></tr></tbody></table></div></div> <div>Date: 25 JUL 2019 09:27:45</div> | | | Type | Ref | Trc | X-value | Y-value | Function | Function Result | M1 | 1 | | 2.40218 GHz | 3.10 dBm | | | M2 | 1 | | 2.4 GHz | -51.02 dBm | | | M3 | 1 | | 2.39 GHz | -55.37 dBm | | | M4 | 1 | | 2.31 GHz | -55.81 dBm | | | M5 | 1 | | 2.399906 GHz | -52.05 dBm | | |
| Type | Ref | Trc | X-value | Y-value | Function | Function Result | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M1 | 1 | | 2.40218 GHz | 3.10 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M2 | 1 | | 2.4 GHz | -51.02 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M3 | 1 | | 2.39 GHz | -55.37 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M4 | 1 | | 2.31 GHz | -55.81 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M5 | 1 | | 2.399906 GHz | -52.05 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CH00 Hopping mode | <div><div>Spectrum</div><div><div>Ref Level 20.00 dBm</div><div>Offset 1.00 dB</div><div>RBW 100 kHz</div><div>Att 30 dB</div><div>SWT 1.1 ms</div><div>VBW 300 kHz</div><div>Mode Auto Sweep</div><div>Count 500/500</div></div><div><div>1PK Max</div><div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>M1[1]</div><div>M2[1]</div><div>M3</div><div>M4</div></div><div><div>3.13 dBm</div><div>2.404930 GHz</div><div>-51.95 dBm</div><div>2.400000 GHz</div></div></div><div><div>Start 2.31 GHz</div><div>691 pts</div><div>Stop 2.405 GHz</div></div><div><div>Marker</div><table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.40493 GHz</td><td>3.13 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-51.95 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-55.36 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-55.24 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.399768 GHz</td><td>-52.71 dBm</td><td></td><td></td></tr></tbody></table></div></div> <div>Date: 25 JUL 2019 09:44:56</div> | | | Type | Ref | Trc | X-value | Y-value | Function | Function Result | M1 | 1 | | 2.40493 GHz | 3.13 dBm | | | M2 | 1 | | 2.4 GHz | -51.95 dBm | | | M3 | 1 | | 2.39 GHz | -55.36 dBm | | | M4 | 1 | | 2.31 GHz | -55.24 dBm | | | M5 | 1 | | 2.399768 GHz | -52.71 dBm | | |
| Type | Ref | Trc | X-value | Y-value | Function | Function Result | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M1 | 1 | | 2.40493 GHz | 3.13 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M2 | 1 | | 2.4 GHz | -51.95 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M3 | 1 | | 2.39 GHz | -55.36 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M4 | 1 | | 2.31 GHz | -55.24 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M5 | 1 | | 2.399768 GHz | -52.71 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CH78 No hopping mode | <div><div>Spectrum</div><div><div>Ref Level 20.00 dBm</div><div>Offset 1.00 dB</div><div>RBW 100 kHz</div><div>Att 30 dB</div><div>SWT 56.9 μs</div><div>VBW 300 kHz</div><div>Mode Auto FFT</div><div>Count 500/500</div></div><div><div>1PK Max</div><div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>M1[1]</div><div>M2[1]</div><div>M3</div><div>M4</div></div><div><div>3.46 dBm</div><div>2.4798310 GHz</div><div>-56.62 dBm</div><div>2.46350000 GHz</div></div></div><div><div>Start 2.478 GHz</div><div>691 pts</div><div>Stop 2.5 GHz</div></div><div><div>Marker</div><table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.479831 GHz</td><td>3.46 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-56.62 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-59.72 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.496971 GHz</td><td>-56.70 dBm</td><td></td><td></td></tr></tbody></table></div></div> <div>Date: 25 JUL 2019 09:30:45</div> | | | Type | Ref | Trc | X-value | Y-value | Function | Function Result | M1 | 1 | | 2.479831 GHz | 3.46 dBm | | | M2 | 1 | | 2.4835 GHz | -56.62 dBm | | | M3 | 1 | | 2.5 GHz | -59.72 dBm | | | M4 | 1 | | 2.496971 GHz | -56.70 dBm | | | | | | | | | |
| Type | Ref | Trc | X-value | Y-value | Function | Function Result | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M1 | 1 | | 2.479831 GHz | 3.46 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M2 | 1 | | 2.4835 GHz | -56.62 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M3 | 1 | | 2.5 GHz | -59.72 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M4 | 1 | | 2.496971 GHz | -56.70 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |




CH78
Hopping mode




| Test Item: | Band edge | Modulation type: | 8DPSK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-------------------------|---|------------------|---------------|------------|----------|-----------------|---------|---------|----------|-----------------|----|---|--|--------------|----------|--|--|----|---|--|------------|------------|--|--|----|---|--|----------|------------|--|--|----|---|--|---------------|------------|--|--|----|---|--|--------------|------------|--|--|
| CH00 No hopping mode | <div><div>Spectrum</div><div><div>Ref Level 20.00 dBm Att 30 dB Count 500/500</div><div>Offset 1.00 dB SWT 1.1 ms Mode Auto Sweep</div><div>RBW 100 kHz VBW 300 kHz</div></div><div><div>1Pk Max</div><div><div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>M1[1]</div><div>M2[1]</div><div>D1 -16.790 dBm</div><div>M3</div><div>M5</div></div><div><div>3.21 dBm</div><div>2.401770 GHz</div><div>-51.22 dBm</div><div>2.400000 GHz</div></div></div><div><div>Start 2.31 GHz</div><div>691 pts</div><div>Stop 2.405 GHz</div></div><div><div>Marker</div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.40177 GHz</td><td>3.21 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-51.22 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-56.20 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-55.49 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.399906 GHz</td><td>-50.77 dBm</td><td></td><td></td></tr></table></div></div><div>Date: 25 JUL 2019 09:32:26</div></div> | | | Type | Ref | Trc | X-value | Y-value | Function | Function Result | M1 | 1 | | 2.40177 GHz | 3.21 dBm | | | M2 | 1 | | 2.4 GHz | -51.22 dBm | | | M3 | 1 | | 2.39 GHz | -56.20 dBm | | | M4 | 1 | | 2.31 GHz | -55.49 dBm | | | M5 | 1 | | 2.399906 GHz | -50.77 dBm | | |
| Type | Ref | Trc | X-value | Y-value | Function | Function Result | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M1 | 1 | | 2.40177 GHz | 3.21 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M2 | 1 | | 2.4 GHz | -51.22 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M3 | 1 | | 2.39 GHz | -56.20 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M4 | 1 | | 2.31 GHz | -55.49 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M5 | 1 | | 2.399906 GHz | -50.77 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CH00 Hopping mode | <div><div>Spectrum</div><div><div>Ref Level 20.00 dBm Att 30 dB Count 500/500</div><div>Offset 1.00 dB SWT 1.1 ms Mode Auto Sweep</div><div>RBW 100 kHz VBW 300 kHz</div></div><div><div>1Pk Max</div><div><div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>M1[1]</div><div>M2[1]</div><div>D1 -17.540 dBm</div><div>M3</div><div>M5</div></div><div><div>2.46 dBm</div><div>2.403830 GHz</div><div>-51.26 dBm</div><div>2.400000 GHz</div></div></div><div><div>Start 2.31 GHz</div><div>691 pts</div><div>Stop 2.405 GHz</div></div><div><div>Marker</div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.40383 GHz</td><td>2.46 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-51.26 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-55.25 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-54.22 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.398804 GHz</td><td>-52.46 dBm</td><td></td><td></td></tr></table></div></div><div>Date: 25 JUL 2019 09:49:40</div></div> | | | Type | Ref | Trc | X-value | Y-value | Function | Function Result | M1 | 1 | | 2.40383 GHz | 2.46 dBm | | | M2 | 1 | | 2.4 GHz | -51.26 dBm | | | M3 | 1 | | 2.39 GHz | -55.25 dBm | | | M4 | 1 | | 2.31 GHz | -54.22 dBm | | | M5 | 1 | | 2.398804 GHz | -52.46 dBm | | |
| Type | Ref | Trc | X-value | Y-value | Function | Function Result | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M1 | 1 | | 2.40383 GHz | 2.46 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M2 | 1 | | 2.4 GHz | -51.26 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M3 | 1 | | 2.39 GHz | -55.25 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M4 | 1 | | 2.31 GHz | -54.22 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M5 | 1 | | 2.398804 GHz | -52.46 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CH78 No hopping mode | <div><div>Spectrum</div><div><div>Ref Level 20.00 dBm Att 30 dB Count 500/500</div><div>Offset 1.00 dB SWT 56.9 μs Mode Auto FFT</div><div>RBW 100 kHz VBW 300 kHz</div></div><div><div>1Pk Max</div><div><div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>M1[1]</div><div>M2[1]</div><div>D1 -16.550 dBm</div><div>M2</div><div>M4</div></div><div><div>3.45 dBm</div><div>2.4801490 GHz</div><div>-57.29 dBm</div><div>2.4835000 GHz</div></div></div><div><div>Start 2.478 GHz</div><div>691 pts</div><div>Stop 2.5 GHz</div></div><div><div>Marker</div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.480149 GHz</td><td>3.45 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-57.29 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-59.20 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.4894783 GHz</td><td>-56.89 dBm</td><td></td><td></td></tr></table></div></div><div>Date: 25 JUL 2019 09:37:05</div></div> | | | Type | Ref | Trc | X-value | Y-value | Function | Function Result | M1 | 1 | | 2.480149 GHz | 3.45 dBm | | | M2 | 1 | | 2.4835 GHz | -57.29 dBm | | | M3 | 1 | | 2.5 GHz | -59.20 dBm | | | M4 | 1 | | 2.4894783 GHz | -56.89 dBm | | | | | | | | | |
| Type | Ref | Trc | X-value | Y-value | Function | Function Result | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M1 | 1 | | 2.480149 GHz | 3.45 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M2 | 1 | | 2.4835 GHz | -57.29 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M3 | 1 | | 2.5 GHz | -59.20 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| M4 | 1 | | 2.4894783 GHz | -56.89 dBm | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

CH78
Hoppig mode




| Test Item: | SE | Modulation type: | GFSK |
|-------------------------|--|------------------|------|
| CH00 Reference level |  <p>4.08 dBm 2.402000 GHz</p> <p>CF 2.402 GHz 691 pts Span 30.0 MHz</p> <p>Date: 25 JUL 2019 09:22:22</p> | | |
| CH00 30MHz~1000MHz |  <p>-52.72 dBm 864.1240 MHz</p> <p>-15.920 dBm</p> <p>Start 30.0 MHz 30001 pts Stop 1.0 GHz</p> <p>Date: 25 JUL 2019 09:22:08</p> | | |
| CH00 1GHz~26GHz |  <p>-44.00 dBm 16.438333 GHz</p> <p>-15.920 dBm</p> <p>Start 1.0 GHz 30001 pts Stop 26.0 GHz</p> <p>Date: 25 JUL 2019 09:22:54</p> | | |


CH39
Reference level




CH39
30MHz~1000MHz




CH39
1GHz~26GHz




CH78
Reference level



CH78
30MHz~1000MHz




CH78
1GHz~26GHz




| Test Item: | SE | Modulation type: | $\pi/4$ DQPSK |
|-------------------------|--|------------------|---------------|
| CH00 Reference level | <p>Spectrum</p> <p>Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100</p> <p>1Pk Max</p> <p>M1[1] 1.87 dBm 2.4018260 GHz</p> <p>CF 2.402 GHz 691 pts Span 30.0 MHz</p> <p>Date: 25 JUL 2019 09:27:51</p> | | |
| CH00 30MHz~1000MHz | <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10</p> <p>1Pk Max</p> <p>M1[1] -51.76 dBm 963.0930 MHz</p> <p>D1 -19.130 dBm</p> <p>Start 30.0 MHz 30001 pts Stop 1.0 GHz</p> <p>Date: 25 JUL 2019 09:28:07</p> | | |
| CH00 1GHz~26GHz | <p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10</p> <p>1Pk Max</p> <p>M1[1] -44.75 dBm 15.687500 GHz</p> <p>D1 -19.130 dBm</p> <p>Start 1.0 GHz 30001 pts Stop 26.0 GHz</p> <p>Date: 25 JUL 2019 09:28:25</p> | | |


CH39
Reference level




CH39
30MHz~1000MHz




CH39
1GHz~26GHz




CH78
Reference level



CH78
30MHz~1000MHz




CH78
1GHz~26GHz




| Test Item: | SE | Modulation type: | 8DPSK |
|-------------------------|---|------------------|-------|
| CH00 Reference level | <div><div>Spectrum</div><div><div>Ref Level 21.00 dBm</div><div>Offset 1.00 dB</div><div>RBW 100 kHz</div><div>Att 30 dB</div><div>SWT 75.9 μs</div><div>VBW 300 kHz</div><div>Mode Auto FFT</div><div>Count 100/100</div></div><div><div>1Pk Max:</div><div><div>M1[1]</div><div>2.25 dBm</div><div>2.4021740 GHz</div></div><div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>CF 2.402 GHz</div><div>691 pts</div><div>Span 30.0 MHz</div></div></div><div>Date: 25 JUL 2019 09:32:02</div></div> | | |
| CH00 30MHz~1000MHz | <div><div>Spectrum</div><div><div>Ref Level 20.00 dBm</div><div>Offset 1.00 dB</div><div>RBW 100 kHz</div><div>Att 30 dB</div><div>SWT 30.1 ms</div><div>VBW 300 kHz</div><div>Mode Auto Sweep</div><div>Count 10/10</div></div><div><div>1Pk Max:</div><div><div>M1[1]</div><div>-52.62 dBm</div><div>524.2150 MHz</div></div><div><div>D1 -17.750 dBm</div></div><div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>Start 30.0 MHz</div><div>30001 pts</div><div>Stop 1.0 GHz</div></div></div><div>Date: 25 JUL 2019 09:32:49</div></div> | | |
| CH00 1GHz~26GHz | <div><div>Spectrum</div><div><div>Ref Level 20.00 dBm</div><div>Offset 1.00 dB</div><div>RBW 100 kHz</div><div>Att 30 dB</div><div>SWT 250 ms</div><div>VBW 300 kHz</div><div>Mode Auto Sweep</div><div>Count 10/10</div></div><div><div>1Pk Max:</div><div><div>M1[1]</div><div>-44.45 dBm</div><div>15.280000 GHz</div></div><div><div>D1 -17.750 dBm</div></div><div><div>10 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>Start 1.0 GHz</div><div>30001 pts</div><div>Stop 26.0 GHz</div></div></div><div>Date: 25 JUL 2019 09:33:07</div></div> | | |


CH39
Reference level




CH39
30MHz~1000MHz




CH39
1GHz~26GHz




CH78
Reference level



CH78
30MHz~1000MHz



CH78
1GHz~26GHz



5.11. Spurious Emissions (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


| Frequency | Limit (dBuV/m @3m) | Value |
|-------------------|--------------------|------------|
| 30 MHz ~ 88 MHz | 40.00 | Quasi-peak |
| 88 MHz ~ 216 MHz | 43.50 | Quasi-peak |
| 216 MHz ~ 960 MHz | 46.00 | Quasi-peak |
| 960 MHz ~ 1 GHz | 54.00 | Quasi-peak |
| Above 1 GHz | 54.00 | Average |
| | 74.00 | Peak |

TEST CONFIGURATION


- Below 30 MHz



- 30 MHz ~1000 MHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10:2013.
2. The EUT is placed on a turn table with 0.8 meter above ground for below 1GHz, 1.5 meter above ground for above 1GHz.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
 - RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
 - If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
 - RBW=1 MHz, VBW=3 MHz Peak detector for Peak value
 - RBW=1 MHz, VBW=10 Hz Peak detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

Note:

- 1) Final Level = Receiver Read level + Factor.
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3) Below 1 GHz, Have pre-scan all modulation mode, found the GFSK modulation High channel which it was worst case, so only the worst case's data on the test report.
- 4) Above 1 GHz, Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report
- 5) The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.


➤ 9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

➤ 30 MHz ~ 1 GHz

Polarization:

Vertical


**MEASUREMENT RESULT: "GM1907246123_red"**

7/24/2019 10:12PM

| Frequency MHz | Level dBμV/m | Transd dB | Limit dBμV/m | Margin dB | Det. | Height cm | Azimuth deg | Polarization |
|------------------|-----------------|--------------|-----------------|--------------|------|--------------|----------------|--------------|
| 51.340000 | 23.60 | -4.9 | 40.0 | 16.4 | QP | 100.0 | 62.00 | VERTICAL |
| 61.040000 | 21.80 | -6.4 | 40.0 | 18.2 | QP | 100.0 | 45.00 | VERTICAL |
| 97.900000 | 21.20 | -6.9 | 43.5 | 22.3 | QP | 100.0 | 72.00 | VERTICAL |
| 307.420000 | 23.80 | -3.4 | 46.0 | 22.2 | QP | 100.0 | 85.00 | VERTICAL |
| 534.400000 | 30.00 | 2.6 | 46.0 | 16.0 | QP | 100.0 | 22.00 | VERTICAL |
| 945.680000 | 39.30 | 10.8 | 46.0 | 6.7 | QP | 100.0 | 313.00 | VERTICAL |

Polarization:

Horizontal

**MEASUREMENT RESULT: "GM1907246122_red"**

7/24/2019 10:10PM

| Frequency MHz | Level dBμV/m | Transd dB | Limit dBμV/m | Margin dB | Det. | Height cm | Azimuth deg | Polarization |
|------------------|-----------------|--------------|-----------------|--------------|------|--------------|----------------|--------------|
| 45.520000 | 23.60 | -4.9 | 40.0 | 16.4 | QP | 100.0 | 320.00 | HORIZONTAL |
| 55.220000 | 22.30 | -5.3 | 40.0 | 17.7 | QP | 100.0 | 320.00 | HORIZONTAL |
| 107.600000 | 20.20 | -6.8 | 43.5 | 23.3 | QP | 100.0 | 320.00 | HORIZONTAL |
| 297.720000 | 24.40 | -3.5 | 46.0 | 21.6 | QP | 100.0 | 161.00 | HORIZONTAL |
| 546.040000 | 29.90 | 2.9 | 46.0 | 16.1 | QP | 100.0 | 109.00 | HORIZONTAL |
| 922.400000 | 39.20 | 10.7 | 46.0 | 6.8 | QP | 100.0 | 14.00 | HORIZONTAL |

➤ 1 GHz ~ 25 GHz

| CH00 | | | | | | | |
|-----------------|---------------------|---------------|----------------|---------------------|-------------|--------------|------------|
| Frequency (MHz) | Read Level (dBuV/m) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Margin (dB) | Polarization | Test value |
| 1220.312 | 37.01 | -5.78 | 31.23 | 74.00 | 42.77 | Vertical | Peak |
| 3043.031 | 37.33 | 0.07 | 37.40 | 74.00 | 36.60 | Vertical | Peak |
| 5257.906 | 33.56 | 8.67 | 42.23 | 74.00 | 31.77 | Vertical | Peak |
| 7205.468 | 34.60 | 15.99 | 50.59 | 74.00 | 23.41 | Vertical | Peak |
| 1259.968 | 36.10 | -5.67 | 30.43 | 74.00 | 43.57 | Horizontal | Peak |
| 3068.000 | 36.44 | 0.18 | 36.62 | 74.00 | 37.38 | Horizontal | Peak |
| 5225.593 | 32.28 | 8.84 | 41.12 | 74.00 | 32.88 | Horizontal | Peak |
| 7205.468 | 39.38 | 15.99 | 55.37 | 74.00 | 18.63 | Horizontal | Peak |
| 7205.468 | 32.77 | 15.99 | 48.76 | 54.00 | 5.24 | Horizontal | Average |

| CH39 | | | | | | | |
|-----------------|---------------------|---------------|----------------|---------------------|-------------|--------------|------------|
| Frequency (MHz) | Read Level (dBuV/m) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Margin (dB) | Polarization | Test value |
| 1221.781 | 37.41 | -5.77 | 31.64 | 74.00 | 42.36 | Vertical | Peak |
| 3204.593 | 36.70 | 0.79 | 37.49 | 74.00 | 36.51 | Vertical | Peak |
| 5094.875 | 32.46 | 8.75 | 41.21 | 74.00 | 32.79 | Vertical | Peak |
| 8017.687 | 31.99 | 18.22 | 50.21 | 74.00 | 23.79 | Vertical | Peak |
| 1214.437 | 36.60 | -5.79 | 30.81 | 74.00 | 43.19 | Horizontal | Peak |
| 3178.156 | 36.16 | 0.73 | 36.89 | 74.00 | 37.11 | Horizontal | Peak |
| 5288.750 | 32.59 | 8.51 | 41.10 | 74.00 | 32.90 | Horizontal | Peak |
| 7322.968 | 36.75 | 16.12 | 52.87 | 74.00 | 21.13 | Horizontal | Peak |


| CH78 | | | | | | | |
|-----------------|---------------------|---------------|----------------|---------------------|-------------|--------------|------------|
| Frequency (MHz) | Read Level (dBuV/m) | Factor (dB/m) | Level (dBuV/m) | Limit Line (dBuV/m) | Margin (dB) | Polarization | Test value |
| 1161.562 | 37.47 | -6.24 | 31.23 | 74.00 | 42.77 | Vertical | Peak |
| 3197.250 | 36.41 | 0.83 | 37.24 | 74.00 | 36.76 | Vertical | Peak |
| 5196.218 | 32.24 | 8.97 | 41.21 | 74.00 | 32.79 | Vertical | Peak |
| 8041.187 | 31.41 | 18.25 | 49.66 | 74.00 | 24.34 | Vertical | Peak |
| 1214.437 | 36.94 | -5.79 | 31.15 | 74.00 | 42.85 | Horizontal | Peak |
| 3188.437 | 35.88 | 0.78 | 36.66 | 74.00 | 37.34 | Horizontal | Peak |
| 5140.406 | 31.77 | 8.87 | 40.64 | 74.00 | 33.36 | Horizontal | Peak |
| 7440.468 | 33.18 | 16.39 | 49.57 | 74.00 | 24.43 | Horizontal | Peak |

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit (54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.


6. TEST SETUP PHOTOS

Conducted Emissions (AC Mains)



Radiated Emissions





7. EXTERANAL AND INTERNAL PHOTOS

Reference to the test report No. CHTEW19080125

-----End of Report-----