

FCC Part 15E Measurement and Test Report

For

Motic china group Co.,Ltd.

Motic BLDG, TORCH HI-TECH INDUSTRIAL DEV ZONE

XIAMEN FUJIAN, CHINA, 361006

FCC ID: PVEMT-1001

FCC Rule(s):	<u>FCC Part 15E</u>	
Product Description:	<u>Tablet PC</u>	
Tested Model:	<u>MT-1001</u>	
Report No.:	<u>STR17028189I-2</u>	
Tested Date:	<u>2017-02-25 to 2017-03-30</u>	
Issued Date:	<u>2017-07-01</u>	
Tested By:	<u>Neil Wong / Engineer</u>	<i>Neil Wong</i>
Reviewed By:	<u>Silin Chen / EMC Manager</u>	<i>Silin Chen</i>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>	<i>Jandy So</i>
Prepared By:		

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING	5
1.5 EUT OPERATING DURING TEST	6
1.6 TEST FACILITY	6
1.7 EUT SETUP AND TEST MODE.....	6
1.8 MEASUREMENT UNCERTAINTY	7
1.9 TEST EQUIPMENT LIST AND DETAILS	7
2. SUMMARY OF TEST RESULTS	8
3. RF EXPOSURE	9
3.1 STANDARD APPLICABLE.....	9
3.2 TEST RESULT.....	9
4. ANTENNA REQUIREMENT	10
4.1 STANDARD APPLICABLE.....	10
4.2 EVALUATION INFORMATION	10
5. CONDUCTED EMISSIONS	11
5.1 TEST PROCEDURE.....	11
5.3 BASIC TEST SETUP BLOCK DIAGRAM.....	11
5.4 ENVIRONMENTAL CONDITIONS	12
5.5 TEST RECEIVER SETUP	12
5.6 SUMMARY OF TEST RESULTS/PLOTS	12
5.7 CONDUCTED EMISSIONS TEST DATA.....	12
6. POWER SPECTRAL DENSITY	15
6.1 STANDARD APPLICABLE.....	15
6.2 TEST PROCEDURE.....	15
6.3 ENVIRONMENTAL CONDITIONS	16
6.4 SUMMARY OF TEST RESULTS/PLOTS	16
7. EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH.....	36
7.1 STANDARD APPLICABLE.....	36
7.2 TEST PROCEDURE.....	36
7.3 ENVIRONMENTAL CONDITIONS	38
7.4 SUMMARY OF TEST RESULTS/PLOTS	38
8. MAXIMUM CONDUCTED OUTPUT POWER.....	68
8.1 STANDARD APPLICABLE.....	68
8.2 TEST PROCEDURE.....	68
8.3 ENVIRONMENTAL CONDITIONS	69
8.4 SUMMARY OF TEST RESULTS/PLOTS	69
9. CONDUCTED SPURIOUS EMISSIONS	88
9.1 STANDARD APPLICABLE.....	88
9.2 TEST PROCEDURE.....	88
9.3 ENVIRONMENTAL CONDITIONS	88
9.4 SUMMARY OF TEST RESULTS/PLOTS	88
10. RADIATED SPURIOUS EMISSIONS.....	125
10.1 STANDARD APPLICABLE.....	125
10.2 TEST PROCEDURE.....	125
10.3 TEST RECEIVER SETUP	126
10.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	126
10.5 ENVIRONMENTAL CONDITIONS	126
10.6 SUMMARY OF TEST RESULTS/PLOTS	127
11. FREQUENCY STABILITY	143
11.1 STANDARD APPLICABLE.....	143

11.2 TEST PROCEDURE.....	143
11.3 ENVIRONMENTAL CONDITIONS	143
11.4 SUMMARY OF TEST RESULTS/PLOTS	143

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Motic china group Co.,Ltd.
Address of applicant: Motic BLDG, TORCH HI-TECH INDUSTRIAL DEV ZONE
XIAMEN FUJIAN, CHINA, 361006

Manufacturer: Motic china group Co.,Ltd.
Address of manufacturer: Motic BLDG, TORCH HI-TECH INDUSTRIAL DEV ZONE
XIAMEN FUJIAN, CHINA, 361006

General Description of EUT

Product Name:	Tablet PC
Trade Name:	Motic
Model No.:	MT-1001
Adding Model(s):	/
Rated Voltage:	DC 3.7V by battery
Battery Capacity:	7000mAh
Power Adapter Model:	/
Software Version:	F1006F.I25LK.1.12
Hardware Version:	9149C

Note: The test data is gathered from a production sample provided by the manufacturer.

Technical Characteristics of EUT

Support Standards:	802.11a, 802.11n(HT20/40) , 802.11ac
Frequency Range:	5150-5250MHz, 5725-5850MHz
RF Output Power:	17.40dBm (Conducted)
Type of Modulation:	BPSK, QPSK, 16QAM, 64QAM, 256QAM
Data Rate:	6-54Mbps, up to 866.6Mbps
Quantity of Channels:	15
Channel Separation:	20MHz/40MHz/80MHz
Type of Antenna:	Integral
Antenna Gain:	Antenna 1: 2.0dBi, Antenna 2: 2.0dBi

1.2 Test Standards

The following report is prepared on behalf of the Motic china group Co.,Ltd. in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 789033 D02 v01r04 for Unlicensed National Information Infrastructure (U-NII) Devices and KDB 662911 D01 Multiple Transmitter Output v02r01 shall be performed also.

1.4 Table for parameters of Test Software setting

The test utility software used during testing was “RPTA1-71W.M4300.01.GD.2015Sep1”. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Mode	Test Frequency (MHz)												
	NCB: 20MHz												
	5180	5200	5240	5260	5300	5320	5500	5580	5700	5720	5745	5785	5825
802.11a 6Mbps	19	19	19	/	/	/	/	/	/	/	15	15	15
802.11n-HT20 MCS0	19	19	19	/	/	/	/	/	/	/	15	15	15
Mode	NCB: 40MHz												
	5190	5230	5270	5310	5510	5550	5670	5710	5755	5795			
802.11n-HT40 MCS0	19	19	/	/	/	/	/	/	15	15			
Mode	NCB: 80MHz												
	5210		5290		5530		5610		5690		5775		
802.11ac-HT80 MCS0/Nss2	19		/		/		/		/		15		

1.5 EUT Operating during test

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under WIN XP were executed.

1.6 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11a	5180MHz,5200MHz,5240MHz, 5745MHz, 5785MHz,5825MHz
TM2	802.11n-HT20	5180MHz,5200MHz,5240MHz, 5745MHz, 5785MHz,5825MHz
TM3	802.11n-HT40	5190MHz,5230MHz,5755MHz,5795MHz
TM4	802.11ac	5210MHz, 5775MHz
Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.		

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Core
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.8 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

1.9 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
SEMT-1042	Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2016-06-04	2017-06-03
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.203; § 15.405	Antenna Requirement	Compliant
§ 15.207; § 15.407(b)(6)	Conducted Emission	Compliant
§ 15.407(a)(1),(2)	Power Spectral Density	Compliant
§ 15.407(e)	Emission Bandwidth and Occupied Bandwidth	Compliant
§ 15.407(a)(1),(2)	Maximum Conducted Output Power	Compliant
§ 15.407(b)(1),(2),(3)	Conducted Spurious Emission	Compliant
§ 15.205; § 15.407(b)(1),(2),(3)	Radiated Emission	Compliant
§ 15.407(g)	Frequency Stability	Compliant
§ 15.407(h)	Dynamic Frequency Selection (DFS)	N/A

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has two integral antennas, fulfill the requirement of this section.


5. Conducted Emissions

5.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

5.3 Basic Test Setup Block Diagram



5.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

5.5 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

5.6 Summary of Test Results/Plots

According to the data in section 5.7, the EUT complied with the FCC Part 15.207 Conducted margin for a Class B device, with the *worst* margin reading of:


-15.67 dB at 4.9060 MHz in the Line, QP detector, 0.15-30MHz

5.7 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Tablet PC
 Tested Model: MT-1001
 Operating Condition: Transmitting
 Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4500	17.11	9.80	26.91	46.88	-19.97	AVG
2	0.6020	29.09	9.79	38.88	56.00	-17.12	QP
3	1.5260	28.62	9.75	38.37	56.00	-17.63	QP
4	1.5940	16.30	9.75	26.05	46.00	-19.95	AVG
5*	4.4620	29.86	9.67	39.53	56.00	-16.47	QP
6	4.6380	15.50	9.67	25.17	46.00	-20.83	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2260	33.82	9.80	43.62	62.60	-18.98	QP
2	0.2300	24.09	9.80	33.89	52.45	-18.56	AVG
3	0.2780	31.59	9.80	41.39	60.88	-19.49	QP
4	0.2780	20.72	9.80	30.52	50.88	-20.36	AVG
5	4.6860	13.73	9.67	23.40	46.00	-22.60	AVG
6*	4.9060	30.67	9.66	40.33	56.00	-15.67	QP

6. Power Spectral Density

6.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25 GHz.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

6.2 Test Procedure

According to 789033 D02 General UNII Test Procedures New Rules v01, the following is the measurement procedure.

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth ($< 1 \text{ MHz}$, or $< 500 \text{ kHz}$) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.1.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

6.3 Environmental Conditions

Temperature:	20° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

6.4 Summary of Test Results/Plots

5150-5250MHz

Operating mode	Test Channel	Power Spectral Density (dBm/MHz)			Limit (dBm/MHz)
		Chain 1	Chain 2	Total	
802.11a	5180	8.114	7.738	10.940	11
	5200	8.223	8.002	11.124	11
	5240	8.535	8.415	11.486	11
802.11n-HT20	5180	8.023	7.581	10.818	11
	5200	8.067	7.666	10.881	11
	5240	8.771	8.849	11.820	11
802.11n-HT40	5190	4.075	3.715	6.909	11
	5230	5.652	4.078	7.946	11
802.11ac-VHT80	5210	1.066	-3.057	2.487	11


5725-5850MHz

Operating mode	Test Channel	Power Spectral Density (dBm/500kHz)			Limit (dBm/500kHz)
		Chain 1	Chain 2	Total	
802.11a	5745	-0.497	-1.573	2.009	30
	5785	0.180	-1.736	2.337	30
	5825	-0.076	-1.606	2.236	30
802.11n-HT20	5745	-0.277	-1.581	2.130	30
	5785	-0.368	-1.602	2.069	30
	5825	0.111	-1.705	2.308	30
802.11n-HT40	5755	-2.369	-3.634	0.055	30
	5795	-2.159	-2.457	0.705	30
802.11ac-VHT80	5775	-4.902	-7.014	-2.821	30


Chain 1

Test Mode: 802.11a


5180MHz




5200MHz




5240MHz




5745MHz



5785MHz




5825MHz




Test Mode: 802.11n-HT20


5180MHz




5200MHz




5240MHz




5745MHz



5785MHz




5805MHz




Test Mode: 802.11n-HT40


5190MHz




5230MHz



5755MHz




5795MHz




Test Mode: 802.11ac

5210MHz



5775MHz




Chain 2

Test Mode: 802.11a


5180MHz




5200MHz




5240MHz




5745MHz



5785MHz




5825MHz




Test Mode: 802.11n-HT20


5180MHz




5200MHz




5240MHz




5745MHz



5785MHz




5805MHz




Test Mode: 802.11n-HT40


5190MHz




5230MHz



5755MHz




5795MHz




Test Mode: 802.11ac

5210MHz



5775MHz



7. Emission Bandwidth and Occupied Bandwidth

7.1 Standard Applicable

According to 15.407 (a) and (e)

(1) For the band 5.15-5.25 GHz.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

7.2 Test Procedure

According to 789033 D02 v01r04 section C&D, the following is the measurement procedure.

1. Emission Bandwidth (EBW)

a) Set RBW = approximately 1% of the emission bandwidth.

b) Set the VBW > RBW.

c) Detector = Peak.

d) Trace mode = max hold.

e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare

this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

D. 99 Percent Occupied Bandwidth

The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section II.G.3.d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the EBW to 789033 D02 v01r04 General UNII Test Procedures New Rules v01 define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot \text{RBW}$
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

7.3 Environmental Conditions

Temperature:	24° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

7.4 Summary of Test Results/Plots

Chain 1:

5150-5250MHz

Test Mode	Test Channel MHz	26 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz
802.11a	5180	21.68	17.117	Pass
	5200	21.65	17.108	Pass
	5240	21.62	17.107	Pass
802.11n-HT20	5180	21.89	18.057	Pass
	5200	21.93	18.037	Pass
	5240	22.00	18.166	Pass
802.11n-HT40	5190	40.75	36.629	Pass
	5230	41.07	36.723	Pass
802.11ac	5210	82.14	75.882	Pass


5725-5850MHz

Test Mode	Test Channel MHz	26 dB Bandwidth MHz	6 dB Bandwidth MHz	99% Bandwidth MHz	Limit KHz
802.11a	5745	21.75	16.50	17.039	≥500
	5785	21.68	16.50	17.142	≥500
	5825	21.63	16.52	17.022	≥500
802.11n-HT20	5745	21.93	17.72	18.179	≥500
	5785	21.87	17.76	18.111	≥500
	5825	21.84	17.75	18.203	≥500
802.11n-HT40	5755	40.88	36.65	36.594	≥500
	5795	36.57	36.47	36.683	≥500
802.11ac	5775	82.45	76.38	75.815	≥500


5150-5250MHz

Test mode: 802.11a


5180MHz



5200MHz




5240MHz




Test mode: 802.11n-HT20


5180MHz




5200MHz




5240MHz




Test mode: 802.11n-HT40
5190MHz




5230MHz




Test mode: 802.11ac
5210MHz





5725-5850MHz
Test mode: 802.11a
5745MHz







5785MHz






5825MHz







Test mode: 802.11-HT20


5745MHz







5785MHz






5825MHz







Test mode: 802.11-HT40


5755MHz






5795MHz






Test mode: 802.11ac

5775MHz





Chain 2:
5150-5250MHz

Test Mode	Test Channel MHz	26 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz
802.11a	5180	21.75	17.073	Pass
	5200	21.74	17.166	Pass
	5240	21.81	17.086	Pass
802.11n-HT20	5180	21.98	18.134	Pass
	5200	21.66	18.109	Pass
	5240	22.17	18.130	Pass
802.11n-HT40	5190	36.63	36.605	Pass
	5230	36.60	36.705	Pass
802.11ac	5210	82.15	75.804	Pass


5725-5850MHz

Test Mode	Test Channel MHz	26 dB Bandwidth MHz	6 dB Bandwidth MHz	99% Bandwidth MHz	Limit KHz
802.11a	5745	21.60	16.49	17.110	≥ 500
	5785	21.79	16.46	17.165	≥ 500
	5825	21.55	16.52	17.032	≥ 500
802.11n-HT20	5745	21.94	17.84	18.131	≥ 500
	5785	21.84	17.72	18.182	≥ 500
	5825	21.86	17.70	18.165	≥ 500
802.11n-HT40	5755	41.27	36.82	36.977	≥ 500
	5795	40.85	36.40	36.782	≥ 500
802.11ac	5775	81.71	76.48	75.892	≥ 500


5150-5250MHz

Test mode: 802.11a


5180MHz



5200MHz




5240MHz




Test mode: 802.11n-HT20


5180MHz




5200MHz




5240MHz




Test mode: 802.11n-HT40
5190MHz




5230MHz




Test mode: 802.11ac
5210MHz





5725-5850MHz
Test mode: 802.11a
5745MHz







5785MHz






5825MHz







Test mode: 802.11-HT20


5745MHz







5785MHz






5825MHz







Test mode: 802.11-HT40


5755MHz






5795MHz






Test mode: 802.11ac

5775MHz





8. Maximum Conducted Output Power

8.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25 GHz.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

8.2 Test Procedure

According to KDB789033 D02 v01r04 section E, the following is the measurement procedure.

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1 MHz.
- (iii) Set VBW ≥ 3 MHz.
- (iv) Number of points in sweep $\geq 2 \text{ Span} / \text{RBW}$. (This ensures that bin-to-bin spacing is $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- (v) Sweep time = auto.

- (vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- (vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq$ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- (viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- (ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

8.3 Environmental Conditions

Temperature:	26° C
Relative Humidity:	65%
ATM Pressure:	1011 mbar


8.4 Summary of Test Results/Plots

Test mode	Frequency MHz	Power 1 dBm	Power 2 dBm	Total Power dBm	Total Power mW	Limit mW
802.11a	5180	16.66	15.81	19.266	84.45	250
	5200	16.62	16.31	19.478	88.67	250
	5240	17.4	16.36	19.921	98.20	250
	5745	11.13	10.38	13.781	23.88	1000
	5785	11.57	10.72	14.176	26.16	1000
	5825	11.46	10.47	14.003	25.14	1000
802.11n-HT20	5180	16.68	16.09	19.405	87.20	250
	5200	16.7	16.1	19.421	87.52	250
	5240	17.29	16.55	19.946	98.76	250
	5745	10.19	10.34	13.276	21.26	1000
	5785	10.37	10.37	13.380	21.78	1000
	5825	10.71	10.5	13.617	23.00	1000
802.11n-HT20	5190	16.33	15.19	18.808	76.00	250
	5230	16.52	15.54	19.068	80.69	250
	5755	11.89	11.05	14.501	28.19	1000
	5795	11.91	11.35	14.649	29.17	1000
802.11ac-VHT80	5210	15.69	15.43	18.572	71.98	250
	5775	11.76	10.85	14.339	27.16	1000


Chain 1:

Test Mode: 802.11a


5180MHz




5200MHz




5240MHz




5745MHz



5785MHz




5825MHz




Test Mode: 802.11n-HT20


5180MHz




5200MHz




5240MHz




5745MHz



5785MHz




5825MHz




Test Mode: 802.11n-HT40


5190MHz




5230MHz



5755MHz




5795MHz




Test Mode: 802.11ac

5210MHz




5775MHz




Chain 2:

Test Mode: 802.11a


5180MHz



5200MHz



5240MHz



5745MHz

