

FCC Test Report

Report No.: AGC01689240814FR01

FCC ID	:	2A2UU-P8NEO
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	AI POS Terminal
BRAND NAME	:	KOZEN
MODEL NAME	:	P8 Neo
APPLICANT	:	Shanghai Xiangcheng Communication Technology Co., Ltd
DATE OF ISSUE	:	Oct. 30, 2024
STANDARD(S)	:	FCC Part 15 Subpart C §15.247
REPORT VERSION	:	V1.0







Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	Oct. 30, 2024	Valid	Initial Release	



Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	
2.2 Test Frequency List	
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Receiver Input Bandwidth	7
2.6 Equally Average Use of Frequencies and Behaviour.	7
2.7 Pseudorandom Frequency Hopping Sequence	
2.8 Special Accessories	
2.9 Equipment Modifications	
2.10 Antenna Requirement	
3. Test Environment	
3.1 Address of The Test Laboratory	
3.2 Test Facility	
3.3 Environmental Conditions	
3.4 Measurement Uncertainty	
3.5 List of Equipment Used	
4.System Test Configuration	
4.1 EUT Configuration	
4.2 EUT Exercise	
4.3 Configuration of Tested System	
4.4 Equipment Used in Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	
6. RF Output Power Measurement	
6.1 Provisions Applicable	
6.2 Measurement Procedure	
6.3 Measurement Setup (Block Diagram of Configuration)	
6.4 Measurement Result	
7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement	
7.1 Provisions Applicable	
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Results	
8. Conducted Band Edge and Out-of-Band Emissions	
8.1 Provisions Applicable	
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	
8.4 Measurement Results	31



9. Radiated Spurious Emission	51
9.1 Measurement Limit	51
9.2 Measurement Procedure	51
9.3 Measurement Setup (Block Diagram of Configuration)	54
9.4 Measurement Result	
10. Number of Hopping Frequency Measurement	64
10.1 Provisions Applicable	64
10.2 Measurement Procedure	64
10.3 Measurement Setup (Block Diagram of Configuration)	64
10.4 Measurement Result	64
11. Time of Occupancy (Dwell Time) Measurement	67
11.1 Provisions Applicable	
11.2 Measurement Procedure	67
11.3 Measurement Setup (Block Diagram of Configuration)	67
11.4 Measurement Result	67
12. Frequency Separation Measurement	71
12.1 Provisions Applicable	71
12.2 Measurement Procedure	71
12.3 Measurement Setup (Block Diagram of Configuration)	71
12.4 Measurement Result	71
13. AC Power Line Conducted Emission Test	73
13.1 Measurement Limit	73
13.2 Measurement Setup (Block Diagram of Configuration)	73
13.3 Preliminary Procedure of Line Conducted Emission Test	74
13.4 Final Procedure of Line Conducted Emission Test	74
13.5 Measurement Results	74
Appendix I: Photographs of Test Setup	77
Appendix II: Photographs of Test EUT	77



1. General Information

Applicant	Shanghai Xiangcheng Communication Technology Co., Ltd
Address	6th Floor, Building 10, No.3000 Longdong Avenue, Pudong New District, Shanghai, China
Manufacturer	Sichuan Xiangcheng Intelligent Technology Co., Ltd.
Address	Factory No. 2 and 7 Zone A, Intelligent Terminal Demonstration Park, West Section of Gangyuan Road, Lingang Economic Development Zone, Yibin City, Sichuan Province China
Factory	Sichuan Xiangcheng Intelligent Technology Co., Ltd.
Address	Factory No. 2 and 7 Zone A, Intelligent Terminal Demonstration Park, West Section of Gangyuan Road, Lingang Economic Development Zone, Yibin City, Sichuan Province China
Product Designation	AI POS Terminal
Brand Name	KOZEN
Test Model	P8 Neo
Date of receipt of test item	Aug. 29, 2024
Date of Test	Aug. 29, 2024~Oct. 30, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BR_EDR-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By

Bibo shang

Bibo Zhang (Project Engineer)

Oct. 30, 2024

in ·

Calvin Liu (Reviewer)

Oct. 30, 2024

Approved By

Reviewed By

Max Zhan

Max Zhang (Authorized Officer)

Oct. 30, 2024



2. Product Information

2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.0
Modulation Type	BR 🖾 GFSK, EDR 🖾 π /4-DQPSK, 🖾 8DPSK
Number of channels	79 Channels
Channel Separation	1 MHz
Maximum Transmitter Power	9.001dBm
Hardware Version	V1.0
Software Version	p0816_kozen_combo
Antenna Designation	PIFA Antenna
Antenna Gain	2.39dBi
Power Supply	DC 7.6V 2500mAh by battery or DC 5V from adapter

2.2 Test Frequency List

Frequency Band	Channel Number	Frequency		
	0	2402 MHz		
	1	2403 MHz		
	:	:		
2400~2483.5MHz	39	2441MHz		
	:	:		
	77	2479 MHz		
	78	2480 MHz		
Note: f = 2402 + 1k MHz, k =	0,, 78 ; "f "is the operating frequency	(MHz); "k" is the operating channel.		



2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID:**2A2UU-P8NEO**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title		
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations		
2	2 FCC 47 CFR Part 15 Radio Frequency Devices			
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices		
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules		

2.5 Receiver Input Bandwidth

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

2.6 Equally Average Use of Frequencies and Behaviour.

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.

2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30).

In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:


The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.



2.7 Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29 1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of The PRBS Sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

44	35	78	03	20	76	02	19		21	64	75
								1	1		
			li						:		
						; ;			i i		
				i		<u></u>		1	i		

Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



2.8 Special Accessories

Not available for this EUT intended for grant.

2.9 Equipment Modifications

Not available for this EUT intended for grant.

2.10 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 2.39dBi



3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range ($^{\circ}$ C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3.76V

3.4 Measurement Uncertainty

The reported uncertainty of measurement y \pm U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



3.5 List of Equipment Used

• R	RF Conducted Test System								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23		
\boxtimes	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31		
\boxtimes	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31		
\boxtimes	AGC-ER-A001	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-09-21	2025-09-20		
	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-05-23	2025-05-22		
	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A		
	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A		

• F	Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31	
\square	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23	
\square	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27	
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04	
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
\square	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30	
\square	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23	
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23	
\bowtie	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22	
\square	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08	

• A	AC Power Line Conducted Emission							
Lised Faunment No. 1. Jest Faunment Manufacturer Model No. 1. Serial No. 1. Serial No. 1.						Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27	
\boxtimes	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08	
\boxtimes	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27	



• Te	Test Software							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information			
\boxtimes	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71			
	AGC-EM-S003	RE Test System	FARA	EZ-EMC	VRA-03A			
\boxtimes	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6			
\boxtimes	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0			



4.System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:



4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

- Test Accessories Come From The Laboratory
- ☑ Test Accessories Come From The Manufacturer

No.	Equipment	Manufacturer	Anufacturer Model No. Specification Information		Cable
1	Adapter	dapter Chongqing Lianmao LM-603E-060200U Input: AC 100-240V 50/60Hz, 0.35A Electronics Co.,Ltd. 02CE Output: DC 5V 2A		1.0m unshielded	
2	Battery	Guangdong Fenghua New Energy Co.,Ltd.	F50114MA	DC 7.6V 2500mAh	



4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(1)	RF Output Power	Pass
3	§15.247 (a)(1)	20 dB Bandwidth	Pass
4	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
5	§15.209	Radiated Spurious Emission	Pass
6	§15.247 (a)(1)(iii)	Number of Hopping Frequency	Pass
7	§15.247 (a)(1)(iii)	Time of Occupancy	Pass
8	§15.247 (a)(1)	Frequency Separation	Pass
9	§15.207	AC Power Line Conducted Emission	Pass



5. Description of Test Modes

Summary table of Test Cases				
Test Item	Data Rate / Modulation			
rest item	Bluetooth – BR_EDR (GFSK/π /4-DQPSK/8DPSK)			
Radiated & Conducted Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps (Battery powered or AC/DC adapter) Mode 2: Bluetooth Tx CH39_2441 MHz_1Mbps (Battery powered or AC/DC adapter) Mode 3: Bluetooth Tx CH78_2480 MHz_1Mbps (Battery powered or AC/DC adapter) Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (Battery powered or AC/DC adapter) Mode 7: Bluetooth Tx CH00_2402 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 9: Bluetooth Tx CH39_2441 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 9: Bluetooth Tx CH78_2480 MHz_3Mbps (Battery powered or AC/DC adapter) Mode 10: Bluetooth Tx Hopping-1Mbps (Battery powered or AC/DC adapter) Mode11: Bluetooth Tx Hopping-3Mbps (Battery powered or AC/DC adapter)			
AC Conducted Emission	Mode 1: Bluetooth Link + Battery + USB Cable (Charging from AC Adapter)			

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

Software Setting Diagram





6. RF Output Power Measurement

6.1 Provisions Applicable

The maximum out power permissible output power is 1 Watt for all frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.

The maximum out power permissible output power is 0.125 watts for all other frequency hopping systems in the 2400-2483.5 MHz band.

6.2 Measurement Procedure

⊠For Peak power test:


- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 3. RBW > 20 dB bandwidth of the emission being measured.
- 4. VBW \geq RBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

For Average power test:

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required


6.3 Measurement Setup (Block Diagram of Configuration)

For Average power test setup






For peak power test setup



6.4 Measurement Result


Test Data of Conducted Output Power						
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail		
	2402	8.881	≤21	Pass		
GFSK	2441	8.542	≤21	Pass		
	2480	9.001	≤21	Pass		
	2402	8.285	≤21	Pass		
π /4-DQPSK	2441	7.860	≤21	Pass		
	2480	8.309	≤21	Pass		
	2402	8.316,	≤21	Pass		
8DPSK	2441	7.874	≤21	Pass		
	2480	8.311	≤21	Pass		






Test Graphs of Conducted Output Power





















7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement

7.1 Provisions Applicable


There is no corresponding limit requirement for this test item.

7.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 6.9.2 (20dB BW).

- The 20dB bandwidth spectrum analyzer setting reference is as follows:
- 1. Set RBW \geq 1% to 5% of the 20dB bandwidth
- 2. VBW = Approximately three times RBW
- 3. Span = Approximately 2 to 5 times the 20dB bandwidth, centered on a hopping channel
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace to stabilize
- 8. Measure the maximum width of the emission that is constrained by the frequencies associated
- 9. with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20
- 10. dB relative to the maximum level in the fundamental emission.
- The 99% bandwidth spectrum analyzer setting reference is as follows:
- 1. Span = 1.5 times to 5 times the OBW
- 2. Set RBW = 1% to 5% the OBW
- 3. VBW \geq 3 × RBW
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace was allowed to stabilize

7.3 Measurement Setup (Block Diagram of Configuration)







7.4 Measurement Results

Test Data of Occupied Bandwidth and -20dB Bandwidth						
Test Mode	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)	-20dB Bandwidth (MHz)	Limits	Pass or Fail	
	2402	0.758	0.847	N/A	Pass	
GFSK	2441	0.750	0.844	N/A	Pass	
	2480	0.757	0.842	N/A	Pass	
	2402	1.155	1.276	N/A	Pass	
π /4-DQPSK	2441	1.144	1.269	N/A	Pass	
	2480	1.144	1.269	N/A	Pass	
	2402	1.155	1.273	N/A	Pass	
8DPSK	2441	1.156	1.280	N/A	Pass	
	2480	1.149	1.267	N/A	Pass	


Test Graphs of Occupied Bandwidth and -20 Bandwidth























8. Conducted Band Edge and Out-of-Band Emissions

8.1 Provisions Applicable


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.10.4 and 7.8.8:


- Reference level measurement
- 1. Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.
- Emission level measurement
- 1. Span = Wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Trace was allowed to stabilize
- 8. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

8.3 Measurement Setup (Block Diagram of Configuration)






8.4 Measurement Results




Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands






Report No.: AGC01689240814FR01 Page 33 of 77


























































	HZ O: Fast →→	Trig: Free #Atten: 3		Avg Type Avg Hold:		TYF DE 1 24.95	57 GHz 69 dBm	Frequend Auto Center 13.75000000 Start	Tune Free
0 dBm					Mkr	1 24.955 -51.9	5 7 GHz 69 dBm	Center 13.75000000	Fre
								13.75000000	
								Start	
							-11.87 dBm	2.50000000	
								Stop 25.00000000	
							1		Ste 0 GF Ma
	Mary Marilton (Marileo (Marineo (Marineo (Marineo (Marineo (Marineo (Marineo (Marineo (Marineo (Marineo (Marine Marineo (Marineo (Mari				an a thing in the state of the st			Freq C	Offse 0⊢
								Scale	Тур
	#VBW	300 kHz				2.152 s (3	2.50 GHz 0000 pts)	Log	Li
		#VBW	#VBW 300 kHz	#VBW 300 kHz	#VBW 300 kHz	#VBW 300 kHz Sweep 2	#VBW 300 kHz Sweep 2.152 s (3	Span 22.50 GHz #VBW 300 kHz status	Image: Span 22.50 GHz #VBW 300 kHz Sweep 2.152 s (30000 pts)






Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands























9. Radiated Spurious Emission

9.1 Measurement Limit

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

9.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average



absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
Start ~Stop Trequency	1MHz/3MHz for Peak, 1MHz/3MHz for Average

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP



• Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

• Peak Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

<u>Average Measurements above 1GHz</u>


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW \geq [3 × RBW]
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




9.3 Measurement Setup (Block Diagram of Configuration)



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/




9.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

	Radiated Emission Test Results at 30MHz-1GHz						
EUT Name	AI POS Terminal	Model Name	P8 Neo				
Temperature	23.2 ℃	Relative Humidity	58.2%				
Pressure	960hPa	Test Voltage	DC 7.6V by battery				
Test Mode	Mode 3	Antenna Polarity	Horizontal				



	Final Average Data List
--	-------------------------

	0							
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	32.91	34.57	12.41	40.00	5.43	100	160	Horizontal
2	55.22	34.84	16.61	40.00	5.16	100	170	Horizontal
3	108.57	37.87	16.62	43.50	5.63	100	90	Horizontal
4	465.53	32.81	23.37	46.00	13.19	100	220	Horizontal
5	615.88	34.54	25.47	46.00	11.46	100	160	Horizontal
6	857.41	40.18	29.93	46.00	5.82	100	140	Horizontal

Report No.: AGC01689240814FR01 Page 56 of 77



			Radia	ted Emissi	ion Test Res	ults at 30MHz	-1GHz		
EUT N	lame	AI PO	OS Terminal			Model Na	me	P8 Neo	
Tempe	erature	23.2	Ĉ			Relative I	Humidity	58.2%	
Press	ure	960h	Pa			Test Volta	age	DC 7.6V b	y battery
Test N	lode	Mode	e 3			Antenna	Polarity	Vertical	
	130				FCC Part 1	5C			
Level[dBµV/m]		Limit Detector	- Horizontal PK	100M	Frequency	Hz]			16
Final A	Average I	Data L	ist						
NO.	Freq [MHz		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	32.9	1	33.33	12.41	40.00	6.67	100	160	Vertical
2	57.1	6	33.05	17.12	40.00	6.95	100	170	Vertical
3	99.84	4	38.03	17.03	43.50	5.47	100	90	Vertical

RESULT: Pass

4 5

6

459.71

621.7

900.09

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

24.69

25.68

30.27

32.75

35.17

40.56

2. All test modes had been pre-tested. The mode 3 is the worst case and recorded in the report.

46.00

46.00

46.00

13.25

10.83

5.44

100

100

100

220

160

140

Vertical

Vertical

Vertical



EUT Name		AI F	POS Terminal		Model Name	P8 Neo	
F emperature		23.	2 °C		Relative Humidity	58.2%	
Pressure		960)hPa		Test Voltage	DC 7.6V	by battery
Fest Mode		Mo	de 1		Antenna Polarity	Horizont	al
		I					
Frequency	Mete Readii		Factor	Emission Level	Limits	Margin	Val e
(MHz)	(dBµ∖	/)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
4804.000	50.13	3	0.08	50.21	74.00	-23.79	peak
4804.000	39.8	5	0.08	39.93	54.00	-14.07	AVG
7206.000	49.3	7	2.21	51.58	74.00	-22.42	peak
7206.000	38.63	3	2.21	40.84	54.00	-13.16	AVG
Remark:	enna Fa	actor	+ Cable Loss –	Pre-amplifier.			
Remark:	enna Fa	Γ	+ Cable Loss – POS Terminal	Pre-amplifier.	Model Name	P8 Neo	
Remark: Factor = Ant		Γ	POS Terminal	Pre-amplifier.	Model Name Relative Humidity	P8 Neo 58.2%	
Remark: Factor = Ant EUT Name		AI F 23.	POS Terminal	Pre-amplifier.		58.2%	by battery
Remark: Factor = Ant EUT Name Femperature		Al F 23.1 960	POS Terminal 2℃	Pre-amplifier.	Relative Humidity	58.2%	by battery
Remark: Factor = Ant EUT Name Femperature Pressure		Al F 23. 960 Mo	POS Terminal 2℃)hPa	Pre-amplifier.	Relative Humidity Test Voltage	58.2% DC 7.6V	Value
Remark: Factor = Ant EUT Name Femperature Pressure Fest Mode	Mete	AI F 23.1 960 Mor ng	POS Terminal 2℃ 0hPa de 1	Emission	Relative Humidity Test Voltage Antenna Polarity	58.2% DC 7.6V Vertical	
Remark: Factor = Ant EUT Name Femperature Pressure Fest Mode Frequency	Mete	AI F 23. 960 Mod r ng /)	POS Terminal 2°C DhPa de 1 Factor	Emission Level	Relative Humidity Test Voltage Antenna Polarity Limits	58.2% DC 7.6V Vertical Margin	Value
Remark: Factor = Ant EUT Name Femperature Pressure Fest Mode Frequency (MHz)	Mete eadii (dBµ\	AI F 23. 960 Mod ng /) 5	POS Terminal 2°C DhPa de 1 Factor (dB)	Emission Level (dBµV/m)	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m)	58.2% DC 7.6V Vertical Margin (dB)	Value Type
Remark: Factor = Ant EUT Name Femperature Pressure Fest Mode Frequency (MHz) 4804.000	Mete eadii (dBµ\ 49.3	AI F 23. 960 Mo ng /) 5 7	POS Terminal 2°C DhPa de 1 Factor (dB) 0.08	Emission Level (dBµV/m) 49.43	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m) 74.00 74.00	58.2% DC 7.6V Vertical Margin (dB) -24.57	Value Type peak
Remark: Factor = Ant EUT Name Femperature Pressure Fest Mode Frequency (MHz) 4804.000 4804.000	Mete eadii (dBμ\ 49.3 40.1	AI F 23.: 960 Mod r ng /) 5 7 3	POS Terminal 2°C DhPa de 1 Factor (dB) 0.08 0.08	Emission Level (dBµV/m) 49.43 40.25	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m) 74.00 54.00	58.2% DC 7.6V Vertical Margin (dB) -24.57 -13.75	Value Type peak AVG

Radiated Emissions Test Results Above 1GHz

RESULT: Pass



EUT Name		AI POS Terminal		Model Name	P8 Neo	
Temperature	•	23.2℃		Relative Humidity	58.2%	
Pressure		960hPa		Test Voltage	DC 7.6V b	y battery
Test Mode		Mode 2		Antenna Polarity	Horizontal	
Frequency	Meter Readin	Factor	Emission Level	Limits	Margin	Value
(MHz)	(dBµV	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
4882.000	50.11	0.14	50.25	74.00	-23.7	peak
4882.000	39.12	0.14	39.26	54.00	-14.74	AVG
7323.000	49.74	2.36	52.10	74.00	-21.90	peak
7323.000	38.55	2.36	40.91	54.00	-13.09	AVG
Remark:						
Factor = An	tenna Fao	tor + Cable Loss –	Pre-amplifier.			
EUT Name		AI POS Terminal	Pre-amplifier.	Model Name	P8 Neo	
EUT Name			Pre-amplifier.	Model Name Relative Humidity	P8 Neo 58.2%	
EUT Name Temperature		AI POS Terminal	Pre-amplifier.			by battery
EUT Name Temperature Pressure		AI POS Terminal 23.2℃	Pre-amplifier.	Relative Humidity	58.2%	y battery
EUT Name Temperature Pressure Test Mode		AI POS Terminal 23.2℃ 960hPa Mode 2	Emission	Relative Humidity Test Voltage Antenna Polarity	58.2% DC 7.6V b Vertical	
EUT Name Temperature Pressure	•	AI POS Terminal 23.2℃ 960hPa Mode 2		Relative Humidity Test Voltage	58.2% DC 7.6V b	Value
EUT Name Temperature Pressure Test Mode	Meter Readin (dBµV	AI POS Terminal 23.2°C 960hPa Mode 2 Factor (dB)	Emission Level (dBµV/m)	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m)	58.2% DC 7.6V b Vertical Margin (dB)	
EUT Name Temperature Pressure Test Mode Frequency	Meter	AI POS Terminal 23.2°C 960hPa Mode 2 Factor	Emission Level	Relative Humidity Test Voltage Antenna Polarity Limits	58.2% DC 7.6V b Vertical Margin	Value
EUT Name Temperature Pressure Test Mode Frequency (MHz)	Meter Readin (dBµV	AI POS Terminal 23.2°C 960hPa Mode 2 Factor (dB)	Emission Level (dBµV/m)	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m)	58.2% DC 7.6V b Vertical Margin (dB)	Value Type
EUT Name Temperature Pressure Test Mode Frequency (MHz) 4882.000	Meter Readin (dBµV 50.11	AI POS Terminal 23.2℃ 960hPa Mode 2 Factor (dB) 0.14	Emission Level (dBµV/m) 50.25	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m) 74.00 1	58.2% DC 7.6V b Vertical Margin (dB) -23.75	Value Type peak
EUT Name Temperature Pressure Test Mode Frequency (MHz) 4882.000 4882.000	Meter Readin (dBµV 50.11 39.12	AI POS Terminal 23.2°C 960hPa Mode 2 5 5 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	Emission Level (dBµV/m) 50.25 39.26	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m) (dBµV/m) 74.00 54.00 0	58.2% DC 7.6V b Vertical Margin (dB) -23.75 -14.74	Value Type peak AVG

RESULT: Pass



Radiated Emissions Test Results for Above 1GHz

EUT Name		AI POS Terminal		Model Name	P8 Neo	
Temperature		23.2℃		Relative Humidity	58.2%	
Pressure		960hPa		Test Voltage	DC 7.6V by	battery
Test Mode		Mode 3		Antenna Polarity	Horizontal	
Frequency	Meter Readin	Lootor	Emission Level	Limits	Margin	Value
(MHz)	(dBµV) (dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
4960.000	50.33	0.22	50.55	74.00	-23.45	peak
4960.000	38.78	0.22	39.00	54.00	-15.00	AVG
7440.000	49.12	2.64	51.76	74.00	-22.24	peak
7440.000	39.53	2.64	42.17	54.00	-11.83	AVG
Remark:						
Factor = Anto	enna Fac	tor + Cable Loss -	- Pre-amplifier.			
Factor = Anto		tor + Cable Loss - Al POS Terminal	· · ·	Model Name	P8 Neo	
				Model Name Relative Humidity	P8 Neo 58.2%	
EUT Name Temperature		AI POS Terminal				v battery
EUT Name		AI POS Terminal 23.2℃		Relative Humidity	58.2%	^v battery
EUT Name Temperature Pressure	Meter	Al POS Terminal 23.2°C 960hPa Mode 3	Emission	Relative Humidity Test Voltage	58.2% DC 7.6V by	y battery Value
EUT Name Temperature Pressure Test Mode Frequency	Meter	AI POS Terminal 23.2°C 960hPa Mode 3 g Factor		Relative Humidity Test Voltage Antenna Polarity	58.2% DC 7.6V by Vertical	
EUT Name Temperature Pressure Test Mode Frequency (MHz)	Meter	Al POS Terminal 23.2°C 960hPa Mode 3 g Factor) (dB)	Emission	Relative Humidity Test Voltage Antenna Polarity Limits	58.2% DC 7.6V by Vertical Margin	Value
EUT Name Temperature Pressure Test Mode Frequency	Meter Readin (dBµV	Al POS Terminal 23.2°C 960hPa Mode 3 	Emission Level (dBµV/m)	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m)	58.2% DC 7.6V by Vertical Margin (dB)	Value Type
EUT Name Temperature Pressure Test Mode Frequency (MHz) 4960.000	Meter Readin (dBµV 50.33	Al POS Terminal 23.2℃ 960hPa Mode 3 g Factor) (dB) 0.22 0.22	Emission Level (dBµV/m) 50.55	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m) 74.00	58.2% DC 7.6V by Vertical Margin (dB) -23.45	Value Type peak
EUT Name Temperature Pressure Test Mode Frequency (MHz) 4960.000 4960.000	Meter Readir (dBµV 50.33 39.16	AI POS Terminal 23.2℃ 960hPa Mode 3 g Factor g (dB) 0.22 0.22 0.22	Emission Level (dBµV/m) 50.55 39.38	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m) 74.00 54.00	58.2% DC 7.6V by Vertical Margin (dB) -23.45 -14.62	Value Type peak AVG
EUT Name Temperature Pressure Test Mode Frequency (MHz) 4960.000 4960.000	Meter Readin (dBµV 50.33 39.16 49.78	AI POS Terminal 23.2℃ 960hPa Mode 3 g Factor g (dB) 0.22 0.22 0.22	Emission Level (dBµV/m) 50.55 39.38 52.42	Relative Humidity Test Voltage Antenna Polarity Limits (dBµV/m) 74.00 54.00 74.00	58.2% DC 7.6V by Vertical Margin (dB) -23.45 -14.62 -21.58	Value Type peak AVG peak


RESULT: Pass

Note:


- 1. The amplitude of other spurious emissions from 1G to 40 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.



EUT Name	AI POS Terminal	Model Name	P8 Neo
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal



Test Graph for Average Measurement




RESULT: Pass




Band Edge Emission Test Results for Rest	ricted Bands
--	--------------

EUT Name	AI POS Terminal	Model Name	P8 Neo
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical




Test Graph for Average Measurement




RESULT: Pass



EUT Name	AI POS Terminal	Model Name	P8 Neo
Temperature	25 ℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 3	Antenna Polarity	Horizontal




Test Graph for Average Measurement




RESULT: Pass



EUT Name	AI POS Terminal	Model Name	P8 Neo
Temperature	25℃	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	DC 7.6V by battery
Test Mode	Mode 3	Antenna Polarity	Vertical



Test Graph for Average Measurement



RESULT: Pass

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



10. Number of Hopping Frequency Measurement

10.1 Provisions Applicable

This frequency hopping system must employ a minimum of 15 hopping channels.


10.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span = The frequency band of operation. Depending on the number of channels the device

- 2. supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- 3. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 4. VBW \geq RBW
- 5. Sweep time = Auto couple
- 6. Detector = Peak
- 7. Trace mode = Max hold
- 8. Allow the trace to stabilize


10.3 Measurement Setup (Block Diagram of Configuration)



10.4 Measurement Result


Test Data of Number of Hopping Frequency					
Test Mode Number of Hopping Frequency Limits Pass or					
8DPSK Hopping	79	>=15	Pass		





Test Graphs of Number of Hopping Frequency





Note: All mode rates are tested and evaluated, GFSK modulated DH5 mode is the worst case and documented in the report.



11. Time of Occupancy (Dwell Time) Measurement

11.1 Provisions Applicable


The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.

11.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span = Zero span, centered on a hopping channel.
- 2. RBW shall be \leq channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- 3. VBW \geq RBW
- 4. Sweep time = As necessary to capture the entire dwell time per hopping channel
- 5. Detector = Peak
- 6. Trace mode = Free Run
- 7. Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time. An oscilloscope may be used instead of a spectrum analyzer. The EUT shall show compliance with the appropriate regulatory limit for the number of hopping channels. A plot of the data shall be included in the test report.


11.3 Measurement Setup (Block Diagram of Configuration)



11.4 Measurement Result


Test Data of Dwell Time					
Channel	Time of Pulse for DH5 (ms)	Number of hops in the period specified in the requirements	Dwell Time (ms)	Limit (ms)	Pass or Fail
2402	2.884	30.0*4	346.080	400	Pass
2441	2.884	26.0*4	299.936	400	Pass
2480	2.884	19.0*4	219.184	400	Pass






Test Graphs of Dwell Time









Note: All mode rates are tested and evaluated, GFSK modulated DH5 mode is the worst case and documented in the report.