

RF Exposure Evaluation declaration

Product Name : V2X DSRC Module
Trade Name : Unex
Model No. : VTX-201, VTX-201E, VTX-201U,
VTX-201J, VTX-201W
FCC ID. : NUK-VTX201

Applicant : Unex Technology Corporation

Address : 11F-3, No. 100, Sec. 1, Jiafeng 11th Rd., Zhubei City,
Hsinchu County 30273, Taiwan, R.O.C.

Date of Receipt : Mar. 03, 2017
Date of Declaration : Mar. 17, 2017
Report No. : 1730061R-RF-US-Exp
Report Version : V1.0



The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd..

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product	V2X DSRC Module
Test Mode	Mode 1: Transmit-ANT1
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 7.6dBi or 5.75 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11p (ANT 1)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
172	5860	101.8591	0.11652
178	5890	89.7429	0.10266
184	5920	95.4993	0.10924

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

Product	V2X DSRC Module
Test Mode	Mode 2: Transmit-ANT2
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 7.6dBi or 5.75 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11p (ANT 2)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
172	5860	124.7384	0.14269
178	5890	117.7606	0.13471
184	5920	100.6932	0.11519

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².