



Out of band emission, Band Edge



Out of band emission, Band Edge



4.6 Antenna Port Test Data and Results for LTE Band 4

Serial Number:	CR22030001-RF-S1	Test Date:	2022-03-09~2022-03-15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Le Qiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23.7	Relative Humidity: (%)	46	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	---------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	Spectrum Analyzer	101474	2021-07-22	2022-07-21
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	149218	2021-07-22	2022-07-21
BACL	TEMP&HUMI Test Chamber	BTH-150	30026	2021-07-22	2022-07-22
UNI-T	Multimeter	UT39A+	C210582554	2021-09-30	2022-09-30
E-Microwave	Two-way Splitter	ODP-1-6	OE0120176	Each Time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

EUT Information@ LTE Band 4▲:

Antenna Gain (dBi):	0.82	Cable Loss (dB):	0.1
Operation Voltage(V _{DC}):			
Lowest:	3.6	Normal:	3.85
		Highest:	4.4

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
1.4MHz	1710.7	1732.5	1754.3
3MHz	1711.5	1732.5	1753.5
5MHz	1712.5	1732.5	1752.5
10MHz	1715	1732.5	1750
15MHz	1717.5	1732.5	1747.5
20MHz	1720	1732.5	1745

Test Data:**FCC§2.1046;§ 27.50(d)(4)****RF Output Power:**

Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
1.4MHz QPSK	RB1#0	22.67	22.65	22.84	23.56	30
	RB1#3	22.64	22.70	22.79		
	RB1#5	22.69	22.70	22.79		
	RB3#0	22.65	22.68	22.75		
	RB3#3	22.70	22.72	22.67		
	RB6#0	21.70	21.68	21.55		
1.4MHz 16QAM	RB1#0	22.33	22.39	21.80	23.13	30
	RB1#3	22.34	22.41	21.64		
	RB1#5	22.41	22.34	21.73		
	RB3#0	21.76	21.62	21.75		
	RB3#3	21.80	21.65	21.64		
	RB6#0	21.41	21.34	21.00		
3MHz QPSK	RB1#0	22.62	22.61	22.77	23.54	30
	RB1#8	22.62	22.65	22.79		
	RB1#14	22.66	22.72	22.82		
	RB6#0	21.67	21.72	21.71		
	RB6#9	21.62	21.68	21.67		
	RB15#0	21.60	21.70	21.54		
3MHz 16QAM	RB1#0	21.85	22.45	21.66	23.17	30
	RB1#8	21.91	22.39	21.67		
	RB1#14	21.92	22.43	21.72		
	RB6#0	21.30	20.99	21.00		
	RB6#9	20.79	21.37	20.97		
	RB15#0	21.29	21.30	20.86		
5MHz QPSK	RB1#0	22.68	22.75	22.57	23.47	30
	RB1#13	22.70	22.64	22.44		
	RB1#24	22.69	22.74	22.41		
	RB15#0	21.72	21.75	21.67		
	RB15#10	21.84	21.64	21.69		
	RB25#0	21.72	21.64	21.74		
5MHz 16QAM	RB1#0	20.80	21.84	21.69	22.56	30
	RB1#13	20.73	21.76	21.58		
	RB1#24	20.80	21.84	21.62		
	RB15#0	21.28	20.60	20.51		
	RB15#10	20.89	21.20	20.65		
	RB25#0	20.89	21.14	20.85		

10MHz QPSK	RB1#0	22.56	22.72	22.68	23.58	30
	RB1#25	22.52	22.61	22.86		
	RB1#49	22.74	22.80	22.77		
	RB25#0	21.53	21.58	21.68		
	RB25#25	21.61	21.67	21.58		
	RB50#0	21.62	21.81	21.87		
10MHz 16QAM	RB1#0	21.82	21.86	21.13	22.71	30
	RB1#25	21.89	21.85	21.27		
	RB1#49	21.92	21.99	21.08		
	RB25#0	20.85	20.93	20.86		
	RB25#25	20.86	20.74	20.86		
	RB50#0	20.76	21.52	20.92		
15MHz QPSK	RB1#0	22.55	22.63	22.72	23.49	30
	RB1#38	22.59	22.64	22.77		
	RB1#74	22.56	22.71	22.76		
	RB36#0	21.72	21.64	21.74		
	RB36#39	21.61	21.58	21.60		
	RB75#0	21.60	21.35	21.60		
15MHz 16QAM	RB1#0	21.81	22.36	21.96	23.17	30
	RB1#38	21.94	22.45	22.03		
	RB1#74	21.80	22.37	21.95		
	RB36#0	20.77	20.77	20.73		
	RB36#39	20.81	20.74	20.71		
	RB75#0	20.81	21.38	20.95		
20MHz QPSK	RB1#0	22.71	22.67	22.70	23.5	30
	RB1#50	22.72	22.73	22.68		
	RB1#99	22.73	22.77	22.78		
	RB50#0	21.61	21.82	21.63		
	RB50#50	21.57	21.59	21.88		
	RB100#0	21.58	21.90	21.59		
20MHz 16QAM	RB1#0	22.38	21.67	22.17	23.16	30
	RB1#50	22.41	21.69	22.32		
	RB1#99	22.44	21.72	22.27		
	RB50#0	20.73	20.85	20.62		
	RB50#50	20.76	21.03	21.00		
	RB100#0	20.88	21.18	20.64		
Note: EIRP=Conducted Power(dBm) - Cable loss(dB) + Antenna Gain(dBi)						
					Result:	Pass

Peak-to-average Ratio(PAR)					
Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
20MHz QPSK	RB1#0	5.83	5.65	5.54	13
	RB100#0	5.42	5.57	5.39	13
20MHz 16QAM	RB1#0	6.96	6.49	6.23	13
	RB100#0	6.32	6.38	6.23	13
Result:					Pass

FCC §2.1049, §27.53:Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
1.4MHz QPSK	1.102	1.102	1.102	1.254	1.260	1.260
1.4MHz 16QAM	1.108	1.090	1.090	1.266	1.248	1.236
3MHz QPSK	2.707	2.695	2.683	3.000	3.000	3.000
3MHz 16QAM	2.695	2.683	2.695	3.012	3.000	3.012
5MHz QPSK	4.531	4.511	4.511	5.000	5.000	4.980
5MHz 16QAM	4.511	4.551	4.551	5.000	5.020	5.000
10MHz QPSK	8.981	8.942	8.942	9.760	9.760	9.760
10MHz 16QAM	8.942	8.981	8.942	9.720	9.840	9.840
15MHz QPSK	13.473	13.533	13.473	15.000	14.940	15.060
15MHz 16QAM	13.473	13.533	13.473	15.000	15.120	15.000
20MHz QPSK	17.884	17.964	17.964	19.440	19.680	19.760
20MHz 16QAM	17.964	18.044	17.964	19.680	19.840	19.680
Note: The test plots please refer to the Plots of Occupied Bandwidth						


FCC §2.1051, § 27.53:Spurious Emissions at Antenna Terminal	
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.

FCC §2.1051, § 27.53:Out of band emission, Band Edge	
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.


FCC §2.1055, §27.54: Frequency Stability						
Test Mode:	20M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1710.529	1710.00	1754.471	1755
	-20	3.85	1710.525	1710.00	1754.472	1755
	-10	3.85	1710.529	1710.00	1754.471	1755
	0	3.85	1710.524	1710.00	1754.473	1755
	10	3.85	1710.528	1710.00	1754.474	1755
	20	3.85	1710.529	1710.00	1754.471	1755
	30	3.85	1710.522	1710.00	1754.475	1755
	40	3.85	1710.529	1710.00	1754.471	1755
	50	3.85	1710.526	1710.00	1754.472	1755
Frequency Stability vs. Voltage	20	3.6	1710.529	1710.00	1754.471	1755
	20	4.4	1710.528	1710.00	1754.473	1755
					Result:	Pass

Test Mode:	20M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	1710.529	1710.00	1754.471	1755
	-20	3.85	1710.528	1710.00	1754.475	1755
	-10	3.85	1710.529	1710.00	1754.471	1755
	0	3.85	1710.527	1710.00	1754.472	1755
	10	3.85	1710.526	1710.00	1754.472	1755
	20	3.85	1710.529	1710.00	1754.471	1755
	30	3.85	1710.525	1710.00	1754.474	1755
	40	3.85	1710.529	1710.00	1754.471	1755
	50	3.85	1710.527	1710.00	1754.476	1755
Frequency Stability vs. Voltage	20	3.6	1710.529	1710.00	1754.471	1755
	20	4.4	1710.524	1710.00	1754.475	1755
					Result:	Pass

Test Plots:



Occupied Bandwidth





Occupied Bandwidth

Channel



5MHz Bandwidth QPSK

5MHz Bandwidth 16QAM



Lowest




Middle




Highest




Occupied Bandwidth



Occupied Bandwidth



Occupied Bandwidth





Spurious Emissions at Antenna Terminal



Channel

1.4MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

3MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

5MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

10MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

15MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

20MHz Bandwidth QPSK



Lowest




Middle




Highest




Out of band emission, Band Edge




Out of band emission, Band Edge



Out of band emission, Band Edge



Out of band emission, Band Edge



4.7 Antenna Port Test Data and Results for LTE Band 7

Serial Number:	CR22030001-RF-S1	Test Date:	2022-03-09~2022-03-15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Le Qiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23.7	Relative Humidity: (%)	46	ATM Pressure: (kPa)	101
----------------------	------	------------------------------	----	---------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	Spectrum Analyzer	101474	2021-07-22	2022-07-21
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	Each time	N/A
Weinschel	Coaxial Attenuators	53-20-34	LN751	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	149218	2021-07-22	2022-07-21
BACL	TEMP&HUMI Test Chamber	BTH-150	30026	2021-07-22	2022-07-22
UNI-T	Multimeter	UT39A+	C210582554	2021-09-30	2022-09-30
E-Microwave	Two-way Splitter	ODP-1-6	OE0120176	Each Time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

EUT Information@ LTE Band 7▲:

Antenna Gain (dBi):	-0.42	Antenna Gain (dBi):	0.1
Operation Voltage(V _{DC}):			
Lowest:	3.6	Normal:	3.85
		Highest:	4.4

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
5MHz	2502.5	2535	2567.5
10MHz	2505	2535	2565
15MHz	2507.5	2535	2562.5
20MHz	2510	2535	2560

Test Data:**FCC§2.1046;§ 27.50(h)(2)****RF Output Power:**

Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
5MHz QPSK	RB1#0	22.55	22.50	22.48	22.03	33
	RB1#13	22.52	22.53	22.49		
	RB1#24	22.47	22.52	22.54		
	RB15#0	21.43	21.47	21.52		
	RB15#10	21.55	21.46	21.57		
	RB25#0	21.51	21.50	21.59		
5MHz 16QAM	RB1#0	20.73	21.20	21.60	21.08	33
	RB1#13	20.77	21.27	21.59		
	RB1#24	20.84	21.26	21.55		
	RB15#0	20.64	20.81	20.41		
	RB15#10	20.65	20.75	20.51		
	RB25#0	20.72	20.84	20.57		
10MHz QPSK	RB1#0	22.29	-15.62	22.53	22.09	33
	RB1#25	22.33	-15.11	22.61		
	RB1#49	22.33	-15.37	22.56		
	RB25#0	21.32	21.44	21.59		
	RB25#25	21.53	21.41	21.65		
	RB50#0	21.54	21.47	21.49		
10MHz 16QAM	RB1#0	21.88	22.20	21.01	21.68	33
	RB1#25	21.76	22.11	20.98		
	RB1#49	21.84	22.16	21.26		
	RB25#0	20.50	20.59	20.73		
	RB25#25	20.49	20.57	20.78		
	RB50#0	20.59	20.96	20.64		
15MHz QPSK	RB1#0	22.36	22.41	22.57	22.1	33
	RB1#38	22.34	22.36	22.59		
	RB1#74	22.36	22.54	22.62		
	RB36#0	21.40	21.49	21.45		
	RB36#39	21.39	21.52	21.47		
	RB75#0	21.54	21.56	21.58		
15MHz 16QAM	RB1#0	21.80	21.83	21.77	21.4	33
	RB1#38	21.72	21.83	21.87		
	RB1#74	21.77	21.88	21.92		
	RB36#0	20.53	20.65	20.59		
	RB36#39	20.63	20.59	20.67		
	RB75#0	20.54	20.94	20.58		

20MHz QPSK	RB1#0	22.44	22.55	22.51	22.17	33
	RB1#50	22.43	22.55	22.58		
	RB1#99	22.50	22.68	22.69		
	RB50#0	21.38	21.44	21.30		
	RB50#50	21.43	21.44	21.47		
	RB100#0	21.53	21.43	21.47		
20MHz 16QAM	RB1#0	21.40	21.73	21.98	21.66	33
	RB1#50	21.42	21.70	22.16		
	RB1#99	21.48	21.81	22.18		
	RB50#0	20.57	20.63	20.53		
	RB50#50	20.60	20.51	20.63		
	RB100#0	20.99	20.88	20.67		
Note: EIRP=Conducted Power(dBm) - Cable loss(dB) + Antenna Gain(dBi)						
					Result:	Pass

Peak-to-average Ratio(PAR)

Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
20MHz QPSK	RB1#0	5.07	4.99	5.28	13
	RB100#0	5.33	5.33	5.25	13
20MHz 16QAM	RB1#0	5.68	6.38	5.59	13
	RB100#0	6.17	5.97	6.06	13
Result:					Pass

FCC §2.1049, §27.53:Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
5MHz QPSK	4.511	4.511	4.511	5.000	5.040	4.980
5MHz 16QAM	4.511	4.551	4.531	5.000	5.020	5.000
10MHz QPSK	8.981	8.942	8.942	9.800	9.800	9.800
10MHz 16QAM	8.942	8.981	8.942	9.760	9.800	9.800
15MHz QPSK	13.533	13.473	13.533	15.060	15.060	15.120
15MHz 16QAM	13.533	13.533	13.533	15.000	15.120	15.060
20MHz QPSK	17.964	17.964	18.044	19.600	19.680	19.840
20MHz 16QAM	18.044	18.044	17.964	19.760	19.840	19.760

Note: The test plots please refer to the Plots of Occupied Bandwidth

FCC §2.1051, § 27.53:Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--

FCC §2.1051, § 27.53:Out of band emission, Band Edge


Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---

FCC §2.1055, §27.54: Frequency Stability


Test Mode:	20M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	2500.529	2500.00	2569.471	2570
	-20	3.85	2500.528	2500.00	2569.472	2570
	-10	3.85	2500.529	2500.00	2569.471	2570
	0	3.85	2500.530	2500.00	2569.473	2570
	10	3.85	2500.524	2500.00	2569.475	2570
	20	3.85	2500.529	2500.00	2569.471	2570
	30	3.85	2500.525	2500.00	2569.476	2570
	40	3.85	2500.529	2500.00	2569.471	2570
Frequency Stability vs. Voltage	20	3.6	2500.529	2500.00	2569.471	2570
	20	4.4	2500.521	2500.00	2569.475	2570
					Result:	Pass

Test Mode:	20M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.85	2500.529	2500.00	2569.471	2570
	-20	3.85	2500.528	2500.00	2569.472	2570
	-10	3.85	2500.529	2500.00	2569.471	2570
	0	3.85	2500.527	2500.00	2569.474	2570
	10	3.85	2500.526	2500.00	2569.477	2570
	20	3.85	2500.529	2500.00	2569.471	2570
	30	3.85	2500.528	2500.00	2569.472	2570
	40	3.85	2500.529	2500.00	2569.471	2570
Frequency Stability vs. Voltage	20	3.6	2500.529	2500.00	2569.471	2570
	20	4.4	2500.521	2500.00	2569.477	2570
					Result:	Pass


Test Plots:




Occupied Bandwidth



Occupied Bandwidth



Occupied Bandwidth





Spurious Emissions at Antenna Terminal



Channel

5MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

10MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

15MHz Bandwidth QPSK



Lowest



Middle



Highest





Spurious Emissions at Antenna Terminal



Channel

20MHz Bandwidth QPSK



Lowest




Middle




Highest




Out of band emission, Band Edge




Out of band emission, Band Edge



Out of band emission, Band Edge



Out of band emission, Band Edge



4.8 Radiated Spurious Emissions

Serial Number:	CR22030001-RF-S1	Test Date:	2022-03-08
Test Site:	966-2, 966-1	Test Mode:	Transmitting
Tester:	Great Qiao, Carl Liang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	19.8	Relative Humidity: (%)	57	ATM Pressure: (kPa)	101.3
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020-10-19	2023-10-18
R&S	EMI Test Receiver	ESR3	102724	2021-07-22	2022-07-21
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2021-07-18	2022-07-17
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2021-07-18	2022-07-17
Sonoma	Amplifier	310N	186165	2021-07-18	2022-07-17
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2021-07-25	2022-07-24
Agilent	Signal Generator	E8247C	MY43321350	2021-04-25	2022-04-24
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021-02-05	2024-02-04
R&S	Spectrum Analyzer	FSV40	101591	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2021-08-08	2022-08-07
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021-11-10	2022-11-09
AH	Preamplifier	PAM-1840VH	190	2021-11-20	2022-11-19
AH	Double Ridge Guide Horn Antenna	SAS-571	1396	2021-10-18	2023-10-17
PASTERNAK	Horn Antenna	PE9852/2F-20	112001	2021-02-05	2024-02-04
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2021-07-25	2022-07-24
Mini Circuits	High Pass Filter	VHF-6010+	31119	2021-08-08	2022-08-07
Mini Circuits	High Pass Filter	VHF-3100+	31251	2021-08-08	2022-08-07

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

Note: The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis according to C63.26 figure 5, the worst orientation was photographed and it's data was recorded.

Cellular Band (PART 22H)**30 MHz-10 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850 Frequency:824.2MHz								
878.32	H	44.44	-55.52	0.00	0.59	-56.11	-13.00	43.11
774.16	V	52.49	-46.91	0.00	0.55	-47.46	-13.00	34.46
1648.40	H	42.12	-62.21	8.68	0.80	-54.33	-13.00	41.33
1648.40	V	40.61	-63.80	8.68	0.80	-55.92	-13.00	42.92
2472.60	H	41.75	-59.03	9.38	1.00	-50.65	-13.00	37.65
2472.60	V	39.08	-61.65	9.38	1.00	-53.27	-13.00	40.27
3296.80	H	39.84	-56.84	10.32	1.15	-47.67	-13.00	34.67
3296.80	V	40.72	-55.72	10.32	1.15	-46.55	-13.00	33.55
GSM 850 Frequency:836.6MHz								
890.73	H	47.42	-52.16	0.00	0.64	-52.80	-13.00	39.80
875.10	V	52.17	-44.84	0.00	0.60	-45.44	-13.00	32.44
1673.20	H	39.47	-64.84	8.71	0.85	-56.98	-13.00	43.98
1673.20	V	35.95	-68.46	8.71	0.85	-60.60	-13.00	47.60
2509.80	H	42.62	-57.99	9.42	1.01	-49.58	-13.00	36.58
2509.80	V	41.61	-59.01	9.42	1.01	-50.60	-13.00	37.60
3346.40	H	39.33	-57.84	10.34	1.16	-48.66	-13.00	35.66
3346.40	V	39.40	-57.63	10.34	1.16	-48.45	-13.00	35.45
GSM 850 Frequency:848.8MHz								
903.31	H	47.67	-51.53	0.00	0.58	-52.11	-13.00	39.11
903.31	V	55.42	-40.94	0.00	0.58	-41.52	-13.00	28.52
1697.60	H	40.30	-63.99	8.74	0.90	-56.15	-13.00	43.15
1697.60	V	36.80	-67.62	8.74	0.90	-59.78	-13.00	46.78
2546.40	H	41.14	-59.19	9.47	1.01	-50.73	-13.00	37.73
2546.40	V	40.42	-59.86	9.47	1.01	-51.40	-13.00	38.40
3395.20	H	37.63	-60.06	10.36	1.19	-50.89	-13.00	37.89
3395.20	V	37.59	-60.07	10.36	1.19	-50.90	-13.00	37.90

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band 5 Frequency:826.4 MHz								
102.00	H	31.38	-80.96	0.00	0.19	-81.15	-13.00	68.15
79.80	V	44.39	-64.07	-0.10	0.16	-64.33	-13.00	51.33
1652.80	H	36.12	-68.21	8.68	0.81	-60.34	-13.00	47.34
1652.80	V	37.14	-67.27	8.68	0.81	-59.40	-13.00	46.40
2479.20	H	35.49	-65.27	9.39	1.01	-56.89	-13.00	43.89
2479.20	V	36.00	-64.73	9.39	1.01	-56.35	-13.00	43.35
3305.60	H	35.84	-60.89	10.32	1.15	-51.72	-13.00	38.72
3305.60	V	35.27	-61.23	10.32	1.15	-52.06	-13.00	39.06
WCDMA Band 5 Frequency:836.6MHz								
80.08	H	35.30	-74.51	0.00	0.16	-74.67	-13.00	61.67
80.08	V	40.69	-67.90	0.00	0.16	-68.06	-13.00	55.06
1673.20	H	36.33	-67.98	8.71	0.85	-60.12	-13.00	47.12
1673.20	V	37.19	-67.22	8.71	0.85	-59.36	-13.00	46.36
2509.80	H	35.94	-64.67	9.42	1.01	-56.26	-13.00	43.26
2509.80	V	35.36	-65.26	9.42	1.01	-56.85	-13.00	43.85
3346.40	H	34.89	-62.28	10.34	1.16	-53.10	-13.00	40.10
3346.40	V	34.50	-62.53	10.34	1.16	-53.35	-13.00	40.35
WCDMA Band 5 Frequency:846.6MHz								
80.08	H	32.83	-76.98	0.00	0.16	-77.14	-13.00	64.14
79.80	V	44.76	-63.70	-0.10	0.16	-63.96	-13.00	50.96
1693.20	H	36.79	-67.51	8.73	0.89	-59.67	-13.00	46.67
1693.20	V	36.60	-67.82	8.73	0.89	-59.98	-13.00	46.98
2539.80	H	35.07	-65.31	9.46	1.01	-56.86	-13.00	43.86
2539.80	V	34.65	-65.69	9.46	1.01	-57.24	-13.00	44.24
3386.40	H	35.01	-62.58	10.35	1.18	-53.41	-13.00	40.41
3386.40	V	34.37	-63.17	10.35	1.18	-54.00	-13.00	41.00

PCS Band (PART 24E)**30 MHz-20 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 1900 Frequency:1850.2MHz								
673.04	H	30.89	-73.77	0.00	0.50	-74.27	-13.00	61.27
48.33	V	34.38	-65.20	-16.54	0.12	-81.86	-13.00	68.86
3700.40	H	38.27	-59.05	10.60	1.25	-49.70	-13.00	36.70
3700.40	V	36.35	-60.95	10.60	1.25	-51.60	-13.00	38.60
5550.60	H	35.78	-57.48	11.44	1.49	-47.53	-13.00	34.53
5550.60	V	36.10	-57.00	11.44	1.49	-47.05	-13.00	34.05
GSM 1900 Frequency:1880MHz								
890.73	H	30.37	-69.21	0.00	0.64	-69.85	-13.00	56.85
48.33	V	35.37	-64.21	-16.54	0.12	-80.87	-13.00	67.87
3760.00	H	35.54	-60.87	10.66	1.24	-51.45	-13.00	38.45
3760.00	V	35.88	-60.41	10.66	1.24	-50.99	-13.00	37.99
5640.00	H	36.77	-56.68	11.33	1.54	-46.89	-13.00	33.89
5640.00	V	35.43	-57.90	11.33	1.54	-48.11	-13.00	35.11
GSM 1900 Frequency:1909.8MHz								
49.01	H	31.17	-68.00	-15.87	0.12	-83.99	-13.00	70.99
48.50	V	34.57	-65.18	-16.37	0.12	-81.67	-13.00	68.67
3819.60	H	37.13	-58.73	10.72	1.29	-49.30	-13.00	36.30
3819.60	V	36.26	-59.46	10.72	1.29	-50.03	-13.00	37.03
5729.40	H	36.98	-56.50	11.22	1.59	-46.87	-13.00	33.87
5729.40	V	35.26	-58.10	11.22	1.59	-48.47	-13.00	35.47

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band II, Frequency:1852.4 MHz								
79.80	H	34.86	-74.80	-0.10	0.16	-75.06	-13.00	62.06
79.80	V	43.68	-64.78	-0.10	0.16	-65.04	-13.00	52.04
3704.80	H	42.98	-54.28	10.60	1.25	-44.93	-13.00	31.93
3704.80	V	41.18	-56.05	10.60	1.25	-46.70	-13.00	33.70
5557.20	H	35.06	-58.22	11.43	1.49	-48.28	-13.00	35.28
5557.20	V	35.15	-57.98	11.43	1.49	-48.04	-13.00	35.04
WCDMA Band II, Frequency:1880 MHz								
79.91	H	34.67	-75.06	-0.05	0.16	-75.27	-13.00	62.27
79.91	V	44.25	-64.28	-0.05	0.16	-64.49	-13.00	51.49
3760.00	H	44.05	-52.36	10.66	1.24	-42.94	-13.00	29.94
3760.00	V	41.91	-54.38	10.66	1.24	-44.96	-13.00	31.96
5640.00	H	35.13	-58.32	11.33	1.54	-48.53	-13.00	35.53
5640.00	V	34.79	-58.54	11.33	1.54	-48.75	-13.00	35.75
WCDMA Band II, Frequency:1907.6MHz								
79.91	H	34.59	-75.14	-0.05	0.16	-75.35	-13.00	62.35
66.34	V	38.93	-64.92	-6.94	0.15	-72.01	-13.00	59.01
3815.20	H	42.75	-53.10	10.72	1.29	-43.67	-13.00	30.67
3815.20	V	41.64	-54.05	10.72	1.29	-44.62	-13.00	31.62
5722.80	H	34.87	-58.62	11.23	1.58	-48.97	-13.00	35.97
5722.80	V	34.66	-58.69	11.23	1.58	-49.04	-13.00	36.04

LTE Bands:**LTE Band 2 (30MHz-20GHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK,Frequency:1850.7 MHz								
79.80	H	31.90	-77.76	-0.10	0.16	-78.02	-13.00	65.02
79.80	V	44.05	-64.41	-0.10	0.16	-64.67	-13.00	51.67
3701.40	H	45.45	-51.86	10.60	1.25	-42.51	-13.00	29.51
3701.40	V	44.30	-52.99	10.60	1.25	-43.64	-13.00	30.64
5552.10	H	34.85	-58.42	11.44	1.49	-48.47	-13.00	35.47
5552.10	V	34.26	-58.84	11.44	1.49	-48.89	-13.00	35.89
QPSK,Frequency:1880 MHz								
80.08	H	32.25	-77.56	0.00	0.16	-77.72	-13.00	64.72
79.80	V	44.32	-64.14	-0.10	0.16	-64.40	-13.00	51.40
3760.00	H	45.74	-50.67	10.66	1.24	-41.25	-13.00	28.25
3760.00	V	44.79	-51.50	10.66	1.24	-42.08	-13.00	29.08
5640.00	H	34.98	-58.47	11.33	1.54	-48.68	-13.00	35.68
5640.00	V	35.42	-57.91	11.33	1.54	-48.12	-13.00	35.12
QPSK,Frequency:1909.3 MHz								
80.08	H	31.63	-78.18	0.00	0.16	-78.34	-13.00	65.34
80.08	V	41.66	-66.93	0.00	0.16	-67.09	-13.00	54.09
3818.60	H	44.86	-51.00	10.72	1.29	-41.57	-13.00	28.57
3818.60	V	43.72	-51.99	10.72	1.29	-42.56	-13.00	29.56
5727.90	H	35.68	-57.80	11.23	1.59	-48.16	-13.00	35.16
5727.90	V	36.30	-57.06	11.23	1.59	-47.42	-13.00	34.42

LTE Band 4 (30MHz-20GHz):

LTE Band 4 (50MHz-20GHz).								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK,Frequency:1710.7 MHz								
80.08	H	31.65	-78.16	0.00	0.16	-78.32	-13.00	65.32
65.11	V	50.11	-54.16	-7.59	0.14	-61.89	-13.00	48.89
3421.40	H	36.25	-61.51	10.37	1.17	-52.31	-13.00	39.31
3421.40	V	36.21	-61.52	10.37	1.17	-52.32	-13.00	39.32
5132.10	H	35.11	-58.46	11.28	1.47	-48.65	-13.00	35.65
5132.10	V	34.49	-58.97	11.28	1.47	-49.16	-13.00	36.16
QPSK,Frequency:1732.5 MHz								
80.08	H	32.49	-77.32	0.00	0.16	-77.48	-13.00	64.48
79.80	V	44.06	-64.40	-0.10	0.16	-64.66	-13.00	51.66
3465.00	H	36.94	-60.87	10.39	1.15	-51.63	-13.00	38.63
3465.00	V	36.29	-61.48	10.39	1.15	-52.24	-13.00	39.24
5197.50	H	34.83	-59.30	11.32	1.44	-49.42	-13.00	36.42
5197.50	V	35.67	-58.31	11.32	1.44	-48.43	-13.00	35.43
QPSK,Frequency:1754.3 MHz								
79.80	H	30.39	-79.27	-0.10	0.16	-79.53	-13.00	66.53
80.08	V	43.47	-65.12	0.00	0.16	-65.28	-13.00	52.28
3505.20	H	35.45	-62.38	10.41	1.18	-53.15	-13.00	40.15
3505.20	V	34.98	-62.79	10.41	1.18	-53.56	-13.00	40.56
5257.80	H	35.19	-58.54	11.35	1.47	-48.66	-13.00	35.66
5257.80	V	34.92	-58.59	11.35	1.47	-48.71	-13.00	35.71

LTE Band 7(30MHz-26.5GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, Frequency: 2502.5MHz								
434.06	H	59.99	-48.42	0.00	0.41	-48.83	-25.00	23.83
99.87	V	55.63	-51.43	0.00	0.19	-51.62	-25.00	26.62
5005.00	H	35.02	-57.94	11.20	1.47	-48.21	-25.00	23.21
5005.00	V	38.74	-54.08	11.20	1.47	-44.35	-25.00	19.35
7507.50	H	33.38	-56.41	10.90	1.95	-47.46	-25.00	22.46
7507.50	V	33.42	-56.87	10.90	1.95	-47.92	-25.00	22.92
QPSK, Frequency: 2535MHz								
138.87	H	64.60	-47.69	0.00	0.22	-47.91	-25.00	22.91
56.99	V	58.49	-46.08	-11.68	0.14	-57.90	-25.00	32.90
5070.00	H	34.83	-58.36	11.24	1.47	-48.59	-25.00	23.59
5070.00	V	35.47	-57.62	11.24	1.47	-47.85	-25.00	22.85
7605.00	H	34.08	-55.39	10.88	2.01	-46.52	-25.00	21.52
7605.00	V	34.21	-55.98	10.88	2.01	-47.11	-25.00	22.11
QPSK, Frequency: 2567.5MHz								
434.06	H	61.16	-47.25	0.00	0.41	-47.66	-25.00	22.66
501.18	V	56.63	-46.07	0.00	0.45	-46.52	-25.00	21.52
5135.00	H	35.13	-58.47	11.28	1.47	-48.66	-25.00	23.66
5135.00	V	34.98	-58.51	11.28	1.47	-48.70	-25.00	23.70
7702.50	H	33.80	-55.72	10.86	1.97	-46.83	-25.00	21.83
7702.50	V	34.28	-55.90	10.86	1.97	-47.01	-25.00	22.01

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

***** END OF REPORT *****