

FCC RF EXPOSURE REPORT

FCC ID: RWO-RC30035302

Project No.	:	2006C161
Equipment	:	Wireless Keyboard
Brand Name	:	RAZER
Test Model	:	RZ03-0353
Series Model	:	RZ03-0353XXXX-XXXX (X can be 0-9 or A-Z)
Applicant	:	Razer Inc.
Address	:	9 Pasteur, Suite 100, Irvine, CA92618, USA.
Manufacturer	:	Razer (Asia-Pacific) Pte.,Ltd.
Address	:	514 Chai Chee Lane, #07-01-06, Singapore 469029
Factory	:	RAZER TECHNOLOGY AND DEVELOPMENT (SHENZHEN) CO.,
		LTD.
Address	:	East Wing, 3rd Floor, Block 2, Phase 1 of Vision Shenzhen Business
		Park Keji South Road, Hi-Tech Industrial Park, Shenzhen 518057,
		China.
Date of Receipt	:	Jun. 23, 2020
Date of Test	:	Jun. 24, 2020 ~ Jul. 30, 2020
Issued Date	:	Sep. 22, 2020
Report Version	:	R01
Test Sample	:	Sample No.: DG20200526139
Standard(s)	:	FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
		FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Welly zhou

Prepared by : Welly Zhou

1/a Phan

Approved by : Ethan Ma



Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town,Dongguan, Guangdong, China. Tel: +86-769-8318-3000 Web: www.newbtl.com



REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Sep. 22, 2020



1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China. BTL's Test Firm Registration Number for FCC: 357015 BTL's Designation Number for FCC: CN1240

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

LE / 2.4G SRD:

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	PSA	RFPCA371112IMAB301	PCB	IPEX	4.75



3. TEST RESULTS

Tune up tolerance (dBm)				
LE	2.4G SRD			
±1	±1			

For LE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
4.75	2.9854	4.63	2.9040	0.00173	1	Complies

For 2.4G SRD:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
4.75	2.9854	4.71	2.9580	0.00176	1	Complies

Note: The calculated distance is 20 cm.

Output power including tune up tolerance.

End of Test Report