

RADIO PERFORMANCE TEST REPORT

Test Report No. : OT-209-RWD-012
Reception No. : 2008003257
Applicant : Continental Automotive Systems Corporation
Address : 45-29, Saeum-ro, Icheon-si, Gyeonggi-Do, Korea
Manufacturer : Continental Automotive Systems Corporation
Address : 45-29, Saeum-ro, Icheon-si, Gyeonggi-Do, Korea
Type of Equipment : Smart Key Fob
FCC ID : SY5MQ4FGE03
Model No. : SVI-MQ4FGE03
Serial number : N/A
Total page of Report : 24 pages (including this page)
Date of Incoming : August 26, 2020
Date of issuing : September 08, 2020

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.209 and Section 15.231**

This test report only contains the result of a single test of the sample supplied for the examination.


It is not a generally valid assessment of the features of the respective products of the mass-production.



Tested by
/ Sieon Lee / Assistant Manager
ONETECH Corp.



Reviewed by
/ Ha-Ram Lee / Manager
ONETECH Corp.



Approved by
/ Ki-Hong, Nam / General Manager
ONETECH Corp.

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	5
2. TEST SUMMARY	6
2.1 TEST ITEMS AND RESULTS	6
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS.....	6
2.3 RELATED SUBMITTAL(S) / GRANT(S)	6
2.4 PURPOSE OF THE TEST	6
2.5 TEST METHODOLOGY.....	6
2.6 TEST FACILITY.....	6
3. GENERAL INFORMATION	7
3.1 PRODUCT DESCRIPTION.....	7
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	7
4. EUT MODIFICATIONS.....	8
5. SYSTEM TEST CONFIGURATION	8
5.1 JUSTIFICATION.....	8
5.2 PERIPHERAL EQUIPMENT	8
5.3 MODE OF OPERATION DURING THE TEST	8
5.4 CONFIGURATION OF TEST SYSTEM	10
5.5 ANTENNA REQUIREMENT	10
6. PRELIMINARY TEST	11
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS.....	11
6.2 GENERAL RADIATED EMISSIONS TESTS	11
7. BANDWIDTH MEASUREMENT	12
7.1 OPERATING ENVIRONMENT	12
7.2 TEST SET-UP	12
7.3 TEST DATE.....	12
7.4 TEST DATA.....	12
8. TRANSMISSION TIME	14
8.1 OPERATING ENVIRONMENT	14
8.2 TEST SET-UP	14
8.3 TEST DATE.....	14
8.4 TEST DATA.....	15

9. RADIATED EMISSION TEST	16
9.1 REGULATION	16
9.2 TEST SET-UP	17
9.3 TEST DATE	17
9.4 TEST DATA.....	18
9.4.1 Field Strength of Fundamental.....	18
9.4.2 Spurious Emission Test	19
9.4.3 Restricted Band Test	23
10. LIST OF TEST EQUIPMENT	24

REVISION HISTORY

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-209-RWD-012	September 08, 2020	Initial Issue	All

1. VERIFICATION OF COMPLIANCE

Applicant : Continental Automotive Systems Corporation
 Address : 45-29, Saeum-ro, Icheon-si, Gyeonggi-Do, Korea
 Contact Person : S. M. Jang / Representative
 Telephone No. : 82-31-645-4864
 FCC ID : SY5MQ4FGE03
 Model Name : SVI-MQ4FGE03
 Brand Name : N/A
 Serial Number : N/A

EQUIPMENT CLASS	DSC - Part 15, Security/Remote Control Transmitter
E.U.T. DESCRIPTION	Smart Key Fob
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER IC RULES PART(S)	FCC PART 15 SUBPART C Section 15.209 and Section 15.231
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	None
FINAL TEST WAS CONDUCTED ON	3 m, Semi Anechoic Chamber

The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.231(c)	Bandwidth Measurement	Met the Limit / PASS
15.231(a)	Transmission Time	Met the Limit / PASS
15.231(b) 15.209(a)	Field Strength of Fundamental and Spurious Emission	Met the Limit / PASS
15.205	Restricted Band	Met the Limit / PASS
15.207	AC Conducted Emissions	N / A (See Note)

Note: This test is not applicable because the EUT uses battery and it's not to be connected to the public utility (AC) power line.

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in section 2.1.

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-4112/ C-14617/ G-10666 / T-1842

-. Lab Accreditation:

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

ISED (Innovation, Science and Economic Development Canada) – Registration No. Site# 3736A-3

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

3. GENERAL INFORMATION

3.1 Product Description

The Continental Automotive Systems Corporation, Model: SVI-MQ4FGE03 (referred to as the EUT in this report) is a Transmitter that it controls locking and unlocking the door of a vehicle. Product specification information described herein was obtained from product data sheet or user's manual.

CHASSIS TYPE	Plastic
TX FREQUENCY	433.92 MHz
RX FREQUENCY	125 kHz
MAX. RF OUTPUT POWER	84.60 dB μ V/m
MODULATION	FSK
LIST OF EACH OSC. OR CRY. FREQ.(FREQ. $\geq$ 1 MHz)	27.6 MHz
DUTY CYCLE FACTOR	9.68 dB (Duty Cycle : 32.8 %)
ANTENNA TYPE	Built-in on the PCB in EUT
ANTEENA GAIN	-24.14 dBi
RATED SUPPLY VOLTAGE	DC 3 V from the battery

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
MAIN BOARD	N/A	N/A	-
Battery	N/A	N/A	-

5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	Description	Connected to
-	-	-	-
-	-	-	-

5.3 Mode of operation during the test

Software was programmed into the EUT to maintain continuous transfer mode. The EUT was set at 433.92 MHz. To get a maximum radiated emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is “XY” axis. So, the worst data was recorded in this test report.


-. Duty Cycle

Frequency (MHz)	Tx On Time [ms]	Tx Off Time [ms]	Duty Cycle [%]	Duty Cycle Factor [dB]
433.92	32.8	67.2	32.8	9.68

Note – Duty Cycle : (Tx On Time / (Tx On Time + Tx Off Time)) * 100

Duty Cycle Factor : 20 * Log(1 / (Duty Cycle / 100))

-. Test Plot



The average field strength may be found by measuring the peak pulse amplitude (in log equivalent units) and determining the duty cycle correction factor (in dB) associated with the pulse modulation as shown in Equation. (ANSI C63.10: 2013)

5.4 Configuration of Test System

Radiated Emission Test: Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m Semi Anechoic Chamber

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The transmitter antenna of the EUT is PCB Antenna, so no consideration of replacement by the user.

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

- It is not need to test this requirement, because the power of the EUT is supplied from a DC battery.

6.2 General Radiated Emissions Tests

During Preliminary Test, the following operating mode was investigated.

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

7. Bandwidth Measurement

7.1 Operating environment

Temperature : 22 °C

Relative humidity : 52 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 3 kHz, and peak detection was used. The bandwidth of fundamental frequency was measured and recorded.



7.3 Test date


August 26, 2020 ~ August 28, 2020

7.4 Test data


-. Test Result : Pass

Frequency (MHz)	20 dB Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	Limit (MHz)
433.92	0.08	0.08	1.085

Remark: See next page for plot of measurement data.



20 dB Bandwidth



99% Bandwidth

8. Transmission Time


8.1 Operating environment

Temperature : 22 °C

Relative humidity : 52 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The bandwidth of fundamental frequency was measured and recorded.



8.3 Test date


August 26, 2020 ~ August 28, 2020

8.4 Test data

-. Test Result : Pass

-. Test Applies : 15.231 (a) (1)

Frequency (MHz)	Transmission Time (s)	Limit (s)	Result
433.92	0.318	5.000	Pass



9. Radiated Emission Test

9.1 Regulation

According to §15.209(a), for an intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency [MHz]	Field strength [μ V/m]	Field strength [dB μ V/m]	Measurement distance [m]
0.009 ~ 0.490	2 400 / F (kHz)	-	300
0.490 ~ 1.705	24 000 / F (kHz)	-	30
1.705 ~ 30	30	29.50	30
30 ~ 88	*100	40.00	3
88 ~ 216	*150	43.52	3
216 ~ 960	*200	46.02	3
Above 960	500	53.98	3

*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

According to §15.231(b), for an intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency [MHz]	Field strength of Fundamental [μ V/m]	Field strength of Spurious Emissions [μ V/m]
40.66 ~ 40.70	2 250	225
70 ~ 130	1 250	125
130 ~ 174	1 250 ~ 3 750 **	125 ~ 375 **
174 ~ 260	3 750	375
260 ~ 470	3 750 ~ 12 500 **	375 ~ 1 250 **
Above 470	12 500	1 250

** Linear interpolations

9.2 Test set-up

The radiated emissions measurements were on the 3 m semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from 30 kHz to 1 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

9.3 Test date

August 26, 2020 ~ August 28, 2020

9.4 Test data

9.4.1 Field Strength of Fundamental

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.

Humidity Level : 52 % R.H. Temperature: 22 °C
 Limits apply to : FCC CFG 47, PART 15, SUBPART C, SECTION 15.231(b)
 Result : PASSED

EUT : Smart Key Fob

Operating Condition : TX mode

Distance : 3 m

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Duty Factor	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
433.92	93.40	Peak	H	21.50	2.50	32.80	-	84.60	100.83	16.23
	-	Avg	H				9.68	74.92	80.83	5.91
	91.04	Peak	V				-	82.24	100.83	18.59
	-	Avg	V				9.68	72.56	80.83	8.27

Remark : “H”: Horizontal, “V”: Vertical

Peak Total (dBμV/m) = Reading (dBμV) + Ant Factor (dB) + Cable Loss (dB) – Amp Gain (dB) – Duty Factor (dB)

Avg Total (dBμV/m) = Peak Total (dBμV/m) - Duty Factor (dB)

Margin (dB) = Limits (dBμV/m) - Total (dBμV/m)

9.4.2 Spurious Emission Test

9.4.2.1 Test data for 9 kHz to 30 MHz

-. Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)


-. Frequency range : 9 kHz ~ 30 MHz

-. Measurement distance : 3 m

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
All emissions observed were 20 dB below the limit.									

9.4.2.2 Test data for 30 MHz to 1 GHz

- Resolution bandwidth : 120 kHz
- Frequency range : 30 MHz ~ 1 000 MHz
- Measurement distance : 3 m



No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	[dBuV]	FACTOR	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	868.070	33.5	27.4	4.4	32.2	33.1	46.0	12.9	100	0
----- Vertical -----										
2	35.820	27.4	18.8	0.9	32.7	14.4	40.0	25.6	100	83
3	117.300	27.2	18.2	1.4	32.7	14.1	43.5	29.4	300	359
4	299.660	26.7	19.2	2.1	32.7	15.3	46.0	30.7	300	359
5	562.529	29.0	23.8	2.9	33.0	22.7	46.0	23.3	100	259
6	687.655	28.8	25.4	3.4	32.9	24.7	46.0	21.3	200	0

9.4.2.3 Harmonics Test data for above 1 GHz

- . Resolution bandwidth : 1 MHz for Peak and Average Mode
- . Video bandwidth : 1 MHz for Peak and Average Mode
- . Frequency range : 1 GHz ~ 5 GHz
- . Measurement distance : 3 m
- . Operating mode : Transmitting mode

Frequency (GHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Duty Factor	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
1 735.68	46.61	Peak	H	26.10	4.30	40.60	-	36.41	80.83	44.42
1 735.68	-	Average	H				9.68	26.73	60.83	34.10
1 735.68	45.74	Peak	V				-	35.54	80.83	45.29
1 735.68	-	Average	V				9.68	25.86	60.83	34.97
2 603.52	43.98	Peak	H	29.30	5.20	41.10	-	37.38	80.83	43.45
2 603.52	-	Average	H				9.68	27.70	60.83	33.13
2 603.52	43.71	Peak	V				-	37.11	80.83	43.72
2 603.52	-	Average	V				9.68	27.43	60.83	33.40
3 037.44	51.11	Peak	H	30.00	5.60	41.10	-	45.61	80.83	35.22
3 037.44		Average	H				9.68	35.93	60.83	24.90
3 037.44	44.66	Peak	V				-	39.16	80.83	41.67
3 037.44		Average	V				9.68	29.48	60.83	31.35
3 471.36	46.74	Peak	H	30.30	6.00	40.70	-	42.34	80.83	38.49
3 471.36	-	Average	H				9.68	32.66	60.83	28.17
3 471.36	44.80	Peak	V				-	40.40	80.83	40.43
3 471.36	-	Average	V				9.68	30.72	60.83	30.11
3 905.28	48.02	Peak	H	31.30	6.30	40.60	-	45.02	80.83	35.81
3 905.28	-	Average	H				9.68	35.34	60.83	25.49
3 905.28	45.67	Peak	V				-	42.67	80.83	38.16
3 905.28	-	Average	V				9.68	32.99	60.83	27.84
4 339.20	52.57	Peak	H	33.00	6.50	40.60	-	51.47	80.83	29.36
4 339.20	-	Average	H				9.68	41.79	60.83	19.04
4 339.20	49.31	Peak	V				-	48.21	80.83	32.62
4 339.20	-	Average	V				9.68	38.53	60.83	22.30

Frequency (GHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Duty Factor	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
4 773.12	62.70	Peak	H	33.60	6.70	40.60	-	62.40	74.00	11.60
4 773.12	-	Average	H				9.68	52.72	54.00	1.28
4 773.12	56.89	Peak	V				-	56.59	74.00	17.41
4 773.12	-	Average	V				9.68	46.91	54.00	7.09

Remark : “H”: Horizontal, “V”: Vertical

Peak Total (dBμV/m) = Reading (dBμV) + Ant Factor (dB) + Cable Loss (dB) – Amp Gain (dB) – Duty Factor (dB)

Avg Total (dBμV/m) = Peak Total (dBμV/m) - Duty Factor (dB)

Margin (dB) = Limits (dBμV/m) - Total (dBμV/m)

9.4.3 Restricted Band Test

- Resolution bandwidth : 1 MHz for Peak and Average Mode
- Video bandwidth : 1 MHz for Peak and Average Mode
- Frequency range : 1 GHz ~ 5 GHz
- Measurement distance : 3 m
- Operating mode : Transmitting mode

Frequency (GHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Duty Factor	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
1 356.65	44.45	Peak	H	25.00	3.70	46.10	-	27.05	74.00	46.95
1 414.63	33.52	Average	H				-	16.12	54.00	37.88
1 374.92	43.60	Peak	V				-	26.20	74.00	47.80
1 384.18	33.31	Average	V				-	15.91	54.00	38.09
4 339.20	52.08	Peak	H	33.00	6.50	40.60	-	50.98	74.00	23.02
4 339.20	-	Average	H				9.68	41.30	54.00	12.70
4 339.20	49.18	Peak	V				-	48.08	74.00	25.92
4 339.20	-	Average	V				9.68	38.40	54.00	15.60
4 773.12	62.59	Peak	H	33.60	6.70	40.60	-	62.29	74.00	11.71
4 773.12	-	Average	H				9.68	52.61	54.00	1.39
4 773.12	56.57	Peak	V				-	56.27	74.00	17.73
4 773.12	-	Average	V				9.68	46.59	54.00	7.41

Remark : “H”: Horizontal, “V”: Vertical

Total (dBμV/m) = Reading (dBμV) + Ant Factor (dB) + Cable Loss (dB) – Amp Gain (dB) – Duty Factor (dB)

Margin (dB) = Limits (dBμV/m) - Total (dBμV/m)

10. LIST OF TEST EQUIPMENT

Model Number	Manufacturer	Description	Serial Number	Last Cal. (Interval)
FSV40-N	Rohde & Schwarz	Spectrum Analyzer	101546	Jun. 24, 2020 (1Y)
ESR7	Rohde & Schwarz	EMI Test Receiver	102190	Oct. 16, 2019 (1Y)
310N	Sonoma Instrument	AMPLIFIER	312545	Mar. 16, 2020 (1Y)
MA-4640-XPET	Innco Systems GmbH	Antenna Master	MA4640/652	N/A
HD100	HD GmbH	Position Controller	N/A	N/A
DT2000-2t	Innco Systems GmbH	Turn Table	N/A	N/A
FMZB 1513	Schwarzbeck	LOOP ANTENNA	1513-235	Mar. 24, 2020 (2Y)
HLP-2008	TDK	Hybrid Antenna	131316	Feb. 27, 2020 (2Y)
AH-118	Com-Power	Horn Antenna	10050061	Oct. 18, 2019 (1Y)
SCU-18F	Rohde & Schwarz	Pre-Amplifier	180117	Mar. 10, 2020 (1Y)
Filter	PHELCOM.CO	Band Reject Filter	N/A	Feb. 20, 2020 (1Y)