BOSCH

Wallscanner D-tect200C
Escáner de pared D-tect200C
Scanneur de murs D-tect200C

Universal Detector
Detector universal
Détecteur universel

0601081610

12 V MAX

Wallscanner D-tect200C
Escáner de pared D-tect200C
Scanneur de murs D-tect200C

Universal Detector
Detector universal
Détecteur universel

0601081610

FEATURES / CARACTERÍSTICAS / CARACTÉRISTIQUES

1. Screenshot functions
   Funciones de captura de pantalla
   Fonctions de capture d'écran
   Screenshot and easy documentation. The scanned images can be saved and transfer-red via USB-C and SD card slot to a computer for further analysis.
   La función de captura de pantalla permite realizar una documentación rápida y fácil. Las imágenes escaneadas se pueden almacenar y transferir a través de un cable USB-C y una ranura de tarjeta SD a una computadora para su análisis adicional.
   La fonction de capture d'écran sur-porte une documentation rapide et facile ; les images scannées peuvent être enregistrées et transférées à un ordinateur par le biais du port de cartes SD et USB-C en vue d'analyse complémentaire.
2. Object view
   Vista de objetos
   Vue d'objets
3. Spot view
   Vista puntual
   Vue de cibles
4. Spiral view 2D
   Vista de la señal 2D
   Vue de signaux 2D
5. Spiral view
   Vista de la señal
   Vue de signaux
6. Screwdriver/Adjustment
   Destornillador/Ajuste
   Tournevis/Réglage
7. USB
   USB-C/SD card interface
   Interfaz de ranura USB-C/tarjeta SD
   Interface de carte USB-C/SD
8. Adjustable detection
   Detección de fases
   Détection de phases

TECHNICAL DATA / DATOS TECNICOS / CARACTÉRISTIQUES TECHNIQUES

Max. depth Profundidad máx. Profondeur max.	8 in
Lateral accuracy Precisión lateral Exactitude latérale	± 0.19 in*

*plus use-dependent deviation / y además desviación dependiente del uso / plus déviation en fonction de l'utilisation.

12 V MAX

Wallscanner D-tect200C
Escáner de pared D-tect200C
Scanneur de murs D-tect200C

Universal Detector
Detector universal
Détecteur universel

0601081610

BOSCH

Wallscanner D-tect200C
Escáner de pared D-tect200C
Scanneur de murs D-tect200C

Universal Detector
Detector universal
Détecteur universel

0601081610

12 V MAX

2 610 067 500

BOSCH

Wallscanner D-tect200C
Escáner de pared D-tect200C
Scanneur de murs D-tect200C

Universal Detector
Detector universal
Détecteur universel

0601081610

FOR PROFESSIONAL USE ONLY
SOLO PARA USO PROFESIONAL
POUR UTILISATION PROFESSIONNELLE SEULEMENT

1 x Li-Ion battery • Bateria de ion Litio • Batterie Lithium-Ion 12V Max 2.0 Ah
1 x Charger • Cargador • Chargeur GAL12V-20
1 x Protective pouch • Funda protectora • Pochette de protection
1 x USB-C™ Cable • Cable USB-C™ • Câble USB-C™

12 V MAX

- 8 in max scanning depth / Espejada de profundidad máx. de escaneo / Profondeur max. de balayage de 20 cm / 8 po
- Wooden studs / Montantes de madera / Poteaux d'ossature en bois
- (Non-) live wires / Cables sin corriente / Fils (non) sous tension
- Live wires / Cables con corriente / Fils sous tension
- Metal / Metal / Métal
- Plastic pipes with water / Tuberías de plástico con agua / Tuyaux en plastique avec de l'eau
- Empty plastic pipes / Tuberías de plástico vacías / Tuyaux en plastique vides

Advanced radar technology
Tecnología avanzada de radar
Technologie radar avancée

Wallscanner D-tect200C
Escáner de pared D-tect200C
Scanneur de murs D-tect200C

Universal Detector
Detector universal
Détecteur universel

0601081610

BOSCH

Robert Bosch Tool Corporation
Mt. Prospect, IL 60056-2230
MSDS / SDS 1 (877) 303-0891

Battery assembled in Malaysia. Cells made in China, Malaysia.
Bater a ensamblada en Malasia. Celdas de bater a fabricadas en China, Malasia.
Pile assembl e en Malaisie. Cellules des piles fabriqu es en Chine, en Malaisie.

Made in China (Protective pouch, USB-C Cable, Battery charger
Fabricado en China (funda protectora, cable USB-C, cargador de baterías)
Fabriqué en Chine (pochette de protection, câble USB-C, chargeur de piles)

DO NOT SCAN
NOT A UPC
3728K

C US
LR39098

Tool complies with relevant OSHA standards
La herramienta cumplen con los estándares OSHA relevantes
L'outil sont conformes aux norms applicables de l'OSHA

BOSCH

PRESS COLORS

PROCESS CYAN	PROCESS MAGENTA	PROCESS YELLOW	PROCESS BLACK	PANTONE PMS 485			

PRESS INFO: Prints 5 colors unless otherwise client directed. CMYK plus 1 spot color match. ALL PRINTED SAM must meet the following minimum requirements on a bar code verifier: ANSI-C grade men or better. Decode % of at least 80% (applicable with laser scanner only).

All 3dB codes must meet the following ajus requirements: Minimum size of 1.5 inches for the width across the band and 0.5 inches for the height (length) of the bars. Maximum size of 1.75 inches for the width across the bars and 1.25 inches for the height (length) of the bars.

FILE NAME: 320271 D-Tect 200C Pack Update **DIE:**
PN: 2 610 067 500 **PA:** 0601081610 **DESIGNER:** KMC **DATE:** 01/17/2022

IMPORTANT NOTICE: SUPPLIER IS RESPONSIBLE FOR CHECKING DRAWINGS FOR ACCURACY IN MEASUREMENTS, PLATE TOLERANCE REQUIREMENTS, REGISTRATION AND CONSTRUCTION DETAILING BEFORE PLATES ARE MADE. ANY CHANGES MADE TO BOT PRODUCTION REQUIREMENTS SHOULD BE APPROVED BY BOTH THE CLIENT AND DESIGNER. COLOR PROOFS SHOULD BE SUBMITTED TO CLIENT AND DESIGNER. ALL COPY AVAILABLE AND PRESPRESS BY CLIENT AND LEGAL REQUIREMENTS CHECKED BY THE CLIENT'S LEGAL DEPARTMENT UNLESS OTHERWISE CLIENT DIRECTED.