





# Test Report - FCC Part 1.1310/ MPE Applicant: Fiplex Communications Inc.

#### Approved for Release By:

Signature:	Bruno Churon			
Name & Title:	Bruno Clavier, General Manager			
Date of Signature	5/25/2023			

This test report shall not be reproduced except in full without the written and signed permission of Timco Engineering Inc. (IIA). This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.



## **Table of Contents**

1.	CUS	STOMER INFORMATION	.3
2.		CATION OF TESTING	
		Test Laboratory Testing was performed, reviewed by	
3.	TES	T SAMPLE(S) (EUT/DUT)	.5
	3.1	Description of the EUT	.5
4.	TES	T METHODS & APPLICABLE REGULATORY LIMITS	.6
	4.1.1	Test methods/Standards/Guidance:	.6
5.	RF E	XPOSURE RESULTS	.8
6.	HIST	TORY OF TEST REPORT CHANGES	.9



#### 1. Customer Information

Applicant: Fiplex Communications Inc.

Address: 2101 NW 79th Avenue

Miami, Florida, 33122, United States

#### 2. Location of Testing

#### 2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at Timco's permanent laboratory located at 849 NW State Road 45, Newberry, Florida 32669

FCC test firm # 578780
FCC Designation # US1070
FCC site registration is under A2LA certificate # 0955.01
ISED Canada test site registration # 2056A
EU Notified Body # 1177
For all designations see A2LA scope # 0955.01



Timco Engineering, Inc., an IIA Company 849 NW State Road 45, Newberry, Florida 32669 (352) 472-5500 / testing@timcoengr.com

# 2.2 Testing was performed, reviewed by

Dates of Testing: 3/14/2023 - 3/27/2023

			0	
C:	-073	Sr. EMC Engineer EMC-003838-NE	i	V
Signature:	Con S. Kog	EMC-003838-NE		MA
			1,	150

Name & Title: Tim Royer, EMC Engineer

Date of Signature 5/25/2023

Signature:

Name & Title: Kristoffer Costa, EMC Technician

Date of Signature 5/25/2023

## 3. Test Sample(s) (EUT/DUT)

The test sample was received: 3/10/2023

#### 3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification					
FCC ID: P3TDH14-11A					
Brief Description Low Band FLEX Remote					
Model(s) # HONBDA-RA					
Firmware version	N/A				
Software version	N/A				
Serial Number	N/A				

Technical Characteristics					
Frequency Range	406.1-439 MHz				
<b>RF O/P Power (Max.)</b> 38.43 dBm/ 6.966W					
Modulation FM					
Bandwidth & Emission Class	4K05F3E, 7K85F3E, 12K3F3E, 8K26F1D, 8K26F1E, 8K12F1W,				
	9K77F1D, 9K77F1E, 9K77D7W				
Duty Cycle	100%				
Antenna Connector	N type				
Voltage Rating (AC or Batt.)	120 VAC				

Antenna Characteristics						
Antenna	Frequency Range	Mode / BW	Antenna Gain			
1	n/a	n/a	0 dBi			

- Note: Information such as antenna gain, firmware/software numbers are provided by manufacturer and cannot be validated by the test lab.

#### 4. Test methods & Applicable Regulatory Limits

#### 4.1 Test methods/Standards/Guidance:

The following guidance FCC KDB 447498 D01 General RF Exposure Guidance v06 was used for RF exposure evaluation as per FCC Part 1.1310 and FCC Part 2.1091 and part 2.1093. Full test results are available in this report.

#### 4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging Time (minutes)					
A Limits for Occupational/Controlled Exposure									
0.3-3.0	614	1.63	*(100)	≤6					
3.0-30	1842/f	4.89/f	*(900/f²)	<6					
30-300	61.4	0.163	1.0	<6					
300-1,500			f/300	<6					
1,500-100,000			5	<6					
B Limits for General Population/Uncontrolled Exposure									
0.3-1.34	614	1.63	*(100)	<30					
1.34-30	824/f	2.19/f	*(180/f²)	<30					
30-300	27.5	0.073	0.2	<30					
300-1,500			f/1500	<30					
1,500-100,000			1.0	<30					



#### 4.2 Equations

#### **POWER DENSITY**

E(V/m) = SQRT (30 \* P \* G) / d

 $Pd(W/m^2) = E^2 / 377$ 

 $S = EIRP / (4 * Pi * D^2v)$ 

Where:

S = Power density, in mW/cm^2

EIRP = Equivalent Isotropic Radiated Power, in mW

D = Separation distance in cm

Power density is converted from units of  $\underline{MW/cm^2}$  to units of  $\underline{W/m^2}$  by multiplying by 10.

#### DISTANCE

$$D = SQRT (EIRP / (4 * Pi * S))$$

Where:

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power, in mW

S = Power density in mW/cm^2

**SOURCE-BASED DUTY CYCLE (**When applicable (for example, multi-slot mobile phone applications) A duty cycle factor may be applied.)

Source-based time-average EIRP = ( DC / 100 ) \* EIRP

Where:

DC = Duty Cycle in % as applicable.

EIRP = Equivalent Isotropic radiated Power, in mW

# 5. RF Exposure Results

MPE									
Frequency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Uncontrolled Exposure	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limt (cm)
425-430 MHz	20	39.00	0.00	100%	7.94	1.58 mW/cm2	0.28 mW/cm2	1.42 mW/cm2	47.51

RESULT: Pass at DISTANCE 47.51 cm

# 6. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
	1	Initial release	3/31/2023
TR_6953-23_FCC 1.1310/ MPE_	2	Updated page 8	5/25/2023

# **END OF TEST REPORT**