

RF Exposure Report

Report No.: SA170731C08

FCC ID: QXO-AP3917I

Test Model: AP3917i

Series Model: AP7662i

Received Date: Jul. 31, 2017

Test Date: Aug. 20 ~ Oct. 03, 2017

Issued Date: Oct. 05, 2017

Applicant: Extreme Networks, Inc.

Address: 6480 VIA DEL ORO SAN JOSE CA 95119 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA170731C08	Original release.	Oct. 05, 2017

1 Certificate of Conformity

Product: Wireless 802.11 a/ac+b/g/n Access Point

Brand: Extreme Networks

Test Model: AP3917i

Series Model: AP7662i

Sample Status: Engineering sample

Applicant: Extreme Networks, Inc.

Test Date: Aug. 20 ~ Oct. 03, 2017


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :


Polly Chien / Specialist

Date:

Oct. 05, 2017

Approved by :



Ken Liu / Senior Manager

Date:

Oct. 05, 2017

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Function	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN	CDD Mode					
	2412-2462	27.15	4.06	20	0.263	1
	Outdoor Access Point Mode					
	5180-5240	15.37	6.18	20	0.028	1
	Indoor Access Point Mode					
	5180-5240	26.06	6.18	20	0.333	1
	5745-5825	26.38	6.18	20	0.359	1
	Beamforming Mode					
	2412-2462	26.97	4.06	20	0.252	1
	Outdoor Access Point Mode					
	5180-5240	15.31	6.18	20	0.028	1
	Indoor Access Point Mode					
	5180-5240	26.06	6.18	20	0.333	1
	5745-5825	26.38	6.18	20	0.359	1
BT LE	2402-2480	3.70	3.53	20	0.001	1
Zigbee	2405-2480	3.70	3.53	20	0.001	1

Note:

1. Antenna was cross-polarized antenna.
2. 2.4GHz: max. gain = 4.06dBi
5GHz: max. gain = 6.18dBi
3. BT LE & Zigbee: Ant. gain = 3.53dBi.

Function	Frequency Band (MHz)	Conducted Output Power	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
4.9GHz	4942.5-4987.5	21.56	6.18	20	0.118	1

* max. gain = 6.18dBi

Frequency Band	Max Power (dBm)			Total Power (dBm)	Power Limit (dBm)
	WLAN	BT LE	Zigbee		
2.4GHz	27.15	3.70	-	27.17	30
2.4GHz	27.15	-	3.70	27.17	30

Conclusion:

2.4GHz & 4.9GHz/5GHz & BT LE or 2.4GHz & 4.9GHz/5GHz & Zigbee technology can transmit at same time.

BT LE and Zigbee cannot transmit simultaneously.

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

1. WLAN 2.4GHz + WLAN 5GHz + BT LE = $0.263 + 0.359 + 0.001 = 0.623$
2. WLAN 2.4GHz + WLAN 5GHz + Zigbee = $0.263 + 0.359 + 0.001 = 0.623$
3. WLAN 2.4GHz + WLAN 4.9GHz + BT LE = $0.263 + 0.118 + 0.001 = 0.382$
4. WLAN 2.4GHz + WLAN 4.9GHz + Zigbee = $0.263 + 0.118 + 0.001 = 0.382$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---