

Approval and Certification



Product	0440 4000 (testo 400)															
Mat.-No.	0440 4000															
Date	07.11.2018															
Country	Comments															
Australia		E 1561														
Canada	Product IC: 6127B-04404000 IC Warnings															
Europa + EFTA	 EU countries: Belgium (BE), Bulgaria (BG), Denmark (DK), Germany (DE), Estonia (EE), Finland (FI), France (FR), Greece (GR), Ireland (IE), Italy (IT), Latvia (LV), Lithuania (LT), Luxembourg (LU), Malta (MT), Netherlands (NL), Austria (AT), Poland (PL), Portugal (PT), Romania (RO), Sweden (SE), Slovakia (SK), Slovenia (SI), Spain (ES), Czech Republic (CZ), Hungary (HU), United Kingdom (GB), Republic of Cyprus (CY). EFTA countries: Iceland, Liechtenstein, Norway, Switzerland															
Turkey	Authorized															
USA	Product FCC ID: WAF-04404000 FCC Warnings															
Bluetooth® Information	<table><tr><th>Feature</th><th>Values</th></tr><tr><td>Qualified Design ID</td><td>D037513)</td></tr><tr><td>Bluetooth radio class</td><td>Class 1</td></tr><tr><td>Bluetooth® company</td><td>Testo SE & Co. KGaA</td></tr></table>		Feature	Values	Qualified Design ID	D037513)	Bluetooth radio class	Class 1	Bluetooth® company	Testo SE & Co. KGaA						
Feature	Values															
Qualified Design ID	D037513)															
Bluetooth radio class	Class 1															
Bluetooth® company	Testo SE & Co. KGaA															
Bluetooth®-Module	<table><tr><th>Feature</th><th>Values</th></tr><tr><td>Bluetooth® Range (testo Klima-probes of newest generation with Bluetooth®)</td><td><20 m (free field)</td></tr><tr><td>Bluetooth® Range (Smart-probes)</td><td><20 m (free field)</td></tr><tr><td>Bluetooth® type</td><td>S25 Series BLE module , based on TI CC2640 chip</td></tr><tr><td>RF Band</td><td>2402-2480MHz</td></tr><tr><td>Output power</td><td>0 dBm</td></tr><tr><td>Antenna gain 3 dBi</td><td></td></tr></table>		Feature	Values	Bluetooth® Range (testo Klima-probes of newest generation with Bluetooth®)	<20 m (free field)	Bluetooth® Range (Smart-probes)	<20 m (free field)	Bluetooth® type	S25 Series BLE module , based on TI CC2640 chip	RF Band	2402-2480MHz	Output power	0 dBm	Antenna gain 3 dBi	
Feature	Values															
Bluetooth® Range (testo Klima-probes of newest generation with Bluetooth®)	<20 m (free field)															
Bluetooth® Range (Smart-probes)	<20 m (free field)															
Bluetooth® type	S25 Series BLE module , based on TI CC2640 chip															
RF Band	2402-2480MHz															
Output power	0 dBm															
Antenna gain 3 dBi																

IC Warnings

RSS-Gen & RSS-247 statement:

This device complies with Industry Canada licence-exempt RSS standard(s).

Operation is subject to the following two conditions:

- (1) this device may not cause interference, and
- (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence.

L'exploitation est autorisée aux deux conditions suivantes :

- (1) l'appareil ne doit pas produire de brouillage, et
- (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Caution: Radio Frequency Radiation Exposure

This equipment complies with IC radiation exposure limits set forth for an uncontrolled environment and meets the IC radio frequency (RF) Exposure Guidelines. This equipment should be installed and operated keeping the radiator at least 20 cm or more away from person's body in normal use position.

Co-Location:

This transmitter must not be co-located or operated in conjunction with any other antenna or transmitter.

Attention : exposition au rayonnement de radiofréquences

Cet équipement est conforme aux limites d'exposition aux radiofréquences IC fixées pour un environnement non contrôlé et aux Lignes directrices relatives à l'exposition aux radiofréquences (RF). Cet équipement devrait être installé et utilisé à une distance d'au moins 20 cm d'un radiateur ou à une distance plus grande du corps humain en position normale d'utilisation.

Co-location

Ce transmetteur ne peut pas être installé en colocation ou être utilisé avec une autre antenne ou transmetteur, quel qu'en soit le type..

FCC Warnings

Information from the FCC (Federal Communications Commission)

For your own safety

Shielded cables should be used for a composite interface. This is to ensure continued protection against radio frequency interference.

FCC warning statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. Shielded interface cable must be used in order to comply with the emission limits.



Testo SE & Co. KGaA

Testo-Straße 1

79853 Lenzkirch

Germany

Tel.: +49 7653 681-0

Fax: +49 7653 681-7699

E-Mail: info@testo.de

www.testo.de