



Maximum Permissible Exposure (MPE) Evaluation Report

Report No. : EME-021514
Model No. : LM-WP210RB
Issued Date : Jan. 10, 2003

Applicant : DELTA NETWORKS, INC.
252, Shang Ying Road, Kuei San Taoyuan Hsien 333,
Taiwan, R.O.C.

Test By : Intertek Testing Services Taiwan Ltd.
No. 11, Ko-Tze-Nan Chia-Tung Li, Shiang-Shan District,
Hsinchu, Taiwan, R.O.C.

This test report consists of 7 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of ITS Laboratory. The test result in this report only applies to the tested sample.

Project Engineer

Jerry Liu

Reviewed By

Elton Chen



Table of Contents

Summary of Tests	3
1. Introduction	4
2. RF Exposure Limit	5
3. RF Exposure calculations	6
Test Condition: Single antenna.....	6
Test Condition: A set of two antennas.....	7



Intertek Testing Services

ETL SEMKO

FCC ID. : PD5LMWP210RB

Report No.: EME-021514

Page 3 of 7

Summary of Tests

MPE Evaluation meet FCC OET No. 65: 1997/ IEEE C95.1-1999

Wireless PCMCIA card-Model: LM-WP210RB

FCC ID: PD5LMWP210RB

Test	Reference	Results
MPE Evaluation	FCC Guidelines for Human Exposure IEEE C95.1	Complies



1. Introduction

The EUT operates in the 2.4GHz ISM band. The EUT (antenna included) is compliant with modular approval and the normal operation distance (after installing in other device, such as router or access point), 20cm from the human body; therefore, the EUT is defined as a Mobile Device.

The EUT can be equipped with two kinds of antenna, the two combinations are listed as below:

Type of EUT	Definition in this report
Single antenna	LM-WP210RB (with antenna A)
A set of two antennas	LM-WP210RB (with antenna B)

The reason to do the MPE Evaluation is to avoid the RF hazard to human body. The maximum output power and gain of the antenna were used to calculate the limited distance from the product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed.

The Notice in Installation Manual has been stated as below:

While installing and operating this transmitter, the radio frequency exposure limit of 1mW/(cm*cm) may be exceeded at distances close to the transmitter, therefore, the user must maintain a minimum distance of 20 cm from the device at all time.



2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational / Control Exposures				
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
(B) Limits for General Population / Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

F= Frequency in MHz



3. RF Exposure calculations

From §FCC 1.1310 table 1, the maximum permissible RF exposure for an uncontrolled environment is $1\text{mW}/(\text{cm}^2)$, where, $(\text{cm}^2) = \text{square cm}$. The electric field generated for a $1\text{mW}/(\text{cm}^2)$ exposure (S) is calculated as follows:

$$S = E^2/Z$$

where, S = Power density

E = Electric field

Z = Impedance

so, $1\text{mW}/(\text{cm}^2) = 10\text{ W}/(\text{m}^2)$

Z is 377 ohm of the impedance of free space, where E and H field are perpendicular.

Thus the Electric field to produce a $1\text{mW}/(\text{cm}^2)$ exposure is:

$$E = (10 \times 377)^{1/2} = 61.4\text{ V/m}, \text{ which is equivalent to } 1\text{mW}/(\text{cm}^2)$$

Test Condition: Single antenna

Maximum conducted peak output power is 16.99 dBm and maximum antenna gain is 3 dBi. The maximum radiated output power resulted in 99.77 mW.

Using the relationship between electric field E, effective radiated power in watts P, and distance in meters D, the corresponding distance D to produce a $1\text{mW}/(\text{cm}^2)$ is calculated by the following expression:

$$D = (P \times 30)^{1/2} / E = (99.77 \times 10 \times 30)^{1/2} / 61.4 = 2.817\text{ cm}$$

where, P: maximum effective radiated power measured, 19.99 dBm (99.77 mW)

E: electric field equivalent to $1\text{mW}/(\text{cm}^2)$, 61.4 V/m

The minimum distance by calculation and normal use distance were listed in the table as below:

E.I.R.P.		Calculated RF Exposure Allowable Minimum Separation Distance(cm)	Normal Use Minimum RF Exposure Separation Distance(cm)
dBm	mW	2.817	20
19.99	99.77		

The calculated Minimum allowable distance is very close to the antenna, and is far away from the normal use distance.



Test Condition: A set of two antennas

Maximum conducted peak output power is 16.99 dBm and maximum antenna gain is 2.4 dBi. The maximum radiated output power resulted in 86.896 mW.

Using the relationship between electric field E, effective radiated power in watts P, and distance in meters D, the corresponding distance D to produce a 1mW/(cm*cm) is calculated by the following expression:

$$D = (P \times 30)^{1/2} / E = (86.896 \times 10 \times 30)^{1/2} / 61.4 = 2.63 \text{ cm}$$

where, P: maximum effective radiated power measured, 19.39 dBm (86.896 mW)

E: electric field equivalent to 1mW/(cm*cm), 61.4 V/m

The minimum distance by calculation and normal use distance were listed in the table as below:

E.I.R.P.		Calculated RF Exposure Allowable Minimum Separation Distance(cm)	Normal Use Minimum RF Exposure Separation Distance(cm)
dBm	mW	2.63	20
19.39	86.896		

The calculated Minimum allowable distance is very close to the antenna, and is far away from the normal use distance.