

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in KDB 447498 D01 V06 and §1.1307(b)

CFR Title 47 §2.1091(b): (b) For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

FCC ID: **2BF4E-RW403B**

EUT Specification

| | |
|-----------------------------------|--|
| EUT | Thermal Label Printer |
| Frequency band (Operating) | <input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others: 2.402GHz~2.480GHz |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____ |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²) |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm ²) | Average Time |
|---|------------------------------|------------------------------|------------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/Uncontrol Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100000 | -- | -- | 1 | 30 |

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

BDR&EDR worst case:

| Operating Mode | Channel Frequency | Measured Power | Tune up tolerance | Max. Tune up Power | Antenna Gain | Power density at 20cm | Power density Limits (mW/cm ²) |
|----------------|-------------------|----------------|-------------------|--------------------|--------------|------------------------|--|
| | (MHz) | (dBm) | (dBm) | (dBm) | (dBi) | (mW/ cm ²) | |
| 8DPSK | 2480 | -0.19 | -0.19±1 | 0.81 | 2.67 | 0.0004 | 1 |

BLE worst case:

| Operating Mode | Channel Frequency | Measured Power | Tune up tolerance | Max. Tune up Power | Antenna Gain | Power density at 20cm | Power density Limits (mW/cm ²) |
|----------------|-------------------|----------------|-------------------|--------------------|--------------|------------------------|--|
| | (MHz) | (dBm) | (dBm) | (dBm) | (dBi) | (mW/ cm ²) | |
| 1M | 2440 | -9.65 | -9.65±1 | -8.65 | 2.67 | 0.0001 | 1 |

Note:

1. BDR&EDR and BLE cannot support simultaneous transmission.

Test Result: Pass