





## **Appendix G-Frequency Stability**

## **Test Data:**

Frequency Stability vs temperature:

1.Test for FDD LTE Band 71 Downlink (Middle Channel: 634.5MHz)

Temperature(°C)	Voltage (V ac)	Frequency Error (Hz)	Tolerance(ppm)
50	120	33.49	0.0528
40	120	22.69	0.0358
30	120	60.48	0.0953
20	120	20.63	0.0325
10	120	49.5	0.078
0	120	36.59	0.0577
-10	120	48.98	0.0772
-20	120	43.42	0.0684
-30	120	26.53	0.0418

## Frequency Stability vs voltage:

1. Test for FDD LTE Band 71 Downlink (Middle Channel: 634.5MHz)

	Voltage (V ac)	Temperature(°C)	Frequency Error (Hz)	Tolerance(ppm)
	108	20	2.39	0.0038
Ī	120	20	20.63	0.0325
	132	20	57.6	0.0908



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions or Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-a-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction is susee defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document on the subject of the subject on the subject of the subject of the subject of the subject on the subject of the subject of the subject on the subject of the subject o

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300 中国・江苏・昆山市留学生创业园伟业路10号 邮编 215300