

5.2. RF EXPOSURE REQUIREMENTS @ 1.1310 & 2.1091

5.2.1. Limits

1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Control Exposures				
30-300	61.4	0.163	1.0	6
(B) Limits for General Population/Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30

5.2.2. Method of Measurements

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi \cdot r^2} = \frac{EIRP}{4\pi \cdot r^2}$$

Where,
P: power input to the antenna in mW
EIRP: Equivalent (effective) isotropic radiated power.
S: power density mW/cm²
G: numeric gain of antenna relative to isotropic radiator
r: distance to centre of radiation in cm

$$r = \sqrt{\frac{PG}{4\pi \cdot S}} = \sqrt{\frac{EIRP}{4\pi \cdot S}}$$

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device.

5.2.3. Evaluation of RF Exposure Compliance Requirements

MPE Limit for Occupational/Controlled Exposure, $S_{\text{controlled}}[\text{mW}/\text{cm}^2] = 1.0$

MPE Limit for General Population/Uncontrolled Exposure, $S_{\text{uncontrolled}}[\text{mW}/\text{cm}^2] = 0.2$

Maximum RF Power conducted, $P_{\text{conducted}}[\text{dBm}] = 43.98$

Maximum Antenna Gain, $G[\text{dBi}] = 9$

Maximum EIRP, $P_{\text{EIRP}} = 52.98 \text{ dBm}$ or 198609.49 mwatts

User-based time-average for PTT = 50%

Calculated RF Safety Distance for Occupational/Controlled Exposure, $r_{\text{safety_controlled}}[\text{cm}] = 89 \text{ cm}$

Calculated RF Safety Distance for General Population/Uncontrolled Exposure, $r_{\text{safety_uncontrolled}}[\text{cm}] = 199 \text{ cm}$

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: 17ICOM-471Q_FCC80
October 24, 2017

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)