

FCC Test Report

Report No.: AGC02762231107FE01

FCC ID	:	2BCTG-FLIP2
PRODUCT DESIGNATION	:	4G Feature Phone
BRAND NAME	:	ESCOLLS
MODEL NAME	:	Flip 2
APPLICANT	:	A.V. World of Technology Ltd
DATE OF ISSUE	:	Dec. 15, 2023
STANDARD(S)	:	FCC Part 15 Subpart B
REPORT VERSION	:	V1.0







Report Revise Record

Report Version	Revise Time	Issued Date Valid Version		Notes	
V1.0	/	Dec. 15, 2023	Valid	Initial Release	



TABLE OF CONTENTS

1. GENERAL INFORMATION	4
2. PRODUCT INFORMATION	5
2.1 PRODUCT TECHNICAL DESCRIPTION	5
2.2 AUXILIARY SURROUNDING DESCRIPTION	5
2.2 TEST METHODOLOGY	6
2.3 DEFINITION OF DEVICE CLASSIFICATION	6
2.3 DESCRIPTION OF TEST MODES	6
3. TEST ENVIRONMENT	7
3.1 ADDRESS OF THE TEST LABORATORY	
3.2 TEST FACILITY	7
3.3 ENVIRONMENTAL CONDITIONS	
3.4 MEASUREMENT UNCERTAINTY	
3.5 LIST OF EQUIPMENTS USED	9
4. SUMMARY OF TEST RESULTS	
5. RADIATED EMISSION MEASUREMENTS	11
5.1 PROVISIONS APPLICABLE	11
5.2 MEASUREMENT SETUP	11
5.3 MEASUREMENT PROCEDURE	
5.4 MEASUREMENT RESULT	14
6. CONDUCTED EMISSION MEASUREMENTS	
6.1 PROVISIONS APPLICABLE	
6.2 MEASUREMENT SETUP	
6.3 MEASUREMENT PROCEDURE	19
6.4 MEASUREMENT RESULT	
APPENDIX I: PHOTOGRAPHS OF TEST SETUP	
APPENDIX II: PHOTOGRAPHS OF TEST EUT	



1. General Information

Applicant	A.V. World of Technology Ltd	
Address	Avinadav 3 Jerusalem Israel	
Manufacturer	A.V. World of Technology Ltd	
Address	Avinadav 3 Jerusalem Israel	
Factory	N/A	
Address	N/A	
Product Designation	4G Feature Phone	
Brand Name	ESCOLLS	
Test Model	Flip 2	
Date of receipt of test item Nov. 17, 2023		
Date of Test	Nov. 17, 2023~Dec. 15, 2023	
Deviation from Standard	No any deviation from the test method	
Condition of Test Sample	Normal	
Test Result	Pass	
Test Report Form No	AGCTR-ER-FCC-SDOC V1.0	

Prepared By

Bibo zhang

Bibo Zhang (Project Engineer)

Dec. 15, 2023

Reviewed By

in Lu

Calvin Liu (Reviewer)

Dec. 15, 2023

Approved By

Max Zhang Max Zhang Authorized Officer

Dec. 15, 2023



2. Product Information

2.1 Product Technical Description

Housing Type	Plastic and metal
Highest Operating Frequency	Greater than 108MHz
Equipment Type	Table-Top
Hardware Version	SF292 MMI_V00
Software Version	V1.0
Power Supply	DC 3.8V 1350mAh by Built-in Li-ion Battery or DC 5V by PC

I/O Port Information (Applicable Information Not Applicable)

I/O Port of EUT						
I/O Port Type Q'TY Cable Tested with						
USB Port	1	1.0m unshielded	1			
Earphone Port	1	1.2m unshielded	1			

2.2 Auxiliary Surrounding Description

The Following Peripheral Devices and Interface Cables Were Connected During The Measurement:

Test Accessories Come From The Laboratory

Test Accessories Come From The Manufacturer

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Adapter	XT-252A-5055	Shenzhen Baijunda Electronic Co., Ltd.	Input: AC 100-240V 50/60Hz, 0.15A Output: DC 5V 0.55A	1.2m unshielded
2	Battery	C533955135L	Dongguan Veken Battery Co., Ltd. DC 3.8V 1350mAh		N/A
3	Earphone	N/A	N/A	N/A	N/A



2.2 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title	
1	FCC 47 CFR Part 15	Radio Frequency Devices	
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	

2.3 Definition of Device Classification

Unintentional radiator:

A device which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment.

Class B Digital Device:

A digital device which is marketed for use by the general public or in a residential environment.

Note:

A manufacturer may also qualify a device intended to be marketed in a commercial, business or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

2.3 Description of Test Modes

No.	Test Mode
1	Data transmission mode (connect computer for data transmitting)



3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106

3.4 Measurement Uncertainty

The reported uncertainty of measurement y \pm U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission	$U_c = \pm 2.9 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$		



3.5 List of Equipment Used

• Ra	Radiated Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2023/02/18	2024/02/17	
\bowtie	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2023/06/03	2024/06/02	
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023/05/11	2025/05/10	
\boxtimes	AGC-EM-E029	Horn Antenna	ETS	3117	00034609	2023/03/23	2024/03/22	
\square	AGC-EM-E096	Pre-amplifier	ETS	3117-PA	00246148	2022/08/04	2024/08/03	
	AGC-EM-S003	Test Software	FARA	V.RA-03A	N/A	N/A	N/A	
\boxtimes	AGC-EM-S004	Test Software	Tonscend	4.0.0.0	N/A	N/A	N/A	

• Co	Conducted Emission										
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)				
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2023/06/03	2024/06/02				
\boxtimes	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2023/06/03	2024/06/02				
\boxtimes	AGC-EM-S001	Test Software	R&S	ES-K1 (Ver.V1.71)	N/A	N/A	N/A				



4. Summary Of Test Results

Item	FCC Rules	Description Of Test	Class/Severity	Result
1	Section 15.107	Radiated Emission	Class B	Pass
2	Section 15.109	Conducted Emission	Class B	Pass




5. Radiated Emission Measurements

5.1 Provisions Applicable


FCC CFR Title 47 Part 15 Subpart B Section 15.109:

Frequency Range	Class B Limit (dBuV/m @3m)	Class A Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	50.00	Quasi-peak
88MHz-216MHz	43.50	53.50	Quasi-peak
216MHz-960MHz	46.00	56.00	Quasi-peak
960MHz-1GHz	54.00	64.00	Quasi-peak
Above 1GHz	54.00	60.00	Average
	74.00	80.00	Peak

5.2 Measurement Setup



Radiated Emission Measurements Test Setup for 30MHz to 1GHz



Radiated Emission Measurements Test Setup for above 1GHz



5.3 Measurement Procedure

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received power by AC 120V/60Hz.
- 5. The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6. The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7. The test mode(s) were scanned during the test:
- 8. Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented. For emissions below 1GHz, use 120KHz RBW and VBW>=3RBW for QP reading.
- 9. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 10. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 11. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 12. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 13. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.
- 14. The test data of the worst case condition (mode 1) was reported on the following Data page.



Emi Test Receiver Setup:

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurment
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
Above T GHz	1MHz	10 Hz	/	Ave.




5.4 Measurement Resul

		R	adiated Emi	ssion 30MHz	-1GHz Test R	esult		
Test M	lode	Mode 1			Polarity:		Horizonta	I
		P Limit — Horizontal PK	100M	FCC Part 15				1G
Final I	Data List							
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	39.7	25.54	10.34	40.00	14.46	100	300	Horizontal
2	67.83	25.73	15.36	40.00	14.27	100	330	Horizontal
3	100.81	29.89	17.03	43.50	13.61	100	160	Horizontal
4	460.68	29.03	24.60	46.00	16.97	100	290	Horizontal
5	604.24	29.84	24.16	46.00	16.16	100	330	Horizontal
6	854.5	34.88	29.83	46.00	11.12	100	340	Horizontal


RESULT: PASS





RESULT: PASS





74.00

74.00

33.52

32.66

100

100

20

350

Horizontal

Horizontal

5	4210.6421	40.48
6	4756.7513	41.34

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

-9.09

-7.82



Radiated Emission Above1GHz Test Result											
Test Mode Mode 1 Polarity: Vertical											
	130				FCC Part 15	B					
	120 110 100 90 80 60 50 40 30 20 10 10 10 10 100 100 100 10		nic Jacoba, participante and a state of the		26 Frequency[H	3G	4 4 4 4 4 4 4 5 4 6	5G	6G		
		PK Limit AV Deteo		Vertical PK							
Final	Data List										
NO.	Freq. [MHz]		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity		
1	1131.02	262	34.96	-18.13	74.00	39.04	100	160	Vertical		
2	2036.20)72	39.31	-13.32	74.00	34.69	100	200	Vertical		
3	2664.33	329	39.49	-12.12	74.00	34.51	100	310	Vertical		
4	3389.47	79	40.37	-10.93	74.00	33.63	100	220	Vertical		
5	4087.61	75	40.45	-9.60	74.00	33.55	100	330	Vertical		
6	4506.70)13	41.28	-7.88	74.00	32.72	100	290	Vertical		

RESULT: PASS

Note:

- 1. Factor=Antenna Factor + Cable loss Amplifier gain, Margin= Limit-Measurement.
- 2. The "Factor" value can be calculated automatically by software of measurement system.



6. Conducted Emission Measurements

6.1 PROVISIONS APPLICABLE

FCC CFR Title 47 Part 15 Subpart B Section 15.107:

 For Class B Limits:

 Maximum RF Line Voltage

 Prequency
 Q.P. (dBµV)
 Average (dBµV)

 150kHz~500kHz
 66-56
 56-46


 500kHz~5MHz
 56
 46

 5MHz~30MHz
 60
 50

For Class A Limits:

Frequency	Maximum RF	Line Voltage
Frequency	Q.P. (dBµV)	Average (dBµV)
150kHz~500kHz	79	66
500kHz~30MHz	73	60

6.2 MEASUREMENT SETUP






6.3 MEASUREMENT PROCEDURE

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. The EUT received AC 120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipments received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.



6.4 Measurement Result



MEASUREMENT RESULT: "agc fin"

2023/12/8 10:50

Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.158000 0.194000 0.210000 0.234000 0.342000 1.070000	53.40 42.60 42.30 39.60 28.80 25.30	6.1 6.1 6.1 6.1 6.2	66 64 63 59 56	12.2 21.3 20.9 22.7 30.4 30.7	QP QP	L1 L1 L1 L1 L1 L1

MEASUREMENT RESULT: "agc fin2"


2023/12/8 10: Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.170000 0.234000 0.778000 1.558000 4.670000 8.878000	35.20 26.30 26.90 24.70 19.40 24.50	6.1 6.2 6.2 6.3 6.6	55 52 46 46 46 50	19.8 26.0 19.1 21.3 26.6 25.5	AV AV AV AV	L1 L1 L1 L1 L1 L1

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/





MEASUREMENT RESULT: "agc_fin"

2023/12/8 10:53

Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.158000 0.182000 0.198000 0.222000 0.230000 1.290000	53.70 43.70 41.00 37.00 37.00 25.50	6.1 6.1 6.1 6.1 6.1 6.2	66 64 63 62 56	11.9 20.7 22.7 25.7 25.4 30.5	QP QP QP QP	N N N N N

MEASUREMENT RESULT: "agc fin2"

2023/12/8 10: Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.158000	36.40	6.1	56	19.2	AV	N
0.234000	24.90	6.1	52	27.4	AV	N
0.778000	25.50	6.2	46	20.5	AV	N
1.558000	23.50	6.2	46	22.5	AV	N
4.674000	19.20	6.3	46	26.8	AV	N
8.666000	24.40	6.6	50	25.6	AV	N

RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Report No.: AGC02762231107FE01 Page 22 of 22

Appendix I: Photographs of Test Setup Refer to the Report No.: AGC02762231107AP05 Appendix II: Photographs of Test EUT Refer to the Report No.: AGC02762231107AP03

-----END OF REPORT-----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.