

# High Frequency Ceramic Solutions

## 2.4 GHz SMD, Above Metal, Low Profile Mini Chip Antenna

P/N 2450AT42E010B


This antenna will generally have a metal layer directly underneath for proper operation, exceptions may apply.

Detail Specification: 10/28/2021

Page 1 of 9

### General Specifications

|                                                                     |                      |             |
|---------------------------------------------------------------------|----------------------|-------------|
| Part Number                                                         | 2450AT42E010B        |             |
| Frequency (MHz)                                                     | 2400 - 2480          |             |
| Return Loss (dB)                                                    | EVB1*                | EVB2*       |
|                                                                     | 2.7 min.             | 3.5 min.    |
| Peak Gain (dBi typ.)                                                | -1.0 (YZ-V)          | -1.0 (YZ-V) |
| Average Gain (dBi typ.)                                             | -3.5 (YZ-V)          | -5.0 (YZ-V) |
| Impedance ( $\Omega$ )                                              | 50                   |             |
| Power Capacity (W)                                                  | 2 max. (CW)          |             |
| Reel Quantity (pcs./reel)                                           | 2,000                |             |
| Operating Temp                                                      | -40 to +85°C         |             |
| Recommended Storage Conditions and Period for unused Product on T&R | +5 to +35°C          |             |
|                                                                     | Humidity 45 - 75% RH |             |
|                                                                     | 18 months max.       |             |



**Zero Clearance!**

Antenna mounts directly above or below the metal layer of PCB. No antenna clearance required ever again!

\* Evaluation boards 1 and 2 are meant to demonstrate the difference in performance achievable with different substrate thicknesses.



This antenna was designed in mind for small coin cell, wearable, IoT, 2.4 BLE, 802.11, ISM, Zigbee, etc. applications in close-range networks where metal or a battery/display covers the entire length or side of the PCB or encasement must be present directly under the antenna and there's no room for usual/typical antenna metal clearance.

### Part Number Explanation

|            |                    |                                                          |            |                     |
|------------|--------------------|----------------------------------------------------------|------------|---------------------|
| P/N Suffix | Packing Style      | Bulk (loose pcs.)                                        | Suffix = S | E.g. 2450AT42E010BS |
|            |                    | T & R                                                    | Suffix = E | E.g. 2450AT42E010BE |
|            | Evaluation Board 1 | 2450AT42E010B-EB1SMA (comes with 1 female SMA connector) |            |                     |
|            | Evaluation Board 2 | 2450AT42E010B-EB2SMA (comes with 1 female SMA connector) |            |                     |


### Mechanical Specifications

|   | In                | mm              |
|---|-------------------|-----------------|
| L | 0.197 $\pm$ 0.008 | 5.00 $\pm$ 0.20 |
| W | 0.079 $\pm$ 0.008 | 2.00 $\pm$ 0.20 |
| T | 0.059 $\pm$ 0.008 | 1.50 $\pm$ 0.20 |
| a | 0.020 $\pm$ 0.008 | 0.50 $\pm$ 0.20 |
| b | 0.059 $\pm$ 0.008 | 1.50 $\pm$ 0.20 |
| C | 0.012 max         | 0.30 max        |



### Terminal Configuration

|   |                 |
|---|-----------------|
| 1 | Feeding Point   |
| 2 | NC <sup>1</sup> |
| 3 | GND             |
| 4 | GND             |



<sup>1</sup>Make sure to have Pin 2 soldered to its PCB land pad but **not** connected to GND or input, it must be NC (or floating).

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 5.1

2021 Johanson Technology, Inc. All Rights Reserved





# High Frequency Ceramic Solutions

2.4 GHz SMD, Above Metal, Low Profile Mini Chip Antenna

P/N 2450AT42E010B

This antenna will generally have a metal layer directly underneath for proper operation, exceptions may apply.


Detail Specification: 10/28/2021

Page 4 of 9

## Typical Electrical Characteristics (T=25 °C)

Evaluation Board 1 (Antenna Efficiency: 18%@ 2.4GHz ; 38%@2.44GHz ; 21%@2.48GHz)


Return Loss



|                                          |                                           |                                          |
|------------------------------------------|-------------------------------------------|------------------------------------------|
| m2<br>freq=2.400GHz<br>dB(S(1,1))=-2.951 | m3<br>freq=2.440GHz<br>dB(S(1,1))=-19.219 | m1<br>freq=2.480GHz<br>dB(S(1,1))=-4.100 |
|------------------------------------------|-------------------------------------------|------------------------------------------|

Evaluation Board 2 (Antenna Efficiency: 27%@ 2.4GHz ; 42%@2.44GHz ; 27%@2.48GHz)

Return Loss



|                                           |                                            |                                           |
|-------------------------------------------|--------------------------------------------|-------------------------------------------|
| m97<br>freq=2.400GHz<br>dB(S(1,1))=-8.572 | m96<br>freq=2.440GHz<br>dB(S(1,1))=-10.958 | m95<br>freq=2.480GHz<br>dB(S(1,1))=-5.426 |
|-------------------------------------------|--------------------------------------------|-------------------------------------------|

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 5.1

2021 Johanson Technology, Inc. All Rights Reserved

# High Frequency Ceramic Solutions

2.4 GHz SMD, Above Metal, Low Profile Mini Chip Antenna


P/N 2450AT42E010B

This antenna will generally have a metal layer directly underneath for proper operation, exceptions may apply.

Detail Specification: 10/28/2021

Page 5 of 9

## Typical Radiation Patterns @ 2.44GHz (T=25 °C)



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 5.1

2021 Johanson Technology, Inc. All Rights Reserved

# High Frequency Ceramic Solutions

2.4 GHz SMD, Above Metal, Low Profile Mini Chip Antenna

P/N 2450AT42E010B


This antenna will generally have a metal layer directly underneath for proper operation, exceptions may apply.

Detail Specification: 10/28/2021


Page 6 of 9

## Mounting Considerations 2 - Circular PCB Environments (coin cell type)

Top View



Bottom View



Note: There's no orderable EVB available for the above "Mounting Considerations 2" reference design

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 5.1

2021 Johanson Technology, Inc. All Rights Reserved

# High Frequency Ceramic Solutions

2.4 GHz SMD, Above Metal, Low Profile Mini Chip Antenna

P/N 2450AT42E010B


This antenna will generally have a metal layer directly underneath for proper operation, exceptions may apply.

Detail Specification: 10/28/2021


Page 7 of 9

## Wider Tuning Example

By re-tuning our Evaluation Board 1, return loss can be improved over the bandwidth as a whole. An additional tuning element is placed between antenna pin 3 and GND.



(Antenna Efficiency: 22%@ 2.4GHz ; 31%@2.44GHz ; 20%@2.48GHz)



m1  
freq=2.400GHz  
dB(S(1,1))=-7.785

m2  
freq=2.440GHz  
dB(S(1,1))=-10.579

m3  
freq=2.480GHz  
dB(S(1,1))=-8.225

Note: This only serves as an example and is not an order-able evaluation board.

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 5.1

2021 Johanson Technology, Inc. All Rights Reserved

# High Frequency Ceramic Solutions

2.4 GHz SMD, Above Metal, Low Profile Mini Chip Antenna

P/N 2450AT42E010B

This antenna will generally have a metal layer directly underneath for proper operation, exceptions may apply.


Detail Specification: 10/28/2021

Page 8 of 9

## How To Choose The Correct Antenna Variant

Since the antenna's efficiency is largely affected by the thickness of the PCB's substrate, we offer another variant of this antenna. This allows a more robust design to fit your PCB. The disparity between antenna variations are internal only; variations are identical in dimension and footprint-compatible.

Refer to the diagram below to understand what is meant by substrate thickness.



\* For PCBs consisting of multiple layers, the thickness (H) is limited distance between the metal layer immediately below the antenna.

| PCB Substrate Thickness | Recommended JTI PN |
|-------------------------|--------------------|
| ≤ 1.0mm                 | 2450AT42E0100      |
| 1.0mm - 2.0mm           | 2450AT42E010B      |

## Typical Efficiency Values @ 2.44GHz for various scenarios for a 30x50mm PCB

The following efficiency values represent performance on a 30x50mm EVB like on page 2. Please note that antenna efficiency varies widely with board layout, size and surroundings.

| PCB Substrate Thickness (H) | Antenna Efficiency @ 2.44GHz |               |
|-----------------------------|------------------------------|---------------|
|                             | 2450AT42E0100                | 2450AT42E010B |
| H = 0.12 mm                 | 1.95%                        | 1.02%         |
| H = 0.7 mm                  | 29.20%                       | 9.30%         |
| H = 1.5 mm                  | 23.30%                       | 38.00%        |
| H = 2.5 mm                  | 21.60%                       | 42.00%        |

Note: "H" substrate thickness of <0.25mm(10mil) is not recommended. The component will still radiate however not optimally.

Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 5.1

2021 Johanson Technology, Inc. All Rights Reserved

# High Frequency Ceramic Solutions

2.4 GHz SMD, Above Metal, Low Profile Mini Chip Antenna

P/N 2450AT42E010B

This antenna will generally have a metal layer directly underneath for proper operation, exceptions may apply.

Detail Specification: 10/28/2021

Page 9 of 9

## Antenna layout review, tuning, and characterization services

<https://www.johansontechnology.com/ipc-antenna-services>

## More SMD Chip Antennas at:

<https://www.johansontechnology.com/antennas>

## Soldering Information

<https://www.johansontechnology.com/ipcsoldering-profile>

## Antenna layout and tuning techniques (How to obtain the new antenna matching values)

<https://www.johansontechnology.com/tuning>

## Packaging information

<http://www.johansontechnology.com/tape-reel-packaging>

## RoHS Compliance


<https://www.johansontechnology.com/rohs-compliance>

## MSL Info

<https://www.johansontechnology.com/msl-rating>

## P/N Explanation and Breakdown

<https://www.johansontechnology.com/ipc-pn-explained>



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



<https://www.johansontechnology.com>

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver. 5.1

2021 Johanson Technology, Inc. All Rights Reserved