

849 NW STATE ROAD 45 NEWBERRY, FL 32669 USA PH: 888.472.2424 OR 352.472.5500 FAX: 352.472.2030 EMAIL: <u>INFO@TIMCOENGR.COM</u> <u>HTTP://WWW.TIMCOENGR.COM</u>

FCC PART 95

MURS TRANSCEIVER

TEST REPORT

APPLICANT	GOTENNA		
	102 S 6TH STREET		
	BROOKLYN NY 11249 USA		
FCC ID	2ABVK02629		
MODEL NUMBER	02629		
PRODUCT DESCRIPTION	MURS RADIO WITH BT		
FCC STANDARD APPLIED	47 CFR § 95 Personal Radio Service		
	Subpart J– Multi-Use Radio Service (MURS)		
DATE SAMPLE RECEIVED	7/21/2014		
DATES TESTED	8/6/2014 & 10/3/2014		
TESTED BY	Cory Leverett		
APPROVED BY	Sid Sanders		
TIMCO REPORT NO.	1267AUT14TestReport.docx		
TEST RESULTS	🖾 PASS 🗌 FAIL		

THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.



Table of Contents

GENERAL REMARKS	3
GENERAL INFORMATION	4
TEST PROCEDURES:	5
TEST REPORT SUMMARY	7
RF POWER OUTPUT	8
EMISSION DESIGNATOR AND FREQUENCIES	9
OCCUPIED BANDWIDTH	11
151.88 MHz Bandwidth = 3.3 KHz 154.57 MHz Bandwidth = 11.27 KHz FREQUENCY STABILITY	11 12 19
EMC EQUIPMENT LIST	

Table of Contents

Page 2 of 20



GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results relate only to the items tested.

Summary

 \boxtimes

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc. 849 NW State Road 45 Newberry, FI 32669

Authorized Signatory Name:

Cory Leverett Engineering Project Manager

Date: February 25, 2015



Table of Contents

Page 3 of 20



GENERAL INFORMATION EUT Specification

EUT Description	MURS RADIO WITH BT		
EUT Application	Pairs with Smart Phone via BTLE, sends text messages over MURS channels.		
FCC I D	2ABVK02629		
Model Number	02629		
Serial Number	N/A		
Operating Frequency	151.820, 151.880, 151.940, 154.570, 154.600 MHz		
No. of Channels	5		
Type of Emission	9K6F1D		
	□ 110–120Vac/50–60Hz (Optional AC power Adapter)		
EUT Power Source	DC Power 13.8V		
	Battery Operated Exclusively		
	Prototype		
Test Item	Pre-Production		
	Production		
	Fixed		
Type of Equipment			
	⊠ Portable		
Antenna	Fixed		
Test Conditions	The temperature was 26°C with a relative humidity of 50-60%.		
Modification to the EUT	None		
Test Exercise	The EUT was placed in continuous transmit mode of operation		
Applicable Standards	ANSI/TIA 603-D:2004, FCC CFR 47 Part 95		
Test Facility	Timco Engineering Inc. 849 NW State Road 45 Newberry, FL 32669 USA.		

Applicant:GOTENNAFCC ID:2ABVK02629Report:G\GOTENNA\1267AUT14\1267AUT14TestReport.docx

Table of Contents

Page 4 of 20



TEST PROCEDURES:

General: The test procedures used are detailed in ANSI/TIA 603-D:2004.

Power Output: RF power was conducted per ANSI/TIA 603-D: 2004



Bandwidth: The measurements were made with the spectrum analyzer's resolution bandwidth (RBW) = 100 KHz and the video bandwidth (VBW) = 300 KHz and the span set as shown on plot.



Antenna Conducted Emissions: The RBW = 100 kHz, VBW = 300 kHz and the span set to 10.0 MHz and the spectrum was scanned from 30 MHz to the 10^{th} Harmonic of the fundamental. Above 1 GHz the resolution bandwidth was 1 MHz and the VBW = 3 MHz and the span to 50 MHz.

Table of Contents

Page 5 of 20



Radiation Interference: The test procedure used was ANSI/TIA 603-C: 2004 using an Agilent spectrum receiver with pre-selector. The bandwidth (RBW) of the spectrum receiver was 100 kHz up to 1 GHz and 1 MHz above 1 GHz with an appropriate sweep speed. The VBW above 1 GHz was 3 MHz. The analyzer was calibrated in dB above a microvolt at the output of the antenna.



Frequency Stability: The EUT was placed into a temperature chamber. After a reference frequency is measured at room temperature, The EUT frequency is measured at the required extreme temperatures after a 20 minute soak time at each said temperature. The EUT antenna output port was connected to a frequency counter for the frequency measurement of an unmodulated CW signal. The voltage was also varied + and – 15% with a variable DC power supply and the frequency measured and compared to the reference frequency.



Report:

G\GOTENNA\1267AUT14\1267AUT14TestReport.docx Page 6

Page 6 of 20



TEST REPORT SUMMARY

Dula Dart Na	Seene of Work	Ctatus
Rule Part No.	Scope of work	Status
		Pass/Fail/NA
Part 2.1033(c)(6)(7),	RF Power Output	Pass
Part 2.1046(a), PART		
95 Subpart A, Part 95		
Subpart B, RSS-210		
<u>2.1049(c)</u> ,	Emission Mask and Occupied	Pass
<u>95.635(b)(1)(3)(7)</u>		
	Bandwidths	
2.1051	Antenna Conducted Emissions	Pass
2.1053, IC RSS-210	Field Strength Spurious Emissions	Pass
Part 2.1055 Part	Frequency Stability	Pass
<u>95.621(b)</u> , <u>IC RSS-210</u>		

TEST REPORT REVISION HISTORY

Date of Revision	Description of changes	Report Rev Number
10/6/2014	Original Report	1267AUT14_Rev1
2/25/2015	Changed Designator from F3E to F1D	1267AUT14_Rev1.1

Table of Contents

Page 7 of 20



RF POWER OUTPUT

Rule Part No.: FCC Part 2.1033(c)(6)(7), FCC Part 95.639(h), FCC Part 95.649

Requirements: No MURS unit, under any condition of modulation, shall exceed 2 Watts transmitter power output. There can be no provisions for increasing the power or varying the power.

Method of Measurement: RF power is measured as conducted; a sample was provided with an antenna connector. With a nominal battery voltage and the transmitter properly adjusted the RF output measures:

Test Data:

Output power

Level dBm	Watts
32.22dBm	1.67W

Results: Pass

Applicant:GOTENNAFCC ID:2ABVK02629Report:G\GOTENNA\1267AUT14\1267AUT14TestReport.docx

Table of Contents

Page 8 of 20



EMISSION DESIGNATOR AND FREQUENCIES

<u>2.1033(c) (3)</u> 95.632 Type of Emission: 9K6F1D

Bn = 2M + 2DKM = 3000 D = 2.0K Bn = 2(3000) + 2(1800) = 9.6K

Authorized Bandwidth – 11.25 kHz for frequencies: 151.820, 151.880, 151.940 MHz

Authorized Bandwidth - 20 kHz for frequencies: 154.570, 154.600 MHz

2.1033(c) (5) MURS Frequency Range: 95.632

1. 151.820 2. 151.880 3. 151.940 4. 154.570 5. 154.600

Table of Contents

Page 9 of 20



OCCUPIED BANDWIDTH

Requirements:

Part 2.1049(c), 95.633(f)

(f) The authorized bandwidth for any emission type transmitted by a MURS transmitter is specified as follows:

(1) Emissions on frequencies 151.820 MHz, 151.880 MHz, and 151.940 MHz are limited to 11.25 kHz.

(2) Emissions on frequencies 154.570 and 154.600 MHz are limited to 20.0 kHz.

(3) Provided, however, that all A3E emissions are limited to 8 kHz.

Table of Contents

Page 10 of 20



OCCUPIED BANDWIDTH

Results:



151.88 MHz Bandwidth = 3.3 KHz

Date:

16.SEP.2014 16:29:37

Applicant: GOTENNA FCC ID: 2ABVK02629 G\GOTENNA\1267AUT14\1267AUT14TestReport.docx Report:

Table of Contents

Page 11 of 20



OCCUPIED BANDWIDTH



Date:

Applicant: GOTENNA FCC ID: 2ABVK02629 Report: G\GOTENNA\1267AUT14\1267AUT14TestReport.docx

Table of Contents

Page 12 of 20



Requirements:

Rule Parts. No.: FCC Part 2.1053, Part 95.635(e)

Frequency	Mask with audio low pass filter	Mask without audio low pass filter
151.820, 151.880, 151.940 MHz	(1)	(1)
154.570, 154.600 MHz	(2)	(3)

(1) Emission Mask 1—For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

(i) On any frequency from the center of the authorized bandwidth fo to 5.625 kHz removed from fo: Zero dB.

(ii) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 5.625 kHz but no more than 12.5 kHz: at least 7.27(fd-2.88 kHz) dB.

(iii) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 12.5 kHz: at least 50 + 10 log (P) dB or 70 dB, whichever is the lesser attenuation.

(2) Emission Mask 2—For transmitters designed to operate with a 25 kHz channel bandwidth that are equipped with an audio low-pass filter, the power of any emission must be below the unmodulated carrier power (P) as follows:

(i) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: at least 25 dB.

(ii) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: at least 35 dB.

(iii) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: at least $43 + 10 \log (P) dB$.

(3) Emission Mask 3—For transmitters designed to operate with a 25 kHz channel bandwidth that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier output power (P) as follows:

(i) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 5 kHz, but not more than 10 kHz: at least 83 log (fd/5) dB.
(ii) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 10 kHz, but not more than 250 percent of the authorized bandwidth: at least 29 log (fd2/11) dB or 50 dB, whichever is the lesser attenuation.
(iii) On any frequency removed from the center of the authorized bandwidth by more than 250 percent of the authorized bandwidth: at least 29 log (fd2/11) dB or 50 dB, whichever is the lesser attenuation.

Test procedure: ANSI/TIA-603-C: 2004 paragraph 2.2.11.

Applicant:GOTENNAFCC ID:2ABVK02629Report:G\GOTENNA\1267AUT14\1267AUT14TestReport.docx

Table of Contents

Page 13 of 20



Test Results:

(i) On any frequency from the center of the authorized bandwidth fo to 5.625 kHz removed from fo: Zero dB.

(ii) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 5.625 kHz but no more than 12.5 kHz: at least 7.27(fd-2.88 kHz) dB.



Applicant:GOTENNAFCC ID:2ABVK02629Report:G\GOTENNA\1267AUT14\1267AUT14TestReport.docx

Table of Contents

Page 14 of 20



151.88 MHz Emission > 100% removed from center

Requirements: 95.635 (e) (1) (iii) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 12.5 kHz: at least 50 + 10 log (P) dB or 70 dB, whichever is the lesser attenuation.

Emission Frequency (MHz)	Power N	l ode	Power Output (dBm)	Power Output (Watts)	FCC Requirer dBc	nent	Bandwidth BW - kHz	
151.88	Hi		32.22	1.67	52.22	2	12.5	
Emiss Frequency	ion y (MHz)	Level dBm		Below Carrier (dBc)		Margin		
303.'	76	-2	9.87	62.	.09		9.87	
455.0	64	_4	6.16	78.	.38		26.16	
607.5	52	-5	51.54	83	.76		31.54	
759.	4	-6	51.52	93.	.74		41.52	
911.2	28	-5	59.58	91	8		39.58	
1063.	.16	-5	58.31	90	.53		38.31	
1215.	04	-	57.5	89	.72		37.5	
1366.	92	-	57.5	89	.72		37.5	
1518	.8	-6	51.62	93.	.84		41.62	

Results : Pass

Table of Contents

Page 15 of 20



(i) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 5 kHz, but not more than 10 kHz: at least 83 log (fd/5) dB.
(ii) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 10 kHz, but not more than 250 percent of the authorized bandwidth: at least 29 log (fd2/11) dB or 50 dB, whichever is the lesser attenuation.



154.57MHz Emission < 250% removed from center Mask 3 (i,ii)

Applicant:GOTENNAFCC ID:2ABVK02629Report:G\GOTENNA\1267AUT14\1267AUT14TestReport.docx

Table of Contents

Page 16 of 20



154.57MHz Emission > 250% removed from center Mask 3 (iii)

Requirements: 95.635 (e) (3) (iii) On any frequency removed from the center of the authorized bandwidth by more than 250 percent of the authorized bandwidth: at least 43 + 10 log (P) dB.

Emission Frequency (MHz)	Power N	l ode	Power Output (dBm)	Power Output (Watts)	FCC Requiren dBc	nent	Bandwidth BW - kHz	
154.57	Hi		32.22	1.67	45.22	2	25	
Emiss Frequenc	sion y (MHz)	Lev	el dBm	Below (d)	Carrier Bc)		Margin	
309.	309.14		86.03	68	.25	23.03		
463.	71	-4	3.33	75	.55 .34		30.33 42.12	
618.	28	<u>ب</u>	55.12	87				
772.	85	-56.47		88.69			43.47	
927.	42	-5	58.28	90).5		45.28	
1081	1081.99		-57.87		90.09		44.87	
1236	1236.56		-58.61		90.83		45.61	
1391	1391.13		53.4	85	.62		40.4	
1545	5.7	-6	51.31	93	.53		48.31	

Results: Pass

Table of Contents

Page 17 of 20



UNWANTED RADIATION (Radiated)

Rule Parts. No.: FCC Part 2.1053, 95.635(C),

METHOD OF MEASUREMENT: The tabulated data shows the results of the radiated field strength emissions test. The spectrum was scanned from 30 MHz to at least the tenth harmonic of the fundamental. This test was conducted per ANSI/TIA 603-C: 2004 using the substitution method. Only the worst case for each antenna polarity is shown.

Test Data:								
Emission	Power Mode		ERP Power	ERP Power	FC	С	Bandwidth -	
Frequency			Output	Output	Require	emen	BW - kHz	
(MHz)			(dBm)	(Watts)	t d	В		
151.88	Fix	ed	31.5	1.41	52.	3	11.25	
Emissio	n	An	t. Polarity	Below Car	rier		Margin	
Frequency (MHz)		-	(dBc)			-	
303.76			V	100.81		48.51		
455.64			V	73.49			21.19	
607.52			V	69.00			16.7	
759.40			Н	77.94		25.64		
911.28			V	80.29			27.99	
1,063.16		V	83.67		31.37			
1,215.04		V	85.46		33.16			
1,366.92		Н	81.12		28.82			
1,518.8	0		V	79.30			27	

Results: Pass

Applicant:GOTENNAFCC ID:2ABVK02629Report:G\GOTENNA\1267AUT14\1267AUT14TestReport.docx

Table of Contents

Page 18 of 20



FREQUENCY STABILITY

Rule Parts. No.: FCC Part 2.1055 FCC PART 95.632(C)

(c) MURS transmitters must maintain a frequency stability of 5.0 ppm, or 2.0 ppm if designed to operate with a 6.25 kHz bandwidth

Temperature and voltage tests were performed to verify that the frequency remains within the 0.00050%, 5.0-ppm specification limit if the device is designed to operate with 11.25 kHz or 12.5 kHz authorized bandwidth and .00020%, 2.0 ppm if the device is designed to operate with 6.25 kHz authorized bandwidth. The test was conducted as follows: The transmitter was placed in the temperature chamber at 25 degrees C and allowed to stabilize for one hour. The transmitter was keyed ON for one minute during which four frequency readings were recorded at 15-second intervals. The worse case number was taken for temperature plotting. The assigned channel frequency was considered to be the reference frequency. The temperature was then reduced to -30 degrees C after which the transmitter was again allowed to stabilize for one hour. The transmitter was designed to stabilize for one hour. The transmitter was then reduced to -30 degrees C after which the transmitter was again allowed to stabilize for one hour. The transmitter was then reduced to -30 degrees C after which the transmitter was again allowed to stabilize for one hour. The transmitter was keyed ON for one minute, and again frequency readings were noted at 15-second intervals. The worst-case number was recorded for temperature plotting. This procedure was repeated in 10 degree increments up to + 50 degrees C.

Readings were also taken at plus and minus 15% of the battery voltage of 6 VDC.

Method of Measurements: ANSI/TIA 603-D: 2004

	Frequency		
Temperature	MHz	Cycles	PPM
25°C (reference)	151.819824		
-30°C	151.819863	-39	-0.257
-20°C	151.819888	-64	-0.422
-10°C	151.819862	-38	-0.250
0°C	151.819847	-23	-0.151
10°C	151.819845	-21	-0.138
20°C	151.819837	-13	-0.086
30°C	151.819793	31	0.204
40°C	151.819833	-9	-0.059
50°C	151.819873	-49	-0.323
Battery Voltage	Frequency	Cycles	PPM
-15%	151.819826	-2	-0.013
15%	151.819827	-3	-0.020

Test Data:

Table of Contents

Page 19 of 20



EMC EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
Antenna: Biconnical	Eaton	94455-1	1096	05/10/13	05/10/15
Antenna: Log- Periodic	Electro-Metrics	LPA-25	1122	05/09/13	05/09/15
Antenna: Dipole Kit	Electro-Metrics	TDA-30/1-4	152	N/A	N?A
Frequency Counter	HP	5352B	2632A00165	06/26/13	06/26/15
Hygro- Thermometer	Extech	445703	0602	06/20/13	06/20/15
Digital Multimeter	Fluke	77	35053830	08/22/13	08/22/15
Temperature Chamber Small	Thermotron Corp.	S1.2 Mini Max	25-1420-09	07/03/12	10/03/14
Software: Field Strength Program	Timco	N/A	Version 4.0	N/A	N/A
Antenna: Passive Loop	EMC Test Systems	EMCO 6512	9706-1211	06/14/12	06/14/15
LISN	Electro-Metrics	EM-7820	2682	02/26/13	02/26/15
Antenna: Double- Ridged Horn/ETS Horn 2	ETS-Lindgren	3117	00041534	10/05/12	10/05/14
EMI Test Receiver R & S ESU 40	Rhode & Schwarz	ESU 40	100320	03/21/13	03/21/15
Frequency Counter	HP	5385A	3242A07460	06/16/13	06/16/15
3-Meter Semi- Anechoic Chamber	Panashield	N/A	N/A	12/31/13	12/31/15

EMI RECEIVER SOFTWARE VERSION

The receiver firmware used was version 4.43 Service Pack 3

Table of Contents

Page 20 of 20